

Technical University of Crete
School of Electrical and Computer Engineering

PLH 613 – Special Topics in Database Systems – 2025

Fall Semester 2025 **Semester Project** **Due: 08.01.2026**

Distributed Skyline Query Processing

with Apache Flink

Student Team:

Spyridon Stamou
2021030090

Georgios Angelos Gravalos
2021030001

Contents

Introduction . . . . . **ii**

Algorithms . . . . . **iii**
MR-Dim iv
MR-Grid iv
MR-Angle vi

System Architecture . . . . . **vii**

Configurations . . . . . **ix**

Implementation . . . . . **ix**

Experiments . . . . . **ix**

Conclusion . . . . . **ix**

Introduction

The Skyline Operator is a fundamental tool for multi-criteria decision-making, particularly in Web Service selection where users balance conflicting attributes like cost and response time. Given a dataset S, a point P is part of the Skyline if it is not dominated by any other point which means that no other point is better or equal in all dimensions and strictly better in at least one.

However, calculating the Skyline is a difficult task when dealing with huge amounts of data. As the volume of data increases, traditional algorithms that run on a single computer become too slow and cannot provide results in real-time. To solve this scalability problem, we need to split the work across multiple computers using distributed systems.

In this project, we build a distributed Skyline query processing system using Apache Flink and Apache Kafka. Our approach is based on the MapReduce model, where data is partitioned into smaller groups and processed in parallel. Specifically, we implement and compare three partitioning strategies proposed in the paper (`MapReduce Skyline Query Processing with A New Angular Partitioning Approach`): MR-Dim, MR-Grid, and MR-Angle. The MR-Dim algorithm splits data based on a single dimension, MR-Grid divides the space into cells, and MR-Angle uses angular coordinates.

The goal of this project is to reproduce these three algorithms and evaluate which one performs best, in order to verify the results reported in the paper

Algorithms

We have to define the `Skyline Query`. Let P be a set of data points in a d-dimensional space, where each point $p \in P$ consists of d attributes $\{p_1, p_2, \ldots, p_d\}$. Assuming that for all dimensions smaller values are preferred, we say that a point p dominates another point q if the following two conditions are met:


- p is as good or better than q in all dimensions:

$$p_i \leq q_i$$


- p is strictly better than q in at least one dimension:

$$p_k < q_k$$

So, the `Skyline` of P is the subset of points that are not dominated by any other point in the dataset.



Before describing the three specific algorithms, it is important to explain the general `MapReduce` logic that all of them follow. The main idea is to split the massive dataset into smaller pieces using a partitioning strategy. The process works in two simple phases:



- **Map Phase:** First, the dataset is split into smaller groups, partitions. Each worker takes one group and finds the no-dominated points within that specific group, (Local Skyline). Any point that is dominated here is thrown away immediately, as it cannot be part of the final result.

- **Reduce Phase** The surviving points from the Local Skylines from all workers are sent to a central node. Here, we compare them one last time to check if they are dominated by points from other previous groups. The points that survive this final check constitute the final Global Skyline of the dataset.

We can proceed to analyze the three specific partitioning algorithms

MR-Dim

The MR-Dim algorithm operates in two distinct stages: the Partitioning Job and the Merging Job. In the first stage, the dataset is divided into subspaces based strictly on the values of a single dimension. The number of partitions, denoted as N_p, is set to be the number of available worker nodes.


V_{max} represents the maximum value of the selected dimension, the range of each partition is defined as

$$Range = \frac{V_{max}}{N_p}$$

Every data point is assigned to a specific partition ID based on the formula:

$$PartitionID = \left\lfloor \frac{value}{Range} \right\rfloor$$

After the data is split, each worker independently calculates the Local Skyline using the standard Block Nested Loop algorithm. Finally, all these local results are gathered in one central place. There, they are compared against each other one last time to remove any remaining dominated points and produce the final Global Skyline.



MR-Grid

As mentioned in various discussions during class, we did not have to modify any code in terms of architecture for Flink, we only had to modify the `Algorithms.scala` file to provide the algorithm's implementation, as well as the `Job.scala` to properly call the algorithm, same as

MR-Dim.
The MR-Grid also operates in the Partitioning Job and Merging Job stages. Our objective is to decompose the original dataset into smaller subspaces, compute the local skylines, then merge these results to produce the global skyline.
In constrast to MR-Dim, which parittions the dataset using one dimension, the MR-Grid partitions the dataspace in multiple dimensions simultaneously (2, in our case). In the 2D case, the dataspace split results in rectangular partitions.
Let us denote as N_p the number of workers, then to construct a balanced grid, each dimension is divided in $g = \sqrt{N_p}$ equal ranges, resulting in total g^2 grid cells (partitions).
Since we have 4 partitions for this job, $g = 2$ cells per dimension.

Assuming the max value of each dimension is V_{max}, the size of each grid cell along a dimension is

$$Cellsize = \frac{V_{max}}{g}$$


Each data point (x, y) is assigned to a cell based on its coordinates. The cell indices in each dimension are computed as:

$$i_x = [\frac{x}{Cellsize}], i_y = [\frac{y}{Cellsize}]$$

The final partitionID is obtained by linearizing the 2D cell coordinates:

$$partID = i_x \cdot g + i_y$$

With this scheme, each point is assigned to exactly one cell, therefore to one worker node.
After partitioning, each worker independently produces the local skyline of its own points, using the BNL skyline algorithm. Due to the tighter bounds imposed by the grid partitions, the number of skyline points per partition tends to be less compared to MR-Dim, which means more efficient local processing.
Once all the local skylines have been computed, and the trigger has been given to Input2, the results are collected in a central merging phase. The union of all local skylines is processed one more time to eliminate any dominated points, and the global skyline is returned.



MR-Angle

The MR-Angle follows the same 2-stage execution model as the previous two algorithms. The key distinction between them is the way that the dataspace is partitioned. MR-Angle partitions the dataset based on the angular orientation of the data points.
The logic behind this, is that partitioning the data according to angular direction groups "similar" points together (about the same y/x ratio), which can lead to smaller local skylines.


Let's once again denote N_p the number of worker nodes. The 2D space is partitioned into N_p angular sectors, each spanning an equal range of angles. For a data point (x, y), its angular coordinate θ to the x-axis is $\theta = arctan(\frac{y}{x})$.
In practice, to properly handle all edge cases (such as those who would return an undefined result for arctan), we compute the angle using the 2-argument arctan function $\theta = atan2(y, x)$ and the result is normalized in $\theta \in [0, 2\pi)$. This range is then divided into N_p same size sectors, each with angular width $width = 2\pi/N_p$.
Each data point is assigned to a partition ID, based on the sector that its angle is in :

$$partID = \frac{\theta}{width}$$

Following this strategy, each data point is assigned to one angular sector, and therefore one worker node.

After the partitioning part, each worker once again independently computes the local skyline of the points in its own angular sector, using the BNL algorithm.
Having grouped together points with similar directional characteristics, the MR-Angle reduces the number of mutually "incomparable" points in a partition. As a result, the local skyline produced by each worker tends to be smaller than those generated by MR-Dim or Grid.

Once again, when all the local skylines have been computed, their results are collected furing the merging phase, and their union is processed a final time to remove any dominated points. The result is the global skyline.



System Architecture

Our system architecture follows a traditional pipeline pattern, consisting of data sources, processing operations, and a sink.


As input, we use two Kafka Topics. The first Kafka topic, `Input1`, is connected to the `GeneratorTest.scala` module. This component produces approximately 15,000,000 random tuples (x, y), which are fed into the system. These points are then distributed to the workers to compute the local skyline before being forwarded to the global operator.

There is also a second input, `Input2`, which is connected directly to the Global Operator. This stream essentially "waits" for a user request to trigger the calculation of the skyline query.

After the final skyline is computed, the results are transferred to the output, which is another Kafka Topic named `Output`. The query results appear there at the specific moment the Global Operator receives the "query" from `Input2`.

In the intermediate stage, we have the operations performed within Flink. The data is ingested through `map()`, and using the `keyBy()` operator, it is partitioned among workers according to the specific algorithm. The local skyline is executed and computed at this stage. These local results are then gathered, connected with the `Input2` stream, and sent to the Global Operator. As mentioned, the Global Skyline is calculated only when triggered.

The pipeline described above is represented in the following figure, which illustrates our system's implementation. Having established this architecture, we proceeded to implement the three algorithms as defined in the paper:



Configurations

We implemented our project in `Scala`, utilizing `JDK 11` as the underlying environment. We defined the `build.sbt` file, which serves as the blueprint for our project. Within this file, we set the Scala version to `2.12` in order to be compatible with Apache Flink. We also set the Flink version to `1.16.2` to ensure consistency across all dependencies.

Additionally, we imported some necessary libraries. These allow us to use the DataStream API and to submit jobs to the cluster using the Web UI. We also included specific libraries to handle the connection with Apache Kafka.

build.sbt

```
name := "FlinkSkyline"

version := "0.1"

scalaVersion := "2.12.15"

val flinkVersion = "1.16.2"

resolvers += Resolver.mavenCentral

libraryDependencies ++= Seq(
  "org.apache.flink" %% "flink-streaming-scala" % flinkVersion,
  "org.apache.flink" %  "flink-clients"        % flinkVersion,
  "org.apache.flink" %  "flink-runtime-web"    % flinkVersion,
  "org.apache.flink" %  "flink-connector-kafka"% flinkVersion


)

libraryDependencies += "org.apache.flink" % "flink-connector-kafka" % "3.0.1-1.17"

Compile / run / fork := true
```

We leverage Docker to implement the services needed for the execution. These include Zookeeper and Kafka, which handle the data sources of the system. Furthermore, we set up the JobManager and TaskManager for the execution in Apache Flink.

We define these services in a `docker-compose.yml` file. This setup allows us to easily start the cluster and scale the TaskManagers to 4 nodes for parallel processing.

A special parameter that we define is the `taskmanager.numberOfTaskSlots` in the TaskManager configuration. We set this value to 1. By doing so, we ensure that each Docker container corresponds to one worker node. This setup is the key to achieving true parallelism in our experiments.



docker-compose.yml

```yaml
version: '3'
services:
  zookeeper:
    image: confluentinc/cp-zookeeper:7.4.0
    container_name: zookeeper
    environment:
      ZOOKEEPER_CLIENT_PORT: 2181
      ZOOKEEPER_TICK_TIME: 2000

  kafka:
    image: confluentinc/cp-kafka:7.4.0
    container_name: kafka
    depends_on:
      - zookeeper
    ports:
      - "9092:9092"
    environment:
      KAFKA_BROKER_ID: 1
      KAFKA_ZOOKEEPER_CONNECT: zookeeper:2181
      KAFKA_LISTENER_SECURITY_PROTOCOL_MAP: PLAINTEXT:PLAINTEXT,PLAINTEXT_INTERNAL:PLAINTEXT
      KAFKA_ADVERTISED_LISTENERS: PLAINTEXT://localhost:9092,PLAINTEXT_INTERNAL://kafka:29092
      KAFKA_LISTENERS: PLAINTEXT://0.0.0.0:9092,PLAINTEXT_INTERNAL://0.0.0.0:29092
      KAFKA_INTER_BROKER_LISTENER_NAME: PLAINTEXT_INTERNAL
      KAFKA_OFFSETS_TOPIC_REPLICATION_FACTOR: 1

  jobmanager:
    image: flink:1.17-scala_2.12-java11
    container_name: jobmanager
    ports:
      - "8081:8081"
    command: jobmanager
    environment:
      - |
        FLINK_PROPERTIES=
        jobmanager.rpc.address: jobmanager

  taskmanager:
    image: flink:1.17-scala_2.12-java11
    depends_on:
      - jobmanager
    command: taskmanager
    environment:
      - |
        FLINK_PROPERTIES=
        jobmanager.rpc.address: jobmanager
        taskmanager.numberOfTaskSlots: 1
```

The experiments to check the algorithms' performance took place on a machine with an `Intel i7` processor and 32GB of RAM.

Implementation

Experiments

Conclusion