




Characteristics:

- 1) Adopts Tube in Shell heat exchanger and with Circulating Pump.
- 2) Efficient Heat Pump SPCific Rotary compressor; Safe, Reliabels, Stable running & durable.
- 3) Efficient Saginomya four-way valve; It is very efficient in defrosting in low ambient temp
- 4) Electronic Expansion Valve (EEV) ; Making sure the best velocity of flow. that make the system to run in a stable state and reduce trouble
- 5) Tube in tube heat exchanger inside with higher heat exchange efficiency than tube in shell heat exchanger used by others, with higher reliability & longer lifetime.
- 6) Green & Environment-friendly Refrigerant : R134A
- 7) Full consideration for noise control; Compressor rubber feet specially selected to reduce vibration.
- 8) Unique super energy saving controlling system can save extra 10% energy than other units in market.
- 9) Reliable Design and Strict Quality Control; All products 100% are tested and run at the factory to assure proper operation of all components and safety switches.



Features and Protection :

High pressure protection	When water flow is too small or water temp. too high ,will prevent compressor to be damaged
Low pressure protection	protection When refrigerant leaked , prevent compressor work without pressure.
Anti - freezing protection	Prevent water pipes and water tank freezing
Water pressure protection	Water tank equipped with safty valve(T/P valve) to prevent water tank to be damaged
Timing function	Freely set heat pump start/stopping time.
Manual switch	Seperated start/stop signal can be connected with solr system(for choice)
WIFI *	Controller with WIFI function, can monitor/set water tank temp.,start /stop heat pump by mobile . (Specific models choice)
Super energy	saving mode Can save extra 10% energy than other heat pump on the market



Model Specific



Model Specific

**Heating in
Winter**



Model Specific

**Cooling in
Summer**

TECHNICAL SPECIFICATION

Model		VDHP 11000 MB
DUTY CONDITIONS	Outlet Temperature	Hot water Flow Rate (Lph)
Heating Capacity(1)	KW	10.17
	Btu/h	34717
Rated heated water output (Inlet water @ 20 °C , Amb Temp @ 25 °C)1	55 °C	250
	60 °C	210
Rated heated water output (Inlet water @ 15 °C , Amb Temp @ 20 °C)2	55 °C	200
	60 °C	180
Rated outlet water temp.	°C	55 °C
Max outlet water temp.	°C	60 °C
Rated Input Power	W	2.70
Rated Input Current	A	14.00
Power Supply		220V/1N/50Hz
Compressor	Type	Fully closed Rotary Type
	Make	PANASONIC/HIGHLY /GMCC
	Start Mode	Direct Start
	Quantity (Nos)	1.00
Water Proof Grade		IP X4
Electric Shock Protection Type		Grade I
Heat Exchanger	Type	High efficiency tube in shell heat exchanger
	Quantity (Nos)	1.00
Evaporter	Fin Type	Hydrophillic Aluminium
	Tube Type	Inner Groove Tube
Refrigerant	Throttle Type	Saginomya/ Sanhua Electronic expansion valve
	Type	R407c
Water Side	Cycle Flow (lpm)	40.00
	Pipe Size (mm)	Rc3/4(DN20)
Fan	Type	Low noise high efficiency axial type
	Input Power (W)	54.00
	Speed (rpm)	880.00
	Direction	Horizontal
	Quantity (Nos)	1.00
Protections		Under / Over voltage protection, Under /Over current protection, Open phase, Phase reversal, Phase imbalance, Compressor high discharge temperature protection, Compressor high discharge pressure protection, Compressor overload, Anti-Freeze protection.
Noise DB(A)		≤55dB(A)
Net Weight		70.00
Cabinet		Stainless steel / Powder coated steel
Dimension	Length (mm)	1000
	Width (mm)	300
	Height (mm)	620

HOT WATER Storage Tank Technical Specification and data sheet



Tank Volume (Ltr.)	750
Inner Tank Dia.	610
Outer tank Dia .	710
Inner Tank Material	4 mm CRC steel
Inner tank Coating	QuartzBlue Glass lining
Coating Thickness	0.15 to 0.5 mm
Pressure withstanding capacity	7 bar
Tank Nipple	MS
Tank Nipple size	G 1" F
Electric Element	3000 W
Sacrifice Anode	Magnesium AZ31B
Outer Tank	0.50 mm Pre-Coated GI
Insulation	High density compressed PUF Insulation
Thickness Of Insulation	50 MM

Optional Accessories for the Pressurised Tank (Safety Kit Pack)				
		WATTS 3/4-inch lead free Vacuum Relief Valve to prevent vacuum conditions that could siphon water from the system and damage water equipment.	Included	
		Safety Pressure Relief Valve 1/2" 3 Bar, Protects hot water cylinders and heating components from high pressure		
		Brass Automatic Air Vent valve 1/2" BSP male thread. It automatically removes trapped air from a central heating installation.		
Optional Accessories For Electric Backup heating				
		Mechlion Skid Mounted hot water Return pumps(1W+1S) with Horizontal Stainless steel pump along with necessary manifold and valves , with control panel with timer and temperature controller for control of operation flow: 2m3/hr @ 25 m	Not applicable	Not applicable
			Heat Pump + Tank Return Pump Safety Accessories Total GST @ 18% Grand Total	256000 46080 302080
TERMS & CONDITIONS 1. Prices applicable are Ex.Godown .F.O.R, Transportation charges extra at actual will be to dealer's account. 2. Delivery: Ex Stock else 1-2 weeks from the date of firm PO along with Advance. 3. Payment terms: 100 % advance against Pro forma 4. Packing charges : 2 % extra 5. Taxes: GST as applicable @ 18% 6. Unloading and Shifting of system to required location, installation with required plumbing and accessories will be in customer scope 7. Warranty: The unit shall carry a 12 months Standard Warranty, from date of Delivery against manufacturing defects. 8. The rates are only for the Heat pump and Hot water tank and not for any other accessories or plumbing with insulation as per site demand. 9. System comes without electric backup in case Electrical backup required it will be at @ extra. 10. Under our guidance, Complete Plumbing along with necessary accessories for heat pump and incoming power 11 . Supply to heat pump will be done by your plumbing & electrical team. 12. Pedestal details for heat pump location at site will be given by us and to be executed by customer.				
 A unit of Mechzephyr Engineering "Shed No: A70 , KSSIDC , Bommasandra Industrial Area , Bommasandra, Bangalore - 560099 Mobile : 9900095490 Email: deepak@vindsol.in Complete water Heating Solutions Domestic water heat pumps Commercial Water Heat Pumps Next Gen Thermodynamics Heat Pumps Swimming pool heat pump				