




Characteristics:

- 1) Adopts Tube in Shell heat exchanger and with inbuilt Circulating Pump inside.
- 2) Efficient Rotary compressor; Safe, Reliably, Stable running & durable.
- 3) Efficient Saginomya four-way valve; It is very efficient in defrosting in low ambient temp
- 4) Saginomya / SANHUA /EMERSON Electronic Expansion Valve (EEV) or Thermostatic expansion valve
- 5) Tube in tube heat exchanger inside with higher heat exchange efficiency than tube in shell heat exchanger used by others, with higher reliability & longer lifetime.
- 6) Green & Environment-friendly Refrigerant : R410A, R407c, R134A
- 7) Full consideration for noise control; Compressor rubber feet specially selected to reduce vibration.
- 8) Unique super energy saving controlling system can save extra 10% energy than other units in market.
- 9) Reliable Design and Strict Quality Control; All products 100% are tested and run at the factory to assure proper operation of all components and safety switches.

Core components

SCROLL COMPRESSOR  Highest durable and reliable compressor in the market EMERSON Copeland Panasonic Fully protected (High/low temp. High/low Pr. over current, phase protection) Anti liquid impact.	4 WAY REVERSING VALVE  Design ensures instantaneous changeover with minimal pressure drop. The valves are equipped with a mechanism that prevents incomplete changeover Danfoss SAGINOMYA The 4-way reversing valves are UL and CE approved SANHUA	HYDROPHILIC FINNED EVAPORATOR  The hydrophilic coated finned evaporator with enhanced frosting and corrosion resistance. The corrugated louvered fin extend heat exchanging surface, thereby facilitating more contact with inlet air and improved efficiency of the evaporator.	TITANIUM HEAT EXCHANGER  High Efficiency of Heat Exchanger Using high efficiency finned tube, heat exchange heating area is 3.6 times than the smooth tube Fins inside & outside tube creates turbulent flow of freon and water, which increases heating capacity The compact helix structure of the coil ensures sufficient heat transfer between gas and water.
ELECTRONIC EXPANSION VALVE  Effectively controls the temperature & regulates optimum refrigerant flow for best in class C.O.P. Danfoss SAGINOMYA SANHUA Better operating conditions means less faults and consequently a reduction in maintenance costs.	REFRIGERANT  Various option of Refrigerant liquid as per application that is environmentally friendly, non flammable and non toxic R410A R417A R134A R407C	LARGE AIR FLOW FAN  Wide fan blade, low noise, high temperature and abrasion resistant. Large air flow design, means more air into the system, accelerating the heat exchange and improve efficiency.	INTELLIGENT LCD CONTROLLER  One touch intelligent controller with Touch screen design, clear working condition displaying, and self-check function of error.

MAIN FUNCTIONS OF HEAT PUMPS

Heat pump protection	High pressure protection	When water flow is too small or water temp. too high ,will prevent compressor to be damaged
	Low pressure protection	When refrigerant leaked , prevent compressor work without pressure.
	Compressor over current protection	Prevent compressor to work when current over max value
	Phase protection	Wrong phase/ absent phase protection (for 380V)
	Anti-freezing protection	Prevent water pipes and water tank freezing
Project function	Water level indication	Indicate high/low water level
	constant water temp. replenishing	Replenishing water temp. can be set, make water tank temp. constant
	Timing water temp. replenishing	Can set heat pump replenish cold water at certain time
	Timing hot water supply	Can supply hot water at certain time
	Cycle water(return water) setting	Can set cycle water temp.
	Timing start/stop heat pump	Can set 2 group of start/stop timing
	Manual switch	Separated start/stop signal can be connected with solr system(for choice



Option of Heating
and cooling Model and
WIFI models with App

Note : For selective models only, Get in touch with us for further details



Nomenclature :
V - Vindsol
CHP - Commercial Heat pump
Model No : 1720
H - Heating only
WF : with wifi and App
HC : with Cooling option

TECHNICAL SPECIFICATION		
Model	Units	VCHP - 36408H
Heating capacity	kW	40
	Btu/h	134826
Rated heated water output	Litre/hr	971
Rated outlet water temp.	°C	55
Max outlet water temp.	°C	60
Power	V/Ph/Hz	380 ~415V/3PH/ 50Hz
Rated input power	kW	9.2
Rated input current	A	18
Compressor type		Scroll*2
Compressor brand		Copeland
Throttle type		Electronic expansion valve (EEV)
Fan type		Low noise high efficiency axial type
Fan direction		Vertical
Fan No.		0
Fan Input power	W	250
Fan Speed	RPM	880
Evaporator fin type		Hydrophilic aluminium
Evaporator tube type		Innergroove tube
Heat exchanger ype		High efficiency tube in tube heat exchanger
Heat exchanger No.		2
Controller type		Intelligent & LCD
Ambient Temperature	°C	(-10°C~+45 °C)
Refrigerant type		R407c
Low pressure protection		Yes
High pressure protection		Yes
Automatic defroting system		Yes
Overload protection		Yes
Water pipe size	(mm)	Rc1-1/2(DN40)
Water flow volume	m3/h	8
Cabinet		Stainless steel
Unit Size	mm	1400/810/1080
N.W	kg	330
Qty		2
Rate of each heat pump		315000
Total		630000
Testing condition : Heating: Ambient temp. (DB/WB): 25°C/20°C, water temp. (input/output): 20°C/55°C.The above data is only for reference: specific data is subject to the product		

HOT WATER Storage Tank Technical Specification and data sheet

Model			
Water tank volume lts	2500		
Insulation material	Insulation Materials Rockwool thickness 100 mm		
Cladding material	24 gauge Aluminum cladding.		
Shell / Dish end thickness	5 / 6 mm		
Inner tank coating	Enamelled Anti corrosion coat		
Inner tank material	MS		
Water conection	25 mm		
Sensor conection	1/2"		
Design working pressure	5 kgf		
Testing pressure	8 kgf		
Electrical backup connection	1 1/4".		
Connection pipes	SS		
Qty - Nos	2		
Tank with cladding and insulation Price each	165000	Total	330000

Safety Kit Pack for Pressurised Tank			Rate	Qty	Amount
	Vacuum Relief Valve GST @ 18% extra	WATTS imported 3/4 inch lead free Vacuum Relief Valve automatically allows air to enter into the piping system to prevent vacuum conditions that could siphon water from the system and damage water equipment.	2800	2	5600
	Safety Pressure Relief Valve GST @ 18% extra	Safety Pressure Relief Valve 5 Bar , Protects hot water cylinders and heating components from high pressure			
	Automatic Air Vent valve GST @ 18% extra	Automatic Air Vent valve male thread. It automatically removes trapped air from a central heating installation.			
	hot water recirculation pumps (1WS) Model No MHM 12-20 18% extra	Hot water circualtion pump Between Heat pump and the stirage tank Flow rate - 8 m3/hr @ 10 m head.Make :Mechlion	25000	2	50000
Total					55600
Consolidated Offer					
1	Rate of each heat pump				630000
2	Tank with cladding and insulation Price each				330000
3	Accessories and Applicable Pumping system				55600
				Total	1015600
				Gst @ 18%	182808
				Grand total	1198408
TERMS & CONDITIONS Prices applicable are Ex.Godown .F.O.R, Transportation charges extra at actual will be to customer account. Packing and forwarding cost 2 % extra GST @ 18 % Extra of order value Unloading/Lifting/posititoning and safe keeping will be in customer scope. Payment to be made 50% as advance along with order and balance against proforma prior to delivery. Delivery : within 8 weeks from date of confirmed order and PO The rates are only for the Heat pump / Tank / accessories mentioned in the offer and not for any other items and accessories or plumbing with insualtion. Plumbing with necessary valves for Cold water inlet & hot water outlet from storage tank under customer scope. Insulation of Hot water line will be in customers scope Electrical work like incoming power supply cabling to heat pumps under customer scope. Any civil work required at site will be in your scope for tank & heat pump positioning					
 A unit of Mechzephyr Engineering Shed No: A70 , KSSIDC , Bommasandra Industrial Area , Bommasandra, Bangalroe - 560099 Mobile : 9900095490 Email: deepak@vindsol.in Domestic water heat pumps Commercial Water Heat Pumps Next Gen Thermodynamics Heat Pumps Swimming pool heat pump Complete water Heating Solutions					