

TECHNICAL DATASHEET - HIGH TEMP DATA SHEET										
Model		VCHT 013BC	VCHT 020BC	VCHT 026BC	VCHT 040BC	VCHT 055BC	VCHT 065BC	VCHT 080BC	VCHT 110BC	VCHT 130BC
Heating capacity	kW	12.7	17.8	25.5	38.3	51	63.8	76.6	102	127.6
	Btu/h	43345	60751	87031	130717	174063	217749	261434	348126	43537
Rated heated water output Heating: Ambient temp. (DB/WB): 20°C/15°C, water temp. (input/output): 15°C/75°C	L/h	187	263	376	565	753	942	1131	1506	1884
Rated heated water output Heating: Ambient temp. (DB/WB): 25°C/20°C, water temp. (input/output): 15°C/75°C	L/h	204	285	409	614	817	1023	1228	1635	2045
Rated heated water output Heating: Ambient temp. (DB/WB): 20°C/15°C, water temp. (input/output): 15°C/60°C	L/h	248	348	499	749	997	1247	1498	1994	2495
Rated heated water output Heating: Ambient temp. (DB/WB): 25°C/20°C, water temp. (input/output): 15°C/60°C	L/h	280	392	561	843	1123	1405	1686	2246	2809
Rated outlet water temp.	°C	75	75	75	75	75	75	75	75	75
Max outlet water temp.	°C	80	80	80	80	80	80	80	80	80
Power	V/Ph/Hz	380 ~ 415V/3N~/50Hz								
Rated input power	kW	4.1	5.8	8.3	12.4	16.5	20.6	24.8	33	41
Rated input current	A	7.4	10.4	14.8	22.2	29.5	36.8	44.4	59	73.6
Compressor type		Scroll*1	Scroll*1	Scroll*2	Scroll*2	Scroll*2	Scroll*2	Scroll*4	Scroll*4	Scroll*4
Throttle type		Electronic expansion valve (EEV)								
Fan type		Low noise high efficiency axial type								
Fan direction		Vertical								
Fan No.		1	1	2	2	2	2	4	4	4
Fan input power	W	250	250	250	550	750	750	750	750	750
Fan speed	RPM	880	880	880	910	940	940	940	940	940
Evaporator fin type		Hydrophilic aluminium								
Evaporator tube type		Innergroove tube								
Heat exchanger type		High efficiency tube in tube heat exchanger								
Heat exchanger No.		1	1	2	2	2	2	4	4	4
Controller type		Intelligent &LCD								
Ambient Temperature	°C	(-10°C ~43°C)								
Refrigerant		R134A								
Low pressure protection		Yes								
High pressure protection		Yes								
Automatic defroting system		Yes								
Overload protection		Yes								
Noise in 1 meter	dB(A)	58	60	63	66	68	68	71	72	74
Water pipe size	(mm)	R1(DN25)	R1(DN25)	Rc1-1/2(DN40)	Rc1-1/2(DN40)	Rc2(DN50)	Rc2(DN50)	Rc2-1/2(DN65)	Rc2-1/2(DN65)	Rc2-1/2(DN65)
Water flow volume	m3/h	4.0	5.0	8.0	12.0	15.5	19.5	24	31	39
Cabinet		Galvanized powder coatedsteel(Stainless steel)								
N.W	kg	160	200	400	480	650	750	940	1200	1500