

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\
db\CourseDatabaseHelper.java
=====
package com.example.newbig.db;

import android.content.ContentValues;
import android.content.Context;
import android.database.Cursor;
import android.database.sqlite.SQLiteDatabase;
import android.database.sqlite.SQLiteOpenHelper;
import android.os.Environment;

import java.io.File;
import java.io.FileWriter;
import java.io.IOException;

public class CourseDatabaseHelper extends SQLiteOpenHelper
{
    // 数据库相关常量
    private static final String DATABASE_NAME =
"course_schedule.db";
    private static final int DATABASE_VERSION = 1;
    public static final String TABLE_NAME = "courses";
    public static final String COL_BUTTON_ID = "button_id";
    public static final String COL_COURSE_NAME =
"course_name";
    public static final String COL_CLASSROOM = "classroom";

    public static final String COL_COLOR_OPTION =
"color_option";

    public CourseDatabaseHelper(Context context) {
        super(context, DATABASE_NAME, null,
DATABASE_VERSION);
    }

    @Override
    public void onCreate(SQLiteDatabase db) {
        // 创建课程表, 新增 COL_COLOR_OPTION 列用于存储颜色选项
        String createTableSQL = "CREATE TABLE " + TABLE_NAME
+ " (" +
            COL_BUTTON_ID + " TEXT PRIMARY KEY, " +
            COL_COURSE_NAME + " TEXT, " +
            COL_CLASSROOM + " TEXT, " +
            COL_COLOR_OPTION + " TEXT)";
        db.execSQL(createTableSQL);
    }
}

```

```

@Override
public void onUpgrade(SQLiteDatabase db, int oldVersion,
int newVersion) {
    db.execSQL("DROP TABLE IF EXISTS " + TABLE_NAME);
    onCreate(db);
}

// 保存课程信息
public boolean saveCourse(String buttonId, String
courseName, String classroom, String colorOption) {
    SQLiteDatabase db = this.getWritableDatabase();
    ContentValues values = new ContentValues();
    values.put(COL_BUTTON_ID, buttonId);
    values.put(COL_COURSE_NAME, courseName);
    values.put(COL_CLASSROOM, classroom);
    values.put(COL_COLOR_OPTION, colorOption); // 保存颜
色选项

    long result = db.insertWithOnConflict(TABLE_NAME,
null, values, SQLiteDatabase.CONFLICT_REPLACE);
    return result != -1;
}

// 获取课程信息
public Cursor getCourse(String buttonId) {
    SQLiteDatabase db = this.getReadableDatabase();
    return db.query(TABLE_NAME, new
String[]{COL_COURSE_NAME, COL_CLASSROOM, COL_COLOR_OPTION},
COL_BUTTON_ID + "=?", new String[]{buttonId},
null, null, null);
}

// 删除课程信息
public boolean deleteCourse(String buttonId) {
    SQLiteDatabase db = this.getWritableDatabase();
    int rowsDeleted = db.delete(TABLE_NAME,
COL_BUTTON_ID + "=?", new String[]{buttonId});
    return rowsDeleted > 0; // 如果删除了至少一行数据, 返回
true
}

//=====
public boolean exportDatabase(String absolutePath) {
    SQLiteDatabase db = this.getReadableDatabase();

```

```

        Cursor cursor = null;
        try {
            //行访问查询返回的数据。这里先将其初始化为 null
            cursor = db.query(TABLE_NAME, null, null, null,
null, null, null);
            if (cursor == null) {
                return false;
            }
            if (!cursor.moveToFirst()) {
                return false;
            }

            // 获取 Download 文件夹的路径
            File downloadFolder =
Environment.getExternalStoragePublicDirectory(Environment
.DIRECTORY_DOWNLOADS);
            if (!downloadFolder.exists()) {
                downloadFolder.mkdirs(); // 如果文件夹不存在，则
创建它
            }

            // 指定文件名
            File file = new File(downloadFolder,
"courses.csv");
            FileWriter writer = new FileWriter(file);

            // 写入 csv 头信息
            writer.append(COL_BUTTON_ID).append(",")
                .append(COL_COURSE_NAME).append(",")
                .append(COL_CLASSROOM).append(",")
                .append(COL_COLOR_OPTION).append("\n");

            // 写入数据，追加字符数据的方法
            do {

writer.append(cursor.getString(cursor.getColumnIndex(COL_
BUTTON_ID))).append(",")
                .append(cursor.getString(cursor.getCo
lumnIndex(COL_COURSE_NAME))).append(",")
                .append(cursor.getString(cursor.getCo
lumnIndex(COL_CLASSROOM))).append(",")
                .append(cursor.getString(cursor.getCo
lumnIndex(COL_COLOR_OPTION))).append("\n");
            } while (cursor.moveToNext());
            writer.flush();//flush 方法可以确保在关闭文件之前，缓
冲区中的所有数据都已经真正写入到文件里
            writer.close();
            return true; // 如果执行到这里，说明文件写入成功
        } catch (IOException e) {

```

```

        e.printStackTrace();
        return false; // 如果有异常, 返回失败
    } finally {
        if (cursor != null) {
            cursor.close();
        }
    }
}

//=====
public boolean importDatabase(String[] data) {
    SQLiteDatabase db = this.getWritableDatabase();
    try {
        ContentValues values = new ContentValues();
        values.put(COL_BUTTON_ID, data[0]);
        values.put(COL_COURSE_NAME, data[1]);
        values.put(COL_CLASSROOM, data[2]);
        values.put(COL_COLOR_OPTION, data[3]);
        db.insertWithOnConflict(TABLE_NAME, null, values,
SQLiteDatabase.CONFLICT_REPLACE);
        return true;
    } catch (Exception e) {
        e.printStackTrace();
        return false;
    }
}
}

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\
db\TodoDatabaseHelper.java
=====
package com.example.newbig.db;

```

```

import android.content.ContentValues;
import android.content.Context;
import android.database.Cursor;
import android.database.sqlite.SQLiteDatabase;
import android.database.sqlite.SQLiteOpenHelper;

public class TodoDatabaseHelper extends SQLiteOpenHelper {

```

```

        // 数据库相关常量
        private static final String DATABASE_NAME =
"todo_list.db";
        private static final int DATABASE_VERSION = 1;
        public static final String TABLE_NAME = "todos";
        public static final String COL_ID = "id";
        public static final String COL_TITLE = "title";
        public static final String COL_IS_COMPLETED =
"isCompleted";
        public static final String COL_DUE_DATE = "due_date";

        public TodoDatabaseHelper(Context context) {
            super(context, DATABASE_NAME, null,
DATABASE_VERSION);
        }

        @Override
        public void onCreate(SQLiteDatabase db) {
            // 创建待办事项表
            String createTableSQL = "CREATE TABLE " + TABLE_NAME
+ " (" +
                COL_ID + " INTEGER PRIMARY KEY AUTOINCREMENT,
" +
                COL_TITLE + " TEXT, " +
                COL_IS_COMPLETED + " INTEGER, " +
                COL_DUE_DATE + " TEXT NOT NULL)";
            db.execSQL(createTableSQL);
        }

        @Override
        public void onUpgrade(SQLiteDatabase db, int oldVersion,
int newVersion) {
            db.execSQL("DROP TABLE IF EXISTS " + TABLE_NAME);
            onCreate(db);
        }

        // 保存待办事项
        public boolean saveTodo(String title, int isCompleted,
String dueDate) {
            SQLiteDatabase db = this.getWritableDatabase();
            ContentValues values = new ContentValues();
            values.put(COL_TITLE, title);
            values.put(COL_IS_COMPLETED, isCompleted);
            values.put(COL_DUE_DATE, dueDate);

            long result = db.insertWithOnConflict(TABLE_NAME,
null, values, SQLiteDatabase.CONFLICT_REPLACE);
            return result != -1;
        }

```

```

    public Cursor getAllTodos() {
        SQLiteDatabase db = this.getReadableDatabase();
        // 按照 due_date 排序, ASC 表示升序 (从最早的日期开始)
        return db.query(TABLE_NAME, new String[]{COL_ID,
COL_TITLE, COL_IS_COMPLETED, COL_DUE_DATE},
            null, null, null, null, COL_DUE_DATE + " ASC");
        // 使用 COL_DUE_DATE 排序
    }

    // 获取待办事项 (按ID查询)
    public Cursor getTodoById(int id) {
        SQLiteDatabase db = this.getReadableDatabase();
        return db.query(TABLE_NAME, new String[]{COL_TITLE,
COL_IS_COMPLETED, COL_DUE_DATE},
            COL_ID + "=?", new
String[]{String.valueOf(id)}, null, null, null);
    }

    // 更新待办事项的完成状态
    public boolean updateTodoCompletionStatus(int id,
boolean isCompleted) {
        SQLiteDatabase db = this.getWritableDatabase();
        ContentValues values = new ContentValues();
        values.put(COL_IS_COMPLETED, isCompleted);

        int rowsAffected = db.update(TABLE_NAME, values,
COL_ID + "=?", new String[]{String.valueOf(id)});
        return rowsAffected > 0;
    }

    // 删除待办事项
    public boolean deleteTodo(int id) {
        SQLiteDatabase db = this.getWritableDatabase();
        int rowsDeleted = db.delete(TABLE_NAME, COL_ID +
"=?", new String[]{String.valueOf(id)});
        return rowsDeleted > 0;
    }

    // 更新数据库中的任务
    public void updateTask(int taskId, String taskTitle,
String dueDate) {
        SQLiteDatabase db = this.getWritableDatabase();
        ContentValues values = new ContentValues();
        values.put(COL_TITLE, taskTitle);
        values.put(COL_DUE_DATE, dueDate);
        // 更新任务
        db.update(TABLE_NAME, values, COL_ID + " = ?", new
String[]{String.valueOf(taskId)});
    }

```

```
}
```

```
=====
```

```
文                件                路                径                :  
D:\code\android\NewBig\app\src\main\java\com\example\newbig\Fragment\HomeFragment.java  
=====
```

```
package com.example.newbig.Fragment;
```

```
import android.os.Bundle;  
import android.view.LayoutInflater;  
import android.view.View;  
import android.view.ViewGroup;
```

```
import androidx.activity.EdgeToEdge;  
import androidx.appcompat.app.AppCompatActivity;  
import androidx.core.graphics.Insets;  
import androidx.core.view.ViewCompat;  
import androidx.core.view.WindowInsetsCompat;  
import androidx.fragment.app.Fragment;
```

```
import com.example.newbig.EditCourseActivity;  
import com.example.newbig.R;  
import android.content.Intent;  
import android.content.SharedPreferences;  
import android.database.Cursor;  
import android.graphics.Color;  
import android.os.Bundle;  
import android.preference.PreferenceManager;  
import android.text.SpannableString;  
import android.text.Spanned;  
import android.text.style.AbsoluteSizeSpan;  
import android.text.style.ForegroundColorSpan;  
import android.view.MenuItem;  
import android.widget.Button;  
import android.widget.GridLayout;  
import android.widget.TextView;  
import android.view.View;
```

```
import androidx.annotation.NonNull;  
import androidx.annotation.Nullable;  
import androidx.appcompat.app.AppCompatActivity;  
import androidx.fragment.app.FragmentTransaction;
```

```
import com.example.newbig.db.CourseDatabaseHelper;  
import  
com.google.android.material.bottomnavigation.BottomNaviga
```

```

tionView;

import java.text.SimpleDateFormat;
import java.util.Calendar;
import java.util.Locale;
public class HomeFragment extends Fragment {

    private CourseDatabaseHelper dbHelper;
    // 按钮ID数组，按照布局文件顺序列出
    private final String[][] buttonIds = {
        {"btnMon1", "btnTue1", "btnWed1", "btnThu1",
"btnFri1", "btnSat1", "btnSun1"},
        {"btnMon2", "btnTue2", "btnWed2", "btnThu2",
"btnFri2", "btnSat2", "btnSun2"},
        {"btnMon3", "btnTue3", "btnWed3", "btnThu3",
"btnFri3", "btnSat3", "btnSun3"},
        {"btnMon4", "btnTue4", "btnWed4", "btnThu4",
"btnFri4", "btnSat4", "btnSun4"},
        {"btnMon5", "btnTue5", "btnWed5", "btnThu5",
"btnFri5", "btnSat5", "btnSun5"},
        // 如果有更多节课，继续添加按钮ID
    };
    private Button[][] buttons; // 存储所有按钮对象
    private TextView tvMon, tvTue, tvWed, tvThu, tvFri,
tvSat, tvSun;

    @Override
    public View onCreateView(LayoutInflater inflater,
ViewGroup container,
Bundle savedInstanceState) {
        // 这里加载 Fragment 的布局
        View rootView =
inflater.inflate(R.layout.fragment_home, container, false);
        dbHelper = new
CourseDatabaseHelper(getActivity()); //this关键字指的是当前的
Activity实例
        // 初始化周一 ~ 周五——周日
        buttons = new
Button[buttonIds.length][buttonIds[0].length];
        for (int row = 0; row < buttonIds.length; row++) {
            for (int col = 0; col < buttonIds[row].length;
col++) {
                // "资源ID名称", "资源类型", "应用包名"
                int resId =
requireContext().getResources().getIdentifier(buttonIds[r
ow][col], "id", requireContext().getPackageName());

                buttons[row][col] =

```

```

rootView.findViewById(resId);
        // 设置点击事件
        String buttonId = buttonIds[row][col]; // 获取按钮唯一ID
        buttons[row][col].setOnClickListener(v ->
openEditActivity(buttonId));
    }
}

// 初始化文本
tvMon = rootView.findViewById(R.id.tvMon);
tvTue = rootView.findViewById(R.id.tvTue);
tvWed = rootView.findViewById(R.id.tvWed);
tvThu = rootView.findViewById(R.id.tvThu);
tvFri = rootView.findViewById(R.id.tvFri);
tvSat = rootView.findViewById(R.id.tvSat);
tvSun = rootView.findViewById(R.id.tvSun);
updateWeekDates();

// 初始化选项来控制显示或隐藏，
getDefaultSharedPreferences 方法会返回一个默认的
SharedPreferences对象
SharedPreferences prefs =
PreferenceManager.getDefaultSharedPreferences(getActivity
());
//如果不存在，就会返回默认值false
boolean showWeekend =
prefs.getBoolean("show_weekend", false);
// 控制显示或隐藏
toggleWeekendVisibility(showWeekend);
//初始化不显示第五行
boolean showNight= prefs.getBoolean("show_night",
false);
// 控制显示或隐藏
toggleNightVisibility(showNight);

// 返回 Fragment 的根视图
return rootView;
}

//*****时间*****
private void updateWeekDates() {
    //获取的时间是当前系统时间
    Calendar calendar = Calendar.getInstance();
    // 获取当前是星期几
    int currentDayOfWeek =
calendar.get(Calendar.DAY_OF_WEEK);

```

[illegible]

```

buttons[row][weekendStartIndex].setVisibility(View.VISIBLE);
    // 设置周日按钮可见
    buttons[row][weekendStartIndex +
1].setVisibility(View.VISIBLE);
    }
    Weekend = true;

} else {
    // 设置周六和周日的TextView不可见
    tvSat.setVisibility(View.GONE);
    tvSun.setVisibility(View.GONE);
    // 隐藏周六和周日的按钮
    for (int row = 0; row < buttons.length-1; row++)
{
    // 隐藏周六按钮

buttons[row][weekendStartIndex].setVisibility(View.GONE);
    // 隐藏周日按钮
    buttons[row][weekendStartIndex +
1].setVisibility(View.GONE);
    }
    Weekend = false;
}
changeWeekendNight();
}
//*****设置晚上
boolean Night = false;
private void toggleNightVisibility(boolean show) {
    if (show) {
        for (int row = 4; row < buttons.length; row++) {
            for (int col = 0; col < 5; col++) {
                // 设置晚上按钮可见

buttons[row][col].setVisibility(View.VISIBLE);
            }
        }
        Night = true;

    } else {
        for (int row = 4; row < buttons.length; row++) {
            for (int col = 0; col < 5; col++) {
                // 设置晚上按钮可见

buttons[row][col].setVisibility(View.GONE);
            }
        }
        Night = false;
    }
}

```

```

        changeWeekendNight();
    }

    private void changeWeekendNight() {
        if(Weekend&&Night){
            buttons[4][5].setVisibility(View.VISIBLE);
            buttons[4][6].setVisibility(View.VISIBLE);
        }
    }

    /**
     *
     */
    private void openEditActivity(String buttonId) {
        Intent intent = new Intent(getActivity(),
        EditCourseActivity.class);
        intent.putExtra("BUTTON_ID", buttonId);
        startActivity(intent);
    }

    //当Activity恢复并变得可见时，刷新按钮的状态，确保用户看到的是最新的信息。
    @Override
    public void onResume() {
        super.onResume();
        refreshButtons();
    }

    private void refreshButtons() {
        for (int row = 0; row < buttons.length; row++) {
            for (int col = 0; col < buttons[row].length;
            col++) {
                setButtonTextAndColor(buttons[row][col],
                buttonIds[row][col]);
            }
        }
    }

    private void setButtonTextAndColor(Button button,
    String buttonId) {
        //从数据库中查询与buttonId对应的课程信息
        Cursor cursor = dbHelper.getCourse(buttonId);
        if (cursor != null && cursor.moveToFirst())
        {
            //将Cursor移动到第一行数据。
            String courseName =
            cursor.getString(cursor.getColumnIndex("course_name"));
            String classroom =
            cursor.getString(cursor.getColumnIndex("classroom"));
            String colorOption =
            cursor.getString(cursor.getColumnIndex("color_option"));

            // 创建 SpannableString 用于设置字体大小

```

```

        String text = courseName + " (" + classroom +
        ")";

        SpannableString spannableString = new
        SpannableString(text);
        // 课程-----加粗
        /*
        spannableString.setSpan(new
        StyleSpan(Typeface.BOLD), 0, courseName.length(),
        Spanned.SPAN_EXCLUSIVE_EXCLUSIVE); // 课程名称加粗
        */
        // 设置课程名称字体颜色为黑色
        spannableString.setSpan(new
        ForegroundColorSpan(Color.BLACK), 0, courseName.length(),
        Spanned.SPAN_EXCLUSIVE_EXCLUSIVE); // 课程名称黑色

        // 教室-----字体大小
        int classroomStartIndex = courseName.length() +
        1; // 跳过" ("字符
        int classroomEndIndex = text.length(); // 去掉右
        括号

        //SPAN_EXCLUSIVE: 这个标记意味着样式标记的起始和结束位
        置不包含在样式化范围内。也就是说,样式不会应用到标记的起始和结束字符上。
        spannableString.setSpan(new AbsoluteSizeSpan(13,
        true), classroomStartIndex, classroomEndIndex,
        Spanned.SPAN_EXCLUSIVE_EXCLUSIVE); // 小字体, 14sp
        // 设置教室名称的字体颜色为类似褐色或灰色
        int classroomColor = Color.parseColor("#8B4513");
        // 深褐色

        spannableString.setSpan(new
        ForegroundColorSpan(classroomColor), classroomStartIndex,
        classroomEndIndex, Spanned.SPAN_EXCLUSIVE_EXCLUSIVE); //
        教室名称褐色

        // 设置按钮文本
        button.setText(spannableString);
        // 设置按钮背景颜色
        setButtonColor(button, colorOption);
    } else {
        button.setText("");
        setButtonColor(button, "默认"); // 设置为默认背景
    }
    cursor.close();
}

private void setButtonColor(Button button, String
colorOption) {
    // 根据颜色选项设置背景颜色
    switch (colorOption) {
        case "白色":

```

```

        button.setBackgroundColor(Color.WHITE);
        break;
    case "粉色":

button.setBackgroundColor(Color.parseColor("#EB8C9F"));
        break;
    case "蓝色":

button.setBackgroundColor(Color.parseColor("#86B1E8"));
        break;
    case "绿色":

button.setBackgroundColor(Color.parseColor("#8FDFA6"));
        break;
    case "淡黄":

button.setBackgroundColor(Color.parseColor("#E8D087"));
        break;
    case "橙色":

button.setBackgroundColor(Color.parseColor("#F1B05B"));
        break;
    case "青色":

button.setBackgroundColor(Color.parseColor("#9FD4CD"));
        break;
    case "紫色":

button.setBackgroundColor(Color.parseColor("#D4B6E6"));
        break;
    default:
        //button.setBackgroundColor(Color.WHITE);
        button.setBackgroundColor(Color.argb(0, 255,
255, 255)); // 默认背景
        break;
    }

}

}

}

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\Fragment\SettingsFragment.java
=====
package com.example.newbig.Fragment;

import static android.app.Activity.RESULT_OK;

import android.app.Activity;
import android.appwidget.AppWidgetManager;
import android.content.ActivityNotFoundException;
import android.content.ComponentName;
import android.content.ContentResolver;
import android.content.Context;
import android.content.Intent;
import android.content.SharedPreferences;
import android.net.Uri;
import android.os.Build;
import android.os.Bundle;
import android.os.Environment;
import android.preference.PreferenceManager;
import android.provider.Settings;
import android.view.LayoutInflater;
import android.view.View;
import android.view.ViewGroup;
import android.widget.Button;
import android.widget.Toast;

import androidx.activity.EdgeToEdge;
import androidx.activity.result.ActivityResultLauncher;
import
androidx.activity.result.contract.ActivityResultContracts;
import androidx.appcompat.app.AppCompatActivity;
import androidx.core.graphics.Insets;
import androidx.core.view.ViewCompat;
import androidx.core.view.WindowInsetsCompat;
import androidx.fragment.app.Fragment;
import androidx.fragment.app.FragmentTransaction;

import com.example.newbig.CourseWidgetProvider;
import com.example.newbig.R;
import com.example.newbig.StartActivity;
import com.example.newbig.db.CourseDatabaseHelper;
import com.example.newbig.web.GuideActivity;
import com.example.newbig.web.WebActivity;
import
com.google.android.material.bottomnavigation.BottomNavigation
tionView;

import java.io.BufferedReader;

```

```

import java.io.File;
import java.io.IOException;
import java.io.InputStream;
import java.io.InputStreamReader;

public class SettingsFragment extends Fragment {

    private CourseDatabaseHelper dbHelper; // 声明 dbHelper
    private static final int REQUEST_CODE_IMPORT_FILE = 1;
    private ActivityResultLauncher<Intent> resultLauncher;

    private static final String PREFS_NAME = "WebPrefs";
    private static final String KEY_URL = "url";

    private Button showWeekendButton;
    private Button showNightButton;

    @Override
    public View onCreateView(LayoutInflater inflater,
        ViewGroup container,
        Bundle savedInstanceState) {
        View rootView =
inflater.inflate(R.layout.fragment_settings, container,
false);

        dbHelper = new
CourseDatabaseHelper(getActivity()); //this关键字指的是当前的
Activity实例

    /*******
        // 获取“使用指南”按钮
        Button guideButton =
rootView.findViewById(R.id.btn_guide);
        // 设置点击事件
        guideButton.setOnClickListener(v -> {
            // 跳转到 GuideActivity 页面
            Intent intent = new Intent(getActivity(),
GuideActivity.class);
            startActivity(intent);
        });
    /*******          显    示    周    六
    *****
        showWeekendButton =
rootView.findViewById(R.id.showWeekend); // 获取按钮
        // 获取当前是否显示周末的设置
        SharedPreferences prefs =

```

```

PreferenceManager.getDefaultSharedPreferences(getActivity()
());
    boolean showWeekend =
prefs.getBoolean("show_weekend", false);
    // 设置按钮文本
    showWeekendButton.setText(showWeekend ? "隐藏周六周日
" : "显示周六周日");
    showWeekendButton.setOnClickListener(view -> {
        // 切换状态
        boolean newState
= !prefs.getBoolean("show_weekend", false);
        SharedPreferences.Editor editor = prefs.edit();
        // 实际上没有真正完成数据存储到持久化存储(如文件)的过程。
它只是在内存中的一个SharedPreferences.Editor对象里记录了要进行的
修改操作
        editor.putBoolean("show_weekend", newState);
        //将修改提交到内存中
        editor.apply();

        // 更新按钮文本
        showWeekendButton.setText(newState ? "隐藏周六周日
" : "显示周六周日");
        // 通知主界面更新显示
        // 设置结果为 OK，通知主界面数据已更新

//=====
        Intent intent = new Intent(getActivity(),
CourseWidgetProvider.class);

        intent.setAction(AppWidgetManager.ACTION_APPWIDGET_UPDATE
); // 触发更新
        int[] appWidgetIds =
AppWidgetManager.getInstance(getActivity()).getAppWidgetI
ds(new ComponentName(getActivity(),
CourseWidgetProvider.class));

        intent.putExtra(AppWidgetManager.EXTRA_APPWIDGET_IDS,
appWidgetIds);
        requireActivity().sendBroadcast(intent);
        // 设置结果并返回，通知 MainActivity 数据已更新
        // 通知主界面更新显示
        FragmentTransaction transaction =
getActivity().getSupportFragmentManager().beginTransaction
();
        transaction.replace(R.id.fragment_container,
new HomeFragment()); // R.id.fragment_container 是你的容器
视图 ID
        transaction.addToBackStack(null); // 如果需要将此

```

```

事务添加到回退栈（可以让用户按返回键时回到原来的 Fragment）
        transaction.commit();
        // 更新底部导航条选中项
        BottomNavigationView bottomNav =
requireActivity().findViewById(R.id.bottom_navigation);
// 获取 BottomNavigationView
        if (bottomNav != null) {

bottomNav.setSelectedItemId(R.id.nav_schedule); // 更新选中
项，假设 home 的 id 是 navigation_home
        }
    });
    //***** 显示晚上
*****
    showNightButton =
rootView.findViewById(R.id.showNight); // 获取按钮
    // 获取当前是否显示周末的设置
    boolean showNight= prefs.getBoolean("show_night",
false);
    // 设置按钮文本
    showNightButton.setText(showNight ? "隐藏第五节课" :
"显示第五节课");
    showNightButton.setOnClickListener(view -> {
        // 切换状态
        boolean newState
= !prefs.getBoolean("show_night", false);
        SharedPreferences.Editor editor = prefs.edit();
        editor.putBoolean("show_night", newState);
        editor.apply();
        // 更新按钮文本
        showNightButton.setText(newState ? "隐藏第五节课" :
"显示第五节课");
        // 通知主界面更新显示
        // 设置结果为 OK，通知主界面数据已更新

//=====
        Intent intent = new Intent(getActivity(),
CourseWidgetProvider.class);

intent.setAction(AppWidgetManager.ACTION_APPWIDGET_UPDATE
); // 触发更新
        int[] appWidgetIds =
AppWidgetManager.getInstance(getActivity()).getAppWidgetI
ds(new ComponentName(getActivity(),
CourseWidgetProvider.class));

intent.putExtra(AppWidgetManager.EXTRA_APPWIDGET_IDS,
appWidgetIds);

```

```

        requireActivity().sendBroadcast(intent);
        // 设置结果并返回，通知 MainActivity 数据已更新
        // 通知主界面更新显示
        FragmentTransaction transaction =
getActivity().getSupportFragmentManager().beginTransaction();
        transaction.replace(R.id.fragment_container,
new HomeFragment()); // R.id.fragment_container 是你的容器
视图 ID
        transaction.addToBackStack(null); // 如果需要将此
事务添加到回退栈（可以让用户按返回键时回到原来的 Fragment）
        transaction.commit();
        BottomNavigationView bottomNav =
requireActivity().findViewById(R.id.bottom_navigation);
// 获取 BottomNavigationView
        if (bottomNav != null) {

bottomNav.setSelectedItemId(R.id.nav_schedule); // 更新选中
项，假设 home 的 id 是 navigation_home
        }
    });

//*****网站*****
    // 找到按钮
    Button webButton =
rootView.findViewById(R.id.webButton);
    // 设置点击监听器
    webButton.setOnClickListener(v -> {
        // 创建一个 Intent 来启动 WebActivity
        Intent intent = new Intent(getActivity(),
WebActivity.class);
        startActivity(intent);
    });
    // 设置长按监听器，清空保存的网址
    webButton.setOnLongClickListener(v -> {
        // 获取 SharedPreferences
        SharedPreferences sharedPreferences =
requireContext().getSharedPreferences(PREFS_NAME,
Context.MODE_PRIVATE);
        // 清空保存的网址

sharedPreferences.edit().remove(KEY_URL).apply();
        // 显示提示信息
        Toast.makeText(requireContext(), "已清空保存的网址
", Toast.LENGTH_SHORT).show();
        return true;
    });

```

```

    });

//*****导出*****
    // 导出按钮的点击事件
    Button exportButton =
    rootView.findViewById(R.id.exportButton);
    exportButton.setOnClickListener(v -> {
        //是否具有外部存储管理器权限的方法,大于 30
        if (Build.VERSION.SDK_INT >=
        Build.VERSION_CODES.R
        && !Environment.isExternalStorageManager()) {

        requestManageExternalStoragePermission(requireActivity());
        } else {
            File exportFile = new
            File(requireContext().getExternalFilesDir(null),
            "courses.csv");
            boolean success =
            dbHelper.exportDatabase(exportFile.getAbsolutePath());
            if (success) {
                Toast.makeText(getActivity(), "导出成功",
                Toast.LENGTH_SHORT).show();
                // 可能需要通知用户文件已保存到特定位置
            } else {
                Toast.makeText(getActivity(), "导出失败",
                Toast.LENGTH_SHORT).show();
            }
        }
    });

//
    resultLauncher = registerForActivityResult(
        new
        ActivityResultContracts.StartActivityForResult(),
        result -> {
            // 处理结果
            if (result.getResultCode() == RESULT_OK &&
            result.getData() != null) {
                Uri selectedFileUri =
                result.getData().getData();
                handleImportFile(selectedFileUri);
            }
        });

//*****导 入*****
    Button importButton =
    rootView.findViewById(R.id.importButton);
    importButton.setOnClickListener(v -> {
        Intent intent = new
        Intent(Intent.ACTION_GET_CONTENT);

```

```

        intent.setType("text/csv");
        intent.addCategory(Intent.CATEGORY_OPENABLE);
        resultLauncher.launch(intent);

    });

    return rootView;
}

//申请管理所有文件的权限，在这里传入的 activity 主要是为了提供
必要的上下文环境以及启动 Intent 所需的启动能力
private void
requestManageExternalStoragePermission(Activity activity)
{
    // Android 11 (Api 30) 或更高版本的写文件权限需要特殊申请，
    需要动态申请管理所有文件的权限
    if (Build.VERSION.SDK_INT >= Build.VERSION_CODES.R)
    {
        Intent appIntent = new
        Intent(Settings.ACTION_MANAGE_APP_ALL_FILES_ACCESS_PERMIS
        SION);
        appIntent.setData(Uri.parse("package:" +
        getContext().getPackageName()));
        try {
            activity.startActivity(appIntent);
        } catch (ActivityNotFoundException ex) {
            ex.printStackTrace();
            //不进入该应用，只进权限设置界面
            Intent allFileIntent = new
            Intent(Settings.ACTION_MANAGE_ALL_FILES_ACCESS_PERMISSION
            );
            activity.startActivity(allFileIntent);
        }
    }
}

// 处理文件选择结果
@Override
public void onActivityResult(int requestCode, int
resultCode, Intent data) {
    super.onActivityResult(requestCode, resultCode,
data);

    if (requestCode == REQUEST_CODE_IMPORT_FILE &&
resultCode == RESULT_OK) {
        // 用户选择了一个文件
        Uri selectedFileUri = data.getData();
    }
}

```

```

        if (selectedFileUri != null) {
            // 调用方法处理选择的文件
            handleImportFile(selectedFileUri);
        }
    }
}
// 读取并导入文件内容
private void handleImportFile(Uri selectedFileUri) {
    try {
        // 获取内容解析器以读取文件
        ContentResolver contentResolver =
requireContext().getContentResolver();
        //ContentResolver 类提供的一个方法
        InputStream inputStream =
contentResolver.openInputStream(selectedFileUri);
        BufferedReader reader = new BufferedReader(new
InputStreamReader(inputStream));

        // 读取文件内容并导入到数据库
        String line;
        reader.readLine(); // 跳过头信息
        while ((line = reader.readLine()) != null) {
            String[] data = line.split(",");
            // 插入或更新数据库
            dbHelper.importDatabase(data); // 传递一个字符
串数组
        }
        reader.close();
        Toast.makeText(getActivity(), " 导 入 成 功 ",
Toast.LENGTH_SHORT).show();
    } catch (IOException e) {
        e.printStackTrace();
        Toast.makeText(getActivity(), " 导 入 失 败 ",
Toast.LENGTH_SHORT).show();
    }
}
}
}

```

=====

文 件 路 径 :

D:\code\android\NewBig\app\src\main\java\com\example\newbig\Fragment\TodoFragment.java

```

=====
package com.example.newbig.Fragment;

import android.app.DatePickerDialog;
import android.content.Context;
import android.os.Bundle;
import android.os.Handler;
import android.os.Looper;
import android.view.LayoutInflater;
import android.view.View;
import android.view.ViewGroup;
import android.app.AlertDialog;
import android.database.Cursor;
import android.os.Bundle;
import android.view.LayoutInflater;
import android.view.View;
import android.view.inputmethod.InputMethodManager;
import android.widget.Button;
import android.widget.DatePicker;
import android.widget.EditText;
import android.widget.TextView;
import android.widget.TimePicker;
import android.widget.Toast;

import androidx.appcompat.app.AppCompatActivity;
import androidx.fragment.app.FragmentTransaction;
import androidx.recyclerview.widget.LinearLayoutManager;
import androidx.recyclerview.widget.RecyclerView;

import androidx.activity.EdgeToEdge;
import androidx.appcompat.app.AppCompatActivity;
import androidx.core.graphics.Insets;
import androidx.core.view.ViewCompat;
import androidx.core.view.WindowInsetsCompat;
import androidx.fragment.app.Fragment;
import java.text.SimpleDateFormat;
import java.util.ArrayList;
import java.util.Calendar;
import java.util.Date;
import java.util.List;
import java.util.Locale;
import com.example.newbig.R;
import com.example.newbig.TODO.TODO;
import com.example.newbig.TODO.TODOAdapter;
import com.example.newbig.db.TODODatabaseHelper;
import
com.google.android.material.floatingactionbutton.Floating
ActionButton;

```

```

public class TodoFragment extends Fragment {

    private TodoDatabaseHelper dbHelper;
    private RecyclerView recyclerViewTodos;
    private FloatingActionButton fabAddTodo;
    private TodoDatabaseHelper db;
    private TextView tvDate;
    private TodoAdapter todoAdapter;
    private List<Todo> todoList;

    private AlertDialog dialog; // 将 dialog 定义为类的成员变量

    @Override
    public View onCreateView(LayoutInflater inflater, ViewGroup container, Bundle savedInstanceState) {
        View rootView = inflater.inflate(R.layout.fragment_todo, container, false);

        recyclerViewTodos = rootView.findViewById(R.id.recyclerViewTodos);
        recyclerViewTodos.setLayoutManager(new LinearLayoutManager(getActivity()));
        dbHelper = new TodoDatabaseHelper(getActivity());

        // 获取任务列表并设置 Adapter
        todoList = getAllTasks();
        todoAdapter = new TodoAdapter(getActivity(), todoList);
        recyclerViewTodos.setAdapter(todoAdapter);

        // 获取添加任务按钮点击 FAB 时，弹出添加任务的弹窗
        fabAddTodo = rootView.findViewById(R.id.fabAddTodo);
        fabAddTodo.setOnClickListener(v -> showAddTaskDialog());

        //显示日期
        tvDate = rootView.findViewById(R.id.tv_date);
        updateDate();

        return rootView;
    }

    //显示日期
    private void updateDate() {
        SimpleDateFormat dateFormat = new SimpleDateFormat("yyyy-M-d ,EEEE", Locale.getDefault());
        String currentDate = dateFormat.format(new Date());
    }
}

```

```

        tvDate.setText(currentDate);
    }

    // 弹出添加任务的对话框
    private void showAddTaskDialog() {
        // 创建对话框
        AlertDialog.Builder builder = new
AlertDialog.Builder(getActivity());
        builder.setTitle("创建作业");

        // 设置自定义视图
        View view =
getLayoutInflater().inflate(R.layout.todo_edit, null);
        builder.setView(view);

        // 获取视图中的组件
        EditText editTextTitle =
view.findViewById(R.id.et_task_title);
        DatePicker datePicker =
view.findViewById(R.id.dp_datetimepicker_date);
        TimePicker timePicker =
view.findViewById(R.id.tp_datetimepicker_time);
        Button btnSave =
view.findViewById(R.id.btn_save_task);
        Button btnCancel = view.findViewById(R.id.cancel);
// 获取取消按钮
        // 让 EditText 获取焦点
        editTextTitle.requestFocus();

        // 使用 Handler 延迟执行软键盘弹出操作，确保视图已经绘制完
        成
        new Handler(Looper.getMainLooper()).postDelayed(()
-> {
            InputMethodManager imm = (InputMethodManager)
requireActivity().getSystemService(Context.INPUT_METHOD_S
ERVICE);
            imm.showSoftInput(editTextTitle,
InputMethodManager.SHOW_IMPLICIT);
        }, 300);
        // 设置 TimePicker 的初始时间为 23:00
        timePicker.setHour(23);
        timePicker.setMinute(00);
        // 设置 TimePicker 为 24 小时制
        timePicker.setIs24HourView(true);

        // 显示对话框
        builder.setCancelable(true);
    }

```

```

        dialog = builder.create();

        dialog.show();

        // 设置按钮的点击事件
        btnSave.setOnClickListener(v -> {
            String taskTitle =
            editTextTitle.getText().toString();
            int day = datePicker.getDayOfMonth();
            int month = datePicker.getMonth();
            int year = datePicker.getYear();
            int hour = timePicker.getHour();
            int minute = timePicker.getMinute();

            // 格式化截止日期
            Calendar calendar = Calendar.getInstance();
            calendar.set(year, month, day, hour, minute);
            Date dueDate = calendar.getTime();
            String dueDateString =
            SimpleDateFormat("yyyy-MM-dd HH:mm",
            Locale.getDefault()).format(dueDate);
            //yyyy-MM-dd HH:mm

            // 保存作业数据到数据库
            saveTask(taskTitle, dueDateString);
            // 关闭弹窗
            dialog.dismiss(); // 保存后关闭对话框

        });
        // 设置取消按钮的点击事件
        btnCancel.setOnClickListener(v -> {
            // 关闭弹窗
            dialog.dismiss(); // 点击取消关闭对话框
        });
    }

    // 保存任务到数据库
    private void saveTask(String taskTitle, String dueDate)
    {
        // 使用 TodoDatabaseHelper 保存任务
        boolean result = dbHelper.saveTodo(taskTitle, 0,
        dueDate); // 默认完成状态是 0 (未完成)

        if (result) {
            // 如果保存成功, 更新 UI 或显示提示
            Toast.makeText(getActivity(), "保存成功!",

```

```

Toast.LENGTH_SHORT).show();

        // 添加任务后刷新 RecyclerView
        todoList.clear();
        todoList.addAll(getAllTasks());
        todoAdapter.notifyDataSetChanged();
    } else {
        // 如果保存失败，显示错误提示
        Toast.makeText(getActivity(), "保存失败...",
Toast.LENGTH_SHORT).show();
    }

}

// 获取所有任务
private List<Todo> getAllTasks() {
    List<Todo> tasks = new ArrayList<>();
    Cursor cursor = dbHelper.getAllTodos(); // 假设你已在数据库 helper 中创建了这个方法
    if (cursor != null && cursor.moveToFirst()) {
        do {
            int id = cursor.getInt(cursor.getColumnIndex("id"));
            String title = cursor.getString(cursor.getColumnIndex("title"));
            int isCompleted = cursor.getInt(cursor.getColumnIndex("isCompleted"));
            String dueDate = cursor.getString(cursor.getColumnIndex("due_date"));
            tasks.add(new Todo(id, title, isCompleted, dueDate));
        } while (cursor.moveToNext());
        cursor.close();
    }
    return tasks;
}

}

```

=====

文 件 路 径 :

D:\code\android\NewBig\app\src\main\java\com\example\newbig\Todo\Todo.java

=====

```
package com.example.newbig.Todo;
```

```
public class Todo {
    private int id;
    private String title;
    private int isCompleted;
    private String dueDate;

    // 构造函数
    public Todo(int id, String title, int isCompleted,
String dueDate) {
        this.id = id;
        this.title = title;
        this.isCompleted = isCompleted;
        this.dueDate = dueDate;
    }
    //将待办事项所涉及的关键属性(如 id、title、isCompleted、dueDate)
    进行了统一的封装,清晰地定义了一个待办事项在程序中所需要包含的各项信息
    // Getter and Setter 方法
    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public int getIsCompleted() {
        return isCompleted;
    }

    public void setIsCompleted(int isCompleted) {
        this.isCompleted = isCompleted;
    }

    public String getDueDate() {
        return dueDate;
    }
}
```

```

        public void setDueDate(String dueDate) {
            this.dueDate = dueDate;
        }
    }
}

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\
ig\Todo\TodoAdapter.java
=====

```

```

package com.example.newbig.Todo;

import android.app.AlertDialog;
import android.content.Context;
import android.database.Cursor;
import android.graphics.Color;
import android.util.Log;
import android.view.LayoutInflater;
import android.view.View;
import android.view.ViewGroup;
import android.widget.AdapterView;
import android.widget.Button;
import android.widget.CheckBox;
import android.widget.CompoundButton;
import android.widget.DatePicker;
import android.widget.EditText;
import android.widget.TextView;
import android.widget.TimePicker;

import androidx.appcompat.app.AppCompatActivity;
import androidx.fragment.app.Fragment;
import androidx.fragment.app.FragmentManager;
import androidx.fragment.app.FragmentTransaction;
import androidx.recyclerview.widget.RecyclerView;

;

import com.example.newbig.Fragment.TodoFragment;
import com.example.newbig.R;
import com.example.newbig.db.TodoDatabaseHelper;

import java.text.ParseException;
import java.text.SimpleDateFormat;
import java.util.ArrayList;
import java.util.Calendar;
import java.util.Date;
import java.util.List;
import java.util.Locale;

```

```

public class TodoAdapter extends
RecyclerView.Adapter<TodoAdapter.TODOViewHolder> {

    private Context context;
    private List<Todo> todoList;
    private TodoDatabaseHelper db;
    private AlertDialog dialog; // 声明 dialog 变量
    private TodoDatabaseHelper dbHelper;

    // 构造函数，传入数据
    public TodoAdapter(Context context, List<Todo> todoList)
    {
        this.context = context;
        this.todoList = todoList;
        this.db = new TodoDatabaseHelper(context); // 初始
        化数据库助手
        this.dbHelper = new TodoDatabaseHelper(context); //
        初始化 dbHelper
    }

    // 创建 RecyclerView 中每个列表项对应的 ViewHolder 实例
    @Override
    public TODOViewHolder onCreateViewHolder(ViewGroup
parent, int viewType) {
        View view =
        LayoutInflater.from(context).inflate(R.layout.todo_item,
parent, false);
        return new TODOViewHolder(view);
    }

    // 绑定数据到 ViewHolder
    @Override
    public void onBindViewHolder(TODOViewHolder holder, int
position) {
        Todo todo = todoList.get(position);
        holder.title.setText(todo.getTitle());
        holder.dueDate.setText(todo.getDueDate());
        holder.checkbox.setChecked(todo.getIsCompleted() ==
1);

        // 计算剩余天数
        String dueDateString = todo.getDueDate(); // 任务的
        截止日期，格式为 "yyyy-MM-dd"
        SimpleDateFormat dateFormat = new
        SimpleDateFormat("yyyy-MM-dd", Locale.getDefault());
        try {
            // 解析截止日期
            Date dueDate = dateFormat.parse(dueDateString);

```

```

        // 获取当前日期并清除时间部分（将小时、分钟、秒、毫秒清零）
        Calendar currentCalendar =
Calendar.getInstance();
        currentCalendar.set(Calendar.HOUR_OF_DAY, 0);
        currentCalendar.set(Calendar.MINUTE, 0);
        currentCalendar.set(Calendar.SECOND, 0);
        currentCalendar.set(Calendar.MILLISECOND, 0);

        // 获取当前日期的时间戳（以毫秒为单位）
        Date currentDate = currentCalendar.getTime();

        // 计算剩余天数
        long differenceInMillis = dueDate.getTime() -
currentDate.getTime();
        long remainingDays = differenceInMillis / (1000
* 60 * 60 * 24); // 将毫秒转换为天数

        // 更新 UI 显示剩余天数
        if (remainingDays > 1) {
            holder.txvHave.setText(" 还 剩 " +
remainingDays + " 天");
            holder.txvHave.setTextColor(Color.BLACK);
// 默认黑色
        } else if (remainingDays == 1) {
            holder.txvHave.setText("明天截止");

holder.txvHave.setTextColor(Color.parseColor("#F4A6C3"));
// 设置红色
        } else if (remainingDays == 0) {
            holder.txvHave.setText("今天截止");

holder.txvHave.setTextColor(Color.parseColor("#FF6347"));
        } else {
            // 显示已过期
            holder.txvHave.setText("已过期");
            holder.txvHave.setTextColor(Color.GRAY); //
设置灰色
        }

    } catch (ParseException e) {
        e.printStackTrace();
        holder.txvHave.setText("日期错误");
    }

    // 为复选框设置状态改变监听器

holder.checkbox.setOnCheckedChangeListener((buttonView,

```

```

isChecked) -> {
    if (isChecked) {
        // 任务完成，删除任务
        deleteTodo(todo.getId(), position);
    } else {
        // 取消完成，更新任务状态
        updateTodoStatus(todo.getId(), false);
    }
});

// 为每个 item 设置点击监听，点击后打开编辑页面
holder.itemView.setOnClickListener(v -> {
    showEditTaskDialog(todo);
});
}

@Override
public int getItemCount() {
    return todoList.size();
}

// 删除待办事项的方法
private void deleteTodo(int id, int position) {
    db.deleteTodo(id); // 从数据库中删除
    todoList.remove(position); // 从列表中移除
    notifyItemRemoved(position); // 通知适配器项已删除
    notifyItemRangeChanged(position, todoList.size());
// 通知适配器数据已更改
}

// 更新待办事项完成状态的方法
private void updateTodoStatus(int id, boolean
isCompleted) {
    db.updateTodoCompletionStatus(id, isCompleted); //
更新数据库中的完成状态
}

// ViewHolder 类
public class TodoViewHolder extends
RecyclerView.ViewHolder {
    TextView title, dueDate, txvHave;
    CheckBox checkbox;

    public TodoViewHolder(View itemView) {
        super(itemView);
        title
itemView.findViewById(R.id.textViewTitle);
        dueDate
itemView.findViewById(R.id.textViewDueDate);

```

```

        checkbox =
itemView.findViewById(R.id.checkboxCompleted);
        txvHave = itemView.findViewById(R.id.txv_have);
    }

    private void showEditTaskDialog(Todo todo) {
        // 获取 LayoutInflater 和创建对话框
        LayoutInflater inflater =
LayoutInflater.from(context);
        View view = inflater.inflate(R.layout.todo_edit,
null);

        // 创建对话框
        AlertDialog.Builder builder = new
AlertDialog.Builder(context);
        builder.setTitle("编辑作业");
        builder.setView(view);

        // 获取视图中的组件
        EditText editTextTitle =
view.findViewById(R.id.et_task_title);
        DatePicker datePicker =
view.findViewById(R.id.dp_datetimepicker_date);
        TimePicker timePicker =
view.findViewById(R.id.tp_datetimepicker_time);
        Button btnSave =
view.findViewById(R.id.btn_save_task);
        Button btnCancel = view.findViewById(R.id.cancel);

        // 填充现有任务数据
        editTextTitle.setText(todo.getTitle());
        // 拆分日期和时间
        String[] dateParts = todo.getDueDate().split(" ");
        String[] date = dateParts[0].split("-");
        datePicker.updateDate(Integer.parseInt(date[0]),
Integer.parseInt(date[1]) - 1, Integer.parseInt(date[2]));

        String[] timeParts = dateParts[1].split(":");
        timePicker.setHour(Integer.parseInt(timeParts[0]));

        timePicker.setMinute(Integer.parseInt(timeParts[1]));
        timePicker.setIs24HourView(true);

        // 设置保存按钮的点击事件
        btnSave.setOnClickListener(v -> {
            String taskTitle =
editTextTitle.getText().toString();
            int day = datePicker.getDayOfMonth();
            int month = datePicker.getMonth();

```

```

        int year = datePicker.getYear();
        int hour = timePicker.getHour();
        int minute = timePicker.getMinute();

        // 格式化截止日期
        Calendar calendar = Calendar.getInstance();
        calendar.set(year, month, day, hour, minute);
        Date dueDate = calendar.getTime();
        String dueDateString = new
SimpleDateFormat("yyyy-MM-dd HH:mm",
Locale.getDefault()).format(dueDate);
        // ///yyyy-MM-dd HH:mm
        // 更新任务到数据库
        updateTask(todo.getId(), taskTitle,
dueDateString);

        // 关闭对话框
        dialog.dismiss(); // 保存后关闭对话框
    });

    // 设置取消按钮的点击事件
    btnCancel.setOnClickListener(v -> {
        dialog.dismiss(); // 取消时关闭对话框
    });

    // 显示对话框
    builder.setCancelable(true);
    dialog = builder.create();
    dialog.show();
}

// 更新任务的方法
private void updateTask(int taskId, String taskTitle,
String dueDate) {
    // 更新任务数据到数据库
    dbHelper.updateTask(taskId, taskTitle, dueDate);
    // 更新列表并刷新 RecyclerView
    todoList.clear();
    todoList.addAll(getAllTasks()); // 获取所有任务并更新
列表
    notifyDataSetChanged(); // 通知适配器更新视图
}

// 获取所有任务
private List<Todo> getAllTasks() {
    List<Todo> tasks = new ArrayList<>();
    Cursor cursor = dbHelper.getAllTodos(); // 假设你已
在数据库 helper 中创建了这个方法

```

```

        if (cursor != null && cursor.moveToFirst()) {
            do {
                int                id                =
cursor.getInt(cursor.getColumnIndex("id"));
                String            title              =
cursor.getString(cursor.getColumnIndex("title"));
                int                isCompleted        =
cursor.getInt(cursor.getColumnIndex("isCompleted"));
                String            dueDate             =
cursor.getString(cursor.getColumnIndex("due_date"));
                tasks.add(new Todo(id, title, isCompleted,
dueDate));
            } while (cursor.moveToNext());
            cursor.close();
        }
        return tasks;
    }
}

```

```

=====
文            件            路            径            :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\
web\GuideActivity.java
=====

```

```

package com.example.newbig.web;

import android.os.Bundle;
import android.webkit.WebView;

import androidx.activity.EdgeToEdge;
import androidx.appcompat.app.AppCompatActivity;
import androidx.core.graphics.Insets;
import androidx.core.view.ViewCompat;
import androidx.core.view.WindowInsetsCompat;

import com.example.newbig.R;

public class GuideActivity extends AppCompatActivity {

    private WebView webView;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.guide_activity);
        // 获取 WebView 组件
        webView = findViewById(R.id.webview_guide);
        // 启用 JavaScript 支持
    }
}

```

```

        webView.getSettings().setJavaScriptEnabled(true);
        // 设置 WebView 客户端
        // webView.setWebViewClient(new WebViewClient());
        // 加载 assets 目录中的 guide.html 文件
        webView.loadUrl("file:///android_asset/guide.html");
    }
}

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\web\WebActivity.java
=====
package com.example.newbig.web;

import android.content.SharedPreferences;
import android.os.Bundle;
import android.webkit.WebView;
import android.webkit.WebViewClient;
import android.widget.EditText;

import androidx.activity.EdgeToEdge;
import androidx.appcompat.app.AlertDialog;
import androidx.appcompat.app.AppCompatActivity;
import androidx.core.graphics.Insets;
import androidx.core.view.ViewCompat;
import androidx.core.view.WindowInsetsCompat;

import com.example.newbig.R;

public class WebActivity extends AppCompatActivity {

    private static final String PREFS_NAME = "WebPrefs";
    private static final String KEY_URL = "url";
    private WebView webView;
    private SharedPreferences sharedPreferences;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.web_activity);

        sharedPreferences = getSharedPreferences(PREFS_NAME,
MODE_PRIVATE);
        webView = findViewById(R.id.webview);

        // 设置 WebViewClient 来处理网页导航

```

```

        webView.setWebViewClient(new WebViewClient() {
            @Override
            public boolean shouldOverrideUrlLoading(WebView
view, String url) {
                // 在 WebView 中打开链接
                view.loadUrl(url);
                return true;
            }
        });

        // 检查是否已有保存的网址
        String savedUrl =
sharedPreferences.getString(KEY_URL, null);
        if (savedUrl == null) {
            // 如果没有保存的网址，弹出输入框
            showUrlInputDialog();
        } else {
            // 如果有保存的网址，直接加载网页
            loadUrl(savedUrl);
        }

        private void showUrlInputDialog() {
            AlertDialog.Builder builder = new
AlertDialog.Builder(this);
            builder.setTitle("输入网址（以后长按按钮可清除）");

            final EditText input = new EditText(this);
            builder.setView(input);

            builder.setPositiveButton("确认", (dialog, which) ->
{
                String url = input.getText().toString();
                if (!url.isEmpty()) {
                    // 保存网址
                    sharedPreferences.edit().putString(KEY_URL,
url).apply();
                    // 加载网页
                    loadUrl(url);
                }
            });

            builder.setNegativeButton("取消", (dialog, which) ->
dialog.cancel());

            builder.show();
        }

        private void loadUrl(String url) {

```

```

        webView.getSettings().setJavaScriptEnabled(true);
        webView.loadUrl(url);
    }

    @Override
    public void onBackPressed() {
        if (webView.canGoBack()) {
            webView.goBack();
        } else {
            super.onBackPressed();
        }
    }

    @Override
    protected void onDestroy() {
        if (webView != null) {
            webView.destroy();
        }
        super.onDestroy();
    }
}

```

```

=====
文            件            路            径            :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\CourseWidgetProvider.java
=====

```

```

package com.example.newbig;

import static android.app.PendingIntent.FLAG_IMMUTABLE;

import android.os.Bundle;

import androidx.activity.EdgeToEdge;
import androidx.appcompat.app.AppCompatActivity;
import androidx.core.graphics.Insets;
import androidx.core.view.ViewCompat;
import androidx.core.view.WindowInsetsCompat;
import android.app.PendingIntent;
import android.appwidget.AppWidgetManager;
import android.content.BroadcastReceiver;
import android.content.ComponentName;
import android.content.Context;
import android.content.Intent;
import android.content.IntentFilter;
import android.content.SharedPreferences;
import android.database.Cursor;
import android.graphics.Color;
import android.preference.PreferenceManager;

```

```

import android.text.SpannableString;
import android.util.TypedValue;
import android.view.View;
import android.widget.LinearLayout;
import android.widget.RemoteViews;
import android.appwidget.AppWidgetProvider;
import android.widget.TextView;

import
androidx.localbroadcastmanager.content.LocalBroadcastManager;

import com.example.newbig.db.CourseDatabaseHelper;

public class CourseWidgetProvider extends
AppWidgetProvider {
    private final String[][] buttonIds = {
        {"btnMon1", "btnTue1", "btnWed1", "btnThu1",
"btnFri1", "btnSat1", "btnSun1"},
        {"btnMon2", "btnTue2", "btnWed2", "btnThu2",
"btnFri2", "btnSat2", "btnSun2"},
        {"btnMon3", "btnTue3", "btnWed3", "btnThu3",
"btnFri3", "btnSat3", "btnSun3"},
        {"btnMon4", "btnTue4", "btnWed4", "btnThu4",
"btnFri4", "btnSat4", "btnSun4"},
        {"btnMon5", "btnTue5", "btnWed5", "btnThu5",
"btnFri5", "btnSat5", "btnSun5"},
    };

    //=====
    @Override
    public void onUpdate(Context context, AppWidgetManager
appWidgetManager, int[] appWidgetIds) {
        super.onUpdate(context, appWidgetManager,
appWidgetIds);
        CourseDatabaseHelper dbHelper = new
CourseDatabaseHelper(context);
        //*****周六周日
        SharedPreferences prefs =
PreferenceManager.getDefaultSharedPreferences(context);
        boolean showWeekend =
prefs.getBoolean("show_weekend", false);
        //初始化不显示第五节课
        boolean showNight= prefs.getBoolean("show_night",
false);
        //*****
        // 创建一个Intent, 指向主页面
        Intent intent = new Intent(context,
StartActivity.class);
        //放置到一个新的任务栈 (Task) 中启动, 当在后台服务中检测到某

```

个条件满足，这个标志可以确保主页面在新的任务栈中启动

```
intent.setFlags(Intent.FLAG_ACTIVITY_NEW_TASK );
// 如果已经存在一个具有相同 Intent 内容，而不是重新创建一个
新的 PendingIntent
//从Android 12 开始，创建PendingIntent时必须明确指定它是
FLAG_IMMUTABLE（不可变）还是FLAG_MUTABLE（可变）。这是因为
PendingIntent可能包含敏感数据，而这个要求有助于提高安全性。
PendingIntent pendingIntent =
PendingIntent.getActivity(
context, 0, intent,
PendingIntent.FLAG_UPDATE_CURRENT|FLAG_IMMUTABLE);

//*****
*****
//循环中每次迭代的变量名
/*for (int i = 0; i < appWidgetIds.length; i++) {
    int appWidgetId = appWidgetIds[i];
    拓展用*/
    for (int appWidgetId : appWidgetIds) {
        //跨进程的场景下创建和更新桌面小组件，在桌面小组件的场景
        下，小组件运行在系统的进程空间中
        RemoteViews views = new
        RemoteViews(context.getPackageName(),
        R.layout.widget_course_layout);

        // 为每个TextView设置点击事件
        String[] days = {"周一", "周二", "周三", "周四", "
        周五"};
        for (int i = 0; i < days.length; i++) {
            int textViewId =
            context.getResources().getIdentifier("textview_" + days[i],
            "id", context.getPackageName());
            views.setOnClickPendingIntent(textViewId,
            pendingIntent);
        }

        // buttonIds是一个二维数组，包含了所有按钮的ID，包括工
        作日和周末的按钮
        for (int row = 0; row < buttonIds.length; row++)
        {
            for (int col = 0; col < buttonIds[row].length;
            col++) {
                String buttonIdStr = buttonIds[row][col];
                int buttonId =
                context.getResources().getIdentifier(buttonIdStr, "id",
                context.getPackageName());

                // 检查是否是周末按钮
```

```

        if (col >= 5 ) {
            if (showWeekend) {
                // 如果是周末按钮且设置为不显示周末，则隐藏按钮
                views.setViewVisibility(buttonId,
View.VISIBLE);
            } else {
                views.setViewVisibility(buttonId,
View.GONE);
            }
        }
        Cursor cursor =
dbHelper.getCourse(buttonIdStr);
        if (cursor != null && cursor.moveToFirst())
        {
            String courseName =
cursor.getString(cursor.getColumnIndex("course_name"));
            String classroom =
cursor.getString(cursor.getColumnIndex("classroom"));
            String colorOption =
cursor.getString(cursor.getColumnIndex("color_option"));

            // 设置字体大小，
            views.setTextSize(buttonId,
TypedValue.COMPLEX_UNIT_SP, 12);

            // 设置课程名称和教室名称
            views.setTextViewText(buttonId,
courseName + " (" + classroom + ")");

            // 调用 setBackgroundColor 的逻辑，但使用
RemoteViews
            int backgroundColor =
getColorForOption(colorOption, context);
            views.setInt(buttonId,
"setBackgroundColor", backgroundColor);
        } else {
            views.setTextViewText(buttonId, "");
            // 可设其余的没动过的按钮的背景为透明
            int transparentColorWithAlpha =
Color.argb(100, 255, 255, 255); // 50%透明度的白色
            views.setInt(buttonId,
"setBackgroundColor", transparentColorWithAlpha);
        }
        cursor.close();
    }
}

```

// 更新 RemoteViews 实例

```

        // 获取第五节课行的线性布局的ID
        int nightClassLayoutId = R.id.night_class_layout;
// 假设你的第五行线性布局的ID是 night_class_layout //
根据设置来显示或隐藏第五节课行
        // 根据设置来显示或隐藏第五节课行
        if (showNight) {
            views.setViewVisibility(nightClassLayoutId,
View.VISIBLE);
        } else {
            views.setViewVisibility(nightClassLayoutId,
View.GONE);
        }

        // 处理周六和周日的标题
        if (showWeekend) {
            views.setViewVisibility(R.id.tvSat,
View.VISIBLE);
            views.setViewVisibility(R.id.tvSun,
View.VISIBLE);
        } else {
            views.setViewVisibility(R.id.tvSat,
View.GONE);
            views.setViewVisibility(R.id.tvSun,
View.GONE);
        }

        appWidgetManager.updateAppWidget (appWidgetId,
views);
    }
}

//===== 用于接收广播消息并处理与桌面小 组 件
=====
@Override
public void onReceive(Context context, Intent intent) {
    super.onReceive(context, intent);
    // 编 辑 界 面
    intent.setAction(AppWidgetManager.ACTION_APPWIDGET_UPDATE
);
    // 这里就是看发送的动作 ( Action ) 是否 是
    ACTION_APPWIDGET_UPDATE
    if
    (AppWidgetManager.ACTION_APPWIDGET_UPDATE.equals(intent.g
etAction())) {
        // 确保重新更新小组件
        AppWidgetManager appWidgetManager =
AppWidgetManager.getInstance(context);
        //从Intent中获取了一个额外的数据，包含了需要更新的App
Widget的ID数组。

```

```

        int[] appWidgetIds =
intent.getIntArrayExtra(AppWidgetManager.EXTRA_APPWIDGET_
IDS);
        if (appWidgetIds != null) {
            onUpdate(context, appWidgetManager,
appWidgetIds); // 调用onUpdate重新更新
        }
    }
}

```

```

private int getColorForOption(String colorOption,
Context context) {
    switch (colorOption) {
        case "白色":
            return Color.WHITE;
        case "粉色":
            return Color.parseColor("#EB8C9F");
        case "蓝色":
            return Color.parseColor("#86B1E8");
        case "绿色":
            return Color.parseColor("#8FDFA6");
        case "淡黄":
            return Color.parseColor("#E8D087");
        case "橙色":
            return Color.parseColor("#F1B05B");
        case "青色":
            return Color.parseColor("#9FD4CD");
        case "紫色":
            return Color.parseColor("#D4B6E6");
        default:
            return Color.argb(100, 255, 255, 255);
    }
}
}

```

```

=====
文      件      路      径      :
D:\code\android\NewBig\app\src\main\java\com\example\newb
ig\EditCourseActivity.java
=====
package com.example.newbig;

import android.appwidget.AppWidgetManager;

```

```

import android.content.ComponentName;
import android.content.Intent;
import android.database.Cursor;
import android.os.Bundle;
import android.widget.ArrayAdapter;
import android.widget.Button;
import android.widget.EditText;
import android.widget.Spinner;
import android.widget.Toast;

import androidx.appcompat.app.AppCompatActivity;

import com.example.newbig.db.CourseDatabaseHelper;

public class EditCourseActivity extends AppCompatActivity
{
    private EditText etCourseName, etClassroom;
    private Spinner spinnerColorOptions; // 用于选择颜色的
Spinner
    private Button btnConfirm, btnDelete;
    private String buttonId; // 用于标识当前编辑的按钮
    private CourseDatabaseHelper dbHelper;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_edit_course);

        // 初始化数据库助手
        dbHelper = new CourseDatabaseHelper(this);

        // 获取传递的按钮 ID
        buttonId = getIntent().getStringExtra("BUTTON_ID");

        // 初始化控件
        etCourseName = findViewById(R.id.etCourseName);
        etClassroom = findViewById(R.id.etClassroom);
        spinnerColorOptions =
findViewById(R.id.spinnerColorOptions); // 初始化 Spinner
        btnConfirm = findViewById(R.id.btnConfirm);
        btnDelete = findViewById(R.id.btnDelete);

        // 字符序列类型, 定义了 Spinner 在未展开下拉列表时, 每个选项
在 Spinner 控件主体部分呈现的基本显示样式
        ArrayAdapter<CharSequence> adapter =
ArrayAdapter.createFromResource(this,
            R.array.color_options,
            android.R.layout.simple_spinner_item);

```

式。
//一个系统提供的布局资源ID, 定义了Spinner中每个选项的显示样

```
adapter.setDropDownViewResource(android.R.layout.simple_spinner_dropdown_item);  
spinnerColorOptions.setAdapter(adapter);
```

```
// 加载已有课程信息  
loadCourseData();
```

```
// 点击保存按钮  
btnConfirm.setOnClickListener(v -> {  
    String courseName =  
etCourseName.getText().toString();  
    String classroom =  
etClassroom.getText().toString();  
    String colorOption =  
spinnerColorOptions.getSelectedItem().toString(); // 获取选  
择的颜色
```

```
    // 保存到数据库  
    boolean isSaved = dbHelper.saveCourse(buttonId,  
courseName, classroom, colorOption);  
    if (isSaved) {  
        Toast.makeText(this, " 保 存 成 功 ",  
Toast.LENGTH_SHORT).show();
```

```
        // 发 送 一 个 广 播 , 通 知 系 统 更 新 与  
CourseWidgetProvider 相 关 的 所 有 App Widget 。  
=====
```

```
        Intent intent = new Intent(this,  
CourseWidgetProvider.class);
```

```
intent.setAction(AppWidgetManager.ACTION_APPWIDGET_UPDATE  
); // 触发更新
```

//AppWidgetManager 是 Android 系统中用于管理桌面小部件的一个重要类, 它提供了诸多操作小部件的方法, 比如查询、更新、删除等功能

//针对 CourseWidgetProvider 这个小部件组件来获取其 ID

```
        int[] appWidgetIds =  
AppWidgetManager.getInstance(this).getAppWidgetIds(new  
ComponentName(this, CourseWidgetProvider.class));
```

```
intent.putExtra(AppWidgetManager.EXTRA_APPWIDGET_IDS,  
appWidgetIds);
```

//带有更新动作以及小部件 ID 数据的 Intent 作为广播发送出去

```

        this.sendBroadcast(intent);
        finish(); // 返回主界面
    } else {
        Toast.makeText(this, "保存失败",
Toast.LENGTH_SHORT).show();
    }
});

// 点击删除按钮
btnDelete.setOnClickListener(v -> {
    boolean isDeleted =
dbHelper.deleteCourse(buttonId);
    if (isDeleted) {
        Toast.makeText(EditCourseActivity.this, "课程
已删除", Toast.LENGTH_SHORT).show();

//=====
        Intent intent = new Intent(this,
CourseWidgetProvider.class);

intent.setAction(AppWidgetManager.ACTION_APPWIDGET_UPDATE
); // 触发更新
        int[] appWidgetIds =
AppWidgetManager.getInstance(this).getAppWidgetIds(new
ComponentName(this, CourseWidgetProvider.class));

intent.putExtra(AppWidgetManager.EXTRA_APPWIDGET_IDS,
appWidgetIds);
        this.sendBroadcast(intent);

        // 返回 MainActivity 并刷新
        setResult(RESULT_OK);
        finish(); // 返回 MainActivity
    } else {
        Toast.makeText(EditCourseActivity.this, "删除
失败", Toast.LENGTH_SHORT).show();
    }
});

}

private void loadCourseData() {
    // 获取当前按钮ID的课程数据
    Cursor cursor = dbHelper.getCourse(buttonId);
    if (cursor != null && cursor.moveToFirst()) {
        // 填充已有数据

```

```

etCourseName.setText(cursor.getString(cursor.getColumnIndex("course_name")));

etClassroom.setText(cursor.getString(cursor.getColumnIndex("classroom")));

        // 获取表示颜色选项的字符串，然后在 Spinner中找到与之匹配的选项位置，并将 Spinner 的选中项设置为该位置对应的选项
        String colorOption =
cursor.getString(cursor.getColumnIndex("color_option"));
        ArrayAdapter<CharSequence> adapter =
(ArrayAdapter<CharSequence>)
spinnerColorOptions.getAdapter();
        int position = adapter.getPosition(colorOption);
// 获取颜色选项的位置
        spinnerColorOptions.setSelection(position); //
设置 Spinner 中的选项

    }
    cursor.close();
}
}

```

```

=====
文 件 路 径 :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\SplashActivity.java
=====
package com.example.newbig;

import android.content.Intent;
import android.os.Bundle;
import android.os.Handler;
import androidx.appcompat.app.AppCompatActivity;

public class SplashActivity extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_splash); // 使用上面创建的开屏布局

        // 延时 2 秒后跳转到主界面
        new Handler().postDelayed(() -> {
            // 启动 StartActivity 或者你的目标 Activity
            Intent intent = new Intent(SplashActivity.this,

```

```

        startActivity(intent);
        finish(); // 结束 SplashActivity, 防止用户按返回键
        回到开屏
    }, 100); // 设置延时 2 秒 (根据需要调整)
    }
}

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\java\com\example\newbig\StartActivity.java
=====
package com.example.newbig;

import android.os.Bundle;
import android.util.Log;
import android.view.MenuItem;

import androidx.annotation.NonNull;
import androidx.appcompat.app.AppCompatActivity;
import androidx.fragment.app.Fragment;
import androidx.fragment.app.FragmentManager;
import androidx.fragment.app.FragmentTransaction;

import com.example.newbig.Fragment.HomeFragment;
import com.example.newbig.Fragment.SettingsFragment;
import com.example.newbig.Fragment.TODOFragment;
import
com.google.android.material.bottomnavigation.BottomNavigationView;

public class StartActivity extends AppCompatActivity {

    // 创建一个 BottomNavigationView 的监听器
    private
    BottomNavigationView.OnNavigationItemSelectedListener
    mOnNavigationItemSelectedListener
        =
        new
    BottomNavigationView.OnNavigationItemSelectedListener() {
        @Override
        public boolean onNavigationItemSelectedListener(@NonNull
        MenuItem item) {
            Fragment fragment = null;

            // 使用 item.getItemId() 获取选中的菜单项 ID
            switch (item.getItemId()) {
                case R.id.nav_schedule:

```

```

        fragment = new HomeFragment();
        break;
    case R.id.nav_undo:
        fragment = new TodoFragment();
        break;
    case R.id.nav_settings:
        fragment = new SettingsFragment();
        break;
    }

    if (fragment != null) {
        getSupportFragmentManager().beginTransaction()
            .replace(R.id.fragment_container,
                fragment)
            .commit();
        return true;
    }
    return false;
}

};

@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_start);

    // 获取 BottomNavigationView
    BottomNavigationView navigation =
        findViewById(R.id.bottom_navigation);

    navigation.setOnNavigationItemSelectedListener(mOnNavigationItemSelectedListener);

    // 默认显示 HomeFragment
    if (savedInstanceState == null) {
        getSupportFragmentManager().beginTransaction()
            .replace(R.id.fragment_container, new
                HomeFragment())
            .commit();
    }
}
}

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\drawable\gradient
_background.xml
=====
<shape
xmlns:android="http://schemas.android.com/apk/res/android
">
    <gradient
        android:type="linear"
        android:startColor="#7583B2"
        android:endColor="#4D5377"
        />
    <corners
        android:radius="10dp"/> <!-- 设置圆角的半径 -->
</shape>
    <!--7583B2-->

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\drawable\ic_delet
e.xml
=====
<?xml version="1.0" encoding="utf-8"?>
<!-- res/drawable/ic_delete.xml -->
<vector
xmlns:android="http://schemas.android.com/apk/res/android
"
    android:width="20dp"
    android:height="20dp"
    android:viewportWidth="20"
    android:viewportHeight="20">
<path
    android:fillColor="#F2EAEA"
    android:pathData="M16,9V7H8v2H6v12h12V9h-2zM8,3h8v2H8V3z"
    />
    </vector>

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\drawable\ic_launc
her_foreground.xml
=====
<vector
xmlns:android="http://schemas.android.com/apk/res/android
"

```

```

xmlns:aapt="http://schemas.android.com/aapt"
android:width="108dp"
android:height="108dp"
android:viewportWidth="108"
android:viewportHeight="108">
<path android:pathData="M31,63.928c0,0 6.4,-11 12.1,-
13.1c7.2,-2.6 26,-1.4 26,-1.4l38.1,38.1l107,108.928l-32,-
1l31,63.928z">
  <aapt:attr name="android:fillColor">
    <gradient
      android:endX="85.84757"
      android:endY="92.4963"
      android:startX="42.9492"
      android:startY="49.59793"
      android:type="linear">
      <item
        android:color="#44000000"
        android:offset="0.0" />
      <item
        android:color="#00000000"
        android:offset="1.0" />
    </gradient>
  </aapt:attr>
</path>
<path
  android:fillColor="#FFFFFF"
  android:fillType="nonZero"
  android:pathData="M65.3,45.828l3.8,-6.6c0.2,-0.4
0.1,-0.9 -0.3,-1.1c-0.4,-0.2 -0.9,-0.1 -1.1,0.3l-3.9,6.7c-
6.3,-2.8 -13.4,-2.8 -19.7,0l-3.9,-6.7c-0.2,-0.4 -0.7,-0.5
-1.1,-0.3C38.8,38.328 38.7,38.828
38.9,39.228l3.8,6.6C36.2,49.428 31.7,56.028
31,63.928h46C76.3,56.028 71.8,49.428
65.3,45.828zM43.4,57.328c-0.8,0 -1.5,-0.5 -1.8,-1.2c-0.3,-
0.7 -0.1,-1.5 0.4,-2.1c0.5,-0.5 1.4,-0.7 2.1,-0.4c0.7,0.3
1.2,1 1.2,1.8C45.3,56.528 44.5,57.328
43.4,57.328L43.4,57.328zM64.6,57.328c-0.8,0 -1.5,-0.5 -
1.8,-1.2s-0.1,-1.5 0.4,-2.1c0.5,-0.5 1.4,-0.7 2.1,-
0.4c0.7,0.3 1.2,1 1.2,1.8C66.5,56.528 65.6,57.328
64.6,57.328L64.6,57.328z"
  android:strokeWidth="1"
  android:strokeColor="#00000000" />
</vector>

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\layout\activity_e
dit_course.xml
=====

```

```

<LinearLayout
xmlns:android="http://schemas.android.com/apk/res/android"
"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:padding="16dp"
    android:background="@drawable/liu">

<!-- 课程名称行 -->

<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:paddingBottom="8dp">
<!-- 课程名称说明 -->
<TextView
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="课程名称: "
    android:textSize="16sp"
    android:layout_gravity="center_vertical" />
<!-- 课程名称输入框 -->
<EditText
    android:id="@+id/etCourseName"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:layout_weight="1"
    android:hint="请输入课程名称"
    android:inputType="text" />
</LinearLayout>

<!-- 教室行 -->
<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:paddingTop="16dp"
    android:paddingBottom="8dp">
<!-- 教室说明 -->
<TextView
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:layout_gravity="center_vertical"
    android:text="教室: "
    android:textSize="16sp" />
<!-- 教室输入框 -->
<EditText

```

```

        android:id="@+id/etClassroom"
        android:layout_width="329dp"
        android:layout_height="wrap_content"
        android:layout_weight="1"
        android:hint="请输入教室名称"

        android:inputType="text" />
</LinearLayout>

<!-- 选择颜色 -->
<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:layout_marginTop="10dp" >

    <TextView
        android:id="@+id/textView8"
        android:layout_width="wrap_content"
        android:layout_height="34dp"
        android:text="选择颜色: " />

    <Spinner
        android:id="@+id/spinnerColorOptions"
        android:layout_width="0dp"
        android:layout_height="wrap_content"
        android:layout_weight="100"
        />
</LinearLayout>

<!-- 确定按钮 -->
<Button
    android:id="@+id/btnConfirm"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="确定"
    android:layout_gravity="center"
    android:layout_marginTop="10dp"/>

<!-- 删除按钮 -->
<Button
    android:id="@+id/btnDelete"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:layout_gravity="center"
    android:layout_marginTop="16dp"
    android:drawableLeft="@drawable/ic_delete"
    android:text="删除课程" />

</LinearLayout>

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\layout\activity_s
plash.xml
=====
<!-- activity_splash.xml -->
<RelativeLayout
xmlns:android="http://schemas.android.com/apk/res/android
"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:background="@color/white">

    <ImageView
        android:id="@+id/splash_image"
        android:layout_width="115dp"
        android:layout_height="124dp"
        android:layout_centerInParent="true"
        android:src="@drawable/course" /> <!-- 这里替换为你自
己的开屏图标 -->

</RelativeLayout>

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\layout\activity_s
tart.xml
=====
<?xml version="1.0" encoding="utf-8"?>
<RelativeLayout
xmlns:android="http://schemas.android.com/apk/res/android
"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    android:layout_width="match_parent"
    android:layout_height="match_parent">

    <!-- 用于显示不同Fragment的容器 -->
    <FrameLayout
        android:id="@+id/fragment_container"
        android:layout_width="match_parent"
        android:layout_height="match_parent"
        android:layout_above="@id/bottom_navigation" />

    <!-- 底部导航栏 -->

```

```

<com.google.android.material.bottomnavigation.BottomNavigation
ationView
    android:id="@+id/bottom_navigation"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_alignParentBottom="true"
    android:background="#FFFFFF"
    android:elevation="8dp"
    app:menu="@menu/bottom_nav_menu" />
</RelativeLayout>

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\layout\fragment_h
ome.xml
=====

```

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android
"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    tools:context=".Fragment.HomeFragment"
    android:background="@drawable/cheng">

```

```

<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical">

```

```

<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:gravity="center"
    android:paddingTop="4dp"
    >
    <!-- 第一行：显示星期一到星期五 -->
    <TextView
        android:id="@+id/tvMon"
        android:layout_width="0dp"
        android:layout_height="wrap_content"
        android:gravity="center"
        android:text="周一"
        android:layout_weight="1"/>

```

```
<TextView
    android:id="@+id/tvTue"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:text="周二"
    android:layout_weight="1"/>

<TextView
    android:id="@+id/tvWed"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:text="周三"
    android:layout_weight="1" />

<TextView
    android:id="@+id/tvThu"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:text="周四"
    android:layout_weight="1" />

<TextView
    android:id="@+id/tvFri"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:text="周五"
    android:layout_weight="1"/>

<TextView
    android:id="@+id/tvSat"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:text="周六"
    android:layout_weight="1"
    android:visibility="gone" />

<TextView
    android:id="@+id/tvSun"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:text="周日"
    android:layout_weight="1"
    android:visibility="gone" />
```

```

</LinearLayout>
<!-- 上半部分，占 70% -->
<FrameLayout
    android:layout_width="match_parent"
    android:layout_height="match_parent">
    <!--height="0dp"并不是指视图的高度为 0，而是指视图的高
度将由weight="9.2 来动态分配-->

```

```

<!-- 课表网格布局 -->
<androidx.gridlayout.widget.GridLayout
    android:id="@+id/gridLayout"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    app:columnCount="7"
    app:layout_constraintTop_toTopOf="parent"
    app:rowCount="6"
>

```

```

<!-- 第二行到第六行：表示每节课 -->
--

```

```

<Button
    android:id="@+id/btnMon1"
    style="@style/CommonButtonStyle"
    app:layout_column="0"
    app:layout_columnWeight="1"
    app:layout_row="1"
    app:layout_rowWeight="1" />

```

```

<Button
    android:id="@+id/btnTue1"
    style="@style/CommonButtonStyle"

    app:layout_column="1"
    app:layout_columnWeight="1"
    app:layout_row="1"
    app:layout_rowWeight="1" />

```

```

<Button
    android:id="@+id/btnWed1"
    style="@style/CommonButtonStyle"

    app:layout_column="2"
    app:layout_columnWeight="1"
    app:layout_row="1"
    app:layout_rowWeight="1" />

```

```

<Button
    android:id="@+id/btnThu1"

```

```
style="@style/CommonButtonStyle"
```

```
app:layout_column="3"  
app:layout_columnWeight="1"  
app:layout_row="1"  
app:layout_rowWeight="1" />
```

```
<Button  
    android:id="@+id/btnFri1"  
    style="@style/CommonButtonStyle"
```

```
app:layout_column="4"  
app:layout_columnWeight="1"  
app:layout_row="1"  
app:layout_rowWeight="1" />
```

```
<Button  
    android:id="@+id/btnSat1"  
    style="@style/CommonButtonStyle"  
    android:visibility="gone"  
    app:layout_column="5"  
    app:layout_columnWeight="1"  
    app:layout_row="1"  
    app:layout_rowWeight="1" />
```

```
<Button  
    android:id="@+id/btnSun1"  
    style="@style/CommonButtonStyle"  
    android:visibility="gone"  
    app:layout_column="6"  
    app:layout_columnWeight="1"  
    app:layout_row="1"  
    app:layout_rowWeight="1" />
```

<!-- 继续定义其他节课（第二节到第五节），可以通过类似方式进行布局 -->

<!-- 第二行到第六行：表示每节课 -->

```
<Button  
    android:id="@+id/btnMon2"  
    style="@style/CommonButtonStyle"
```

```
app:layout_column="0"  
app:layout_columnWeight="1"  
app:layout_row="2"
```

```

        app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnTue2"
    style="@style/CommonButtonStyle"

    app:layout_column="1"
    app:layout_columnWeight="1"
    app:layout_row="2"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnWed2"
    style="@style/CommonButtonStyle"

    app:layout_column="2"
    app:layout_columnWeight="1"
    app:layout_row="2"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnThu2"
    style="@style/CommonButtonStyle"

    app:layout_column="3"
    app:layout_columnWeight="1"
    app:layout_row="2"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnFri2"
    style="@style/CommonButtonStyle"

    app:layout_column="4"
    app:layout_columnWeight="1"
    app:layout_row="2"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnSat2"
    style="@style/CommonButtonStyle"

    android:visibility="gone"

```

```

        app:layout_column="5"
        app:layout_columnWeight="1"
        app:layout_row="2"
        app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnSun2"
    style="@style/CommonButtonStyle"

    android:visibility="gone"
    app:layout_column="6"
    app:layout_columnWeight="1"
    app:layout_row="2"
    app:layout_rowWeight="1" />
<!-- 分割线 -->

<!-- 第三行 -->
<Button
    android:id="@+id/btnMon3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    app:layout_column="0"
    app:layout_columnWeight="1"
    app:layout_row="3"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnTue3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    app:layout_column="1"
    app:layout_columnWeight="1"
    app:layout_row="3"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnWed3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    app:layout_column="2"
    app:layout_columnWeight="1"
    app:layout_row="3"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnThu3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

```

```

        app:layout_column="3"
        app:layout_columnWeight="1"
        app:layout_row="3"
        app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnFri3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    app:layout_column="4"

    app:layout_columnWeight="1"
    app:layout_row="3"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnSat3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"
    android:visibility="gone"
    app:layout_column="5"
    app:layout_columnWeight="1"
    app:layout_row="3"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnSun3"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"
    android:visibility="gone"
    app:layout_column="6"
    app:layout_columnWeight="1"
    app:layout_row="3"
    app:layout_rowWeight="1" />

<!--四-->
<Button
    android:id="@+id/btnMon4"
    style="@style/CommonButtonStyle"

    app:layout_column="0"
    app:layout_columnWeight="1"
    app:layout_row="4"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnTue4"
    style="@style/CommonButtonStyle"

```

```
app:layout_column="1"
app:layout_columnWeight="1"
app:layout_row="4"
app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnWed4"
    style="@style/CommonButtonStyle"
```

```
app:layout_column="2"
app:layout_columnWeight="1"
app:layout_row="4"
app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnThu4"
    style="@style/CommonButtonStyle"
```

```
app:layout_column="3"
app:layout_columnWeight="1"
app:layout_row="4"
app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnFri4"
    style="@style/CommonButtonStyle"
```

```
app:layout_column="4"
app:layout_columnWeight="1"
app:layout_row="4"
app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnSat4"
    style="@style/CommonButtonStyle"
```

```
android:visibility="gone"
app:layout_column="5"
app:layout_columnWeight="1"
app:layout_row="4"
app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnSun4"
    style="@style/CommonButtonStyle"
```

```
        android:visibility="gone"
        app:layout_column="6"
        app:layout_columnWeight="1"
        app:layout_row="4"
        app:layout_rowWeight="1" />
```

```
<!--5-->
```

```
<Button
    android:id="@+id/btnMon5"
    style="@style/CommonButtonStyle"

    android:layout_marginTop="10dp"
    android:visibility="gone"
    app:layout_column="0"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnTue5"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    android:visibility="gone"
    app:layout_column="1"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnWed5"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    android:visibility="gone"
    app:layout_column="2"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />
```

```
<Button
    android:id="@+id/btnThu5"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"

    android:visibility="gone"
    app:layout_column="3"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />
```

```

<Button
    android:id="@+id/btnFri5"
    style="@style/CommonButtonStyle"

    android:layout_marginTop="10dp"
    android:visibility="gone"
    app:layout_column="4"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnSat5"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"
    android:visibility="gone"
    app:layout_column="5"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />

<Button
    android:id="@+id/btnSun5"
    style="@style/CommonButtonStyle"
    android:layout_marginTop="10dp"
    android:visibility="gone"
    app:layout_column="6"
    app:layout_columnWeight="1"
    app:layout_row="5"
    app:layout_rowWeight="1" />
</androidx.gridlayout.widget.GridLayout>
</FrameLayout>

```

```

</LinearLayout>

```

```

</androidx.constraintlayout.widget.ConstraintLayout>

```

```

=====
文      件      路      径      :
D:\code\android\NewBig\app\src\main\res\layout\fragment_s
ettings.xml
=====

```

```

<LinearLayout
xmlns:android="http://schemas.android.com/apk/res/android
"

```

```
xmlns:tools="http://schemas.android.com/tools"
android:id="@+id/main"
android:layout_width="match_parent"
android:layout_height="match_parent"
android:orientation="vertical"
android:padding="16dp"
android:background="@drawable/plane"
>
```

```
<Button
    android:id="@+id/importButton"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="8dp"
    android:text="导入数据" />
```

```
<Button
    android:id="@+id/exportButton"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="8dp"
    android:text="导出数据" />
```

```
<Button
    android:id="@+id/showNight"
    android:text="显示第五节课"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="8dp"/>
```

```
<Button
    android:id="@+id/showWeekend"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="8dp"
    android:text="显示周六周日" />
```

```
<Button
    android:id="@+id/webButton"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="8dp"
    android:text="学校官网" />
```

```
<Button
    android:id="@+id/btn_guide"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="8dp"
    android:text="使用指南" />
```

```
</LinearLayout>
```

```
=====
```

```
文                件                路                径                :  
D:\code\android\NewBig\app\src\main\res\layout\fragment_todo.xml
```

```
=====
```

```
<androidx.constraintlayout.widget.ConstraintLayout  
xmlns:android="http://schemas.android.com/apk/res/android"  
"
```

```
    xmlns:app="http://schemas.android.com/apk/res-auto"  
    xmlns:tools="http://schemas.android.com/tools"  
    android:layout_width="match_parent"  
    android:layout_height="match_parent"  
    android:background="@drawable/night">
```

```
<!-- 日期显示区域 -->
```

```
<TextView  
    android:id="@+id/tv_date"  
    android:layout_width="393dp"  
    android:layout_height="59dp"  
    android:layout_margin="10dp"  
    android:gravity="center"  
    android:textSize="24sp"  
    app:layout_constraintEnd_toEndOf="parent"  
    app:layout_constraintStart_toStartOf="parent"  
    app:layout_constraintTop_toTopOf="parent" />
```

```
<!-- RecyclerView 用来显示待办事项 -->
```

```
<androidx.recyclerview.widget.RecyclerView  
    android:id="@+id/recyclerViewTodos"  
    android:layout_width="411dp"  
    android:layout_height="646dp"  
    android:layout_marginTop="85dp"  
    app:layout_constraintStart_toStartOf="parent"  
    app:layout_constraintTop_toTopOf="parent" />
```

```
<!-- Snackbar for showing delete action or other  
feedback -->
```

```
<com.google.android.material.floatingactionbutton.FloatingActionButton  
    android:id="@+id/fabAddTodo"  
    android:layout_width="wrap_content"  
    android:layout_height="wrap_content"  
    android:layout_gravity="end|bottom"
```

```

        android:layout_marginEnd="32dp"
        android:layout_marginBottom="80dp"

        app:layout_constraintBottom_toBottomOf="parent"
        app:layout_constraintEnd_toEndOf="parent"
        app:srcCompat="@android:drawable/ic_input_add" />

```

```

</androidx.constraintlayout.widget.ConstraintLayout>

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\layout\guide_acti
vity.xml
=====

```

```

<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    tools:context=".web.GuideActivity">

    <WebView
        android:id="@+id/webview_guide"
        android:layout_width="match_parent"
        android:layout_height="match_parent"
        />

```

```

</androidx.constraintlayout.widget.ConstraintLayout>

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\layout\todo_edit.
xml
=====

```

```

<LinearLayout
xmlns:android="http://schemas.android.com/apk/res/android"
"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="vertical"

    android:gravity="center_vertical">

```

```
<EditText
    android:id="@+id/et_task_title"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_margin="10dp"
    android:hint="输入作业">

</EditText>

<TextView
    android:id="@+id/textView"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="截止时间: "
    android:textSize="18dp"
    android:layout_marginTop="10dp"
    android:layout_marginLeft="10dp"/>

<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:gravity="center_vertical"
    android:layout_marginTop="5dp">

    <TextView
        android:id="@+id/textView2"
        android:layout_width="103dp"
        android:layout_height="match_parent"
        android:text="年"
        android:gravity="center"/>

    <TextView
        android:id="@+id/textView3"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:layout_weight="1"
        android:gravity="center"
        android:text="月" />

    <TextView
        android:id="@+id/textView4"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:layout_weight="1"
        android:gravity="center"
        android:text="日" />

    <TextView
        android:id="@+id/textView5"
```

```

        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:layout_weight="1"
        android:gravity="center"
        android:text="时" />

<!--      <TextView
        android:id="@+id/textView6"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:layout_weight="1"
        android:gravity="center"
        android:text="分" />-->
</LinearLayout>

<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:gravity="center_vertical"
    android:layout_marginTop="5dp">

    <DatePicker
        android:id="@+id/dp_datetimepicker_date"
        android:layout_width="0dp"
        android:layout_height="wrap_content"
        android:calendarViewShown="false"
        android:spinnersShown="true"
        android:theme="@android:style/Theme.Holo.Light"
        android:layout_weight="5"/>

    <TimePicker
        android:id="@+id/tp_datetimepicker_time"
        android:layout_width="0dp"
        android:layout_height="wrap_content"
        android:theme="@android:style/Theme.Holo.Light"
        android:timePickerMode="spinner"
        android:layout_weight="2"/>
</LinearLayout>

<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginLeft="40dp"
    android:layout_marginRight="20dp"
    android:layout_marginTop="5dp"
    android:layout_marginBottom="10dp">

    <Button
        android:id="@+id/cancel"
        android:layout_width="wrap_content"

```

```

        android:layout_height="wrap_content"
        android:layout_gravity="center"
        android:layout_marginEnd="20dp"
        android:layout_weight="1"
        android:text="取消" />

<Button
    android:id="@+id/btn_save_task"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:layout_gravity="center"
    android:layout_marginEnd="20dp"
    android:layout_weight="1"
    android:text="保存作业" />

</LinearLayout>
</LinearLayout>

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\layout\todo_item.
xml
=====
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
xmlns:android="http://schemas.android.com/apk/res/android
"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:orientation="horizontal"
    android:padding="10dp"

    android:background="?android:attr/selectableItemBackground"
    >
        android:gravity="center_vertical"
        >

        <!-- CheckBox for marking as completed -->

        <androidx.appcompat.widget.AppCompatCheckBox
            android:id="@+id/checkboxCompleted"
            android:layout_width="28dp"
            android:layout_height="38dp"
            android:layout_marginEnd="16dp"
            android:layout_marginBottom="10dp"
            />

        <LinearLayout

```

```

        android:layout_width="280dp"
        android:layout_height="82dp"
        android:orientation="vertical"
        android:background="@drawable/gradient_background"
    >
    <LinearLayout
        android:layout_width="280dp"
        android:layout_height="wrap_content"
        android:orientation="horizontal">

        <TextView
            android:id="@+id/textViewDueDate"
            android:layout_width="189dp"
            android:layout_height="wrap_content"
            android:layout_weight="1"
            android:paddingLeft="5dp"
            android:paddingTop="5dp"
            android:text="2024-12-25 23:00"
            android:textColor="#FFFFFF"
            android:textSize="14sp" />

        <TextView
            android:id="@+id/txv_have"
            android:layout_width="wrap_content"
            android:layout_height="wrap_content"
            android:text="n"
            android:layout_marginRight="10dp"
            />

    </LinearLayout>
    <TextView
        android:id="@+id/textViewTitle"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:layout_weight="3"
        android:paddingTop="5dp"
        android:paddingLeft="5dp"
        android:textStyle="bold"
        android:text="Sample Todo"
        android:textColor="@android:color/black"
        android:textSize="18sp" />

</LinearLayout>

</LinearLayout>

```

=====

文 件 路 径 :
D:\code\android\NewBig\app\src\main\res\layout\web_activity.xml

```
=====
<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:id="@+id/main"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    tools:context=".web.WebActivity">
    <WebView
        android:id="@+id/webview"
        android:layout_width="match_parent"
        android:layout_height="match_parent" />
</androidx.constraintlayout.widget.ConstraintLayout>
```

文 件 路 径 :
D:\code\android\NewBig\app\src\main\res\layout\widget_course_layout.xml

```
=====
<!-- widget_course_layout-->
<LinearLayout
xmlns:android="http://schemas.android.com/apk/res/android"
"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    >

    <!-- 第一行：显示星期一到星期五 -->
    <LinearLayout
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:orientation="horizontal"
        >
        <TextView
            android:id="@+id/textview_周一"
            android:layout_width="0dp"
            android:layout_height="wrap_content"
            android:gravity="center"
            android:background="#77CFD0"
            android:text="周一"
            android:layout_weight="1" />
```

```
<TextView
    android:id="@+id/textview_周二"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:background="#77CFD0"
    android:text="周二"
    android:layout_weight="1"
/>
<TextView
    android:id="@+id/textview_周三"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:background="#77CFD0"
    android:text="周三"
    android:layout_weight="1" />
<TextView
    android:id="@+id/textview_周四"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:background="#77CFD0"
    android:text="周四"
    android:layout_weight="1" />
<TextView
    android:id="@+id/textview_周五"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:background="#77CFD0"
    android:text="周五"
    android:layout_weight="1" />
<TextView
    android:id="@+id/tvSat"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:background="#77CFD0"
    android:text="周六"
    android:layout_weight="1"
    android:visibility="gone"/>
<TextView
    android:id="@+id/tvSun"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:background="#77CFD0"
    android:text="周日"
```

```

        android:layout_weight="1"
        android:visibility="gone"/>

</LinearLayout>

<!-- 第一行：显示星期一到星期五 -->
<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:orientation="horizontal"
    android:layout_weight="1">
    <Button
        android:id="@+id/btnMon1"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
    <Button
        android:id="@+id/btnTue1"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
    <Button
        android:id="@+id/btnWed1"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
    <Button
        android:id="@+id/btnThu1"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
    <Button
        android:id="@+id/btnFri1"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
    <Button
        android:id="@+id/btnSat1"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        android:visibility="gone" />
    <Button
        android:id="@+id/btnSun1"
        android:layout_width="0dp"
        android:layout_height="match_parent"

```

```

        android:layout_weight="1"
        android:visibility="gone" />
</LinearLayout>

<!-- 继续其他行的布局 -->
<!-- 第二节课的按钮 -->
<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:orientation="horizontal"
    android:layout_weight="1"> <!-- 假设你想在第一节课和第
二节课之间有 8dp 的间距 -->

    <Button
        android:id="@+id/btnMon2"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnTue2"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnWed2"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnThu2"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnFri2"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnSat2"

```

```

        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        android:visibility="gone" />
    <Button
        android:id="@+id/btnSun2"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        android:visibility="gone" />
</LinearLayout>
<!-- 第三节课的按钮 -->
<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:orientation="horizontal"
    android:layout_weight="1"
    android:layout_marginTop="4dp"> <!-- 添加 8dp的间距 -
->

    <Button
        android:id="@+id/btnMon3"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnTue3"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnWed3"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnThu3"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnFri3"
        android:layout_width="0dp"

```

```

        android:layout_height="match_parent"
        android:layout_weight="1"
    />
<Button
    android:id="@+id/btnSat3"
    android:layout_width="0dp"
    android:layout_height="match_parent"
    android:layout_weight="1"
    android:visibility="gone" />
<Button
    android:id="@+id/btnSun3"
    android:layout_width="0dp"
    android:layout_height="match_parent"
    android:layout_weight="1"
    android:visibility="gone" />
</LinearLayout>

<!-- 第四节课的按钮 -->
<LinearLayout
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:orientation="horizontal"
    android:layout_weight="1"> <!-- 添加 8dp的间距 -->

    <Button
        android:id="@+id/btnMon4"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />

    <Button
        android:id="@+id/btnTue4"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />

    <Button
        android:id="@+id/btnWed4"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />

    <Button
        android:id="@+id/btnThu4"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />

```

```

<Button
    android:id="@+id/btnFri4"
    android:layout_width="0dp"
    android:layout_height="match_parent"
    android:layout_weight="1"
/>

<Button
    android:id="@+id/btnSat4"
    android:layout_width="0dp"
    android:layout_height="match_parent"
    android:layout_weight="1"
    android:visibility="gone" />
<Button
    android:id="@+id/btnSun4"
    android:layout_width="0dp"
    android:layout_height="match_parent"
    android:layout_weight="1"
    android:visibility="gone" />
</LinearLayout>

<!-- 第五节课的按钮 -->
<LinearLayout
    android:id="@+id/night_class_layout"
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:orientation="horizontal"
    android:layout_weight="1"
    android:layout_marginTop="4dp"
    android:visibility="gone"> <!-- 添加 8dp的间距 -->

    <Button
        android:id="@+id/btnMon5"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"

        />

    <Button
        android:id="@+id/btnTue5"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
        />

    <Button
        android:id="@+id/btnWed5"
        android:layout_width="0dp"
        android:layout_height="match_parent"

```

```

        android:layout_weight="1"
    />

    <Button
        android:id="@+id/btnThu5"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />

    <Button
        android:id="@+id/btnFri5"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"

    />

    <Button
        android:id="@+id/btnSat5"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
    <Button
        android:id="@+id/btnSun5"
        android:layout_width="0dp"
        android:layout_height="match_parent"
        android:layout_weight="1"
    />
</LinearLayout>

</LinearLayout>

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\menu\bottom_nav_m
enu.xml
=====
<?xml version="1.0" encoding="utf-8"?>
<menu
xmlns:android="http://schemas.android.com/apk/res/android
">
    <item
        android:id="@+id/nav_schedule"
        android:icon="@drawable/course"
        android:title="@string/schedule" />

```

```

        <item
            android:id="@+id/nav_undo"
            android:icon="@drawable/undo"
            android:title="@string/undo" />
        <item
            android:id="@+id/nav_settings"
            android:icon="@drawable/set"
            android:title="@string/settings" />
    </menu>

```

=====

文件路径： D:\code\android\NewBig\app\src\main\res\mipmap-anydpi\ic_launcher.xml

=====

```

<?xml version="1.0" encoding="utf-8"?>
<adaptive-icon
xmlns:android="http://schemas.android.com/apk/res/android"
">
    <foreground
android:drawable="@drawable/ic_launcher_foreground" />
    <monochrome
android:drawable="@drawable/ic_launcher_foreground" />
</adaptive-icon>

```

=====

文件路径： D:\code\android\NewBig\app\src\main\res\mipmap-anydpi\ic_launcher_round.xml

=====

```

<?xml version="1.0" encoding="utf-8"?>
<adaptive-icon
xmlns:android="http://schemas.android.com/apk/res/android"
">

    <foreground
android:drawable="@drawable/ic_launcher_foreground" />
    <monochrome
android:drawable="@drawable/ic_launcher_foreground" />
</adaptive-icon>

```

=====

文 件 路 径 :

D:\code\android\NewBig\app\src\main\res\values\colors.xml

=====

```

<?xml version="1.0" encoding="utf-8"?>
<resources>
    <color name="purple_200">#FFBB86FC</color>
    <color name="purple_500">#FF6200EE</color>
    <color name="purple_700">#FF3700B3</color>
    <color name="teal_200">#FF03DAC5</color>
    <color name="teal_700">#FF018786</color>
    <color name="black">#FF000000</color>
    <color name="white">#FFFFFFFF</color>
    <color name="red">#ffff4444</color>
    <color name="pink">#F944FF</color>
</resources>

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\values\strings.xml
1
=====

```

```

<resources>
    <string name="app_name">super课表</string>

    <string name="schedule">课表</string>
    <string name="settings">设置</string>
    <string name="undo">作业</string>

    <string-array name="color_options">
        <item>默认</item>
        <item>粉色</item>
        <item>淡黄</item>
        <item>蓝色</item>
        <item>绿色</item>
        <item>白色</item>
        <item>橙色</item>
        <item>青色</item>
        <item>紫色</item>
    </string-array>
</resources>

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\res\values\style.xml
=====
<?xml version="1.0" encoding="utf-8"?>
<resources xmlns:app="http://schemas.android.com/apk/res-
auto">

```

```

        <style name="CommonButtonStyle">
            <item name="android:layout_width">0dp</item>
            <item name="android:layout_height">0dp</item>
            <item name="android:maxHeight">200dp</item>
            <item name="android:gravity">center</item>
            <item name="android:padding">0dp</item>
            <item name="android:layout_margin">0dp</item>
            <!--<item
name="android:background">#9F5DEBC3</item>-->
        </style>
</resources>

```

```

=====
文      件      路      径      :
D:\code\android\NewBig\app\src\main\res\values\themes.xml
=====
<resources xmlns:tools="http://schemas.android.com/tools">
    <!-- Base application theme. -->
    <style name="Theme.NewBig"
parent="Theme.MaterialComponents.DayNight.NoActionBar">
        <!-- Primary brand color. -->
        <item name="colorPrimary">#7EA08C</item>
        <item name="colorPrimaryVariant">#9DC3E0</item>
        <item name="colorOnPrimary">@color/white</item>
        <!-- Secondary brand color. -->
        <item name="colorSecondary">@color/teal_200</item>
        <item
name="colorSecondaryVariant">@color/teal_700</item>
        <item name="colorOnSecondary">@color/black</item>
        <!-- Status bar color. -->
        <item
name="android:statusBarColor">?attr/colorPrimaryVariant</
item>
        <!-- Customize your theme here. -->
    </style>
</resources>

```

```

=====
文件路径: D:\code\android\NewBig\app\src\main\res\values-
night\themes.xml
=====
<resources xmlns:tools="http://schemas.android.com/tools">
    <!-- Base application theme. -->
    <style name="Theme.NewBig"
parent="Theme.MaterialComponents.DayNight.NoActionBar">
        <!-- Primary brand color. -->
        <item name="colorPrimary">#7EA08C</item>

```

```

        <item name="colorPrimaryVariant">#9DC3E0</item>
        <item name="colorOnPrimary">@color/white</item>
        <!-- Secondary brand color. -->
        <item name="colorSecondary">@color/teal_200</item>
        <item
name="colorSecondaryVariant">@color/teal_700</item>
        <item name="colorOnSecondary">@color/black</item>
        <!-- Status bar color. -->
        <item
name="android:statusBarColor">?attr/colorPrimaryVariant</
item>
        <!-- Customize your theme here. -->
    </style>
</resources>

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\xml\backup_rules.
xml
=====
<?xml version="1.0" encoding="utf-8"?><!--
    Sample backup rules file; uncomment and customize as
    necessary.
    See
https://developer.android.com/guide/topics/data/autobacku
p
    for details.
    Note: This file is ignored for devices older than API 31
    See
https://developer.android.com/about/versions/12/backup-
restore
-->
<full-backup-content>
    <!--
        <include domain="sharedpref" path="."/>
        <exclude domain="sharedpref" path="device.xml"/>
    -->
</full-backup-content>

```

```

=====
文                件                路                径                :
D:\code\android\NewBig\app\src\main\res\xml\course_widget
_info.xml
=====
<!-- res/xml/course_widget_info.xml -->
<appwidget-provider

```

```

xmlns:android="http://schemas.android.com/apk/res/android"
"
    android:minWidth="90dp"
    android:minHeight="90dp"
    android:maxWidth="300dp"
    android:maxHeight="500dp"
    android:resizeMode="horizontal|vertical"
    android:initialLayout="@layout/widget_course_layout" />

```

```

=====
文          件          路          径          :
D:\code\android\NewBig\app\src\main\AndroidManifest.xml
=====
<?xml version="1.0" encoding="utf-8"?>
<manifest
xmlns:android="http://schemas.android.com/apk/res/android"
"
    xmlns:tools="http://schemas.android.com/tools">
    <!-- 存储权限 -->
    <uses-permission
android:name="android.permission.WRITE_EXTERNAL_STORAGE"
/>
    <uses-permission
android:name="android.permission.READ_EXTERNAL_STORAGE" />
    <uses-permission

android:name="android.permission.MANAGE_EXTERNAL_STORAGE"
    tools:ignore="ScopedStorage" />
    <uses-permission
android:name="android.permission.INTERNET" />

    <application
        android:allowBackup="true"
        android:fullBackupContent="@xml/backup_rules"
        android:icon="@drawable/course"
        android:label="@string/app_name"
        android:roundIcon="@drawable/course"
        android:supportsRtl="true"
        android:theme="@style/Theme.NewBig"
        tools:targetApi="31">
        <activity
            android:name=".Fragment.TODOFragment"
            android:exported="false" />
        <activity
            android:name=".web.GuideActivity"
            android:exported="false" />
        <activity
            android:name=".web.WebActivity"
            android:exported="false" />

```

```

        <activity
            android:name=".EditCourseActivity"
            android:exported="false" />

        <activity
            android:name=".StartActivity"
            android:exported="false"/>

        <activity
            android:name=".SplashActivity"
            android:exported="true">
            <intent-filter>
                <action
                    android:name="android.intent.action.MAIN" />

                    <category
                        android:name="android.intent.category.LAUNCHER" />
                    </intent-filter>
                </activity>
            <activity
                android:name=".Fragment.SettingsFragment"
                android:exported="false" />
            <activity
                android:name=".Fragment.HomeFragment"
                android:exported="false" />

        <receiver
            android:name=".CourseWidgetProvider"
            android:exported="true">
            <intent-filter>
                <action
                    android:name="android.appwidget.action.APPWIDGET_UPDATE"
                    />
                </intent-filter>

                <meta-data
                    android:name="android.appwidget.provider"
                    android:resource="@xml/course_widget_info" />
            <!-- 这里引用了配置文件 -->
            </receiver>
        </application>

    </manifest>

```

```

=====
文件路径: D:\code\android\NewBig\app\build.gradle
=====
plugins {
    alias(libs.plugins.android.application)

```

```

}

android {
    namespace 'com.example.newbig'
    compileSdk 34

    defaultConfig {
        applicationId "com.example.newbig"
        minSdk 29
        targetSdk 34
        versionCode 1
        versionName "1.0"

        testInstrumentationRunner
"androidx.test.runner.AndroidJUnitRunner"
    }

    buildTypes {
        release {
            //开启代码混淆
            minifyEnabled true
            //移除无用的resource文件
            shrinkResources true
            //使用ProGuard
            proguardFiles getDefaultProguardFile('proguard-
android.txt'), 'proguard-rules.pro'

        }
    }
    compileOptions {
        sourceCompatibility JavaVersion.VERSION_1_8
        targetCompatibility JavaVersion.VERSION_1_8
    }
}

dependencies {

    implementation libs.appcompat
    implementation libs.material
    implementation libs.activity
    implementation libs.constraintlayout
    // testImplementation libs.junit
    //androidTestImplementation libs.ext.junit
    // androidTestImplementation libs.espresso.core

    implementation 'androidx.gridlayout:gridlayout:1.0.0'
    //                                implementation
'com.google.android.material:material:1.9.0'
    // RecyclerView库

```

```
        implementation
'androidx.recyclerview:recyclerview:1.3.0' // 或更新的版本

        implementation 'androidx.webkit:webkit:1.4.0'
        //implementation 'androidx.activity:activity:1.3.0'
    }
```

=====

文件路径：D:\code\android\NewBig\gradle\wrapper\gradle-wrapper.properties

=====

```
#Sat Dec 28 15:02:53 CST 2024
distributionBase=GRADLE_USER_HOME
distributionPath=wrapper/dists
distributionUrl=https\://services.gradle.org/distributions/gradle-8.7-bin.zip
zipStoreBase=GRADLE_USER_HOME
zipStorePath=wrapper/dists
```

=====

文件路径：D:\code\android\NewBig\gradle\libs.versions.toml

=====

```
[versions]
agp = "8.6.0"
junit = "4.13.2"
junitVersion = "1.1.5"
espressoCore = "3.5.1"
appcompat = "1.6.1"
material = "1.10.0"
activity = "1.8.0"
constraintlayout = "2.1.4"

[libraries]
junit = { group = "junit", name = "junit", version.ref = "junit" }
ext-junit = { group = "androidx.test.ext", name = "junit", version.ref = "junitVersion" }
espresso-core = { group = "androidx.test.espresso", name = "espresso-core", version.ref = "espressoCore" }
appcompat = { group = "androidx.appcompat", name = "appcompat", version.ref = "appcompat" }
material = { group = "com.google.android.material", name = "material", version.ref = "material" }
activity = { group = "androidx.activity", name = "activity", version.ref = "activity" }
constraintlayout = { group = "androidx.constraintlayout",
```

```
name          =      "constraintlayout",      version.ref      =
"constraintlayout" }
```

```
[plugins]
android-application = { id = "com.android.application",
version.ref = "agp" }
```

```
=====
文件路径: D:\code\android\NewBig\build.gradle
=====
// Top-level build file where you can add configuration
options common to all sub-projects/modules.
plugins {
alias(libs.plugins.android.application) apply false
}
```

```
=====
文件路径: D:\code\android\NewBig\gradle.properties
=====
# Project-wide Gradle settings.
# IDE (e.g. Android Studio) users:
# Gradle settings configured through the IDE *will
override*
# any settings specified in this file.
# For more details on how to configure your build
environment visit
#
http://www.gradle.org/docs/current/userguide/build\_environment.html
# Specifies the JVM arguments used for the daemon process.
# The setting is particularly useful for tweaking memory
settings.
org.gradle.jvmargs=-Xmx2048m -Dfile.encoding=UTF-8
# When configured, Gradle will run in incubating parallel
mode.
# This option should only be used with decoupled projects.
For more details, visit
# https://developer.android.com/r/tools/gradle-multi-project-decoupled-projects
# org.gradle.parallel=true
# AndroidX package structure to make it clearer which
packages are bundled with the
# Android operating system, and which are packaged with
your app's APK
# https://developer.android.com/topic/libraries/support-library/androidx-rn
```

```
android.useAndroidX=true
# Enables namespacing of each library's R class so that its
R class includes only the
# resources declared in the library itself and none from
the library's dependencies,
# thereby reducing the size of the R class for that library
android.nonTransitiveRClass=true
```

```
#####3
#android.enableJetifier=false
#android.defaults.buildfeatures.buildconfig=true
```

```
android.nonFinalResIds=false
```

```
android.injected.testOnly=false
```

```
=====
```

```
文件路径: D:\code\android\NewBig\local.properties
```

```
=====
```

```
## This file must *NOT* be checked into Version Control
Systems,
# as it contains information specific to your local
configuration.
#
# Location of the SDK. This is only used by Gradle.
# For customization when using a Version Control System,
please read the
# header note.
#Fri May 08 18:46:20 CST 2026
sdk.dir=D:\\work_soft\\Android\\SDK
```

```
=====
```

```
文件路径: D:\code\android\NewBig\settings.gradle
```

```
=====
```

```
pluginManagement {
    repositories {
        google {
            content {
                includeGroupByRegex("com\\.android.*")
                includeGroupByRegex("com\\.google.*")
                includeGroupByRegex("androidx.*")
            }
        }
        mavenCentral()
        gradlePluginPortal()
    }
}
```

```
}
dependencyResolutionManagement {

repositoriesMode.set(RepositoriesMode.FAIL_ON_PROJECT_REP
OS)
    repositories {
        google()
        mavenCentral()
    }
}

rootProject.name = "NewBig"
include ':app'
```