

---

## Table of Contents

Lab report-1 .....	1
Loads and formats the data. ....	1
Naive Bayes function .....	2
Calculating the loss for the training and test sets .....	2


## Lab report-1

Name: Ventrpragada Sai Shravani PRN:17070123120 Batch: G3(17-21)

```
clc;  
clear all;  
close all;
```

A naïve Bayes classifier assumes the independence of the predictors within each class. A probability distribution within each class. We can determine a new observation at a given location.

```
img= imread("C:\Users\acer\Documents\4th year\Machine Learning  
\naive_bayer.png");  
imshow(img)
```



## Loads and formats the data.

```
heartData = readtable("C:\Users\acer\Documents\4th year\Machine  
Learning\mlml_course_files\Course Files\heartDiseaseData.csv");
```

---

```
heartData.HeartDisease = categorical(heartData.HeartDisease);
% Partitions the data into training and test sets.
pt = cvpartition(heartData.HeartDisease,"HoldOut",0.3);
hdTrain = heartData(training(pt),:);
hdTest = heartData(test(pt),:);
```

## Naive Bayes function

You can set the "DistributionNames" property using an array of distribution names. Repmat function to create a string array with repeated values.

```
dists = [repmat("kernel",1,11) repmat("mvmn",1,10)];
mdl = fitcnb(hdTrain,"HeartDisease","DistributionNames",dists)
% mdl = fitcnb(hdTrain,"HeartDisease","DistributionNames","kernel")
```

```
mdl =
```

```
ClassificationNaiveBayes
    PredictorNames: {1x21 cell}
    ResponseName: 'HeartDisease'
    CategoricalPredictors: [12 13 14 15 16 17 18 19 20 21]
    ClassNames: [false true]
    ScoreTransform: 'none'
    NumObservations: 299
    DistributionNames: {1x21 cell}
    DistributionParameters: {2x21 cell}
    CategoricalLevels: {1x21 cell}
    Kernel: {1x21 cell}
    Support: {1x21 cell}
    Width: [2x21 double]
```

## Calculating the loss for the training and test sets

Shows us the error in the prediction of the data in the training and the testing set. Also shows the loss in data for training and testing test.

```
errTrain = resubLoss(mdl);
errTest = loss(mdl,hdTest);
disp("Training Error: " + errTrain)
disp("Test Error: " + errTest)
```

```
Training Error: 0.16054
```

```
Test Error: 0.32735
```

*Published with MATLAB® R2020a*