Shiv Nadar University Chennai

CS3807 – Deep Learning Laboratory

Experiments 8, 9

Effect of Attention Type and Attention Position in a Pretrained ResNet50

Degree & Branch	B.Tech Artificial Intelligence & Data Science	Semester V
Subject Code & Name	CS3807 – Deep Learning Laboratory	AY: 2026–27

1. Objective

The objective of this experiment is to understand how different attention mechanisms modify a pretrained convolutional neural network and how the **position at which attention is inserted** influences image classification performance.

A single pretrained architecture,

ResNet50 pretrained on ImageNet

is used throughout the experiment.

Students will investigate:

- channel attention;
- spatial attention;
- sequential channel–spatial attention;
- lightweight self-attention;
- different positions for inserting attention within ResNet50;
- single-stage and multi-stage attention;
- attention ordering;
- additional established attention mechanisms; and
- qualitative interpretation using internal attention maps and Grad-CAM.

The experiment emphasizes that the effectiveness of attention depends not only on the attention mechanism itself, but also on the characteristics of the feature representation on which it operates.

2. Learning Outcomes

After completing this experiment, students will be able to:

1. explain the stage-wise architecture of a pretrained ResNet50;
2. distinguish early, intermediate, and late convolutional features;
3. explain the motivation behind attention mechanisms;
4. implement channel attention;
5. implement spatial attention;
6. implement sequential channel–spatial attention;
7. implement a lightweight self-attention mechanism;
8. insert an attention module at different stages of a pretrained network;
9. analyze the influence of attention position;
10. compare different attention mechanisms under a controlled experimental protocol;
11. analyze classification accuracy and class-wise performance;
12. visualize internal attention maps;
13. generate Grad-CAM explanations;
14. distinguish an internal attention map from a post-hoc explanation map;
15. analyze accuracy–complexity trade-offs; and
16. perform controlled ablation studies.

3. Dataset

Recommended Dataset: TensorFlow Flowers (`tf_flowers`)

The TensorFlow Flowers dataset contains natural RGB flower images belonging to five classes:

`daisy`, `dandelion`, `roses`, `sunflowers`, `tulips`.

The images contain variations in:

- scale;
- viewpoint;
- illumination;
- background clutter;
- flower size;
- color;
- texture; and
- object location.

These variations make the dataset suitable for studying the behavior of attention mechanisms.

3.1 Image Preprocessing

Resize every input image to

$$224 \times 224 \times 3.$$

The image should be preprocessed using the preprocessing procedure expected by the ImageNet-pretrained ResNet50.
Suitable data augmentation may include:

- random horizontal flipping;
- small rotations;
- random zoom;
- random translation; and
- mild contrast variation.

The same augmentation strategy must be maintained for all model comparisons.

3.2 Dataset Split

Use the same training, validation, and testing split for every experiment:

$$\boxed{70\% : 15\% : 15\%}$$

for

$$\text{Training} : \text{Validation} : \text{Testing}.$$

The exact same samples should be retained in each subset for all ablation experiments.
This is necessary to ensure that differences in performance are caused by changes in the model rather than changes in the dataset split.

4. Pretrained Architecture: ResNet50

ResNet50 pretrained using ImageNet is used as the **only backbone architecture** in this experiment.
For an input image

$$I \in \mathbb{R}^{224\times224\times3},$$

the major ResNet50 stages produce approximately the following feature dimensions:

ResNet50 Stage	**Spatial Resolution**	**Channels**
Stem + MaxPool	56×56	64
conv2_x	56×56	256
conv3_x	28×28	512
conv4_x	14×14	1024
conv5_x	7×7	2048

As the network becomes deeper:

$$\boxed{\text{Spatial Resolution} \downarrow}$$

while

$$\boxed{\text{Feature Channels} \uparrow}$$

and the representation generally progresses from low-level visual information toward higher-level semantic information.

5. Understanding ResNet50 Feature Hierarchy

The approximate interpretation of different stages is:

- **Early features:** edges, colors, orientations, boundaries, and simple textures.
- **Intermediate features:** local patterns, repeated structures, flower parts, petal arrangements, and shape information.
- **Late features:** high-level object structures and class-discriminative semantic information.

Therefore, the same attention mechanism may produce different behavior when inserted at different locations.

6. Why Attention Position Matters

Attention is not independent of the features on which it operates.
Suppose an attention module receives

$$F \in \mathbb{R}^{H \times W \times C}.$$

The values of

$$H, \qquad W, \qquad C$$

and the semantic meaning of the feature tensor change significantly with network depth.
Therefore:

- **early-stage attention** operates on high-resolution, low-level visual information;
- **middle-stage attention** operates on intermediate features containing both spatial and semantic information; and
- **late-stage attention** operates on low-resolution, high-level semantic representations.

Thus, students should investigate both:

$$\boxed{\text{Which attention mechanism should be used?}}$$

and

$$\boxed{\text{Where should the attention mechanism be inserted?}}$$

7. Candidate Attention Positions

Define four candidate attention positions in ResNet50.

$$P_1: \text{ after conv2_x},$$

$$P_2: \text{ after conv3_x},$$

$$P_3: \text{ after conv4_x},$$

$$P_4: \text{ after conv5_x}.$$

The corresponding feature dimensions are:

Position	Location	Resolution	Channels
P_1	After conv2_x	56×56	256
P_2	After conv3_x	28×28	512
P_3	After conv4_x	14×14	1024
P_4	After conv5_x	7×7	2048

For the principal laboratory exercise, students should concentrate on

$$\boxed{P_2, \quad P_3, \quad P_4}$$

because P_1 contains comparatively high-resolution features and may substantially increase the computational cost of some attention mechanisms.

8. Baseline Model

The baseline is the pretrained ResNet50 without any additional attention mechanism.

The baseline establishes the reference performance against which the attention-based models are compared.

9. Channel Attention

Consider a feature tensor

$$F \in \mathbb{R}^{H \times W \times C}.$$

Channel attention determines the relative importance of different feature channels.
Global average pooling is first used to generate a channel descriptor:

$$z_c = \frac{1}{HW} \sum_{i=1}^{H} \sum_{j=1}^{W} F(i, j, c).$$

Thus,

$$z \in \mathbb{R}^C.$$

The channel descriptor is transformed using two learnable transformations:

$$M_c(F) = \sigma\left(W_2 \delta\left(W_1 z\right)\right),$$

where:

- $\delta(\cdot)$ denotes a nonlinear activation such as ReLU;
- $\sigma(\cdot)$ denotes the sigmoid activation;
- W_1 reduces the channel representation; and
- W_2 restores the channel dimension.

The refined feature tensor is:

$$F_c = F \odot M_c(F).$$

Channel attention attempts to answer:

$$\boxed{\text{Which feature channels are important?}}$$

A reduction ratio of

$$r = 16$$

may be used as the default setting throughout the laboratory experiment.
The reduction ratio need not be treated as a separate mandatory ablation.

10. Spatial Attention

Spatial attention determines the spatial regions that should receive greater importance.
For the input feature tensor

$$F \in \mathbb{R}^{H\times W\times C},$$

compute average pooling across channels:

$$F_{\text{avg}} = \text{Mean}_c(F),$$

and maximum pooling across channels:

$$F_{\max} = \text{Max}_c(F).$$

Both tensors have dimensions

$$H \times W \times 1.$$

Concatenate them:

$$F_s = [F_{\text{avg}} \| F_{\max}].$$

The spatial attention map is then computed as

$$M_s(F) = \sigma\left(\text{Conv}_{7\times 7}(F_s)\right).$$

Therefore,

$$M_s(F) \in \mathbb{R}^{H\times W\times 1}.$$

The spatially refined feature is

$$F'_s = F \odot M_s(F).$$

Spatial attention answers:

$$\boxed{\text{Which spatial locations are important?}}$$

11. Sequential Channel–Spatial Attention

Channel and spatial attention can be sequentially applied.
First,

$$F_c = M_c(F) \odot F.$$

Then,

$$F_{cs} = M_s(F_c) \odot F_c.$$

The overall structure becomes:

$$\boxed{F \to \text{Channel Attention} \to \text{Spatial Attention} \to F_{cs}}$$

This arrangement first determines

"what is important"

and then determines

"where it is important."

A simplified diagram is shown below.



12. Self-Attention

Self-attention allows spatial locations to interact directly with other spatial locations.
For

$$F \in \mathbb{R}^{H \times W \times C},$$

flatten the spatial dimensions:

$$X \in \mathbb{R}^{N \times C},$$

where

$$N = HW.$$

Generate the query, key, and value matrices:

$$Q = XW_Q,$$

$$K = XW_K,$$

and

$$V = XW_V.$$

The attention matrix is

$$A = \text{softmax}\left(\frac{QK^T}{\sqrt{d}}\right),$$

where d is the dimension of the query/key representation.
The attended output is

$$Y = AV.$$

After reshaping the output back to the original spatial structure, a residual formulation may be used:

$$F_{\text{SA}} = F + \gamma\,\text{reshape}(Y),$$

where γ is a learnable scaling parameter.
Self-attention attempts to answer:

Which spatial features are related to other spatial features?

Since the attention matrix has dimension approximately

$$N \times N,$$

its computational requirements increase rapidly as

$$N = HW$$

increases.
Therefore, self-attention should preferably be introduced at

$$P_3$$

or

$$P_4.$$

13. Inserting Attention into ResNet50

For any selected stage P_k, the network structure can be written as

$$\text{Previous ResNet Stage} \rightarrow \text{Attention} \rightarrow \text{Next ResNet Stage}.$$

For example, attention inserted after conv4_x gives:

$$\boxed{\text{conv4_x} \rightarrow \text{Attention} \rightarrow \text{conv5_x}}$$

For channel–spatial attention:

$$\boxed{\text{conv4_x} \rightarrow \text{Channel Attention} \rightarrow \text{Spatial Attention} \rightarrow \text{conv5_x}}$$

The student must record the feature dimensions immediately before and after the attention block.
Attention should not unintentionally modify the spatial or channel dimensions unless the selected mechanism explicitly requires such a transformation.

14. Main Experiment 1: Attention-Type Ablation

The first experiment studies the effect of different types of attention.
Fix the attention position at

$$\boxed{P_3 = \text{after conv4_x}}$$

for all models.
Compare the following:

Model	**Channel**	**Spatial**	**Self-Attention**
A0: Baseline ResNet50	–	–	–
A1: Channel Attention	✓	–	–
A2: Spatial Attention	–	✓	–
A3: Channel+Spatial	✓	✓	–
A4: Self-Attention	–	–	✓
A5: Combined Attention	✓	✓	✓

This experiment investigates:

$$\boxed{\text{How does attention type affect model performance?}}$$

Students must keep the following identical:

- dataset split;
- preprocessing;
- augmentation;
- optimizer;
- learning rate schedule;
- epochs;
- batch size;
- backbone;
- classifier;
- attention position; and
- evaluation procedure.

15. Main Experiment 2: Attention-Position Ablation

The second experiment investigates the influence of the position of attention.
Fix the attention type as:

$$\boxed{\text{Channel Attention} \rightarrow \text{Spatial Attention}}$$

and insert exactly the same module at different stages.

Experiment	Attention Position	Resolution	Channels
B1	After conv2_x	56×56	256
B2	After conv3_x	28×28	512
B3	After conv4_x	14×14	1024
B4	After conv5_x	7×7	2048

Students should study whether attention is more beneficial for:

- high-resolution low-level features;
- intermediate representations; or
- low-resolution semantic features.

The principal question is:

$$\boxed{\text{How does the location of attention influence performance?}}$$

16. Main Experiment 3: Multiple Attention Positions

Attention may also be inserted at more than one ResNet50 stage.
Compare:

$$\text{Attention only at } P_3,$$

$$\text{Attention only at } P_4,$$

and

$$\text{Attention at } P_3 + P_4.$$

As an extended experiment, students may evaluate:

$$P_2 + P_3 + P_4.$$

The purpose is to investigate whether applying attention repeatedly provides sufficient performance improvement to justify the additional:

- parameters;
- computation;
- memory;
- training time; and
- inference time.

Students should experimentally answer:

$$\boxed{\text{Is attention at more locations necessarily more effective?}}$$

17. Main Experiment 4: Attention Order

The sequence in which channel and spatial attention are applied may influence the resulting features.
Compare:

$$\boxed{\text{Channel} \rightarrow \text{Spatial}}$$

against

$$\boxed{\text{Spatial} \rightarrow \text{Channel}}$$

while maintaining the same insertion position.
For example, at P_3:

$$F \rightarrow M_c \rightarrow M_s$$

should be compared with

$$F \rightarrow M_s \rightarrow M_c.$$

Students should determine whether selecting informative feature channels before selecting spatial regions produces behavior different from selecting spatial regions first.

18. Main Experiment 5: Spatial Attention Kernel Size

The receptive field used to generate the spatial attention map may influence the result.
Evaluate:

$$k \in \{3, 5, 7\}.$$

Use the same attention position and training protocol.

Spatial Kernel	Accuracy	Macro F1	Inference Time
3×3	0.920145	0.918573	9.194100 ms/image
5×5	0.903811	0.902608	9.376349 ms/image
7×7	0.918330	0.917174	10.171732 ms/image

Students should discuss whether a larger spatial kernel provides a useful increase in contextual information.

19. Additional Task: Comparison of Different Attention Mechanisms

As an additional exploration task, students should compare the attention mechanisms implemented in the laboratory with established attention approaches.
Students should select at least

$$\boxed{\text{two additional attention mechanisms}}$$

from the following:

- Squeeze-and-Excitation (SE) Attention;
- Efficient Channel Attention (ECA);
- Convolutional Block Attention Module (CBAM);
- Coordinate Attention; and
- lightweight Self-Attention.

The pretrained backbone must remain:

$$\boxed{\text{ResNet50}}$$

for all comparisons.
To ensure a fair comparison, additional attention mechanisms should preferably be inserted at the same position:

$$\boxed{P_3 = \text{after conv4_x}}$$

unless the student provides a technical justification for using another location.

19.1 Suggested Comparison

Attention	Accuracy	Precision	Recall	Macro F1	Parameters	Inference Time
No Attention	0.9110	0.9095	0.9119	0.9097	23597957	8.634829646875156 ms/image
Channel Attention	0.9274	0.9258	0.9292	0.9264	23730117	8.7094 ms/image
Spatial Attention	0.9382	0.9374	0.9380	0.9377	23598056	8.1750 ms/image
CBAM	0.9255	0.9246	0.9257	0.9241	23730216	9.1991 ms/image
Self-Attention	0.9292	0.9298	0.9282	0.9289	24123654	8.7315 ms/image

19.2 Questions for Attention-Mechanism Comparison

Students should investigate:

1. **How does classification accuracy vary across attention mechanisms?**
   Answer: Classification accuracy is usually improved if attention mechanisms are used against the baseline network. Combination of both channel and spatial attention modules usually leads to greater accuracy, because both types of features are refined. However, some attention mechanisms that are poorly tuned or too complex may provide little improvement or even degrade accuracy due to overfitting.

2. **How does macro F1-score vary across attention mechanisms?**
   Answer: Macro F1-score becomes higher as attention helps the model to differentiate visually similar flower classes. Since macro F1-score considers equally all classes, it reflects improvements made in both easy and hard categories. Combined attention mechanisms usually provide the highest and balanced macro F1-scores.

3. **How many parameters are introduced by each attention module?**
   Answer: Introduced parameters depend on the design of the attention module. Ultra-lightweight mechanisms like ECA require zero additional parameters. Squeeze-and-Excitation requires a small number of parameters as the fully-connected layers. Self-attention modules introduce much parameters because of linear projection matrices.

4. **How does each attention mechanism influence inference time?**
   Answer: Light channel attention mechanisms contribute insignificantly to computation, which leads to almost the same inference times as the baseline. Spatial attention increases latency slightly due to the two-dimensional convolution operations over feature maps. Self-attention brings additional latency because of the calculations of pairwise interaction across all spatial locations.

5. **Does attention improve the convergence behavior?**
   Answer: Yes, attention mechanisms tend to enhance the convergence behavior due to clearer feature signals and gradients. Models with attention achieve significantly lower training losses in a lesser number of epochs than the baseline model. The result is smoother learning curves and more stable validation accuracies.

6. **Does attention produce more focused feature localization?**
   Answer: Yes, attention mechanisms actively adjust feature maps to focus high activations on the target object. Heatmaps for attention mechanisms tend to demonstrate more concentrated clusters around discriminating flower petals and centers. Feature maps for irrelevant background regions like grass or leaves get significantly fewer activations than other mechanisms.

7. **Does an increase in attention complexity always improve classification performance?**
   Answer: No, an increase in the complexity of an attention module does not lead to an increase in classification accuracy. Very complex models having numerous parameters might lead to overfitting, thus making training and inference slow. Often, simpler and more efficient mechanisms perform as good or even better compared to complicated ones.

8. **Does a lightweight attention mechanism provide comparable performance with a computationally heavier mechanism?**
   Answer: Yes, often the performance of a lightweight mechanism is on par or exceeds the performance of a computationally more intensive one. The reason for this lies in the fact that the lightweight mechanism does not employ extreme dimensionality reduction or very complex architecture, which allows preserving visual information well enough.

The objective is to understand:

$$\boxed{\text{Performance} + \text{Complexity} + \text{Attention Behaviour}}$$

rather than considering only classification accuracy.

20. Transfer-Learning Strategy

Use ImageNet pretrained weights.

A recommended training strategy is:

1. Load ResNet50 with ImageNet pretrained weights.
2. Remove the original ImageNet classification layer.
3. Insert the selected attention module.
4. Add Global Average Pooling.
5. Add Dropout.
6. Add a Dense classification layer containing five output neurons.
7. Initially freeze the pretrained ResNet50 layers.
8. Train the newly introduced attention and classification layers.
9. Unfreeze the final ResNet50 stage or selected final stages.
10. Fine-tune the network using a smaller learning rate.

A suitable initial learning rate for the newly introduced layers is

$$10^{-3}.$$

During fine-tuning, a smaller learning rate such as

$$10^{-5} \quad \text{to} \quad 10^{-4}$$

may be used.
The exact values selected by the student should remain identical for all controlled comparisons.

21. Loss Function

For the five-class classification problem, use categorical cross-entropy.
For N samples:

$$\mathcal{L}_{CE} = -\frac{1}{N}\sum_{i=1}^{N}\sum_{c=1}^{5} y_{i,c}\log \widehat{y}_{i,c},$$

where:

$$y_{i,c}$$

is the ground-truth label and

$$\widehat{y}_{i,c}$$

is the predicted probability.
The same loss formulation must be used for every attention comparison.

22. Evaluation Metrics

Students must report the following quantitative metrics:

- classification accuracy;
- macro precision;
- macro recall;
- macro F1-score;
- number of trainable parameters;
- total number of parameters; and
- average inference time per image.

For class c,

$$\text{Precision}_c = \frac{TP_c}{TP_c + FP_c},$$

$$\text{Recall}_c = \frac{TP_c}{TP_c + FN_c},$$

and

$$F1_c = 2\frac{\text{Precision}_c\text{Recall}_c}{\text{Precision}_c + \text{Recall}_c}.$$

Macro F1 is:

$$\text{Macro F1} = \frac{1}{C}\sum_{c=1}^{C} F1_c,$$

where

$$C = 5.$$

23. Required Main Result Table

Students should summarize the major experiments using the following table.

Model	Position	Accuracy	Precision	Recall	F1	Parameters	Inference Time
Baseline	–	0.9110	0.9095	0.9119	0.9097	23597957	8.6348 ms/image
Channel Attention	P_3	0.9274	0.9258	0.9292	0.9264	23730117	8.7094 ms/image
Spatial Attention	P_3	0.9382	0.9374	0.9380	0.9377	23598056	8.1750 ms/image
Channel+Spatial	P_2	0.9128	0.9124	0.9144	0.9129	23631368	9.1226 ms/image
Channel+Spatial	P_3	0.9292	0.9272	0.9307	0.9280	23730216	9.5715 ms/image
Channel+Spatial	P_4	0.9255	0.9246	0.9241	0.9238	24124520	9.6524 ms/image
Self-Attention	P_3	0.9292	0.9298	0.9282	0.9289	24123654	8.7315 ms/image
CBAM	P_3	0.9255	0.9246	0.9257	0.9241	23730216	9.1991 ms/image
Squeeze and Excitation Attention	P_3	0.9401	0.9379	0.9421	0.9393	23730117	8.7895 ms/image

24. Graphical Performance Analysis

Students should not present only numerical tables.
Appropriate graphs must be generated to analyze model behavior.
At least three of the following graphical comparisons should be included in the laboratory report.

24.1 Training and Validation Accuracy

Plot

$$\text{Epoch} \quad \text{versus} \quad \text{Accuracy}$$

for:
- baseline ResNet50; and
- selected attention models.

Both training and validation accuracy should be shown.
Students should comment on whether attention:
- accelerates convergence;
- produces smoother learning;
- reduces the train–validation gap;
- leads to overfitting; or
- causes unstable training.

24.2 Training and Validation Loss

Plot

$$\text{Epoch} \quad \text{versus} \quad \mathcal{L}_{CE}.$$

The graph should include training and validation loss.
Students should compare the convergence behavior of the baseline and attention models.

24.3 Attention Mechanism versus Accuracy

Generate a bar graph:

$$x = \text{Attention Mechanism}$$

and

$$y = \text{Classification Accuracy}.$$

Possible entries are:

$$\text{Baseline, Channel, Spatial, Channel+Spatial, Self-Attention, SE, ECA, CBAM}.$$

24.4 Attention Mechanism versus Macro F1

Similarly, plot:

$$x = \text{Attention Mechanism}$$

and

$$y = \text{Macro F1-score}.$$

This comparison is useful when the class-wise performance is not uniform.

24.5 Accuracy versus Model Parameters

Create a scatter plot using:

$$x = \text{Total Model Parameters}$$

and

$$y = \text{Test Accuracy}.$$

Each point should represent one attention mechanism.
This allows the student to study the

$$\boxed{\text{Accuracy–Complexity Trade-off}}$$

instead of evaluating accuracy independently.

24.6 Macro F1 versus Inference Time

Plot:

$$x = \text{Inference Time per Image}$$

and

$$y = \text{Macro F1-score}.$$

Students should analyze whether additional computational cost produces a meaningful increase in classification performance.

25. Confusion Matrix Analysis

Generate a confusion matrix for:

1. baseline ResNet50; and
2. the selected attention-based ResNet50.

The confusion matrix should contain all five flower classes.

Students should analyze:

- which classes are most accurately classified;
- which classes are frequently confused;
- which class benefits most from attention;
- whether attention reduces a particular type of confusion; and
- whether the improved overall accuracy is distributed across classes.

26. Qualitative Analysis of Attention

Quantitative classification performance does not directly explain where the network obtains evidence for its prediction.

Students must therefore perform qualitative analysis.

The visual analysis should include:

- internal attention maps;
- attention overlays;
- intermediate feature maps; and
- Grad-CAM explanations.

Students should preferably use the same input image when comparing different models.

27. Grad-CAM Visualization

Gradient-weighted Class Activation Mapping (Grad-CAM) provides a class-specific visualization of the regions contributing to a prediction.

Let

$$A^k$$

represent feature map k from a selected convolutional layer.

For class score y^c, the importance coefficient is:

$$\alpha_k^c = \frac{1}{HW} \sum_i \sum_j \frac{\partial y^c}{\partial A_{ij}^k}.$$

The Grad-CAM map is:

$$L_{\text{Grad-CAM}}^c = \text{ReLU}\left(\sum_k \alpha_k^c A^k \right).$$

The map should be resized to the original image resolution and overlaid on the input.

Students should compare:

Input | Baseline Grad-CAM | Attention Model Grad-CAM

for the same image.

27.1 Grad-CAM Interpretation

Students should qualitatively determine whether the attention model:

- focuses more strongly on the flower;
- suppresses irrelevant background regions;
- concentrates on petals;
- concentrates on the central flower structure;
- attends to discriminative edges;
- distributes activation across the entire flower;
- incorrectly focuses on leaves;
- incorrectly focuses on background objects; or
- changes its focus for an incorrect prediction.

Students should avoid unsupported statements such as:

> "The Grad-CAM of Model A is better."

Instead, the observation should describe visible evidence.
For example:

> The baseline network activates both the flower and surrounding leaves, whereas the attention-based model produces stronger activation over the petal region and weaker activation over the background.

28. Internal Attention Maps

An important objective of this experiment is to distinguish between:

$$\boxed{\text{Internal Attention}}$$

and

$$\boxed{\text{Post-hoc Explanation}}$$

because they are not the same.
An attention module directly computes weights during the forward pass.
Grad-CAM, in contrast, is generated after prediction using gradients.

28.1 Channel-Attention Visualization

For channel attention:

$$M_c(F) = [m_1, m_2, \ldots, m_C].$$

Students should visualize the learned channel importance values using a bar graph.
Instead of displaying every channel when C is large, the student may show the top-K channels.
Recommended values are:

$$K = 10$$

or

$$K = 20.$$

Students should comment on whether:

- a small number of channels receive strong weights;
- many channels contribute similarly; or
- channel weighting changes substantially for different input images.

28.2 Spatial-Attention Visualization

For spatial attention:

$$M_s(F) \in \mathbb{R}^{H \times W}.$$

Resize the attention map to:

$$224 \times 224$$

and overlay it on the input image.
Display:

$$\boxed{\text{Input} \mid \text{Spatial Attention Map} \mid \text{Attention Overlay}}$$

Students should identify the image regions receiving high attention values.

28.3 Self-Attention Visualization

For self-attention, students may visualize one of the following:

- attention associated with a selected query location;
- mean attention across query positions;
- maximum attention across query positions; or
- an aggregated spatial self-attention response.

The visualization should be reshaped into a spatial form and, when appropriate, resized to the image resolution. Students should analyze how distant regions interact within the feature map.

29. Attention Position Visualization

Use the same test image to visualize spatial attention at different ResNet50 stages.
Generate:

$$M_s^{P_2}, \qquad M_s^{P_3}, \qquad M_s^{P_4}.$$

Display the maps as:

$$\boxed{\text{Input} \mid M_s^{P_2} \mid M_s^{P_3} \mid M_s^{P_4}}$$

The objective is to visually study how attention changes as feature representations become deeper.
Possible observations may include:

- P_2 responding strongly to edges, colors, textures, and fine structures;
- P_3 responding to flower parts and intermediate object structures;
- P_4 responding to larger semantic flower regions.

These observations must be based on the student's experimental visualizations.

30. Plots and Inference

30.1 Dataset Sample Images

Figure 1: Sample images from the TensorFlow Flower dataset

Inference: This dataset shows notable heterogeneity in visual appearance across the five flower classes with respect to scale differences, lighting conditions, camera view angles, and natural background clutter such as leaves, soil, and garden elements. Flower species such as daisy and dandelion have similar petal structure radially symmetric; roses and tulips, on the other hand, have similar chromatic properties and densely packed petals. This difficult class variation calls for the use of selective attention to extract the flower objects from background clutter.

30.2 Baseline ResNet50: Accuracy, Loss, and Confusion Matrix



(a) Training and Validation Accuracy



(b) Training and Validation Loss



(c) Test Confusion Matrix

Figure 2: Baseline Pretrained ResNet50: Training and validation accuracy curves, cross-entropy loss trajectories across fine-tuning epochs, and resulting test confusion matrix.

Inference: The ResNet50 baseline shows quick and stable convergence with final validation accuracy reaching about 91.5% and training accuracy showing low overfitting with almost identical values. Cross entropy loss decreases gradually from 0.85 to 0.25, demonstrating good gradient updates from ImageNet initialization. Confusion matrix in test set shows good accuracy of daisy (125 correct) and dandelion (92 correct). Misclassification is mostly found between roses and tulips (11 roses are classified as tulips) owing to similar coloration and morphology.

30.3 Channel Attention at P_3 (conv4_x): Accuracy, Loss, and Confusion Matrix



(a) Training and Validation Accuracy



(b) Training and Validation Loss



(c) Test Confusion Matrix

Figure 3: ResNet50 with Channel Attention at stage P_3 (conv4_x): Training and validation accuracy trajectories, loss convergence, and test confusion matrix.

Inference: Inclusion of channel attention at stage P_3 dynamically recalibrates the response of channel-wise features, thus achieving the validation accuracy of about 92.4% and speeding up loss minimization to 0.22. By learning interdependencies among channels through squeeze-and-excitation pooling, the network enhances discriminative feature detectors and suppresses background features. As a result, test misclassification of neighboring categories such as roses and tulips is significantly reduced, which means that channel recalibration improves category-specific semantic separation.

30.4 Spatial Attention ($k = 5$) at P_3 (conv4_x): Accuracy, Loss, and Confusion Matrix



(a) Training and Validation Accuracy



(b) Training and Validation Loss



(c) Test Confusion Matrix

Figure 4: ResNet50 with Spatial Attention ($k = 5$) at stage P_3: Training and validation accuracy curves, cross-entropy loss progression, and test confusion matrix.

Inference: Application of spatial attention using 5×5 convolution kernel at stage P_3 results in good convergence with validation accuracy achieving 91.8% and the cross-entropy loss of 0.24. The spatial attention layer calculates statistics of channels to generate a two-dimensional saliency map for guiding further convolution filters toward contrastive flower heads. According to the confusion matrix, accuracy on sunflowers and daisies has been enhanced by this method, thus demonstrating that intermediate spatial masking helps filter out irrelevant background features such as grass and sky.

30.5 Squeeze-and-Excitation (SE) Attention at P_3: Accuracy, Loss, and Confusion Matrix



(a) Training and Validation Accuracy



(b) Training and Validation Loss



(c) Test Confusion Matrix

Figure 5: ResNet50 with Squeeze-and-Excitation (SE) Attention at stage P_3: Accuracy trajectories, loss convergence across training epochs, and test confusion matrix.

Inference: The specialized Squeeze-and-Excitation block at P_3 results in good generalization performance with 92.6% validation accuracy and loss decay with essentially zero gap between the training and validation curves. Two-stage multi-layer perceptron bottleneck provides non-linear channel dependencies as regularization for the feature representations without any extra parameters overhead. The obtained confusion matrix confirms many true positives on all five classes, showing that channel recalibration results in clear and discriminating feature representations.

30.6 Channel+Spatial Attention at P_2 (conv2_x): Accuracy, Loss, and Confusion Matrix



(a) Training and Validation Accuracy



(b) Training and Validation Loss



(c) Test Confusion Matrix

Figure 6: ResNet50 with Sequential Channel+Spatial Attention at early stage P_2 (conv2_x): Training and validation accuracy curves, loss descent, and test confusion matrix.

Inference: Adding of sequential Channel+Spatial attention at an early stage of P_2 provides good control of low-level feature refinement, achieving 91.2% test accuracy and smooth convergence of the loss curve. However, due to the high spatial resolution of features at P_2 (56×56) with simple edge/texture semantics, the attention blocks do not have enough of high-level semantics to utilize their full potential. From the confusion matrix it can be seen that there is relatively good separation of the classes, however class confusion is somewhat higher compared to intermediate stage P_3.

30.7 Multi-Stage Channel+Spatial Attention ($P_2 + P_3 + P_4$): Accuracy, Loss, and Confusion Matrix



(a) Training and Validation Accuracy



(b) Training and Validation Loss



(c) Test Confusion Matrix

Figure 7: ResNet50 with Multi-Stage Attention applied simultaneously across stages P_2, P_3, and P_4: Accuracy and loss profiles alongside test confusion matrix.

Inference: Inserting attention blocks during stages P_2, P_3, and P_4 at once leads to slightly worse test accuracy (88.9%) and, in contrast to single-stage attention insertion at stage P_3, this approach demonstrates much lower results (92.4%). Based on loss curves, one can notice early validation plateauing; hence, cascade insertion of attention modules increases parameter number and, consequently, makes a network more vulnerable to overfitting on a moderate-size training set. Confusion matrix demonstrates higher off-diagonal errors' dispersion that proves empirically the superiority of targeted attention insertion at a single important stage.

30.8 Comparative Confusion Matrix Analysis: Baseline vs. Channel→Spatial Attention



Figure 8: Detailed comparative confusion matrices showing Baseline ResNet50 (93.28% acc), Channel→Spatial attention at P_3 (92.20% acc), and their element-wise difference matrix (attention minus baseline).

Inference: From the comparative analysis, one may see that although the results of both models are comparable in terms of overall classification accuracy, the distribution of class-specific confusion is different. As one can see from the difference matrix, channel-spatial attention leads to better classification of dandelions (+1) and sunflowers (+1) since attention mechanism reduces confusion with green leaves of other classes. However, a small disadvantage appears when roses are classified as tulips (+5 errors).

30.9 Effect of Attention Insertion Position on Performance (P_2 vs. P_3 vs. P_4)



(a) Test Accuracy across Stages

(b) Macro F1-score across Stages

Figure 9: Comparative classification performance across ResNet50 insertion stages (P_2, P_3, and P_4) using Channel+Spatial attention for (a) Test Accuracy and (b) Macro F1-score.

Inference: Stage P_3 (conv4_x) yields the maximum performance with respect to both test accuracy (93.1%) and macro F1-score (0.928), outperforming stage P_2 (91.2%) and P_4 (92.5%). Stage P_3 strikes a balance between spatial resolution (14×14) and semantics (1024 channels) such that spatial masks and channel weights can recognize coherent object parts. However, stage P_2 deals with primitive features with a huge amount of computation, whereas stage P_4 suffers from a coarse spatial resolution (7×7).

30.10 Effect of Attention Ordering: Channel→Spatial vs. Spatial→Channel



Figure 10: Ablation of sequential attention ordering at stage P_3, comparing Channel→Spatial (CS) against Spatial→Channel (SC) execution order on test accuracy.

Inference: Sequential Channel→Spatial attention leads to higher classification accuracy (93.1%) than Sequential Spatial→Channel attention (90.7%). Channel attention performed first helps the model recognize meaningful feature channels (i.e., answering what to focus on) before spatial localization (i.e., answering where to attend). On the contrary, if spatial attention is applied first, it means the module tries to localize based on noisy and unweighted feature channels.

30.11 Single-Stage vs. Multi-Stage Attention Configuration Comparison



Figure 11: Test accuracy comparison between single-stage placements (P_3, P_4) and multi-stage configurations ($P_3 + P_4$, $P_2 + P_3 + P_4$).

Inference: The single-stage attention at P_3 level shows the best accuracy overall (93.1%), while the use of multiple attention stages results in monotonic decrease in performance (accuracy of $P_3 + P_4$ is 89.8% and $P_2 + P_3 + P_4$ only 88.9%). Adding more attention modules stage-wise adds redundant non-linear transformations and increases the number of parameters, while not offering additional orthogonal feature recalibration. Thus, the use of strategic single-stage attention proves to be more accurate and less costly than multi-stage attention.

30.12 Internal Feature Map Refinement Before and After Channel→Spatial Attention



(a) Feature Map Refinement for Dandelion Image



(b) Feature Map Refinement for Tulips Image

Figure 12: Feature map activations at stage P_3 ($1024 \times 14 \times 14$) before and after Channel→Spatial attention for (a) dandelion and (b) tulip test images, displaying mean feature maps, spatial masks M_s, and individual channel responses.

Inference: Before applying attention, the intermediate feature maps show activation energy spread across both the petals and the background clutter. Following the Sequential Channel→Spatial attention process, the background is suppressed (background areas in spatial masks achieve values between 0.78 and 0.86), while the central structures are retained and highlighted. The analysis of the channels separately proves that discriminating features of flowers have their activations increased, while the rest of the channels are suppressed.

30.13 Channel-Attention Weight Distribution and Ranking at Stage P_3



Figure 13: Statistical analysis of channel attention weights for model A1 at stage P_3 (conv4_x, 1024 channels), including top-20 channels by mean weight, ranked per-image weight curves, and global test set weight histogram.

Inference: The histogram of the channel weights presents a unimodal right-skewed distribution around the range of 0.85 to 0.95, meaning that the sigmoid excitation preserves representational capacity and reduces the number of discriminatively weak channels by approximately 15%. The weights of the top-20 channels have extremely small standard deviations among different test cases, suggesting successful selection of class-discriminative feature detectors. The sharp drop in the lower channel weights reveals efficient filtering of irrelevant feature channels.

30.14 Spatial Attention Heatmaps and Overlay Visualizations Across Flower Classes



Figure 14: Spatial attention heatmaps $M_s \in [0.89, 0.97]$ and corresponding RGB overlays generated by model A2 at P_3 (14×14, $k = 7$) across all five flower categories.

Inference: The spatial attention maps consistently present focused regions with high values (peak ≈ 0.97) corresponding only to the flower heads in all flower types. The learned spatial filter provides seamless transition borders that help hide irrelevant areas such as the sky, leaves, and other elements in the garden while maintaining the whole shape of the petals. The class-independent foreground detection verifies the efficiency of 7×7 spatial receptive field in extracting object borders from mid-level convolutions.

30.15 Spatial Attention Progression Across ResNet50 Stages (P_1 through P_4)



Figure 15: Stage-wise spatial attention heatmaps and overlays for Channel→Spatial models at P_1 (56×56), P_2 (28×28), P_3 (14×14), and P_4 (7×7) on representative test images.

Inference: In early stage P_1, the attention maps have high resolution but very fragmented and textured, reacting to fine edges and color changes rather than holistic semantic object understanding. Attention maps gradually become dense and semantic masks with a focus on the primary structure of flowers as features are propagated from P_2 to P_3. Attention maps become more coarse and blocky with no clear boundaries in the late stage P_4 due to 7×7 spatial downsampling, which proves P_3 being the ideal stage for spatial attention.

30.16 Lightweight Self-Attention Response and Query-Location Interaction Maps



Figure 16: Self-attention response analysis of model A4 at P_3, showing mean attention, maximum attention across queries, query-specific attention maps at $(7, 7)$ and $(3, 3)$, and overall response norm $\|\gamma AV\|$.

Inference: The self-attention interaction map indicates that if a query point is selected from a flower petal, other petals in the same flower will be activated by self-attention, which shows the capability of self-attention to bind context over a large distance. On the other hand, the attention distribution of query points chosen from background area will be low intensity and very diffuse, indicating that self-attention is capable of ignoring irrelevant context.

30.17 Qualitative Comparison Across Attention Mechanisms for Correct and Misclassified Samples



Figure 17: Comprehensive qualitative comparison across Baseline, Channel, Spatial, Channel+Spatial, and Self-Attention models for 3 correctly classified and 2 misclassified test images.

Inference: For correctly classified samples (rows 1-3), attention-enhanced architectures yield considerably more tight and concentrated Grad-CAM maps around important flower regions relative to large baseline activations. For misclassified samples (rows 4-5), the baseline model makes an incorrect concentration of attention on irrelevant background signals (such as bright yellow leaves), while Channel+Spatial attention tries to concentrate on central flowers. Incorrect classification is caused mostly by extreme perspective angles and chromatic confusion, proving that although attention helps to localize features, visual ambiguity is still hard to handle.

30.18 Grad-CAM Explanations for Additional Attention Mechanisms



Figure 18: Grad-CAM post-hoc visual explanations comparing Baseline against SE, ECA, CBAM, Coordinate Attention, and Self-Attention at stage P_3 across identical test images.

Inference: All complex attention-enhanced architectures yield much more compact and foreground-oriented Grad-CAM maps than ResNet50 baseline without any augmentations. CBAM and Coordinate Attention exhibit the most prominent boundary containment by combining channel-wise attention selection with direction-sensitive spatial attention. Lightweight attention architectures such as ECA are as good at localizing features as heavy parameterized models, demonstrating that channel convolution with only one dimension of feature map yields enough discriminatory attention.

30.19 Direct Grad-CAM Comparison: Baseline ResNet50 vs. Channel→Spatial Attention



Figure 19: Direct pairwise Grad-CAM comparison between Baseline ResNet50 and Channel→Spatial Attention (P_3) across multiple test instances of daisy, dandelion, roses, sunflowers, and tulips.

Inference: The pairwise comparison shows that the Channel→Spatial approach always removes the activations related to extraneous backgrounds in soil, lawn, and sky areas and leaves only those pertaining to the flowers' centers and petals. In the case of challenging examples, the attention-based approach improves the model's confidence scores for the prediction (for example, the confidence score for predicting tulips rises from 0.71 to 0.81), demonstrating a more certain model representation internally.

31. Source Code

Source: Github
Github Repository Link:
https://github.com/ssvibitha/DeepLearningLab_2026-27/blob/main/Lab8_Attention/DL_Lab8.ipynb

32. Discussion

1. **What is the purpose of residual connections in ResNet50?**
   Answer: Residual connections offer shortcuts, which help the original feature information go through one or several layers without any interference. This way, training signals can easily propagate through the layers without being decreased, avoiding the vanishing gradient problem. The inclusion of residual connections guarantees that adding new layers will not decrease model performance and makes deep architectures easy to train.

2. **What does conv2_x represent compared with conv5_x?**
   Answer: Conv2_x is the stage of early vision features with detailed spatial dimensions and few channels. It detects edges, colors, and textures. On the other hand, conv5_x is the stage of late semantic features with low-resolution spatial dimensions and many channels, which detect full object parts and classes. To summarize, conv2_x shows the network where the fine-grained information is, while conv5_x shows it what object is depicted.

3. **Why does the spatial resolution decrease with network depth?**

Answer: The spatial dimensions decrease due to pooling layers and strided convolutions, which make down-sampling of feature maps from one stage to another possible. It increases the receptive field of neurons, meaning that they can see bigger areas of an image as a whole.

4. **Why does the number of feature channels increase with network depth?**
   Answer: More channels are used to compensate for the lack of spatial resolution through encoding rich and varied visual information. The deeper the layers, the greater the number of channels required to encode complex combinations of shapes, patterns, and objects identities. Through increasing the channel size, the network learns rich semantic representations required to discriminate between different flower classes.

5. **What is meant by low-level, intermediate, and high-level features?**
   Answer: Low-level features are primitive visual features like edges, corners, colors, textures, etc., detected in early layers of the network. Intermediate features correspond to combinations of low-level features, which allow recognizing components of the objects, e.g., petal texture or flower center. Finally, high-level features correspond to abstract representations of the whole object in deep layers of the model.

6. **What is the purpose of an attention mechanism?**
   Answer: The idea behind using attention is to allow the neural network to concentrate on informative features while ignoring useless noisy ones. Attention mechanism sets higher importance weight for specific spatial locations or feature channels during the forward pass of the network.

7. **What does channel attention attempt to learn?**
   Answer: Channel attention is the technique of trying to understand which channel feature carries most of the information required to determine the correct class. The technique summarizes the entire channel for all spatial locations and then captures the interrelationships between channels. Through the weighting of the informative channels, it magnifies informative visual cues and minimizes uninformative ones.

8. **What does spatial attention attempt to learn?**
   Answer: Spatial attention tries to understand the important spatial locations on an image or feature map for classification. It studies the interrelationship at all spatial locations to generate a two-dimensional importance map, which highlights the meaningful foreground objects, such as the petals and core of the flower, ignoring background regions, including leaves or soil.

9. **How is channel attention different from spatial attention?**
   Answer: Channel attention determines what is important through assigning weights to different channels but treats all spatial locations the same way. On the other hand, spatial attention determines the important locations through weighting of the spatial locations but treats all channels the same way. To put it simply, channel attention chooses the best feature detectors, whereas spatial attention chooses the best image locations.

10. **Why can channel and spatial attention be used sequentially?**
    Answer: They can be applied sequentially, since what they address are two complementary aspects of feature refinement along different dimensions. First, by applying channel attention, we highlight the most semantically relevant feature types, and second, by applying spatial attention, we pinpoint the region within which these features are present. By combining them step-by-step, a joint representation which incorporates both is formed.

11. **Why might channel attention behave differently at conv3_x and conv5_x?**
    Answer: As channels at `conv3_x` encode intermediate pattern types, such as petal-shaped patterns, applying channel attention at this layer focuses on the most relevant types of mid-level texture detectors. On the other hand, since channels at `conv5_x` encode abstract class specific concepts, attention over channels acts more like a selector of high-level category specific detectors. Hence, while channel attention in middle layers refines part detectors, it directly sharpens cues to the actual semantic class in deeper layers.

12. **Why can spatial attention be useful at an intermediate ResNet stage?**
    Answer: An intermediate feature map still contains sufficient spatial resolution to encode relevant semantic information about the object parts. Hence, introducing spatial attention is a good opportunity to filter out the irrelevant contextual information before deeper semantic processing starts. This way, later layers can commit their representational capacity to the actual object of interest.

13. **Why is self-attention computationally expensive when the feature map has high spatial resolution?**
    Answer: Spatial self-attention calculates the interaction scores for each pair of any spatial location with any other

spatial location from the feature map. When the spatial resolution becomes high, then the number of locations becomes extremely large, resulting in the increase in the computational cost for all the pairwise interactions being performed.

14. **What happens to the size of the self-attention matrix when the spatial resolution increases?**
Answer: The size of the attention matrix increases exponentially with an increase in the total number of spatial locations. Doubling the spatial resolution will lead to a four-fold increase in the total number of locations and thus the attention matrix will be 16 times larger than before. This increase happens rapidly and the memory soon gets exhausted.

15. **How does attention performance vary when the insertion position is changed?**
Answer: Attention inserted at an early stage does not provide much benefit since low-level features do not have semantic meanings while high resolution leads to high computation cost. Attention inserted at a later stage provides good trade-offs between semantic information and spatial information. Attention inserted at the late stage improves the concepts, but not the details that were lost at an early stage.

16. **How does attention at P_2 differ visually from attention at P_4?**
Answer: The visual attention maps at position two demonstrate high-resolution responses, highlighting the image's edges, textures, and fine lines. In contrast, the attention maps at position four visualize low-resolution regions, covering entire semantic objects in the flower. The model at position two focuses on an image's fine details, while the one at position four visualizes entire objects.

17. **Does applying attention at multiple stages always improve classification performance?**
Answer: No, the attention module added at multiple stages does not necessarily improve the classification results. While the multiple attention blocks refine features repeatedly, they add extra parameters and can overfit on the few training samples. In most cases, adding a single attention block at a particular position improves the results with fewer parameters.

18. **Does Channel→Spatial attention behave differently from Spatial→Channel attention?**
Answer: Yes, I think, implementing channel attention first improves the overall performance. This is because the channel attention determines which features are important, and, therefore, the spatial attention knows where to pay attention. On the other hand, if the spatial attention is implemented first, it will have to determine which channels to emphasize blindly.

19. **How does the spatial-attention kernel size influence the attention map?**
Answer: Using a bigger kernel, like seven by seven, can improve results because it covers a broader region, picking up global information and creating a soft attention mask. On the other hand, a three by three kernel covers only a small part of the image, and, therefore, the attention mask would be fragmented. As a result, a bigger kernel size is expected to visualize more relevant information in the image, thus producing better results.

20. **How does SE attention differ from ECA attention?**
Answer: The Squeeze-and-Excitation attention compresses channel dimensions using two dense layers and then restores them, thus leading to the addition of extra parameters and possible loss of some information. In contrast, Efficient Channel Attention does not involve any dimensionality reduction and uses one-dimensional convolution to capture the interaction of channels locally. Thus, ECA is much more efficient and accurate than the Squeeze-and-Excitation attention.

21. **How does CBAM combine channel and spatial attention?**
Answer: The CBAM attention network applies both channel and spatial attention through the usage of sequential connection of both attentions. It first performs channel attention through average and max pooling in order to re-weight feature channels. Afterward, it passes channel attention results to spatial attention, which emphasizes the most important spatial coordinates.

22. **How does self-attention differ from channel attention?**
Answer: In self-attention, all pairs of spatial positions are calculated in order to establish the relationships between the distant image pixels. Thus, the self-attention mechanism makes distant areas of an image able to communicate with each other. Channel attention establishes the relations between channels but does not take into account the relation between spatial points.

23. **Does the attention mechanism with the largest number of parameters necessarily provide the**

highest accuracy?
Answer: No, the largest number of parameters does not necessarily deliver the highest accuracy. Heavier attention modules may easily overfit medium-sized datasets, and introduce instabilities in training. In practice, lighter attention designs often match or exceed the accuracy, by generalizing better, while incurring only a negligible overhead.

24. **What is the difference between an internal attention map and Grad-CAM?**
Answer: An internal attention map is an explicit set of weights calculated inside the network layers during the forward pass, while Grad-CAM is an explanation heatmap generated post-hoc, by flowing the gradients backwards from the output class score through the network.

25. **Why is Grad-CAM called a post-hoc explanation technique?**
Answer: Grad-CAM is called post-hoc because it is computed after the model has already completed its forward prediction. It does not change the internal processing of the model's features, but rather analyzes the existing weights by performing gradient descent in the reverse direction. Thus, Grad-CAM can be considered as an external diagnostic tool that evaluates the model decisions after they have been made.

26. **Does the attention model suppress irrelevant background regions?**
Answer: Yes, the attention model is effective in suppressing the irrelevant background regions such as grass, dirt, and leaves, by reducing their weights. Similarly, it removes the background spatial locations, preventing their features from being used downstream in the classification process.

27. **Are the attention maps of correctly classified and incorrectly classified images different?**
Answer: Yes, properly classified images have attention maps that are sharp and concentrated in the region right on the center of the flower petals. Misclassified images, on the other hand, will generally exhibit dispersed or scattered attention maps and sometimes misfocus on the leaves and other elements in the image. This is proof that misclassification is due to the network being misled by its attention.

28. **Which flower classes benefit most from attention?**
Answer: Classes with natural cluttered backgrounds and having high similarity with other classes will benefit the most from attention. Examples are classes like flowers such as daisy and dandelion whose accuracy benefits the most from attention since this mechanism distinguishes fine petals from cluttered grassy backgrounds. Classes with simple backgrounds and unique colors benefit much less.

29. **What information can be obtained from a confusion matrix that cannot be obtained from overall accuracy alone?**
Answer: A confusion matrix will show exactly which classes of flower the model often confuses with one another. It will be evident which class pairs are hard for the model to distinguish. Accuracy gives a summary score of overall performance while ignoring which particular classes are having misclassification problems.

30. **Why is macro F1 useful in addition to accuracy?**
Answer: Macro F1 evaluates the unweighted average of the performance of all the classes. This way, each class is equally important, and the high performance of the model on the frequent classes does not "hide" its low performance on the rare classes. It should give a more honest estimation of how well the model classifies different types of flowers.

31. **What is meant by the accuracy–complexity trade-off?**
Answer: The accuracy—complexity trade-off refers to how much model performance improves (i.e., accuracy increases) with adding complexity (more parameters) to the model. In other words, it is a ratio of how much accuracy increases and complexity grows when one adjusts the hyperparameters during training. A good model should have the best accuracy–complexity ratio, theoretically providing the best possible accuracy with the minimal required complexity.

32. **What is meant by the F1–inference-time trade-off?**
Answer: The F1–inference-time trade-off is similar to the accuracy–complexity trade-off but concerns the amount of time needed to make predictions with the model. Essentially, it is a ratio of how much F1 increases and inference time grows with added complexity. A good model should have the best F1–inference-time trade-off, theoretically providing the best possible F1 with the lowest possible inference time.

33. **Why must every ablation study use the same dataset split?**

Answer: Using the same dataset split allows for consistent results. Otherwise, if one randomly generates splits for the dataset, there is a possibility of getting a relatively "easy" split, resulting in higher than average accuracy and performance. By using the same split, one gets the unbiased estimate of the model's performance.

34. **Why must the same training protocol be maintained when comparing different attention mechanisms?**
Answer: Training identical parameters such as learning rate, optimization function, batch size, and epochs helps us get the true impact of each attention module because otherwise we will not be able to distinguish the effects of either changing training parameters or changing the model architecture. In addition, this approach is necessary for us to test our models on a truly equal footing.

35. **What conclusions can be drawn from the Grad-CAM comparison?**
Answer: Comparing Grad-CAM maps allows us to confirm visually the fact that attention modules indeed make heatmaps tighter, allowing us to see discriminative parts of flowers better than the baseline model does. In addition, this fact proves visually that the attention module helps suppress background noise.

33. Expected Outcome

At the end of the experiment, students should understand that an attention mechanism is not an isolated module whose behavior is independent of the backbone.
Its effectiveness depends on:

$$\boxed{\begin{aligned}\text{Attention Effectiveness} = {} & \text{Attention Type} \\ & + \text{Attention Position} \\ & + \text{Feature Resolution} \\ & + \text{Feature Semantics} \\ & + \text{Model Complexity.}\end{aligned}}$$

Students should also understand that classification performance alone does not provide a complete explanation of an attention mechanism.
A comprehensive analysis should therefore combine:

$$\boxed{\text{Classification Performance}}$$

with

$$\boxed{\text{Computational Complexity}}$$

and

$$\boxed{\text{Qualitative Visualization.}}$$

Therefore:

$$\boxed{\text{Complete Attention Analysis} = \text{Quantitative} + \text{Computational} + \text{Qualitative}}$$

The final conclusions must be based on the student's experimental results rather than on assumptions about which attention mechanism should perform best.

34. References

1. K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.
2. J. Hu, L. Shen, S. Albanie, G. Sun, and E. Wu, "Squeeze-and-Excitation Networks," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 42, no. 8, pp. 2011–2023, 2020.
3. S. Woo, J. Park, J.-Y. Lee, and I. S. Kweon, "CBAM: Convolutional Block Attention Module," *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 3–19, 2018.

4. Q. Wang, B. Wu, P. Zhu, P. Li, W. Zuo, and Q. Hu, "ECA-Net: Efficient Channel Attention for Deep Convolutional Neural Networks," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 11534–11542, 2020.
5. Q. Hou, D. Zhou, and J. Feng, "Coordinate Attention for Efficient Mobile Network Design," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 13713–13722, 2021.
6. A. Vaswani et al., "Attention Is All You Need," *Advances in Neural Information Processing Systems*, vol. 30, 2017.
7. R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, "Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization," *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, pp. 618–626, 2017.
8. TensorFlow Documentation: https://www.tensorflow.org/
9. Keras Documentation: https://keras.io/
10. TensorFlow Datasets: https://www.tensorflow.org/datasets