AI-Based Smart Waste Management System: Image-Based Classification, Smart Bin Monitoring and Automated Segregation

Vaishnavi R. Kathale
Department of Computer Engineering (CO5K), S.S.V.P.S's B. S. Deore Polytechnic, Dhule, Maharashtra, India

***Abstract*—Rapid urbanisation has increased municipal solid waste (MSW) far beyond the capacity of traditional collection and sorting methods, which depend on manual labour, fixed schedules and unreliable source segregation. This paper presents a review-based design of an AI-based smart waste management system that combines three cooperating modules: (1) image-based waste classification using convolutional neural networks (CNNs), (2) smart bin monitoring using ultrasonic sensing and Internet of Things (IoT) connectivity, and (3) AI-based automatic waste segregation using actuators driven by the classifier output. The architecture, data pipeline, training strategy, evaluation metrics and bin-fill estimation model are described. A comparison with conventional practice shows that the proposed approach can improve sorting accuracy, reduce unnecessary collection trips and give city authorities real-time data. Key challenges, such as dataset diversity, model size on edge devices and cost, are discussed along with future directions.**

***Index Terms*—Artificial intelligence, convolutional neural network, deep learning, Internet of Things, smart bin, waste classification, waste segregation.**

I. INTRODUCTION

Solid waste generation is rising together with population growth, urbanisation and changing consumption patterns. Poorly managed waste causes overflowing bins, foul odour, disease spread, blocked drains, groundwater contamination and greenhouse gas emissions from open dumps. Conventional systems rely on households to separate waste at source and on workers to collect it on fixed routes. In practice, mixed waste is common, recyclable material is lost to landfill, and collection vehicles often visit bins that are nearly empty while other bins overflow.

Artificial intelligence (AI) offers a practical way to address these problems. Deep learning models can recognise waste from images, low-cost sensors can report how full a bin is, and IoT networks can send this information to a central server. When these parts are combined, waste can be identified at the point of disposal, routed to the correct compartment, and collected only when needed.

The objectives of this paper are: (a) to review AI techniques for waste classification, monitoring and segregation; (b) to propose a layered architecture that integrates the three functions; and (c) to describe the methodology and evaluation metrics needed to build and test such a system.

II. RELATED WORK

Image-based classification. Early work used hand-crafted features with classifiers such as SVM. The TrashNet dataset of Yang and Thung [1] provided about 2,500 labelled images in six classes (glass, paper, cardboard, plastic, metal and trash) and became a common benchmark. Since then, CNN architectures such as ResNet [2], MobileNet [3] and EfficientNet [4] have been widely applied through transfer learning, because they reach good accuracy even with small waste datasets. Object detectors such as YOLO [5] are used when several items appear in one frame.

Waste detection in real environments. Majchrowska et al. [6] studied deep learning-based waste detection in natural and urban scenes and showed that cluttered backgrounds, deformed items and varying light make real-world detection harder than laboratory classification.

IoT-enabled systems. Rahman et al. [7] proposed a waste management architecture that combines a CNN, used to sort digestible and indigestible waste, with IoT for real-time data monitoring. Such work shows that classification and bin monitoring are most useful when designed as one system rather than separate tools.

III. PROPOSED SYSTEM ARCHITECTURE

The proposed system has four layers, shown in Fig. 1. The *sensing layer* contains a camera, an ultrasonic distance sensor and an optional load cell. The *edge layer* is a Raspberry Pi or similar board that runs the trained model locally, so that decisions are fast and do not depend on the network. The *actuation layer* contains servo motors or a small conveyor that drops the item into the correct compartment. The *cloud layer* receives bin status through Wi-Fi or GSM, stores it, and shows it on a dashboard for municipal staff.



Fig. 1. Layered architecture of the proposed AI-based smart waste management system.

A. Image-Based Waste Classification

A camera captures an image when an item is placed in the bin. The image is resized (for example 224×224), normalised and augmented during training with rotation, flipping, brightness change and zoom. A pre-trained CNN is fine-tuned on a waste dataset, with its final layers replaced by a softmax layer for the target classes in Table I. Lightweight models such as MobileNet are preferred for edge deployment because of their small size and low computation.

TABLE I
WASTE CLASSES AND BIN MAPPING

Class	Examples	Bin / Action
Organic	Food scraps, leaves	Green bin (compost)
Paper / Cardboard	Newspaper, boxes	Blue bin (recycle)
Plastic	Bottles, wrappers	Yellow bin (recycle)
Metal	Cans, foil	Grey bin (recycle)
Glass	Bottles, jars	White bin (recycle)
Hazardous / E-waste	Batteries, bulbs	Red bin (special)

B. Smart Bin Monitoring

An ultrasonic sensor mounted under the lid measures the distance d from the lid to the waste surface. If H is the empty-bin depth, the fill level is estimated as

$$\text{Fill}\ (\%) = ((H - d) / H) \times 100. \qquad (1)$$

When the fill level crosses a threshold (for example 80%), the microcontroller sends an alert to the cloud server. A load cell can add weight data, and a gas sensor can warn of excessive odour. Collected readings can feed a route planner that visits only the bins that need service, saving fuel and time.

C. AI-Based Waste Segregation

After the CNN predicts a class with confidence above a set limit, the edge unit rotates the servo or moves the conveyor so that the item falls into the matching compartment. Items with low confidence are sent to a 'manual check' compartment and their images are saved, so that they can be labelled later and used for retraining. This feedback loop lets the model improve over time.

TABLE II
HARDWARE AND SOFTWARE COMPONENTS

Component	Purpose
Camera module	Captures image of waste item
Ultrasonic sensor	Measures bin fill level
Load cell (optional)	Measures weight of waste
Raspberry Pi / ESP32	Edge inference and control
Servo motor / conveyor	Moves item to correct bin
Wi-Fi / GSM module	Sends data to cloud
Python, TensorFlow / PyTorch, OpenCV	Model training and image processing
Cloud dashboard (MQTT / REST)	Monitoring, alerts, route planning

IV. METHODOLOGY AND EVALUATION

Data. Public datasets such as TrashNet [1] can be combined with locally collected images that reflect the waste actually found in the target city (for example food waste, plastic pouches and leaf litter). Local images are important because public datasets mostly contain single items on plain backgrounds.

Training. The dataset is split into training, validation and test sets. Transfer learning with a small learning rate is used first, followed by optional fine-tuning of deeper layers. Early stopping avoids over-fitting.

Metrics. Classification performance is measured with accuracy, precision, recall and F1-score:

$$\text{Precision} = TP/(TP+FP), \quad \text{Recall} = TP/(TP+FN),$$

$$F1 = 2 \cdot \text{Precision} \cdot \text{Recall} / (\text{Precision} + \text{Recall}). \qquad (2)$$

System-level metrics include inference time per item, mis-sorting rate at the actuator, sensor error in fill estimation, alert delay and power consumption. A confusion matrix is used to find classes that are often mixed up, such as paper and cardboard, or glass and plastic.

V. DISCUSSION

Table III compares conventional practice with the proposed system. The main benefits are higher segregation quality, fewer unnecessary trips, lower human exposure to waste and availability of data for planning. Better segregation also raises the value of recyclable material and reduces the load on landfills.

TABLE III
CONVENTIONAL VS. AI-BASED WASTE MANAGEMENT

Aspect	Manual / Fixed Schedule	AI-Based Smart System
Segregation	Human sorting, error-prone	Automatic CNN-based sorting
Collection	Fixed routes, often half-empty bins	Fill-level triggered, optimised routes
Monitoring	None or periodic inspection	Real-time dashboard and alerts
Worker safety	Direct contact with waste	Reduced human contact
Data for planning	Little or none	Continuous data logging

Challenges. (i) *Dataset gap:* models trained on clean images may fail on dirty, wet, crushed or overlapping items [6]. (ii) *Look-alike materials:* transparent plastic and glass, or coated paper and plastic, are difficult to separate by vision alone; adding sensors such as inductive (metal) or moisture sensors can help. (iii) *Edge limits:* low-power boards restrict model size, so model compression and quantisation may be needed. (iv) *Cost and maintenance:* cameras and sensors must resist dust, moisture and vandalism. (v) *Connectivity and privacy:* bins in areas with weak networks need low-power long-range communication, and images should be processed locally and not stored longer than needed.

VI. CONCLUSION AND FUTURE SCOPE

This paper presented an AI-based smart waste management system that unites image-based classification, smart bin monitoring and automated segregation in one architecture. By recognising waste at the source, reporting fill levels in real time and sorting items automatically, the system addresses the main weaknesses of manual waste handling. Future work includes building a large local waste dataset, using object detection for multiple items, adding multi-sensor fusion, applying federated learning so that many bins can improve a shared model without sharing images, and predicting waste generation to plan collection in advance.

REFERENCES

[1] M. Yang and G. Thung, “Classification of trash for recyclability status,” Stanford Univ., CS229 Project Report, 2016.

[2] K. He, X. Zhang, S. Ren and J. Sun, “Deep residual learning for image recognition,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2016, pp. 770–778.

[3] A. G. Howard *et al.*, “MobileNets: Efficient convolutional neural networks for mobile vision applications,” arXiv:1704.04861, 2017.

[4] M. Tan and Q. V. Le, “EfficientNet: Rethinking model scaling for convolutional neural networks,” in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2019, pp. 6105–6114.

[5] J. Redmon, S. Divvala, R. Girshick and A. Farhadi, “You only look once: Unified, real-time object detection,” in *Proc. IEEE CVPR*, 2016, pp. 779–788.

[6] S. Majchrowska *et al.*, “Deep learning-based waste detection in natural and urban environments,” *Waste Manag.*, vol. 138, pp. 274–284, 2022, doi: 10.1016/j.wasman.2021.12.001.

[7] M. W. Rahman, R. Islam, A. Hasan, N. I. Bithi, M. M. Hasan and M. M. Rahman, “Intelligent waste management system using deep learning with IoT,” *J. King Saud Univ. Comput. Inf. Sci.*, vol. 34, no. 5, pp. 2072–2087, 2022, doi: 10.1016/j.jksuci.2020.08.016.