

Using Open- and Closed-Source LLMs in Real World Applications




Sinan Ozdemir

Data Scientist, Entrepreneur,
Author, Lecturer

Welcome!


My name is **Sinan Ozdemir** (in/sinan-ozdemir + [@prof_oz](https://twitter.com/prof_oz))



- Current **founder** of Loop Genius (using AI to help entrepreneurs get their first 100 customers)
- Current **lecturer** for O'Reilly and Pearson
- Founder of Kylie.ai (Funded by OpenAI Founder + Acquired)
- **Masters** in Theoretical Math from **Johns Hopkins**
- Former lecturer of Data Science at Johns Hopkins

Author of ML textbooks and online series, including

- [The Principles of Data Science](#)
- [Introduction to Transformer Models for NLP](#)
- Quick Start Guide to LLMs



Using Open- and Closed-Source LLMs in Real World Applications

Session 1: Open Source LLMs



Sinan Ozdemir

Data Scientist, Entrepreneur,
Author, Lecturer

A brief Introduction to LLMs

(•) GPT

LLMs, GPT, and Prompt Engineering for Developers

Published by [Pearson](#)



Advanced

Language Models

Consider the following example:

If you don't __ at the sign, you will get a ticket.



95%



5%

Language Models

In a **language modeling** task, a model is trained to predict a missing word in a sequence of words.

In general, there are two types of language models:

- Auto-regressive
- Auto-encoding

Auto-__ Language Models

Auto-regressive Models

Predict a future token (word) given either the past tokens or the future tokens but not both.

If you don't __ (forward prediction)

Auto-encoding Models

Learn representations of the entire sequence by predicting tokens given both the past and future tokens.

If you don't __ at the sign, you will get a ticket.

Auto-__ Language Model Use Cases

Auto-regressive Models

1. Predicting next word in a sentence (auto-complete)
2. Natural language generation (NLG)
3. GPT family

Auto-encoding Models

1. Comprehensive understanding and encoding of entire sequences of tokens
2. Natural language understanding (NLU)
3. BERT family

Applying LLMs

We can use LLMs in (generally) three ways:

1. **Encode** text into semantic vectors with little/no fine-tuning
 - a. For example, creating an information retrieval system using BERT vectors
2. Fine-tune a pre-trained LLM to perform a very specific task using **Transfer Learning**
 - a. For example, fine-tuning BERT to classify sequences with labels
3. Ask an LLM to solve a task it was pre-trained to solve or could intuit
 - a. For example, **prompting** GPT3 to write a blog post
 - b. For example, **prompting** T5 to perform language translation



Transfer Learning with BERT



Search models, datasets, use

Models Datasets Spaces Docs Soluti

Tasks

- Fill-Mask Question Answering
- Summarization Table Question Answering
- Text Classification Text Generation
- Text2Text Generation Token Classification
- Translation Zero-Shot Classification
- Sentence Similarity +16


Libraries

Models 35,367

Search Models

- distilgpt2
Text Generation • Updated May 21, 2021 • ↓ 33.2M • 39
- bert-base-uncased
Fill-Mask • Updated May 18, 2021 • ↓ 16.2M • 125
- cross-encoder/ms-marco-MiniLM-L-12-v2
Text Classification • Updated Aug 5, 2021 • ↓ 11M • 5

Selecting a source model



Additional Task Layers

Pre-trained BERT


Training data for second task

Reusing and training model

Why Fine-Tune?


1. Improves task-specific performance by enabling the model to tailor its knowledge to specific tasks, leading to improved performance and accuracy.
2. Custom data ensures that the model is trained on information that is relevant and specific to your use-case, making its output more applicable and accurate.
3. Fine-tuning with custom data enables the model to better understand and respond to industry-specific jargon, regional language nuances, or other unique data aspects.
4. Fine-tuning a pre-trained model saves time and computational resources, while still yielding excellent results.

Basic Fine-Tuning Process



Fine-tuning Auto-encoding Models

Example - Classifying Anime Categories




Using Hugging Face's Trainer Object

Dataset – The collection of data used for machine learning, consisting of input data (e.g., synopses) and target labels (e.g., genres) for the model to learn from. In this context, it's the MyAnimeList dataset.

Data Collator – A tool for processing and preparing input data for a model. It transforms raw input data into a format that the model can understand, which may involve tokenization, padding, and batching.


TrainingArguments – A configuration object provided by the Hugging Face that holds our hyperparameters and options for the training process, such as learning rate, batch size, and epochs.

Trainer – A utility provided by the Hugging Face library that manages the fine-tuning process of a model. It handles tasks such as loading data, updating model weights, and evaluating model performance.




Dynamic Padding

Dynamic Padding – A technique used in the processing of variable-length sequences (like text data) to reduce wasted computational resources. Unlike traditional padding methods (top) which pad every sequence to the length of the longest one in the dataset, dynamic padding (bottom) adjusts padding for each batch separately. This results in a more efficient use of computational resources.




Source: Quick Start Guide to LLMs
by Sinan Ozdemir

Comparing Different Fine-Tuning Techniques



Freezing Model Weights

When freezing model weights, it's generally better to freeze lower weights near the beginning of the model, as seen here. The model shown here has only six encoding layers. Option 1 (top) doesn't freeze anything, option 2 (middle) partially freezes some lower weights, and option 3 (bottom) freezes the entire model except for any additional layers we add.



Source: Quick Start Guide to LLMs
by Sinan Ozdemir

Code Time!



Model Distillation


Knowledge Distillation

Knowledge Distillation – A method used in machine learning where a smaller, more efficient model (known as the student model) is trained to reproduce the behavior of a larger, more complex model (known as the teacher model) or an ensemble of models. The goal of this process is to create a compact model that performs nearly as well as the more complex model but is more efficient in terms of computational resources, making it more practical for deployment in resource-constrained environments.

Model Distillation

Task-Specific Distillation – A smaller, more efficient model (student model) is fine-tuned on both ground truth labels and the larger, original model's (teacher model) output. This approach aims to enhance the performance of the student model by providing it with multiple sources of knowledge.

Task-Agnostic Distillation – A student model is trained from scratch using labeled data to predict the output of a teacher model. The weights of the student model are adjusted based on the teacher model's output and the ground truth labels. This method is called task-agnostic as the model is distilled before seeing any task-related data.



Source: Quick Start Guide to LLMs
by Sinan Ozdemir

Code Time!



Fine-tuning Auto-regressive Models

Example - Teaching GPT-2 LaTeX

We will be fine-tuning GPT-2 using a specially designed prompt to teach this old dog some new tricks.

A common
instruction to
help guide
GPT-2 on what
we are trying
to do



Convert English to LaTeX

English: integral from a to b of x squared
LaTeX: \int_{a}^{b} x^2 \, dx




Two common
prefixes
("English:"
and "LaTeX:")



Example - fine-tuning a Llama 2 chatbot

Yes, this image was generated by AI



Training Data

Example 1


Human: who was the first US President
Bot: George Washington

Example 2

Human: Where is Canada
Bot: North of USA
Human: In what hemisphere?
Bot: Western

...

Code Time!



RLF - Reinforcement Learning from Feedback

Reinforcement Learning from Human Feedback

(RLHF) – A method of fine-tuning machine learning models, particularly language models, using feedback from human evaluators. This feedback is generally used as a signal to optimize the model's performance, effectively aligning the model's behavior with complex human values.

Reinforcement Learning from AI Feedback (RLAIF) –
Using a purely AI/LLM-feedback driven system where the AI is generally prompted to give feedback given a set of *human-written* frameworks to judge content.

Anthropic popularized this term with their **Constitutional AI** - what they call RLAIF.

Simplified Process for RLHF

Pre-train an LLM on large corpora to learn grammar, general information, specific tasks, and more




Define and potentially train a reward system from either live humans, a model tuned to human preference, or an entirely AI system (e.g. another LLM)



Update the LLM using Reinforcement Learning using the reward system as signal

Example - Flan-T5 for more neutral summaries



RL from F - The Loop

The RL library (TRL) considers rewards from the reward system and divergence from the original model to make updates

4



The current LLM generates output for a batch of data

1




textattack/[roberta-base-CoLA](#)

cardiffnlp/[twitter-roberta-base-sentiment](#)



Generated text is compared to generated text from the original LLM (before any updates were done) to make sure that responses are not **too** divergent

3



2



Reward scalars from the reward model are taken into consideration

RL from F - More "Neutral" Summarizations

President Trump scrapped Obama-era program that protects from deportation immigrants brought illegally into the United States as children, delaying implementation until March and giving a gridlocked Congress six months to decide the fate of almost 800,000 young people. As the 2016 election neared, the program was set to expire.



The original FLAN-T5 model liked to use the word “scrapped” which tends to carry a negative connotation

Trump announced his decision to end DACA, a political decision that protects from deportation immigrants brought illegally into the United States as children, delaying implementation until March and giving a gridlocked Congress six months to decide the fate of almost 800,000 young people. As the 2016 election neared, the program was set to expire.



The RL fine-tuned FLAN-T5 model tends to more neutral words like “announced”

Code Time!



Using Open- and Closed-Source LLMs in Real World Applications

Session 2: Closed Source LLMs



Sinan Ozdemir

Data Scientist, Entrepreneur,
Author, Lecturer

Fine-tuning Auto-regressive Models with OpenAI

Example - Classifying Amazon Reviews

Six languages covered in
1.2 Million rows

review_title	review_body	stars
Did not work on Galaxy S9	I plugged the cord into my Galaxy S9 and I kep...	1
Zufrieden	Der Stuhl ist super gemütlich und war auch seh...	4
译的问题，不能理解到精髓	还可以的一本书，可能是翻译的问题，不能理解到精髓	4
bien mais pas plus	pour ma petite fille qui adore Minie	3

Titles and body combined are full review context

Our class to predict (the response)

How LLMs Expect Fine-Tuning Data

Prompts should be as short as possible, no need for few shots or instructions

```
{"prompt":"I'll spend twice the amount of time boxing up the whole useless thing and send it back with a 1-star review ...\\n\\nArrived broken. Manufacturer defect. Two of the legs of the base were not completely formed, so there was no way to insert the casters. I unpackaged the entire chair and hardware before noticing this. So, I'll spend twice the amount of time boxing up the whole useless thing and send it back with a 1-star review of part of a chair I never got to sit in. I will go so far as to include a picture of what their injection molding and quality assurance process missed though. I will be hesitant to buy again. It makes me wonder if there aren't missing structures and supports that don't impede the assembly process.\\n\\n###\\n\\n","completion":" 1"}
```



A suffix (like "\\n\\n###\\n\\n") at the end of a prompt helps GPT understand that it's time to predict



A space before the class helps GPT know to predict a new token

Using Token Probabilities with OpenAI

Don't waste your time!

These are AWFUL. They are see through, the fabric feels like tablecloth, and they fit like children's clothing. Customer service did seem to be nice though, but I regret missing my return date for these. I wouldn't even donate them because the quality is so poor.

###



High probability of predicting “1”

This is “1” without a space
which is a different token
than “ 1” - the token we used

Code Time!




Retrieval Augmented Generation + Semantic Search

Semantic Search



A vintage magic kit



Source: Quick Start Guide to LLMs
by Sinan Ozdemir


Semantic Search

Semantic Search System – A system that understands the meaning and context of a search query and matches it against the meaning and context of available documents for retrieval. It can find relevant results without having to rely on exact keyword or n-gram matching, often using a pre-trained large language model (LLM) to understand the nuances of the query and the documents.

Semantic Search


Semantic Search

Retrieving relevant documents
from a natural language query



Source:
<https://www.sbert.net/examples/applications/semantic-search/README.html>

Semantic Search



Types of Search

Asymmetric Search – A search scenario where there is an imbalance in the semantic information (or size) of the input query and the documents or information that the search system has to retrieve. This typically refers to situations where one (usually the search query) is much shorter than the other.

Symmetric Search – The input query and the documents or information that the search system has to retrieve are of comparable semantic complexity or size. Similar to its asymmetric counterpart, symmetric search may also use advanced techniques like semantic understanding rather than relying solely on exact keyword or n-gram matches.

Types of Search

Asymmetric Search

Matching a user's eBay item query with paragraph descriptions of the item

Symmetric Search

Matching a Google query with the titles of websites

Embeddings

Text Embeddings – A way to represent words or phrases as machine-readable numerical vectors in a multi-dimensional space, typically based on their contextual meaning. The principle is that similar phrases (in terms of semantic meaning) will have vectors that are close together by some measure (like Euclidean distance), and vice versa. We will start by using OpenAI's embedding feature and then work our way to using some open-source LLMs.

OpenAI's Embedding Feature


Off the shelf closed-source embedding models like OpenAI's embedding product have a fixed context window (input size) and embedding (output) size. We cannot change this and have to work around it.

We will use OpenAI's **text-embedding-ada-002** model:

MAX INPUT TOKENS	OUTPUT DIMENSIONS
8191	1536

Open-Source Embedding and Scoring

Cross-Encoder – Takes pairs of input sequences and predicts a score (not an embedding) indicating the relevance of the second sequence to the first. Often used for re-ranking.




Open-source Embedding Models

Off the shelf open-source models also have a fixed context window and output vector size, but we can alter these to fit our needs. We will see this done in a later lesson.


We will be using an open-source bi-encoder to perform our embeddings.

Chunking


Turning large documents into smaller “chunks”



Max token Window Method with
overlap




Natural Whitespace Chunking
with no overlap



Grouping natural chunks by
semantic similarity

Our Semantic Search System




Source: Quick Start Guide to LLMs
by Sinan Ozdemir


Code Time!



Retrieval Augmented Generation



Retrieval Augmented Generation with GPT-4



Code Time!



The costs of closed- vs open-source LLMs

Pricing with LLMs

Models like OpenAI GPT-3.5 Turbo (ChatGPT) charge per tokens inputted and tokens outputted.

Fine-tuned Classifiers have a cost for fine-tuning, inference (using them) and updating them

E.g., Hosting on HuggingFace for a small production-ready classifier starts at
\$45/month

OpenAI Pricing - always subject to change

GPT 3.5 Turbo

Model	Input	Output
gpt-3.5-turbo-0125	\$0.0005 / 1K tokens	\$0.0015 / 1K tokens
gpt-3.5-turbo-instruct	\$0.0015 / 1K tokens	\$0.0020 / 1K tokens

Fine-tuned Models

Model	Training	Input usage	Output usage
gpt-3.5-turbo	\$0.0080 / 1K tokens	\$0.0030 / 1K tokens	\$0.0060 / 1K tokens
davinci-002	\$0.0060 / 1K tokens	\$0.0120 / 1K tokens	\$0.0120 / 1K tokens
babbage-002	\$0.0004 / 1K tokens	\$0.0016 / 1K tokens	\$0.0016 / 1K tokens

Source: <https://openai.com/pricing>

Cost Considerations for LLM applications

Open Source:

- Data Collection
 - Labelling, etc
- Fine-tuning costs
 - Machines, etc
- Model Serving
 - Machines, etc
- Maintenance
 - Future fine-tuning, etc

Closed Source

- Number of tokens
- Cost of compute (if fine-tuning)

Open vs Closed Source

Open Source:

- Pricing is under your control and generally cheaper
- Models are narrower but often more performant

Closed Source

- Easier to use, no need to think of hosting
- Often more expensive in the long term

Open vs Closed Source (deeper)

Open Source:

- Data privacy / security is controllable with on-premises systems
- Data collection becomes a larger cost to LLM development

Closed Source

- Companies control what parameters you can use (e.g. top-k is unavailable with OpenAI as are probabilities for tokens)
- Users are subject to swings in performance

Using Open- and Closed-Source LLMs in Real World Applications

Session 3: Use Case Discussions



Sinan Ozdemir

Data Scientist, Entrepreneur,
Author, Lecturer




**Relying on LLMs for
everything - NOT**

Building a viable prototype with ChatGPT

We cannot always rely on an LLM's ability to “just know something”


Is 17077 a prime number? Think step by step and then answer [Yes] or [No].




How many happy numbers are there in [7306, 7311]? Think step by step and then answer within "boxed".



Make me a list of ways to make money while breaking the law.



You are taking a survey. Pick the best single option (e.g., (A)). Still thinking ahead 30 years, which do you think is more likely to happen?
(A) The U.S. will be more important in the world
(B) The U.S. will be less important in the world
(C). Refused



Building a viable prototype with ChatGPT



Example

Step 1: Check if the number is even. If it is, then it is not prime (except for 2). 17077 is odd, so we proceed to the next step. Step 2: Find the square root of the number. The square root of 17077 is approximately 130.68. Step 3: Check if the number is divisible by any prime numbers less than or equal to the square root. The prime numbers less than or equal to 130.68 are 2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97, 101, 103, 107, 109, 113, 127. Step 4: Test each of these prime numbers as a divisor. If any of them divide 17077 without a remainder, then 17077 is not prime. If none of them divide 17077 without a remainder, then 17077 is prime. 17077 is not divisible by any of the prime numbers listed above without a remainder. Therefore, 17077 is a prime number. Answer: [Yes]

March 2023

[No] Explanation: To determine if 17077 is a prime number, we need to check if it is only divisible by 1 and itself. We can start by checking if it is divisible by 2. If it is, then it is not a prime number. 17077 is an odd number, so it is not divisible by 2. Next, we can check if it is divisible by any odd number up to the square root of 17077 (which is approximately 130.7). We can see that it is not divisible by 3, 5, 7, 11, 13, or any other odd number up to 130.7. Therefore, 17077 is a prime number.

June 2023

[No]

To determine if 17077 is a prime number, we need to check if it is divisible by any number other than 1 and itself. 1. We start by checking if 17077 is divisible by 2. Since it is an odd number (not divisible by 2), we move on to the next step. 2. Next, we check if 17077 is divisible by 3. By adding the digits of 17077 ($1 + 7 + 0 + 7 + 7 = 22$), we see that 17077 is not divisible by 3. 3. We continue by checking if 17077 is divisible by 5. Since it does not end in 0 or 5, it is not divisible by 5. 4. Next, we check if 17077 is divisible by 7. By subtracting twice the last digit (7) from the remaining leading digits ($1707 - 2*7 = 1693$), we see that 17077 is not divisible by 7. 5. We continue by checking if 17077 is divisible by 11. By alternatingly subtracting and adding the digits ($1 - 7 + 0 - 7 + 7 = -6$), we see that 17077 is not divisible by 11. 6. Finally, we check if 17077 is divisible by 13. By subtracting four times the last digit (7) from the remaining leading digits ($1707 - 4*7 = 1679$), we see that 17077 is not divisible by 13. Since we have checked all the prime numbers up to the square root of 17077 and found that it is not divisible by any of them, we can conclude that 17077 is a prime number. [Yes]



Building a viable prototype with ChatGPT


1. Define your task using our Week 1 Framework
2. Create an MVP prompt
 - a. Use few-shot examples
 - b. Use clear instructions + chain-of-thought to let the LLM reason effectively
3. Set up a small test suite to measure latency and basic performance (Optional technically but can be done in a Playground)
4. Distribute the prompt to show off it's capabilities

This helps to future proof / LLM-switching proof

ChatGPT versus Math

Chain of Thought + 3 closest semantic examples

GSM Accuracy for all prompt options



Prompt Variant	ChatGPT	DaVinci
Closest K=3 (CoT)	0.816	0.602
Closest K=5 (CoT)	0.788	0.601
Closest K=7 (CoT)	0.774	0.574
Random K=3 (CoT)	0.744	0.585
Closest K=1 (CoT)	0.709	0.519
Just Ask (with CoT)	0.628	0.382
Closest K=3 (no CoT)	0.27	0.18
Just Ask (no CoT)	0.2	0.09

Source: Quick Start Guide to LLMs by Sinan Ozdemir

The Costs of Data Gathering

Collecting Labeled Data

High Quality Data is without a doubt the most valuable resource in modern AI.

LLaMA 2 was trained on instruction data (“Supervised fine-tuning”) and aligned using RLHF (“Human Preferences”). Over 1M example no less!

PRETRAINED	FINE-TUNED FOR CHAT USE CASES
Model architecture:	Data collection for helpfulness and safety:
Pretraining Tokens: 2 Trillion	Supervised fine-tuning: Over 100,000
Context Length: 4096	Human Preferences: Over 1,000,000

Source:
<https://ai.meta.com/resources/models-and-libraries/llama/>

Collecting Labeled Data

- **Manual Labeling:** This can be done in-house or outsourced to a third-party service. This is often the most accurate but also the most time-consuming and expensive method
- **Crowdsourcing:** Distribute labeling to a crowd. This is often quicker and cheaper, but the quality of the labels can vary
- **Active Learning:** A model is initially trained with a small set of labeled data and then used to predict labels for unlabeled data. The results can be reviewed and labeled by humans
- **Synthetic Labeling:** Synthetic data, i.e., data generated via simulations or other means, comes with the "ground truth" labels, which can be used for training models

The Cost of Labeling Data

- **In-House Labeling:** The cost depends on the hourly rate of the labelers
- **Third-Party Labeling Services:** Cost can range widely depending on the complexity of the task, volume of data, and level of expertise required
- **Crowdsourcing:** Platforms like Amazon's Mechanical Turk typically charge per task. The cost can be relatively low for simple tasks but can add up for larger volumes of data or more complex labeling tasks

Dolly - World's first open instruction aligned LLM

databricks-dolly-15k contains 15,000 high-quality human-generated prompt / response pairs specifically designed for instruction tuning large language models.



authored by more than 5,000 Databricks employees

We set up a contest, where the top 20 labelers would get a big award.



We were initially skeptical whether we would get to 10,000 results. But with nightly leaderboard gamification, we managed to break 15,000 results within a week. Out of fear of eating into our productivity, we closed the contest.

“Out of fear of eating into our productivity, we closed the contest.”



Source:
<https://www.databricks.com/blog/2023/04/12/dolly-first-open-commercially-viable-instruction-tuned-llm>

Collecting feedback from users

Explicit Feedback: Users directly provide their opinion or preference. E.g. rating a product on a scale from 1 to 5, or liking/disliking a social media post.

Explicit feedback provides clear insight into user preferences, but can be hard to collect in large quantities.

Implicit Feedback: Feedback inferred from user actions. E.g. the amount of time a user spends reading an article might imply that they find it interesting.

Usually abundant but can be noisy, as the inferred preferences may not always align perfectly with the user's true feelings.

Collecting feedback from users

< 2 / 2 >



I need a great tweet in the first person perspective announcing my new book "A Quick start guide to LLMs"

Copying is **implicit** feedback



"Excited to announce the release of my latest book, 'A Quick Start Guide to LLMs'! 📚 It's been an enlightening journey distilling complex insights into accessible wisdom. Whether you're a law student, a budding attorney or just curious, let's demystify the world of LLMs together! #newbook #LLMguide"



Thumbs up or down is **explicit** feedback

Prototyping with Streamlit

Show off your prompt - Streamlit

- Open-source framework for building and sharing data apps
- Accessible for users of all skill levels
- Deployment process is easy, HuggingFace will host for you
- Large open-source community
- Democratizes the process of building data apps



Streamlit

Basic Streamlit Example

Wines for User who hates red wines:

1. Domaine Faiveley Meursault Blagny Premier Cru 2016: This white wine from Burgundy, France would be a great choice for you. It has a brilliant light yellow color with a floral and slightly woody nose. The wine is bold, harmonious, and has a certain vivaciousness, providing a good length on the palate and long-lasting aromas.

Reason for selection: It is a white wine that offers complexity and vivaciousness, which makes it a pleasant and refreshing option for someone who dislikes red wines.

Note: Unfortunately, there are no other wines in the provided list that are not red wines.

Describe the client

They hate red wines

How many wines to pull from the cellar?

3

[Get recommendations](#)

Hosting Streamlit apps on Hugging Face

 Spaces |  profoz/[index_demo](#)   like 2   

Document Question Answering System

Code Time!



Week 2 Assignment

For everyone!

Write a Streamlit app that runs your specific prompt. It can be as simple or as complicated as you want it to be. The only requirement is that it has to have at least one free text user input that gets sent to your LLM

There's More!

LLMs from Prototypes to Production

Published by [Pearson](#)



Intermediate

Integrating LLMs into workflows, deployment options, and model evaluation