
SBC with on-board AMD Geode™ LX 800 Processor VGA/LVDS/TTL,



Features

- 3.5" form factor embedded board with AMD Geode™ LX 800 processor and RoHS compliant
- 333/400 MHz DDR SDRAM SO-DIMM supports up to 1 GB
- Complete I/O support with two SATA, IDE, CF Type II, PC/104, dual LAN and four USB 2.0
- 24-bit TTL/18-bit single-channel LVDS
- Value embedded applications with low power and fanless design. Support Windows® XP/CE/XPe
- The best choice for thin client Windows® CE 5.0, XPe OS image with ICA, RDP and IE APs ready

Specifications

- AMD Geode™ LX800 (500 MHz) processor
- ◆ Chipset: AMD CS5536
- ◆ BIOS: Award BIOS
- ◆ System Memory One 200-pin 400/333 MHz DDR SDRAM SO-DIMM slot supports up to 1 GB
- Ethernet Dual LAN: 10/100Mbps RTL8100C Ethernet Controller
- ◆ External I/O Interface 1 x RS-232 2 x USB 2.0
- ◆ Internal I/O Interface
- 1 x CF Type II 1 x IDE (2x22 pin, P=2.0) 1 x KB/MS (1x6 pin) 1 x LPT (2x13 pin, P=2.0)
- 1 x RS-232 (2x5 pin, P=2.0)
- 1 x RS-422/485 (2x2 pin, P=2.0)
- 2 x SATA 1.5Gb/s (RAID 0, 1 support) 2 x USB 2.0 (2x4 pin, P=2.0)
- ◆ Expansion: 1 x PC/104
- ◆ Digital I/O: 8-bit digital I/O (2x5 pin)
- ◆ Audio: Realtek ALC203 with AC'97 codec

- ◆ Display Output
 - 1 x VGA (up to 1920x1440@60Hz) 1 x 18-bit single-channel LVDS (up to 1280x1024@60Hz)
- ◆ Infrared Interface: 1 x Infrared interface (1x5 pin) ◆ Watchdog Timer
- Software programmable supports 1~255 sec system reset
- ◆ Power Supply 5V only DC input
- 1 x Internal power connector (1x4 pin) Support AT/ATX mode
- ◆ Power Consumption 5V@1.53A (AMD LX800 with one 1 GB 400 MHz
- ◆ Operating Temperature: 0°C ~ 60°C
- ◆ Storage Temperature: -10°C ~ 70°C
- ◆ Operating Humidity: 5% ~ 95%, non-condensing ◆ Dimensions: 146 mm x 102 mm

48.46


- ◆ Weight: GW: 670g / NW: 230g

94.54

◆ CE/FCC compliant

8.82

3.5" SBC with AMD Geode™ LX 800 Processor, Eight COM, DDR 400 MHz, VGA/LVDS/TTL Display Interfaces, PC/104, Four USB 2.0, Embedded OS Support



Features


- 3.5" form factor with AMD Geode™ LX 800 CPU
- One 333/400 MHz DDR SO-DIMM socket supports up to 1 GB memory
- VGA, 24-bit TTL, 18-bit LVDS display interfaces
- Seven RS-232 and one RS-232/422/485

Specifications

- AMD Geode™ LX 800 (500 MHz)
- ◆ Chipset CS5536
- ♦ BIOS
- Award BIOS
- ◆ System Memory One 200-pin 400/333 MHz DDR SDRAM SO-DIMM slot supports up to 1 GB
- ◆ Ethernet LAN: 10/100Mbps RTL8100C Ethernet
- Controller ◆ External I/O Interface 4 x USB 2 0 1 x RS-232
- ◆ Internal I/O Interface 1 x CF Type II 1 x IDE (2x22 pin, P=2.0)
- 1 x RS-232/422/485 (2x7 pin, P=2.0) 6 x RS-232 (2x5 pin, P=2.0) ◆ Expansion
- 1 x PC/104 (ISA Bus)
- 8-bit digital I/O (2x5 pin)

- ◆ Display Output 1 x VGA (up to 1920x1440@60Hz) 1 x 24-bit single-channel TTL (up to 1600x1200@60Hz) 1 x 18-bit single-channel LVDS (up to 1280x1024@60Hz)
- ◆ Audio: Realtek ALC203 with AC`97 codec
- ◆ Watchdog Timer Software programmable supports 1 ~255 sec.
- Power Supply 5V only DC input 1 x Internal power connector (1x4 pin) Support AT/ATX mode
- ◆ Power Consumption 5V@1.33A (AMD Geode™ LX 800 with one 1 GB 400 MHz DDR memory)
- ◆ Operating Temperature 0°C ~ 60°C (32°F ~ 140°F)
- ◆ Storage Temperature: -10°C ~ 70°C
- ◆ Operating Humidity 5% ~ 95%, non-condensing
- ♦ Dimensions: 146 mm x 102 mm
- ◆ Weight: GW: 670g / NW: 230g
- ◆ CE/FCC compliant

Dimensions (Unit: mm)




Packing List

1 acking List		
	1 x WAFER-LX single board computer	1 x SATA power cable
	1 x Audio cable	1 x USB cable
	1 x IDE flat cable 44p/44p	2 x SATA cable
	1 x KB/MS Y cable	1 x Mini jumper pack
	1 x RS-232/422/485 cable	1 x QIG

Ordering Information

Part No.	Description
WAFER-LX-800-R12	3.5" SBC with AMD Geode™ LX 800 processor, audio, VGA/ LVDS/TTL, dual LAN and SATA connectors
WAFER-LX-800-NS-R12	3.5" SBC with AMD Geode™ LX 800 processor, audio, VGA/ LVDS/TTL, dual LAN and w/o SATA connectors
32200-015100-RS	LPT cable, 280mm, P=2.0

Dimensions (Unit: mm)



Packing List

1 x WAFER-LX2 single board computer	2 x Quad RS-232 adapter cable
1 x Audio cable	1 x Mini jumper pack
1 x IDE flat cable 44p/44p	1 x QIG

Ordering Information

Part No.	Description
WAFER-LX2-800-R12	3.5" SBC with AMD Geode™ LX 800 processor, Audio, VGA/LVDS, TTL/LVDS, four USB 2.0, seven RS-232 and one RS-232/422/485

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

IEI:

WAFER-LX-800-NS-R12