

Final Project

Hugh Ford and Lauren Chandler-Holtz

This is an abstract

Causal Question

Using data assembled by Cheng Cheng and Mark Hoekstra for their study, “Does Strengthening Self-Defense Law Deter Crime or Escalate Violence? Evidence from Expansions to Castle Doctrine” (2013), primarily sourced from the FBI Uniform Crime Reports Summary, we sought to examine the causal relationship between implementing Castle Doctrine and murder rates in the U.S. Focusing on the “treated” population—states that passed Castle Doctrine laws between 2001 and 2010—we investigated whether these states should repeal Castle Doctrine laws in order to bring down murder rates. Formally, our causal question was: among the states that passed Castle Doctrine laws between 2001 and 2010, what was the effect of that implementation on the state’s murder rate?

Background

As Cheng and Hoekstra explain in their work, “Castle Doctrine” stems from English Common Law, allowing an exception to the “duty to retreat” when an individual is in their own home. In the United States, the legal history of Castle Doctrine dates back to the 1700s as a legacy of English colonial rule. During the era of Westward Expansion, the concept broadened to cover not only the home but also surrounding property and, in many cases, any place one had a legal right to be. Castle Doctrine principles were formally codified in 1985, when Colorado passed the “Make My Day” law, which removed any civil or criminal liability for the use of force, including lethal force, against a home invader.

The modern expansion of self-defense laws began with Florida in 2005, when it became the first state to strengthen its self-defense protections and explicitly expand Castle Doctrine to places outside the home. This change in statute was quickly adopted by about twenty other states in the following years. Since 2005, Castle Doctrine has spread to the significant majority of US states. However, laws vary state to state, with some being limited to the home while others are expanded to include other places, e.g., one's place of work or in one's vehicle.

Castle Doctrine often goes hand-in-hand with so-called "Stand Your Ground" laws; however, Castle Doctrine is distinguished from such laws in that it specifically applies to the home (and sometimes other areas such as one's workplace or car) and allows the use of deadly force, even if disproportionate. In contrast, Stand Your Ground typically applies to anywhere one has a legal right to be but only allows defensive proportional force.


Proponents of Castle Doctrine argue that it is a useful deterrent to crime and contributes to public safety. Critics, on the other hand, contend that these laws may instead unnecessarily escalate levels of violence. The aim of our research is to investigate whether Castle Doctrine laws have a significant impact on states' murder rates. For the purpose of our research, "murder rate" excludes cases that were ruled justifiable homicides.

Creating a Directed Acyclic Graph (DAG)

We began by creating a DAG to represent the causal relationships between variables in our dataset. First, we specified our outcome as the state's murder rate per 100,000 citizens and our exposure as passing a "Castle Doctrine" law between 2001 and 2010, as designated by Cheng and Hoekstra. We then identified several covariates we thought would play important causal roles in relation to murder rate and whether a state would pass a Castle Doctrine law.

For example, we believed that the murder rate as well as the decision to pass a Castle Doctrine Law could depend on the state's demographics as well as the prevalence of certain crimes in the year prior, such as robbery with a firearm, assault, and even murder itself, as these crimes would likely create an atmosphere of fear that would sway voters and politicians to pass such a law. In our analysis, we lagged all the crime variables (assault, burglary, motor vehicle theft, murder, robbery, and robbery with a firearm) by one year, so we were able to accurately capture their causal effect on the next year.

Our full DAG illustrating the causal relationships we believe are in effect is presented **Figure 1**.



DAG

Figure 1: DAG

Adjustments and Missing Data

Adjustment Sets

After mapping out our DAG, the next step in our Causal Analysis was identifying potential confounders that we would need to adjust for in our model. There are two possible adjustment sets for our DAG as shown in **Figure 2**. The minimal adjustment set includes homicide, assault, burglary, robbery, robbery involving a firearm, and motor vehicle theft, while the second is made up of robbery, poverty, robbery involving a firearm, and all four male age-race variables (% of Black males age 15-24, % of white males age 15-24, % of black males age 25-44, % of white males age 25-44).

ult, burglary, homicide, motor, robbery, robbery_gi poverty, robbery, robbery_gun_r, young_male_race




Figure 2: DAG w. Adjustment Sets

Missing Data

In our analysis of missing data, we found that robbery involving a firearm has about 1.09% missing data (6 observations), and is only missing for one state, Washington. No other variables include missing data. Due to the low level of missingness and the fact that Washington did not implement Castle Doctrine, which is the much larger subpopulation, we proceeded with a complete case analysis and excluded the state of Washington from consideration.




Figure 3: Missing Data Visualization

Table 1: **Table 1: Sample Characteristics by Castle Doctrine**

Characteristic	Post-Doctrine N = 74	Pre-Doctrine N = 411	Overall N = 485
Assault	312 (188, 456)	226 (161, 348)	235 (163, 357)
Burglary	906 (703, 1,008)	634 (510, 882)	663 (515, 936)
Homicide	6.14 (4.65, 7.02)	4.44 (2.46, 6.33)	4.73 (2.61, 6.50)
Motor Vehicle Theft	310 (225, 378)	308 (209, 426)	309 (214, 417)
Robbery	116 (90, 145)	97 (63, 153)	100 (67, 152)
Robbery w. Firearm	0.46 (0.37, 0.51)	0.34 (0.25, 0.45)	0.36 (0.26, 0.46)

¹ Rates per 100,000 persons


Propensity Weighting

We will use propensity scores in our analysis, which help us simulate what the relationship between exposure (implementing Castle Doctrine) and outcome (murder rates) would have looked like if our data was from a randomized trial instead of observational. Since we are interested in the effect on the treated states, we will use the inverse probability weight for the Average Treatment Effect Among the Treated (ATT) to estimate the ATT using propensity score weighting. Here, the propensity score for each observation is the probability of the state implementing Castle Doctrine given their particular covariate values. To simplify our model, we used the minimum adjustment set to identify confounders to include. We use logistic regression to calculate these probabilities with the model shown below:

$$\log_odds_i = S_{1:3}(Homicide_i) + S_{1:2}(Burglary_i) + Assault_i + MotorTheft_i + Robbery_i + ArmedRobbery_i$$

Unweighted

Before ATT weighting, we see we have a very large class imbalance and the majority of the propensity scores are between 0 and .2.



Unweighted

Weighted




Figure 4: Mirrored Histogram, Unweighted and Weighted




Figure 5: Mirrored Histogram, ATT Only

After plotting the propensity scores in a mirrored histogram, we do not see any clear positivity issues, and the Love plot shown below illustrates that the variables are well-balanced on the mean.




Figure 6: Love Plot

Additionally, we compared the empirical CDFs (eCDFs) of our confounders. While we were unable to achieve perfect correspondence between the two subpopulations through weighting, with the addition of splines Homicide and Burglary, brought the empirical CDFs closer together (see appendix). Overall, our assumptions appear to be sufficiently met, and we will proceed with our effect calculations.

ADD TABLE STUFF

G-Computation

To capture the time-varying effect of the implementation of Castle Doctrine, we performed G-Computation using the model with ATT weighting from our IPW model:

$$Murder_i = CastleDoctrine_i + Years_i + CastleDoctrine_i : Years_i$$

Characteristic ¹	Post-Doctrine N = 74; ESS = 74.0 ¹	Pre-Doctrine N = 411; ESS = 143.7 ¹
Assault	311 (188, 456)	310 (207, 404)
Burglary	903 (703, 1,008)	825 (639, 1,035)
Homicide	6.07 (4.65, 7.02)	6.19 (4.79, 7.34)
Motor Vehicle Theft	309 (225, 378)	296 (234, 394)
Robbery	116 (90, 145)	101 (83, 139)
Armed Robbery	0.46 (0.37, 0.51)	0.44 (0.36, 0.49)

¹Rates per 100,000 persons

Abbreviation: ESS = Effective Sample Size

Years Before After Castle Doctrine	ATT Point Est.
1	-0.797
2	-1.593
3	-2.390
4	-3.186

We simulated counterfactual data for each year for four years post and prior to enactment of Castle Doctrine laws. We then took the difference in murder rates between the years post and prior for Castle Doctrine data and the difference in murder rates between the years post and prior for Non-Castle Doctrine data. We then performed a pseudo-Difference in Differences analysis to estimate the treatment effect of Castle Doctrine across different years.

Measures of Uncertainty

In order to understand the uncertainty in our estimates, we used bootstrap methodology, resampling our data 1000 times to create a synthetic distribution of estimates. Taking the upper and lower 0.05/2-level quantiles, we were able to get an estimate for lower and upper bounds on each of our estimates. All four confidence intervals include zero, so none of our effects are statistically significant at the 95% level.

Years Before	After Castle Doctrine	ATT Estimate	ATT Standard Dev.	95% CI Lower Bound	Upper Bound
	1	-0.781	0.584	-1.881	0.319
	2	-1.546	1.137	-3.847	0.755
	3	-2.323	1.737	-5.580	0.934
	4	-3.110	2.370	-7.829	1.609

Years Before	After Castle Doctrine	ATT Point Est.
	1	-0.394
	2	-0.788
	3	-1.181
	4	-1.575

Sensitivity Analysis:

Alternate Adjustment Set:

First, we do an alternate DAG analysis. If our variables are well-measured and our DAG is correct, then we would expect each different adjustment set to result in very similar effects (each adjustment set should produce an unbiased estimate of the true causal effect). However, we see that the effects for the alternative adjustment set are notably smaller than those for the initial adjustment set—the effect direction is the same, but, especially the further out from implementation we go, the smaller the effect compared to the original DAG. This discrepancy strongly suggests that the causal structure specified in our DAG is incorrect; we made some alterations to the DAG, such as connecting the police presence variable to crime variables, but there was little to no change in the results.

Our confidence intervals still include zero and thus the effects are once again not significant.


Years Before	After Castle Doctrine	ATT Estimate	ATT Standard Dev.	95% CI Lower Bound	Upper Bound
	1	-0.3990121	0.618287	-1.558908	0.760874
	2	-0.8096308	1.189591	-3.101460	1.482190
	3	-1.1934031	1.768889	-4.361682	1.974876
	4	-1.6158240	2.385107	-6.166124	2.934472

Tipping Point Analysis


Finally, we assessed the potential impact of an unmeasured confounder on the relationship between Castle Doctrine and Murder Rate. The graph below illustrates how varying strength of an unmeasured confounder's associations with the exposure (Castle Doctrine) and the outcome (Murder Rate) would bias the estimated effect. Based on the graphs, we can identify tipping points, where the adjusted effect crosses the null.

For example, if a one standard deviation change in the unmeasured confounder reduced murder rate by 1 percent and was associated with a probability of 0.35 of not passing a Castle Doctrine law (i.e. -0.35 on the x-axis), then the upper bound of adjusted effect would cross zero, such that the 95% CI for the ATT is entirely below zero, representing a significant negative effect. Since our dataset is limited in its scope of variables, it is reasonable to believe that such a confounder might exist.

Finally, we assessed the potential impact of an unmeasured confounder on the causal relationship using a tipping point analysis. Because our effect at 1 through 4 years from implementation was not significant at a 95% significance level, our tipping point focused on the confounder needed to make the effect significant in either a positive or negative direction. For conciseness, we focused on the effect at 1 year before and after implementation. The graphs below illustrate how varying strength of an unmeasured confounder's associations with the exposure (Castle Doctrine) and the outcome (Murder Rates) would bias the estimated effect at one year before and after exposure. Based on the graph, we can identify tipping points, where the adjusted effect crosses the null.



Looking at the negative plot (shown above), we observed that, for example, if a one standard deviation change in the unmeasured confounder reduced murder rate by 2 percent and was associated with a probability of 0.45 of not passing a Castle Doctrine law (i.e. -0.45 on the x-axis), then the upper bound of the adjusted effect would cross zero, such that the 95% CI for the ATT is entirely below zero, representing a significant negative effect. Since our dataset is limited in its scope of variables, it is reasonable to believe that such a confounder might exist.



Looking at the positive plot (shown above), we observe that, if a one standard deviation change in the unmeasured confounder increased murder rate by 3 percent and was associated with a probability of 0.67 of not passing a Castle Doctrine law (i.e. -0.67 on the x-axis), then the lower bound of the adjusted effect would cross zero, such that the 95% CI for the ATT is entirely positive, representing a significant positive effect on the murder rate. Such a confounder is somewhat less likely than the previous; however, again, given the limitations in our data, more investigation would be needed to completely rule out such a confounder.

References

Cheng, Cheng, and Mark Hoekstra. 2013. “Does Strengthening Self-Defense Law Deter Crime or Escalate Violence? Evidence from Expansions to Castle Doctrine.” *Journal of Human Resources* 48 (3): 821–54.

Huntington-Klein, N., & Barrett, M. (2024, October 24). Castle Dataset. R PACKAGES. <https://r-packages.io/datasets/castle>

```
library(causaldata)
library(dagitty)
library(ggdag)
library(tidyverse)
library(knitr)
library(naniar)
library(gtsummary)
library(gt)
library(broom)
library(readxl)
library(propensity)
library(halfmoon)
library(patchwork)
library(visdat)
library(survey)
library(labelled)
library(tipr)
library(kableExtra)

data("castle")
castle$treat_year <- ifelse(castle$post == 1, castle$year, 0)

lower <- 1
upper <- 11
i <- 1
while(i < 51){
  treat_year_1 <- min(castle$treat_year[lower:upper][castle$treat_year[lower:upper] !=
  castle$treat_year[lower:upper] <- rep(treat_year_1, 11)
  lower <- upper + 1
  upper <- lower + 10
  i <- i + 1
}

castle <- castle |>
  mutate(years_after_treat = year - treat_year)

castle$years_after_treat <- ifelse(castle$years_after_treat == -Inf, NA, castle$years_
```

```

castle <- castle |>
  group_by(sid) |>
  mutate_at(c("assault", "burglary", "homicide", "larceny", "motor", "l_larceny", "l_murder",
              "l_police", "l_income", "l_exp_subsidy", "l_exp_pubwelfare"), lag) |>
  mutate(murder_lag = lag(murder)) |>
  ungroup()

castle$sid <- ifelse(as.numeric(castle$sid) > 8, castle$sid - 1, castle$sid)

state_id_list <- read_excel("state_id_list_fixed.xlsx", col_names = FALSE)
colnames(state_id_list) <- c("state", "pop", "sid")
state_id_ranks <- state_id_list |>
  select(state, sid)
castle_dat <- full_join(castle, state_id_list, by = "sid")

castle_dat <- castle_dat[castle_dat$year != 2000,]

castle_for_tab <- castle_dat |>
  select(!(starts_with("r20") |
              starts_with("trend") |
              starts_with("lead") |
              starts_with("lag") |
              starts_with("years"))))

#CCA + Dropping Washington
castle_dat <- castle_dat |>
  select(!(starts_with("r20") |
              starts_with("trend") |
              starts_with("lead") |
              starts_with("lag")))) |>
  drop_na(robbery_gun_r) |>
  filter(sid != 47)
# young_male_race is taking place of blackm_15_24 + whitem_15_24 + blackm_25_44 + whitem_25_44

castle_dag <- dagify(
  murder ~ young_male_race + poverty + popwt + robbery_gun_r + l_police + post + years
  post ~ homicide + robbery_gun_r + assault + burglary + motor + murder_lag + robbery,

```

```

burglary ~ poverty + young_male_race,
homicide ~ poverty + young_male_race,
motor ~ poverty + young_male_race,
robbery ~ poverty + young_male_race,
assault ~ poverty + young_male_race,

poverty ~ unemployrt + l_exp_subsidy + l_exp_pubwelfare + l_income,

l_police ~ l_income,

outcome = "murder",
exposure = "post",
labels = c(
  murder = "Murder",
  murder_lag = "Murder Lagged",
  unemployrt = "Unemployment",
  young_male_race = "Male Demo.",
  poverty = "Poverty",
  popwt = "Population",
  robbery_gun_r = "Robbery w. Firearm",
  l_exp_subsidy = "Subsidy",
  l_exp_pubwelfare = "Welfare",
  l_police = "Police",
  post = "Castle Doctrine",
  years_after_treat = "Years Post Castle",

  homicide = "Homicide",
  robbery = "Robbery",
  assault = "Assault",
  burglary = "Burglary",
  motor = "Auto Theft",
  l_income = "Income")
)
ggdag(castle_dag, layout = "nicely", use_labels = "label", text = FALSE) +
  labs(caption = "DAG") +
  theme_dag()
ggdag_adjustment_set(castle_dag, text_col = "black",
  use_labels = "label",
  text = FALSE) +
  theme_dag()

```

```

vis_dat(castle_for_tab)
castle_select <- castle_dat |>
  select(c(post, assault, burglary, homicide, motor, robbery, robbery_gun_r)) |>
  mutate(post = ifelse(post == 0, "Pre-Doctrine", "Post-Doctrine")) |>
  set_variable_labels(
    post = "Passage of Castle Doctrine",
    assault = "Assault",
    burglary = "Burglary",
    homicide = "Homicide",
    motor = "Motor Vehicle Theft",
    robbery = "Robbery",
    robbery_gun_r = "Robbery w. Firearm"
  )

tbl_summary(
  castle_select,
  by = post
) |>
  add_overall(last = TRUE) |>
  modify_caption("**Table 1: Sample Characteristics by Castle Doctrine**") |>
  modify_footnote(everything() ~ "Rates per 100,000 persons") |>
  as_kable_extra(format = "latex") |>
  kable_styling(
    latex_options = c("scale_down", "hold_position"),
    full_width = FALSE,
    position = "center"
  )

propensity_model <- glm(post ~ splines::ns(homicide, 3) +
  splines::ns(burglary, 2) +
  assault + motor + robbery +
  robbery_gun_r ,
  data = castle_dat,
  family = "binomial")

castle_dat <- propensity_model |>
  augment(type.predict = "response", data = castle_dat) |>
  mutate(w_att = wt_att(.fitted, post, exposure_type = "binary"))
ggplot(castle_dat, aes(x = .fitted, group = post, fill = post)) +
  geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post))) +
  labs(x = "Propensity Score", fill = "Passed Castle Doctrine", caption = "Unweighted")

```



```

scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")
ggplot(castle_dat, aes(x = .fitted, group = post, fill = post)) +
geom_mirror_histogram(bins = 30, alpha = .6, fill = "grey") +
labs(x = "Propensity Score", y = "Count") +
geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post), weight = w_att))
theme(legend.position = "bottom") +
labs(x = "Propensity Score", y = "Count", fill = "Passed Castle Doctrine") +
scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")

ggplot(castle_dat, aes(x = .fitted, group = post, fill = post)) +
geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post), weight = w_att))
theme(legend.position = "bottom") +
labs(x = "Propensity Score", y = "Count", fill = "Passed Castle Doctrine") +
scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")
dat_for_love <- castle_dat %>%
  select(assault, burglary, homicide, motor, robbery, robbery_gun_r, post, w_att)

colnames(dat_for_love) <- c("Assault", "Burglary", "Homicide", "Motor Vehicle Theft",

weighted_for_love <- tidy_smd(
  dat_for_love,
  .vars = c(Assault, Burglary, Homicide, `Motor Vehicle Theft`, Robbery, `Armed Robber
  .group = post,
  .wts = c(w_att)
)

ggplot(data = weighted_for_love, aes(x = abs(smd), y = variable, group = method, color
  geom_love() +
  scale_color_manual(values = c("coral", "turquoise"), labels = c("Observed", "ATT Wei
  labs(color = "Method", x = "Absolute Value of SMD", y = "Variable") +
  theme_minimal()

```

```

castle_select2 <- castle_dat |>
  select(c(post, assault, burglary, homicide, motor, robbery, robbery_gun_r, w_att)) |
  mutate(post = ifelse(post == 0, "Pre-Doctrine", "Post-Doctrine")) |>
  set_variable_labels(
    post = "Passage of Castle Doctrine",
    assault = "Assault",
    burglary = "Burglary",
    homicide = "Homicide",
    motor = "Motor Vehicle Theft",
    robbery = "Robbery",
    robbery_gun_r = "Armed Robbery"
  )

svy_des <- svydesign(
  ids = ~1,
  data = castle_select2,
  weights = ~w_att
)

hdr <- paste0(
  "**{level}** \n",
  "N = {n_unweighted}; ESS = {format(n, digits = 1, nsmall = 1)}"
)

tbl_svysummary(svy_des,
  by = post,
  include = c(assault, burglary, homicide, motor, robbery, robbery_gun_r)
  add_overall(last = TRUE) |>
  add_ess_header(header = hdr) |>
  modify_caption("**Table 2: Sample Characteristics by Re-Weighted Castle Doctrine**")
  modify_footnote(everything() ~ "Rates per 100,000 persons")

standardized_model <- lm(murder ~ post*years_after_treat, data = castle_dat, weights =
years_pre_post <- c(1:4)

estimate_df <- data.frame("years_pre_post" = years_pre_post,
  "ATT_est" = rep(NA, 4))

for (j in years_pre_post){

```

```

standardized_model <- lm(murder ~ post*years_after_treat,
                        data = castle_dat, weights = w_att)

castle_dat_minus_j_yes <- castle_dat |>
  mutate(years_after_treat = -1*j, post = 1)

castle_dat_minus_j_no <- castle_dat |>
  mutate(years_after_treat = -1*j, post = 0)

castle_dat_plus_j_yes <- castle_dat |>
  mutate(years_after_treat = j, post = 1)

castle_dat_plus_j_no <- castle_dat |>
  mutate(years_after_treat = j, post = 0)

new_data_plus_j_yes <- standardized_model |>
  augment(newdata = castle_dat_plus_j_yes) |>
  rename(murder_est = .fitted)

new_data_plus_j_no <- standardized_model |>
  augment(newdata = castle_dat_plus_j_no) |>
  rename(murder_est = .fitted)

new_data_minus_j_yes <- standardized_model |>
  augment(newdata = castle_dat_minus_j_yes) |>
  rename(murder_est = .fitted)

new_data_minus_j_no <- standardized_model |>
  augment(newdata = castle_dat_minus_j_no) |>
  rename(murder_est = .fitted)

estimate_df$years_pre_post[j] <- j

estimate_df$ATT_est[j] <- (mean(new_data_plus_j_yes$murder_est) -
                          mean(new_data_minus_j_yes$murder_est)) -
  (mean(new_data_plus_j_no$murder_est) -
   mean(new_data_minus_j_no$murder_est))
}

estimate_df$ATT_est <- round(estimate_df$ATT_est, 3)

```

```

colnames(estimate_df) <- c("Years Before After \n Castle Doctrine", "ATT Point Est.")

estimate_df |>
  gt()
set.seed(779)

n_bootstrap <- 1000

bootstrap_df <- data.frame("years_pre_post" = years_pre_post,
                           "mean_ATT" = rep(NA, 4),
                           "sd_ATT" = rep(NA, 4),
                           "ci.l" = rep(NA, 4),
                           "ci.u" = rep(NA, 4))

for (j in years_pre_post){

  bootstrap_est <- vector(length = n_bootstrap)

  for (b in 1:n_bootstrap){
    boot_dat <- castle_dat |>
      slice_sample(n = nrow(castle_dat), replace = T)

    standardized_boot <- lm(murder ~ post*years_after_treat,
                           data = boot_dat, weights = w_att)

    boot_dat_minus_j_yes <- boot_dat |>
      mutate(years_after_treat = -1*j, post = 1)

    boot_dat_minus_j_no <- boot_dat |>
      mutate(years_after_treat = -1*j, post = 0)

    boot_dat_plus_j_yes <- boot_dat |>
      mutate(years_after_treat = j, post = 1)

    boot_dat_plus_j_no <- boot_dat |>
      mutate(years_after_treat = j, post = 0)

    new_data_plus_j_yes <- standardized_boot |>
      augment(newdata = boot_dat_plus_j_yes) |>

```

```

    rename(murder_est = .fitted)

new_data_plus_j_no <- standardized_boot |>
  augment(newdata = boot_dat_plus_j_no) |>
  rename(murder_est = .fitted)

new_data_minus_j_yes <- standardized_boot |>
  augment(newdata = boot_dat_minus_j_yes) |>
  rename(murder_est = .fitted)

new_data_minus_j_no <- standardized_boot |>
  augment(newdata = boot_dat_minus_j_no) |>
  rename(murder_est = .fitted)

bootstrap_est[b] <- (mean(new_data_plus_j_yes$murder_est) -
                     mean(new_data_minus_j_yes$murder_est)) -
  (mean(new_data_plus_j_no$murder_est) - mean(new_data_minus_j_no$murder_est))
}

bootstrap_df$mean_ATT[j] <- round(mean(bootstrap_est),3)

bootstrap_df$sd_ATT[j] <- round(sd(bootstrap_est),3)

bootstrap_df$ci.l[j] <- round(quantile(bootstrap_est, 0.025),3)

bootstrap_df$ci.u[j] <- round(quantile(bootstrap_est, 0.975),3)
}

colnames(bootstrap_df) <- c("Years Before After \n Castle Doctrine", "ATT Estimate", "

bootstrap_df |>
  gt()

propensity_model_alt <- glm(post ~ splines::ns(poverty, 5) + robbery + splines::ns(rob

castle_dat_alt <- propensity_model_alt |>
  augment(type.predict = "response", data = castle_dat) |>
  mutate(w_att = wt_att(.fitted, post, exposure_type = "binary"))

```

```

years_pre_post <- c(1:4)

estimate_df <- data.frame("years_pre_post" = years_pre_post,
                          "ATT_est" = rep(NA, 4))

for (j in years_pre_post){

  standardized_model <- lm(murder ~ post*years_after_treat,
                          data = castle_dat_alt, weights = w_att)

  castle_dat_minus_j_yes <- castle_dat_alt |>
    mutate(years_after_treat = -1*j, post = 1)

  castle_dat_minus_j_no <- castle_dat_alt |>
    mutate(years_after_treat = -1*j, post = 0)

  castle_dat_plus_j_yes <- castle_dat_alt |>
    mutate(years_after_treat = j, post = 1)

  castle_dat_plus_j_no <- castle_dat_alt |>
    mutate(years_after_treat = j, post = 0)

  new_data_plus_j_yes <- standardized_model |>
    augment(newdata = castle_dat_plus_j_yes) |>
    rename(murder_est = .fitted)

  new_data_plus_j_no <- standardized_model |>
    augment(newdata = castle_dat_plus_j_no) |>
    rename(murder_est = .fitted)

  new_data_minus_j_yes <- standardized_model |>
    augment(newdata = castle_dat_minus_j_yes) |>
    rename(murder_est = .fitted)

  new_data_minus_j_no <- standardized_model |>
    augment(newdata = castle_dat_minus_j_no) |>
    rename(murder_est = .fitted)

  estimate_df$years_pre_post[j] <- j
}

```

```

    estimate_df$ATT_est[j] <- (mean(new_data_plus_j_yes$murder_est) -
                               mean(new_data_minus_j_yes$murder_est)) -
                              (mean(new_data_plus_j_no$murder_est) -
                               mean(new_data_minus_j_no$murder_est))
  }

estimate_df$ATT_est <- round(estimate_df$ATT_est, 3)

colnames(estimate_df) <- c("Years Before After \n Castle Doctrine", "ATT Point Est.")

estimate_df %>%
  gt()
set.seed(779)

n_bootstrap <- 1000

bootstrap_df <- data.frame("years_pre_post" = years_pre_post,
                           "mean_ATT" = rep(NA, 4),
                           "sd_ATT" = rep(NA, 4),
                           "ci.l" = rep(NA, 4),
                           "ci.u" = rep(NA, 4))

bootstrap_df_names_clean <- bootstrap_df

for (j in years_pre_post){

  bootstrap_est <- vector(length = n_bootstrap)

  for (b in 1:n_bootstrap){
    boot_dat <- castle_dat_alt |>
      slice_sample(n = nrow(castle_dat_alt), replace = T)

    standardized_boot <- lm(murder ~ post*years_after_treat,
                           data = boot_dat, weights = w_att)

    boot_dat_minus_j_yes <- boot_dat |>
      mutate(years_after_treat = -1*j, post = 1)

    boot_dat_minus_j_no <- boot_dat |>
      mutate(years_after_treat = -1*j, post = 0)
  }
}

```

```

boot_dat_plus_j_yes <- boot_dat |>
  mutate(years_after_treat = j, post = 1)

boot_dat_plus_j_no <- boot_dat |>
  mutate(years_after_treat = j, post = 0)

new_data_plus_j_yes <- standardized_boot |>
  augment(newdata = boot_dat_plus_j_yes) |>
  rename(murder_est = .fitted)

new_data_plus_j_no <- standardized_boot |>
  augment(newdata = boot_dat_plus_j_no) |>
  rename(murder_est = .fitted)

new_data_minus_j_yes <- standardized_boot |>
  augment(newdata = boot_dat_minus_j_yes) |>
  rename(murder_est = .fitted)

new_data_minus_j_no <- standardized_boot |>
  augment(newdata = boot_dat_minus_j_no) |>
  rename(murder_est = .fitted)

bootstrap_est[b] <- (mean(new_data_plus_j_yes$murder_est) -
                     mean(new_data_minus_j_yes$murder_est)) -
  (mean(new_data_plus_j_no$murder_est) - mean(new_data_minus_j_no$murder_est))
}

bootstrap_df_names_clean$mean_ATT[j] <- mean(bootstrap_est)

bootstrap_df_names_clean$sd_ATT[j] <- sd(bootstrap_est)

bootstrap_df_names_clean$ci.l[j] <- quantile(bootstrap_est, 0.025)

bootstrap_df_names_clean$ci.u[j] <- quantile(bootstrap_est, 0.975)

## Unrounded

bootstrap_df$mean_ATT[j] <- round(mean(bootstrap_est), 3)

```



```

bootstrap_df$sd_ATT[j] <- round(sd(bootstrap_est),3)

bootstrap_df$ci.l[j] <- round(quantile(bootstrap_est, 0.025),3)

bootstrap_df$ci.u[j] <- round(quantile(bootstrap_est, 0.975),3)
}

colnames(bootstrap_df_names_clean) <- c("Years Before After \n Castle Doctrine", "ATT")

bootstrap_df_names_clean |>
  gt()

#Unmeasured confounder to make significant negative effect - 1 year pre/post
ci.u <- bootstrap_df[1,"ci.u"]

adjust_df <- adjust_coef(
  effect_observed = ci.u,
  exposure_confounder_effect = rep(seq(0, -1, by = -0.05), each = 7),
  confounder_outcome_effect = rep(seq(-1, -7, by = -1), times = 21),
  verbose = FALSE
)

ggplot(
  adjust_df,
  aes(
    x = exposure_confounder_effect,
    y = effect_adjusted,
    group = confounder_outcome_effect
  )
) +
  geom_hline(yintercept = ci.u, lty = 2) +
  geom_hline(yintercept = 0, lty = 3, color = "red", lwd = 1) +
  geom_point() +
  geom_line() +
  geom_label(
    data = adjust_df[141:147, ],
    aes(
      x = exposure_confounder_effect,
      y = effect_adjusted,
      label = confounder_outcome_effect
    )
  )

```

```

    )
  ) +
  labs(
    x = "Exposure - unmeasured confounder effect",
    y = "Adjusted Effect",
    title = "Effect of Unmeasured Confounder on Treatment Effect"
  )

#Unmeasured confounder to make significant positive effect - 1 year pre/post
ci.l <- bootstrap_df[1,"ci.l"]

adjust_df <- adjust_coef(
  effect_observed = ci.l,
  exposure_confounder_effect = rep(seq(0, -1, by = -0.05), each = 7),
  confounder_outcome_effect = rep(seq(1, 7, by = 1), times = 21),
  verbose = FALSE
)

ggplot(
  adjust_df,
  aes(
    x = exposure_confounder_effect,
    y = effect_adjusted,
    group = confounder_outcome_effect
  )
) +
  geom_hline(yintercept = ci.l, lty = 2) +
  geom_hline(yintercept = 0, lty = 3, color = "red", lwd = 1) +
  geom_point() +
  geom_line() +
  geom_label(
    data = adjust_df[141:147, ],
    aes(
      x = exposure_confounder_effect,
      y = effect_adjusted,
      label = confounder_outcome_effect
    )
  ) +
  labs(

```

```

    x = "Exposure - unmeasured confounder effect",
    y = "Adjusted Effect",
    title = "Effect of Unmeasured Confounder on Treatment Effect"
  )
miss_tab <- miss_var_summary(castle_for_tab)
colnames(miss_tab) <- c("Variable", "Missing (n)", "Percent Missing")

miss_tab |>
  gt()
propensity_model_test <- glm(post ~ homicide + burglary + assault + motor + robbery +

castle_dat_test <- propensity_model_test |>
  augment(type.predict = "response", data = castle_dat) |>
  mutate(w_att = wt_att(.fitted, post, exposure_type = "binary"))

ggplot(castle_dat_test, aes(x = .fitted, group = post, fill = post)) +
  geom_mirror_histogram(bins = 30, alpha = .6, fill = "grey") +
  geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post), weight = w_att))
labs(x = "Propensity Score", fill = "Passed Castle Doctrine", caption = "ATT", y = "
scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")

ggplot(castle_dat_test, aes(x = .fitted, group = post, fill = post)) +
  geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post), weight = w_att))
labs(x = "Propensity Score", fill = "Passed Castle Doctrine", caption = "ATT", y = "
scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")
dat_for_love <- castle_dat_test %>%
  select(assault, burglary, homicide, motor, robbery, robbery_gun_r, post, w_att)

colnames(dat_for_love) <- c("Assault", "Burglary", "Homicide", "Motor Vehicle Theft",
weighted_for_love <- tidy_smd(
  castle_dat_test,
  .vars = c(assault, burglary, homicide, motor, robbery, robbery_gun_r),
  .group = post,
  .wts = c(w_att)

```

```

)

ggplot(data = weighted_for_love, aes(x = abs(smd), y = variable, group = method, color = method)) +
  geom_love() +
  theme_minimal()

p1 <- ggplot(castle_dat_test, aes(x = burglary, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Burglary", color = "Castle Implemented") +
  theme_minimal()

p2 <- ggplot(castle_dat_test, aes(x = burglary, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Burglary", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p3 <- ggplot(castle_dat_test, aes(x = assault, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Assault", color = "Castle Implemented") +
  theme_minimal()

p4 <- ggplot(castle_dat_test, aes(x = assault, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Assault", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p5 <- ggplot(castle_dat_test, aes(x = robbery, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Robbery", color = "Castle Implemented") +
  theme_minimal()

p6 <- ggplot(castle_dat_test, aes(x = robbery, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +

```

```

labs(x = "Robbery", color = "Castle Implemented") +
ggtitle("ATT") +
theme_minimal()

p7 <- ggplot(castle_dat_test, aes(x = homicide, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Homicide", color = "Castle Implemented") +
  theme_minimal()

p8 <- ggplot(castle_dat_test, aes(x = homicide, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Homicide", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p9 <- ggplot(castle_dat_test, aes(x = robbery_gun_r, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Robbery with Gun", color = "Castle Implemented") +
  theme_minimal()

p10 <- ggplot(castle_dat_test, aes(x = robbery_gun_r, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Robbery with Gun", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p11 <- ggplot(castle_dat_test, aes(x = motor, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Motor", color = "Castle Implemented") +
  theme_minimal()

p12 <- ggplot(castle_dat_test, aes(x = motor, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Motor", color = "Castle Implemented") +

```

```

  ggtitle("ATT") +
  theme_minimal()

(p1+p2)/(p3+p4)+ plot_layout(guides = "collect") & theme(legend.position = "bottom")
(p5+p6)/(p7+p8)+ plot_layout(guides = "collect") & theme(legend.position = "bottom")
(p9+p10)/(p11+p12)+ plot_layout(guides = "collect") & theme(legend.position = "bottom")
p1 <- ggplot(castle_dat, aes(x = burglary, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Burglary", color = "Castle Implemented") +
  theme_minimal()

p2 <- ggplot(castle_dat, aes(x = burglary, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Burglary", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p3 <- ggplot(castle_dat, aes(x = assault, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Assault", color = "Castle Implemented") +
  theme_minimal()

p4 <- ggplot(castle_dat, aes(x = assault, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Assault", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p5 <- ggplot(castle_dat, aes(x = robbery, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Robbery", color = "Castle Implemented") +
  theme_minimal()

p6 <- ggplot(castle_dat, aes(x = robbery, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +

```

```

theme(legend.position = "bottom") +
labs(x = "Robbery", color = "Castle Implemented") +
ggtitle("ATT") +
theme_minimal()

p7 <- ggplot(castle_dat, aes(x = homicide, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Homicide", color = "Castle Implemented") +
  theme_minimal()

p8 <- ggplot(castle_dat, aes(x = homicide, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Homicide", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p9 <- ggplot(castle_dat, aes(x = robbery_gun_r, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Robbery with Gun", color = "Castle Implemented") +
  theme_minimal()

p10 <- ggplot(castle_dat, aes(x = robbery_gun_r, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +
  labs(x = "Robbery with Gun", color = "Castle Implemented") +
  ggtitle("ATT") +
  theme_minimal()

p11 <- ggplot(castle_dat, aes(x = motor, color = factor(post))) +
  geom_ecdf() +
  theme(legend.position = "bottom") +
  labs(x = "Motor", color = "Castle Implemented") +
  theme_minimal()

p12 <- ggplot(castle_dat, aes(x = motor, color = factor(post))) +
  geom_ecdf(aes(weights = w_att)) +
  theme(legend.position = "bottom") +

```

```

labs(x = "Motor", color = "Castle Implemented") +
ggtitle("ATT") +
theme_minimal()

(p1+p2)/(p3+p4)+ plot_layout(guides = "collect") & theme(legend.position = "bottom")
(p5+p6)/(p7+p8)+ plot_layout(guides = "collect") & theme(legend.position = "bottom")
(p9+p10)/(p11+p12)+ plot_layout(guides = "collect") & theme(legend.position = "bottom")

p1 <- ggplot(castle_dat_alt, aes(x = .fitted, group = post, fill = post)) +
  geom_mirror_histogram(bins = 30, alpha = .6, fill = "grey") +
  geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post), weight = w_att)) +
  labs(x = "Propensity Score", y = "Count", fill = "Passed Castle Doctrine", caption =
scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")

p2 <- ggplot(castle_dat_alt, aes(x = .fitted, group = post, fill = post)) +
  geom_mirror_histogram(bins = 30, alpha = 1, aes(fill = factor(post), weight = w_att)) +
  labs(x = "Propensity Score", y = "Count", fill = "Passed Castle Doctrine", caption =
scale_y_continuous(labels = abs) +
scale_fill_manual(labels = c("No", "Yes"), values = c("turquoise", "coral")) +
theme_minimal() +
theme(legend.position = "bottom")

(p1 + p2) + plot_layout(guides = "collect") & theme(legend.position = "bottom")
weighted_for_love_alt <- tidy_smd(
  castle_dat_alt,
  .vars = c(poverty, robbery, robbery_gun_r, whitem_15_24, blackm_15_24, whitem_25_44,
  .group = post,
  .wts = c(w_att)
)


ggplot(data = weighted_for_love_alt, aes(x = abs(smd), y = variable, group = method, c
  geom_love() +
  scale_color_manual(values = c("coral", "turquoise"), labels = c("Observed", "ATT W
  labs(color = "Method", x = "Absolute Value of SMD", y = "Variable") +
  theme_minimal()

```


Appendix:

Model before the splines:

Mirrored Histogram:




ATT


ATT


Variable	Missing (n)	Percent Missing
robbery_gun_r	5	1
year	0	0
sid	0	0
jhcitizen_c	0	0
jhpolice_c	0	0
homicide	0	0
robbery	0	0
assault	0	0
burglary	0	0
larceny	0	0
motor	0	0
murder	0	0
unemployrt	0	0
blackm_15_24	0	0
whitem_15_24	0	0
blackm_25_44	0	0
whitem_25_44	0	0
poverty	0	0
l_homicide	0	0
l_larceny	0	0
l_motor	0	0
l_police	0	0
l_income	0	0
l_prisoner	0	0
l_lagprisoner	0	0
l_exp_subsidy	0	0
l_exp_pubwelfare	0	0
post	0	0
popwt	0	0
treat_year	0	0
murder_lag	0	0
state	0	0
pop	0	0

Love Plot:




eCDFs:







With splines:

eCDFS:







Alternate Adjustment Set:

