

# Final Project - Predicting March Madness

Anmol Sapru and Rohit Gunda

## Introduction and Data

### Motivation

Duke is synonymous with basketball. As Duke students who love Duke Basketball and March Madness, we are interested in performing a statistical analysis on the most thrilling tournament in sports. While watching the 2023 March Madness tournament and the many upsets that came with it, we were motivated to see if we could use statistical methods to predict March Madness winners. Upon scouring sites such as FiveThirtyEight and the KenPom rankings, we were inspired to create models of our own to predict tournament success.

**Fundamental Research Question:** What variables are important to March Madness success and which outliers over the past 15 years have existed that bring “Madness” to “March?”

### Packages

```
library(tidyverse)
library(tidymodels)
library(Stat2Data)
library(caret)
library(leaps)
library(MASS)
```

### Data

Data was found from the [Sports Reference college basketball team stats website](#) and [Bart Torvik analytics website](#), with these general and deeper stats being taken going back to 2008 (excluding the cancelled March Madness of 2020). From here, the data was cleaned in Excel to separate the year and result of each team then joined for all of this data together. With the nature of March Madness being over time, the data most definitely violates expectations

of independence, with similar players, coaches, and more between years, but there would not be a reasonable way to complete such analysis without this independence.

### **Key Variables**

- ADJOE/ADJDE - Points scored per 100 possessions on offense/defense, adjusted for opponent strength and game location
- TOR/TORD - Turnovers committed/forced per game on offense/defense
- ADJT - Estimate possessions per game a team would have against the average tempo
- EFG% - Field goal percentage adjusted for value of baskets scored

### **Exploratory Data Analysis**

**EXPLORATORY DATA ANALYSIS-Averages for stats—add by year/by round,  
Averages for winner stats**

### **Description of Data Cleaning**

For further cleaning, the non-March Madness teams added in the join were removed and simple variable names and values were cleaned up to be easier to work with.

**ADD CLEARER DESCRIPTION OF DATA CLEANING**

### **Methodology**

We determined it would be best to try different regressions, with logistic regressions by round and an ordinal regression—each with their different assumptions to look into. The issue with the first of these is the low levels of data that limit the creation of a model beyond around the Elite Eight. In preparing for the round-by-round logistic regressions we split up the data from the original data sets into multiple data sets for each round, with a TRUE or FALSE value of whether they won their game in that round.

**WHY CHOSE EACH VARIABLE**

## Round-by-Round Logistic Regression

The following is an example of the regression that was ran on all of the Round of 64 teams to create a regression that predicts winners (`round_64 = TRUE`) against losers (`round_64 = FALSE`) for the round. Using `stepAIC` works to attempt to limit the overfitting with the data. This was also done for the Round of 32 and Sweet Sixteen.

### WHY LOGISTIC REG?

```
round_64 <- na.omit(round_64)

round_64_max <- glm(round_64 ~ G.x + WINS + LOSSES + ADJOE + ADJDE +
  `EFG%` + `EFGD%` + TOR + TORD + ORB + DRB + FTR +
  FTRD + `2P%` + `2P%D` + `3P%` + `3P%D` + `3PR` +
  `3PRD` + `ADJ T` + `Conf. W-L%` + `Home W-L%` +
  `Away W-L%` + `AVG PPG` + `AVG DPPG` + `AVG PD` +
  `AST/TOV` + `PF/G` + WINS*G.x + LOSSES*G.x +
  ADJOE*ADJDE + `EFG%`*`EFGD%` + TOR*TORD + ORB*DRB +
  FTR*FTRD + `2P%`*`2P%D` + `3P%`*`3P%D` + `3PR`*`3PRD` +
  `2P%`*`3P%` + `2P%D`*`3P%D` + `AVG PPG`*`AVG DPPG`,
  data = round_64,
  family = "binomial")

round_64_min <- glm(round_64 ~ 1,
  data = round_64,
  family = "binomial")

round_64_model <- stepAIC(round_64_max,
  scope = list(lower = round_64_min, upper = round_64_max),
  data = round_64, direction = "both")
```

The following are the regression models that were found from the three rounds of data and regression models run through `stepAIC`:

## Overall Ordinal Regression

```
cbb$march_madness <- fct_relevel(cbb$march_madness,
  c("R64", "R32", "S16", "E8",
    "F4", "2ND", "Champions"))

mmb_ord_model <- polr(march_madness ~ ADJOE + ADJDE + TORD +
```

```
FTRD + `2P%D` + `3P%D` + `AVG PPG` +
`AVG DPPG` + `PF/G`, data = cbb)
```

## ADD ASSESSMENT OF CONDITIONS + DIAGNOSTICS

### Results

```
`2023sr` <- read_csv("data/2023sportsreference.csv")
```

Rows: 363 Columns: 13

-- Column specification -----

Delimiter: ","

chr (1): School

dbl (12): G, Overall W-L%, Overall SRS, Overall SOS, Conf. W-L%, Home W-L%, ...

i Use `spec()` to retrieve the full column specification for this data.

i Specify the column types or set `show\_col\_types = FALSE` to quiet this message.

```
`2023analytics` <- read_csv("data/2023torvik.csv")
```

Rows: 363 Columns: 22

-- Column specification -----

Delimiter: ","

chr (1): TEAM

dbl (21): RK, G, WINS, LOSSES, ADJOE, ADJDE, EFG%, EFGD%, TOR, TORD, ORB, DR...

i Use `spec()` to retrieve the full column specification for this data.

i Specify the column types or set `show\_col\_types = FALSE` to quiet this message.

```
`2023stats` <- left_join(`2023analytics`, `2023sr`, by = c("TEAM" = "School"))
```

```
`2023teams` <- read_csv("data/2023teams.csv")
```

Rows: 64 Columns: 1

-- Column specification -----

Delimiter: ","

```
chr (1): TEAM
```

i Use ``spec()`` to retrieve the full column specification for this data.

i Specify the column types or set ``show_col_types = FALSE`` to quiet this message.

```
`2023stats` <- `2023stats` |>
  filter(`2023stats`$TEAM %in% `2023teams`$TEAM)

tibble(predict(round_64_model, `2023stats`)) |>
  mutate(rank = seq(1:64)) |>
  left_join(mutate(`2023stats`, rank = seq(1:64))) |>
  arrange(desc(predict(round_64_model, `2023stats`)))
```

Joining, by = "rank"

# A tibble: 64 x 36

	predi~1	rank	RK	TEAM	G.x	WINS	LOSSES	ADJOE	ADJDE	`EFG%`	`EFGD%`	TOR
	<dbl>	<int>	<dbl>	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	3.67	1	1	Hous~	34	31	3	117.	88	52.7	42.5	15.3
2	3.37	3	3	UCLA	34	29	5	113.	87.4	50.9	46.8	15.3
3	2.54	6	6	Purd~	34	29	5	118.	92.6	52.2	47.2	17
4	2.48	12	12	San ~	32	26	6	111.	90.1	50.1	47.5	17.6
5	2.47	2	2	Alab~	34	29	5	115.	88.3	52.7	41.5	19
6	2.10	9	9	Texas	34	26	8	115.	91.6	52.7	47.8	16.5
7	2.07	11	11	Marq~	34	28	6	119.	96.1	56	51.1	15.2
8	2.05	4	4	Tenn~	33	23	10	111.	86.2	50.3	42.4	18.1
9	1.98	13	13	Kans~	34	27	7	113.	91.5	52.4	47.1	17.5
10	1.85	5	5	Conn~	33	25	8	119.	92.5	53.5	45.5	18.9

# ... with 54 more rows, 24 more variables: TORD <dbl>, ORB <dbl>, DRB <dbl>,  
# FTR <dbl>, FTRD <dbl>, `2P%` <dbl>, `2P%D` <dbl>, `3P%` <dbl>,  
# `3P%D` <dbl>, `3PR` <dbl>, `3PRD` <dbl>, `ADJ T` <dbl>, G.y <dbl>,  
# `Overall W-L%` <dbl>, `Overall SRS` <dbl>, `Overall SOS` <dbl>,  
# `Conf. W-L%` <dbl>, `Home W-L%` <dbl>, `Away W-L%` <dbl>, `AVG PPG` <dbl>,  
# `AVG DPPG` <dbl>, `AVG PD` <dbl>, `AST/TOV` <dbl>, `PF/G` <dbl>, and  
# abbreviated variable name 1: `predict(round\_64\_model, `2023stats`))`

```
tibble(predict(round_32_model, `2023stats`)) |>
  mutate(rank = seq(1:64)) |>
  left_join(mutate(`2023stats`, rank = seq(1:64))) |>
  arrange(desc(predict(round_32_model, `2023stats`)))
```

Warning in predict.lm(object, newdata, se.fit, scale = 1, type = if (type == :  
prediction from a rank-deficient fit may be misleading

Joining, by = "rank"

Warning in predict.lm(object, newdata, se.fit, scale = 1, type = if (type == :  
prediction from a rank-deficient fit may be misleading

# A tibble: 64 x 36

	predi~1 <dbl>	rank <int>	RK TEAM <dbl> <chr>	G.x <dbl>	WINS <dbl>	LOSSES <dbl>	ADJOE <dbl>	ADJDE <dbl>	`EFG%` <dbl>	`EFGD%` <dbl>	TOR <dbl>
1	2.04	1	1 Hous~	34	31	3	117.	88	52.7	42.5	15.3
2	1.78	3	3 UCLA	34	29	5	113.	87.4	50.9	46.8	15.3
3	1.67	38	42 Penn~	35	22	13	115.	99.9	55.5	49.2	13.7
4	1.49	2	2 Alab~	34	29	5	115.	88.3	52.7	41.5	19
5	1.03	12	12 San ~	32	26	6	111.	90.1	50.1	47.5	17.6
6	0.996	6	6 Purd~	34	29	5	118.	92.6	52.2	47.2	17
7	0.750	16	16 Memp~	34	26	8	114.	94.2	53.2	46.8	18.4
8	0.635	14	14 Crei~	33	21	12	114.	92.8	54.3	47.3	16.6
9	0.603	10	10 Gonz~	32	27	5	123.	98.6	58.5	51.7	14.6
10	0.574	50	78 Oral~	30	26	4	112.	101.	56.1	48.5	13.2

# ... with 54 more rows, 24 more variables: TORD <dbl>, ORB <dbl>, DRB <dbl>,  
# FTR <dbl>, FTRD <dbl>, `2P%` <dbl>, `2P%D` <dbl>, `3P%` <dbl>,  
# `3P%D` <dbl>, `3PR` <dbl>, `3PRD` <dbl>, `ADJ T` <dbl>, G.y <dbl>,  
# `Overall W-L%` <dbl>, `Overall SRS` <dbl>, `Overall SOS` <dbl>,  
# `Conf. W-L%` <dbl>, `Home W-L%` <dbl>, `Away W-L%` <dbl>, `AVG PPG` <dbl>,  
# `AVG DPPG` <dbl>, `AVG PD` <dbl>, `AST/TOV` <dbl>, `PF/G` <dbl>, and  
# abbreviated variable name 1: `predict(round\_32\_model, `2023stats`)`

```
tibble(predict(sweet_sixteen_model, `2023stats`)) |>
  mutate(rank = seq(1:64)) |>
  left_join(mutate(`2023stats`, rank = seq(1:64))) |>
  arrange(desc(predict(sweet_sixteen_model, `2023stats`)))
```

Joining, by = "rank"

# A tibble: 64 x 36

	predi~1 <dbl>	rank <int>	RK TEAM <dbl> <chr>	G.x <dbl>	WINS <dbl>	LOSSES <dbl>	ADJOE <dbl>	ADJDE <dbl>	`EFG%` <dbl>	`EFGD%` <dbl>	TOR <dbl>
1	2.47	6	6 Purd~	34	29	5	118.	92.6	52.2	47.2	17

```

2  1.84      1      1 Hous~    34    31      3 117.  88      52.7  42.5  15.3
3  1.30      5      5 Conn~    33    25      8 119.  92.5  53.5  45.5  18.9
4  1.22     13     13 Kans~    34    27      7 113.  91.5  52.4  47.1  17.5
5  0.880     22     22 Texa~    34    25      9 113.  94.8  49      47.9  18.3
6  0.826     24     24 Kans~    32    23      9 110.  93.1  51.5  47.5  20
7  0.752     21     21 Duke     34    26      8 112.  93.1  51.1  46.3  18.2
8  0.714     12     12 San ~    32    26      6 111.  90.1  50.1  47.5  17.6
9  0.657     38     42 Penn~    35    22     13 115.  99.9  55.5  49.2  13.7
10 0.606     26     26 TCU      33    21     12 110.  93.4  50.2  47.8  17.1
# ... with 54 more rows, 24 more variables: TORD <dbl>, ORB <dbl>, DRB <dbl>,
#   FTR <dbl>, FTRD <dbl>, `2P%` <dbl>, `2P%D` <dbl>, `3P%` <dbl>,
#   `3P%D` <dbl>, `3PR` <dbl>, `3PRD` <dbl>, `ADJ T` <dbl>, G.y <dbl>,
#   `Overall W-L%` <dbl>, `Overall SRS` <dbl>, `Overall SOS` <dbl>,
#   `Conf. W-L%` <dbl>, `Home W-L%` <dbl>, `Away W-L%` <dbl>, `AVG PPG` <dbl>,
#   `AVG DPPG` <dbl>, `AVG PD` <dbl>, `AST/TOV` <dbl>, `PF/G` <dbl>, and
#   abbreviated variable name ...

```

```

tibble(predict(mmb_ord_model, `2023stats`)) |>
  mutate(rank = seq(1:64)) |>
  left_join(mutate(`2023stats`, rank = seq(1:64))) |>
  arrange(predict(mmb_ord_model, `2023stats`, type = "probs"))

```

Joining, by = "rank"

```

# A tibble: 64 x 36
  predi-1 rank  RK TEAM  G.x WINS LOSSES ADJOE ADJDE `EFG%` `EFGD%` TOR
  <fct>   <int> <dbl> <chr> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
1 E8      1      1 Hous~    34    31      3 117.  88      52.7  42.5  15.3
2 S16     3      3 UCLA    34    29      5 113.  87.4  50.9  46.8  15.3
3 S16     5      5 Conn~    33    25      8 119.  92.5  53.5  45.5  18.9
4 S16     4      4 Tenn~    33    23     10 111.  86.2  50.3  42.4  18.1
5 R32     6      6 Purd~    34    29      5 118.  92.6  52.2  47.2  17
6 R32     2      2 Alab~    34    29      5 115.  88.3  52.7  41.5  19
7 R32     9      9 Texas    34    26      8 115.  91.6  52.7  47.8  16.5
8 R32    11     11 Marq~    34    28      6 119.  96.1  56      51.1  15.2
9 R32    10     10 Gonz~    32    27      5 123.  98.6  58.5  51.7  14.6
10 R32     8      8 Sain~    32    25      7 112.  89.1  52.5  46.7  16.4
# ... with 54 more rows, 24 more variables: TORD <dbl>, ORB <dbl>, DRB <dbl>,
#   FTR <dbl>, FTRD <dbl>, `2P%` <dbl>, `2P%D` <dbl>, `3P%` <dbl>,
#   `3P%D` <dbl>, `3PR` <dbl>, `3PRD` <dbl>, `ADJ T` <dbl>, G.y <dbl>,
#   `Overall W-L%` <dbl>, `Overall SRS` <dbl>, `Overall SOS` <dbl>,

```

```
# `Conf. W-L%` <dbl>, `Home W-L%` <dbl>, `Away W-L%` <dbl>, `AVG PPG` <dbl>,  
# `AVG DPPG` <dbl>, `AVG PD` <dbl>, `AST/TOV` <dbl>, `PF/G` <dbl>, and  
# abbreviated variable name 1: `predict(mmb_ord_model, `2023stats`)
```

**INTERPRET SOMETHING - MOST IMPORTANT VARIABLES**

**ADD ASSUMPTIONS**

**MODEL'S PREDICTIVE POWER**

**Outliers and Randomness of March Madness**

## **Discussion**

**MISSING ASSUMPTIONS**

**HYPOTHESIS TESTS**

**COOK'S DISTANCE**

**IDEA'S FOR FUTURE WORK**