

Lecture 4: Functions

Last time

```
1 nsim <- 1000
2 n <- 100 # sample size
3 beta0 <- 0.5 # intercept
4 beta1 <- 1 # slope
5 results <- rep(NA, nsim)
6
7 for(i in 1:nsim){
8   x <- runif(n, min=0, max=1)
9   noise <- rchisq(n, 1)
10  y <- beta0 + beta1*x + noise
11
12  lm_mod <- lm(y ~ x)
13  ci <- confint(lm_mod, "x", level = 0.95)
14
15  results[i] <- ci[1] < 1 & ci[2] > 1
16 }
17 mean(results)
```

What if I want to repeat my simulations with a different sample size n ?

Simulation code for multiple sample sizes

```
1  nsim <- 1000
2  beta0 <- 0.5 # intercept
3  beta1 <- 1 # slope
4  results <- rep(NA, nsim)
5
6  n <- 100 # sample size
7  for(i in 1:nsim){
8    ...
9  }
10
11 n <- 200 # new sample size
12 for(i in 1:nsim){
13   ...
14 }
```

Are there any issues with this code?

Coding best practices

So far:

- No magic numbers
- Comment your code
- Use informative names
- Set a seed for reproducibility

Also: *don't repeat the same chunk of code multiple times*

Functions

```
1 assess_coverage <- function(n, nsim){
2   results <- rep(NA, nsim)
3
4   for(i in 1:nsim){
5     x <- runif(n, min=0, max=1)
6     noise <- rchisq(n, 1)
7     y <- 0.5 + 1*x + noise
8
9     lm_mod <- lm(y ~ x)
10    ci <- confint(lm_mod, "x", level = 0.95)
11
12    results[i] <- ci[1] < 1 & ci[2] > 1
13  }
14  return(mean(results))
15 }
16
17 assess_coverage(n = 100, nsim = 1000)
```

```
[1] 0.947
```

Functions

Now I can change the value of `n` without re-writing all the code!

```
1 assess_coverage(n = 100, nsim = 1000)
```

```
[1] 0.957
```

```
1 assess_coverage(n = 200, nsim = 1000)
```

```
[1] 0.947
```

Function components

Here is a simple function to calculate the absolute value:

```
1 my_abs <- function(x){  
2   return(ifelse(x >= 0, x, -1*x))  
3 }  
4  
5 my_abs(-3)
```

```
[1] 3
```

```
1 my_abs(c(-2, 5))
```

```
[1] 2 5
```

- **name:** `my_abs`
- **arguments:** `x`
- **body:** everything in the curly braces `{ }`

Function arguments

- The *arguments* `n` and `nsim` allow us to change the sample size and number of simulations
- What other parts of the simulation might we want to change?

```
1 assess_coverage <- function(n, nsim){  
2   results <- rep(NA, nsim)  
3  
4   for(i in 1:nsim){  
5     x <- runif(n, min=0, max=1)  
6     noise <- rchisq(n, 1)  
7     y <- 0.5 + 1*x + noise  
8  
9     lm_mod <- lm(y ~ x)  
10    ci <- confint(lm_mod, "x", level = 0.95)  
11  
12    results[i] <- ci[1] < 1 & ci[2] > 1  
13  }
```


Function arguments

```
1 assess_coverage <- function(n, nsim, beta0, beta1){
2   results <- rep(NA, nsim)
3
4   for(i in 1:nsim){
5     x <- runif(n, min=0, max=1)
6     noise <- rchisq(n, 1)
7     y <- beta0 + beta1*x + noise
8
9     lm_mod <- lm(y ~ x)
10    ci <- confint(lm_mod, "x", level = 0.95)
11
12    results[i] <- ci[1] < beta1 & ci[2] > beta1
13  }
14  return(mean(results))
15 }
```

Ordering and arguments

```
1 my_power <- function(x, y){  
2   return(x^y)  
3 }
```

```
1 my_power(x = 2, y = 3)
```

```
[1] 8
```

```
1 my_power(y = 3, x = 2)
```

```
[1] 8
```

```
1 my_power(2, 3)
```

```
[1] 8
```

```
1 my_power(3, 2)
```

```
[1] 9
```

- If you don't name the arguments when calling a function, R assumes you passed them in the order of the function definition

Function defaults

```
1 my_power <- function(x, y){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(3)
```

Function defaults

```
1 my_power <- function(x, y){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(3)
```

Error in my_power(3): argument "y" is missing, with no default

Function defaults

```
1 my_power <- function(x, y=2){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(3)
```

Function defaults

```
1 my_power <- function(x, y=2){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(3)
```

```
[1] 9
```

Function defaults

```
1 my_power <- function(x, y=2){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(2, 3)
```

Function defaults

```
1 my_power <- function(x, y=2){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(2, 3)
```

```
[1] 8
```


Function defaults

```
1 my_power <- function(x, y){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(3)
```

Function defaults

```
1 my_power <- function(x, y){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power(3)
```

Error in my_power(3): argument "y" is missing, with no default

Function defaults

```
1 my_power <- function(x=2, y=4){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power()
```

Function defaults

```
1 my_power <- function(x=2, y=4){  
2   return(x^y)  
3 }
```

What will happen when I run the following code?

```
1 my_power()
```

```
[1] 16
```

Function arguments

We can also pass functions as arguments!

```
1 assess_coverage <- function(n, nsim, beta0, beta1, noise_dist){
2   results <- rep(NA, nsim)
3
4   for(i in 1:nsim){
5     x <- runif(n, min=0, max=1)
6     noise <- noise_dist(n)
7     y <- beta0 + beta1*x + noise
8
9     lm_mod <- lm(y ~ x)
10    ci <- confint(lm_mod, "x", level = 0.95)
11    results[i] <- ci[1] < beta1 & ci[2] > beta1
12  }
13  return(mean(results))
14 }
```

```
1 assess_coverage(n = 100, nsim = 1000, beta0 = 0.5, beta1 = 1,
2                 noise_dist = rexp)
```

```
[1] 0.948
```

Summary

- Functions can be used to avoid repeating code
- Arguments allow us specify the inputs when we call a function
- If inputs are not named when calling the function, R uses the ordering from the function definition
- All arguments must be specified when calling a function
- Default arguments can be specified when the function is defined
- The input to a function can be a function!

Class activity

https://sta279-f23.github.io/class_activities/ca_lecture_4.html

- If finished early, you may work on homework
- Solutions will be posted on course website

