

Profiling & Parallelization

Lecture 21

Dr. Colin Rundel

Profiling & Benchmarking

profvis demo

```
1 n = 1e6
2 d = tibble(
3   x1 = rt(n, df = 3),
4   x2 = rt(n, df = 3),
5   x3 = rt(n, df = 3),
6   x4 = rt(n, df = 3),
7   x5 = rt(n, df = 3),
8 ) |>
9   mutate(y = -2*x1 - 1*x2 + 0*x3 + 1*x4 + 2*x5 + rnorm(n))
```

```
1 profvis::profvis({
2   lm(y~., data=d)
3 })
```

profvis demo 2

```
1 profvis::profvis({  
2   data = data.frame(value = runif(5e4))  
3  
4   data$sum[1] = data$value[1]  
5   for (i in seq(2, nrow(data))) {  
6     data$sum[i] = data$sum[i-1] + data$value[i]  
7   }  
8 })
```

```
1 profvis::profvis({  
2   x = runif(5e4)  
3   sum = x[1]  
4   for (i in seq(2, length(x))) {  
5     sum[i] = sum[i-1] + x[i]  
6   }  
7 })
```

Benchmarking - bench

```
1 d = tibble(  
2   x = runif(10000),  
3   y = runif(10000)  
4 )  
5  
6 (b = bench::mark(  
7   d[d$x > 0.5, ],  
8   d[which(d$x > 0.5), ],  
9   subset(d, x > 0.5),  
10  filter(d, x > 0.5)  
11 ))
```

A tibble: 4 × 6

| expression | min | median | `itr/sec` | mem_alloc | `gc/sec` |
|--------------------------|----------|----------|-----------|-----------|----------|
| <bch:expr> | <bch:tm> | <bch:tm> | <dbl> | <bch:byt> | <dbl> |
| 1 d[d\$x > 0.5,] | 75.8µs | 90.8µs | 10784. | 234.56KB | 42.0 |
| 2 d[which(d\$x > 0.5),] | 78.2µs | 94.8µs | 10396. | 268.33KB | 78.2 |
| 3 subset(d, x > 0.5) | 93.6µs | 116.8µs | 8267. | 287.09KB | 61.3 |
| 4 filter(d, x > 0.5) | 249.4µs | 285µs | 3457. | 1.47MB | 25.8 |

Larger n

```
1 d = tibble(  
2   x = runif(1e6),  
3   y = runif(1e6)  
4 )  
5  
6 (b = bench::mark(  
7   d[d$x > 0.5, ],  
8   d[which(d$x > 0.5), ],  
9   subset(d, x > 0.5),  
10  filter(d, x > 0.5)  
11 ))
```

A tibble: 4 × 6

| expression | min | median | `itr/sec` | mem_alloc | `gc/sec` |
|--------------------------|----------|----------|-----------|-----------|----------|
| <bch:expr> | <bch:tm> | <bch:tm> | <dbl> | <bch:byt> | <dbl> |
| 1 d[d\$x > 0.5,] | 7.54ms | 7.99ms | 125. | 13.3MB | 54.2 |
| 2 d[which(d\$x > 0.5),] | 9.11ms | 9.35ms | 107. | 24.8MB | 112. |
| 3 subset(d, x > 0.5) | 11.61ms | 12.11ms | 80.9 | 24.8MB | 91.0 |
| 4 filter(d, x > 0.5) | 9.5ms | 10.37ms | 94.8 | 24.8MB | 105. |

bench - relative results

```
1 summary(b, relative=TRUE)
```

```
# A tibble: 4 × 6
```

| | expression <bch:expr> | min <dbl> | median <dbl> | `itr/sec` <dbl> | mem_alloc <dbl> | `gc/sec` <dbl> |
|---|--------------------------|--------------|-----------------|--------------------|--------------------|-------------------|
| 1 | d[d\$x > 0.5,] | 1 | 1 | 1.55 | 1 | 1 |
| 2 | d[which(d\$x > 0.5),] | 1.21 | 1.17 | 1.32 | 1.86 | 2.06 |
| 3 | subset(d, x > 0.5) | 1.54 | 1.52 | 1 | 1.86 | 1.68 |
| 4 | filter(d, x > 0.5) | 1.26 | 1.30 | 1.17 | 1.86 | 1.94 |

t.test

Imagine we have run 1000 experiments (rows), each of which collects data on 50 individuals (columns).
The first 25 individuals in each experiment are assigned to group 1 and the rest to group 2.

The goal is to calculate the t-statistic for each experiment comparing group 1 to group 2.

```
1 m = 1000
2 n = 50
3 X = matrix(
4   rnorm(m * n, mean = 10, sd = 3),
5   ncol = m
6 ) |>
7   as.data.frame() |>
8   set_names(paste0("exp", seq_len(m))) |>
9   mutate(
10     ind = seq_len(n),
11     group = rep(1:2, each = n/2)
12 ) |>
13   as_tibble() |>
14   relocate(ind, group)
```

```
1 X
```

```
# A tibble: 50 × 1,002
      ind group  exp1  exp2  exp3  exp4  exp5
exp6
  <int> <int> <dbl> <dbl> <dbl> <dbl> <dbl>
<dbl>
1      1      1      1  2.83  7.90  8.39 10.5  11.5
11.5
2      2      2      1 14.5   8.59 11.8   9.75  9.34
4.43
3      3      3      1  8.74  6.79  7.33  8.43  7.66
11.5
4      4      4      1 13.1   5.51  6.39  9.67  8.55
16.3
5      5      5      1  4.51 13.1  13.4   4.57  2.89
10.4
6      6      6      1 11.3   5.18 12.2   5.59 10.7
12.2
7      7      7      1  0.65  0.53  5.33 11.0  11.5
```


Implementations

```
1 ttest_formula = function(X, m) {  
2   for(i in 1:m) t.test(X[[2+i]] ~ X$group)$stat  
3 }  
4 system.time(ttest_formula(X,m))
```

```
user  system elapsed  
0.143   0.005   0.148
```

```
1 ttest_for = function(X, m) {  
2   for(i in 1:m) t.test(X[[2+i]][X$group == 1], X[[2+i]][X$group == 2])$stat  
3 }  
4 system.time(ttest_for(X,m))
```

```
user  system elapsed  
0.044   0.000   0.044
```

```
1 ttest_apply = function(X) {  
2   f = function(x, g) {  
3     t.test(x[g==1], x[g==2])$stat  
4   }  
5   apply(X[,-(1:2)], 2, f, X$group)  
6 }  
7 system.time(ttest_apply(X))
```

```
user  system elapsed  
0.037   0.000   0.037
```

Implementations (cont.)

```
1 ttest_hand_calc = function(X) {  
2   f = function(x, grp) {  
3     t_stat = function(x) {  
4       m = mean(x)  
5       n = length(x)  
6       var = sum((x - m) ^ 2) / (n - 1)  
7  
8       list(m = m, n = n, var = var)  
9     }  
10  
11     g1 = t_stat(x[grp == 1])  
12     g2 = t_stat(x[grp == 2])  
13  
14     se_total = sqrt(g1$var / g1$n + g2$var / g2$n)  
15     (g1$m - g2$m) / se_total  
16   }  
17  
18   apply(X[,-(1:2)], 2, f, X$group)  
19 }  
20 system.time(ttest_hand_calc(X))
```

| user | system | elapsed |
|-------|--------|---------|
| 0.010 | 0.000 | 0.011 |

Comparison

```
1 bench::mark(  
2   ttest_formula(X, m),  
3   ttest_for(X, m),  
4   ttest_apply(X),  
5   ttest_hand_calc(X),  
6   check=FALSE  
7 )
```

Warning: Some expressions had a GC in every iteration; so filtering is disabled.

A tibble: 4 × 6

| | expression | min | median | `itr/sec` | mem_alloc | `gc/sec` |
|---|---------------------|----------|----------|-----------|-----------|----------|
| | <bch:expr> | <bch:tm> | <bch:tm> | <dbl> | <bch:byt> | <dbl> |
| 1 | ttest_formula(X, m) | 137.04ms | 139.3ms | 7.14 | 8.24MB | 14.3 |
| 2 | ttest_for(X, m) | 46.77ms | 53.69ms | 19.1 | 1.91MB | 15.3 |
| 3 | ttest_apply(X) | 39.74ms | 45.43ms | 21.9 | 3.48MB | 14.0 |
| 4 | ttest_hand_calc(X) | 6.35ms | 6.66ms | 127. | 3.44MB | 15.8 |

Parallelization

parallel

Part of the base packages in R

- tools for the forking of R processes (some functions do not work on Windows)
- Core functions:
 - `detectCores`
 - `pvec`
 - `mclapply`
 - `mcpipeline` & `mccollect`

detectCores

Surprisingly, detects the number of cores of the current system.

```
1 detectCores()
```

```
[1] 14
```

pvec

Parallelization of a vectorized function call

```
1 system.time(pvec(1:1e7, sqrt, mc.cores = 1))
```

| user | system | elapsed |
|-------|--------|---------|
| 0.011 | 0.007 | 0.018 |

```
1 system.time(pvec(1:1e7, sqrt, mc.cores = 4))
```

| user | system | elapsed |
|-------|--------|---------|
| 0.211 | 0.876 | 1.005 |

```
1 system.time(pvec(1:1e7, sqrt, mc.cores = 8))
```

| user | system | elapsed |
|-------|--------|---------|
| 0.087 | 0.842 | 0.816 |

```
1 system.time(sqrt(1:1e7))
```

| user | system | elapsed |
|-------|--------|---------|
| 0.012 | 0.012 | 0.026 |

pvec - bench::system_time

```
1 bench::system_time(pvec(1:1e7, sqrt, mc.cores = 1))
```

| process | real |
|---------|--------|
| 22.1ms | 21.9ms |

```
1 bench::system_time(pvec(1:1e7, sqrt, mc.cores = 4))
```

| process | real |
|---------|-------|
| 482ms | 802ms |

```
1 bench::system_time(pvec(1:1e7, sqrt, mc.cores = 8))
```

| process | real |
|---------|-------|
| 551ms | 835ms |


```
1 bench::system_time(Sys.sleep(.5))
```

| process | real |
|---------|-------|
| 80µs | 497ms |

```
1 system.time(Sys.sleep(.5))
```

| user | system | elapsed |
|-------|--------|---------|
| 0.000 | 0.000 | 0.505 |

Cores by size

```
1 cores = c(1,4,6,8,10)
2 order = 6:8
3 f = function(x,y) {
4   system.time(
5     pvec(1:(10^y), sqrt, mc.cores = x)
6   )[3]
7 }
8
9 res = map(
10   cores,
11   function(x) {
12     map_dbl(order, f, x = x)
13   }
14 ) |>
15   do.call(rbind, args = _)
16
17 rownames(res) = paste0(cores," cores")
18 colnames(res) = paste0("10^",order)
```

1 res

| | | 10 ⁶ | 10 ⁷ | 10 ⁸ |
|----|-------|-----------------|-----------------|-----------------|
| 1 | cores | 0.003 | 0.026 | 0.348 |
| 4 | cores | 0.093 | 0.736 | 8.363 |
| 6 | cores | 0.085 | 0.762 | 7.685 |
| 8 | cores | 0.105 | 0.760 | 7.987 |
| 10 | cores | 0.117 | 0.785 | 7.915 |

mclapply

implements a parallelized version of `lapply`

```
1 system.time(rnorm(1e7))
```

```
user system elapsed  
0.158  0.004  0.161
```

```
1 system.time(unlist(mclapply(1:10, function(x) rnorm(1e6), mc.cores = 2)))
```

```
user system elapsed  
0.202  0.770  0.851
```

```
1 system.time(unlist(mclapply(1:10, function(x) rnorm(1e6), mc.cores = 4)))
```

```
user system elapsed  
0.206  0.744  0.764
```

```
1 system.time(unlist(mclapply(1:10, function(x) rnorm(1e6), mc.cores = 8)))
```

```
user system elapsed  
0.212  0.799  0.778
```

```
1 system.time(unlist(mclapply(1:10, function(x) rnorm(1e6), mc.cores = 10)))
```

```
user system elapsed  
0.210  0.794  0.768
```

mcpParallel

Asynchronously evaluation of an R expression in a separate process

```
1 m = mcpParallel(rnorm(1e6))  
2 n = mcpParallel(rbeta(1e6,1,1))  
3 o = mcpParallel(rgamma(1e6,1,1))
```

```
1 str(m)
```

List of 2

```
$ pid: int 33195  
$ fd : int [1:2] 5 8  
- attr(*, "class")= chr [1:3] "parallelJob" "childProcess" "process"
```

```
1 str(n)
```

List of 2

```
$ pid: int 33196  
$ fd : int [1:2] 6 10  
- attr(*, "class")= chr [1:3] "parallelJob" "childProcess" "process"
```

mccollect

Checks `mcparallel` objects for completion

```
1 str(mccollect(list(m,n,o)))
```

List of 3

```
$ 33195: num [1:1000000] 0.12 0.987 -0.498 -1.111 -1.084 ...  
$ 33196: num [1:1000000] 0.997 0.082 0.139 0.198 0.649 ...  
$ 33197: num [1:1000000] 0.594 0.291 1.73 1.022 0.347 ...
```

mccollect - waiting

```
1 p = mcpipeline(mean(rnorm(1e5)))
```

```
1 mccollect(p, wait = FALSE, 10)
```

```
$`33198`  
[1] 0.002961617
```

```
1 mccollect(p, wait = FALSE)
```

```
Warning in selectChildren(jobs, timeout): cannot wait for child 33198  
as it does not exist
```

```
NULL
```

```
1 mccollect(p, wait = FALSE)
```

```
Warning in selectChildren(jobs, timeout): cannot wait for child 33198  
as it does not exist
```

```
NULL
```

doMC & foreach

doMC & foreach

Packages by Revolution Analytics that provides the `foreach` function which is a parallelizable `for` loop (and then some).

- Core functions:
 - `registerDoMC`
 - `foreach, %dopar%, %do%`

registerDoMC

Primarily used to set the number of cores used by `foreach`, by default uses `options("cores")` or half the number of cores found by `detectCores` from the `parallel` package.

```
1 options("cores")
```

```
$cores  
NULL
```

```
1 detectCores()
```

```
[1] 14
```

```
1 getDoParWorkers()
```

```
[1] 1
```

```
1 registerDoMC(4)  
2 getDoParWorkers()
```

```
[1] 4
```

foreach

A slightly more powerful version of base `for` loops (think `for` with an `lapply` flavor). Combined with `%do%` or `%dopar%` for single or multicore execution.

```
1 for(i in 1:10) {  
2   sqrt(i)  
3 }
```

```
1 foreach(i = 1:5) %do% {  
2   sqrt(i)  
3 }
```

```
[[1]]  
[1] 1
```

```
[[2]]  
[1] 1.414214
```

```
[[3]]  
[1] 1.732051
```

```
[[4]]  
[1] 2
```

```
[[5]]  
[1] 2.236068
```

foreach - iterators

`foreach` can iterate across more than one value, but it doesn't do length coercion

```
1 foreach(i = 1:5, j = 1:5) %do% {  
2   sqrt(i^2+j^2)  
3 }
```

```
[[1]]  
[1] 1.414214
```

```
[[2]]  
[1] 2.828427
```

```
[[3]]  
[1] 4.242641
```

```
[[4]]  
[1] 5.656854
```

```
[[5]]  
[1] 7.071068
```

```
1 foreach(i = 1:5, j = 1:2) %do% {  
2   sqrt(i^2+j^2)  
3 }
```

```
[[1]]  
[1] 1.414214
```

```
[[2]]  
[1] 2.828427
```

foreach - combining results

```
1 foreach(i = 1:5, .combine='c') %do% {  
2   sqrt(i)  
3 }
```

```
[1] 1.000000 1.414214 1.732051 2.000000 2.236068
```

```
1 foreach(i = 1:5, .combine='cbind') %do% {  
2   sqrt(i)  
3 }
```

```
      result.1 result.2 result.3 result.4 result.5  
[1,]          1 1.414214 1.732051          2 2.236068
```

```
1 foreach(i = 1:5, .combine='+') %do% {  
2   sqrt(i)  
3 }
```

```
[1] 8.382332
```

foreach - parallelization

Swapping out `%do%` for `%dopar%` will use the parallel backend.

```
1 registerDoMC(4)
2 system.time(foreach(i = 1:10) %dopar% mean(rnorm(1e6)))
```

```
   user  system elapsed
0.124    0.035    0.080
```

```
1 registerDoMC(8)
2 system.time(foreach(i = 1:10) %dopar% mean(rnorm(1e6)))
```

```
   user  system elapsed
0.149    0.044    0.061
```

```
1 registerDoMC(10)
2 system.time(foreach(i = 1:10) %dopar% mean(rnorm(1e6)))
```

```
   user  system elapsed
0.186    0.050    0.050
```



furrr / future

```
1 system.time( purrr::map(c(1,1,1), Sys.sleep) )
```

```
   user  system elapsed  
0.000   0.000   3.012
```

```
1 system.time( furrr::future_map(c(1,1,1), Sys.sleep) )
```

```
   user  system elapsed  
0.032   0.008   3.074
```

```
1 future::plan(future::multisession) # See also future::multicore  
2 system.time( furrr::future_map(c(1,1,1), Sys.sleep) )
```

```
   user  system elapsed  
0.188   0.007   1.314
```

Example - Bootstrapping

Bootstrapping is a resampling scheme where the original data is repeatedly reconstructed by taking a samples of size n (with replacement) from the original data, and using that to repeat an analysis procedure of interest. Below is an example of fitting a local regression (`loess`) to some synthetic data, we will construct a bootstrap prediction interval for this model.


```
1 set.seed(3212016)
2 d = data.frame(x = 1:120) |>
3   mutate(y = sin(2*pi*x/120) + runif(length(x),-1,1))
4
5 l = loess(y ~ x, data=d)
6 p = predict(l, se=TRUE)
7
8 d = d |> mutate(
9   pred_y = p$fit,
10  pred_y_se = p$se.fit
11 )
```



```

1 ggplot(d, aes(x,y)) +
2   geom_point(color="gray50") +
3   geom_ribbon(
4     aes(ymin = pred_y - 1.96 * pred_y_se,
5         ymax = pred_y + 1.96 * pred_y_se),
6     fill="red", alpha=0.25
7   ) +
8   geom_line(aes(y=pred_y)) +
9   theme_bw()

```



Bootstrapping Demo

What to use when?

Optimal use of parallelization / multiple cores is hard, there isn't one best solution

- Don't underestimate the overhead cost
- Experimentation is key
- Measure it or it didn't happen
- Be aware of the trade off between developer time and run time

BLAS and LAPACK

Statistics and Linear Algebra

An awful lot of statistics is at its core linear algebra.

For example:

- Linear regression models, find

$$\hat{\beta} = (X^T X)^{-1} X^T y$$

- Principle component analysis
 - Find $T = XW$ where W is a matrix whose columns are the eigenvectors of $X^T X$.
 - Often solved via SVD - Let $X = U\Sigma W^T$ then $T = U\Sigma$.

Numerical Linear Algebra

Not unique to Statistics, these are the type of problems that come up across all areas of numerical computing.

- Numerical linear algebra \neq mathematical linear algebra
- Efficiency and stability of numerical algorithms matter
 - Designing and implementing these algorithms is hard
- Don't reinvent the wheel - common core linear algebra tools (well defined API)

BLAS and LAPACK

Low level algorithms for common linear algebra operations

BLAS

- **B**asic **L**inear **A**lgebra **S**ubprograms
- Copying, scaling, multiplying vectors and matrices
- Origins go back to 1979, written in Fortran

LAPACK

- **L**inear **A**lgebra **P**ackage
- Higher level functionality building on BLAS.
- Linear solvers, eigenvalues, and matrix decompositions
- Origins go back to 1992, mostly Fortran (expanded on LINPACK, EISPACK)

Modern variants?

Most default BLAS and LAPACK implementations (like R's defaults) are somewhat dated

- Written in Fortran and designed for a single cpu core
- Certain (potentially non-optimal) hard coded defaults (e.g. block size).

Multithreaded alternatives:


- ATLAS - Automatically Tuned Linear Algebra Software
- OpenBLAS - fork of GotoBLAS from TACC at UTexas
- Intel MKL - Math Kernel Library, part of Intel's commercial compiler tools
- cuBLAS / Magma - GPU libraries from Nvidia and UTK respectively
- Accelerate / vecLib - Apple's framework for GPU and multicore computing

OpenBLAS Matrix Multiply Performance

```
1 x=matrix(runif(5000^2),ncol=5000)
2
3 sizes = c(100,500,1000,2000,3000,4000,5000)
4 cores = c(1,2,4,8,16)
5
6 sapply(
7   cores,
8   function(n_cores) {
9     flexiblas::flexiblas_set_num_threads(n_cores)
10    sapply(
11      sizes,
12      function(s) {
13        y = x[1:s,1:s]
14        system.time(y %*% y)[3]
15      }
16    )
17  }
18 )
```

| n | 1 core | 2 cores | 4 cores | 8 cores | 16 cores |
|----------|---------------|----------------|----------------|----------------|-----------------|
| 100 | 0.000 | 0.000 | 0.000 | 0.000 | 0.000 |
| 500 | 0.004 | 0.003 | 0.002 | 0.002 | 0.004 |
| 1000 | 0.028 | 0.016 | 0.010 | 0.007 | 0.009 |
| 2000 | 0.207 | 0.110 | 0.058 | 0.035 | 0.039 |
| 3000 | 0.679 | 0.352 | 0.183 | 0.103 | 0.081 |
| 4000 | 1.587 | 0.816 | 0.418 | 0.227 | 0.145 |
| 5000 | 3.104 | 1.583 | 0.807 | 0.453 | 0.266 |

Matrix Multiply of (n x n) matrices



Matrix Multiply of (n x n) matrices

