

Tidy data - dplyr & tidyr

Lecture 08

Dr. Colin Rundel



Tidy data

country	year	cases	population
Afghanistan	1999	37745	19987071
Afghanistan	2000	2666	20595360
Brazil	1999	37737	172006362
Brazil	2000	80488	174604898
China	1999	212258	1272915272
China	2000	213766	1280425583

variables

country	year	cases	population
Afghanistan	1999	37745	19987071
Afghanistan	2000	2666	20595360
Brazil	1999	37737	172006362
Brazil	2000	80488	174604898
China	1999	212258	1272915272
China	2000	213766	1280425583

observations

country	year	cases	population
Afghanistan	1999	37745	19987071
Afghanistan	2000	2666	20595360
Brazil	1999	37737	172006362
Brazil	2000	80488	174604898
China	1999	212258	1272915272
China	2000	213766	1280425583

values

Tidy vs Untidy

Happy families are all alike; every unhappy family is unhappy in its own way

— Leo Tolstoy, Anna Karenina

```
# A tibble: 317 × 7
  artist      track      date.entered  wk1  wk2  wk3  wk4
  <chr>      <chr>      <date>      <dbl> <dbl> <dbl> <dbl>
1 2 Pac      Baby Don't Cry... 2000-02-26    87    82    72    77
2 2Ge+her    The Hardest Pa... 2000-09-02    91    87    92    NA
3 3 Doors Down Kryptonite      2000-04-08    81    70    68    67
4 3 Doors Down Loser            2000-10-21    76    76    72    69
5 504 Boyz   Wobble Wobble   2000-04-15    57    34    25    17
6 98^0       Give Me Just O... 2000-08-19    51    39    34    26
7 A*Teens    Dancing Queen   2000-07-08    97    97    96    95
8 Aaliyah    I Don't Wanna   2000-01-29    84    62    51    41
9 Aaliyah    Try Again       2000-03-18    59    53    38    28
10 Adams, Yolanda Open My Heart    2000-08-26    76    76    74    69
# i 307 more rows
```

Is this data tidy?



Modern data frames

The tidyverse includes the tibble package that extends data frames to be a bit more modern. The core features of tibbles are a nicer printing method as well as being “lazy”.

```
1 library(tibble)
```

```
1 iris
```

	Sepal.Length	Sepal.Width	Petal.Length
1	5.1	3.5	1.4
2	4.9	3.0	1.4
3	4.7	3.2	1.3
4	4.6	3.1	1.5
5	5.0	3.6	1.4
6	5.4	3.9	1.7
7	4.6	3.4	1.4
8	5.0	3.4	1.5
9	4.4	2.9	1.4
10	4.9	3.1	1.5
11	5.4	3.7	1.5
12	4.8	3.4	1.6
13	4.8	3.0	1.4
14	4.3	3.0	1.1
15	5.8	4.0	1.2
16	5.7	4.4	1.5
17	5.4	3.9	1.3
18	5.1	3.5	1.4
19	5.7	3.8	1.7
20	5.1	3.8	1.5
21	5.4	3.4	1.7
22	5.1	3.7	1.5

```
1 (tbl_iris = as_tibble(iris))
```

```
# A tibble: 150 × 5
  Sepal.Length Sepal.Width Petal.Length
      <dbl>         <dbl>         <dbl>
1         5.1         3.5         1.4
2         4.9         3.0         1.4
3         4.7         3.2         1.3
4         4.6         3.1         1.5
5          5.0         3.6         1.4
6         5.4         3.9         1.7
7         4.6         3.4         1.4
8          5.0         3.4         1.5
9         4.4         2.9         1.4
10        4.9         3.1         1.5
# i 140 more rows
# i 2 more variables: Petal.Width <dbl>,
#   Species <fct>
```


Tibbles are lazy (preserving type)

By default, subsetting tibbles always results in another tibble (`$` or `[[` can still be used to subset for a specific column).

```
1 tbl_iris[1,]
```

```
# A tibble: 1 × 5
```

	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Species
	<dbl>	<dbl>	<dbl>	<dbl>	<fct>
1	5.1	3.5	1.4	0.2	setosa

```
1 tbl_iris[,1]
```

```
# A tibble: 150 × 1  
  Sepal.Length  
    <dbl>  
1         5.1  
2         4.9  
3         4.7  
4         4.6  
5          5  
6         5.4  
7         4.6  
8          5  
9         4.4  
10        4.9  
# i 140 more rows
```

```
1 head(tbl_iris[[1]])
```

```
[1] 5.1 4.9 4.7 4.6 5.0 5.4
```

```
1 head(tbl_iris$Species)
```

```
[1] setosa setosa setosa setosa setosa set  
Levels: setosa versicolor virginica
```

Tibbles are lazy (partial matching)

Tibbles do not use partial matching when the `$` operator is used.

```
1 head( iris$Species )
```

```
[1] setosa setosa setosa setosa  
Levels: setosa versicolor virg
```

```
1 head( tbl_iris$Species )
```

```
[1] setosa setosa setosa setosa  
Levels: setosa versicolor virg
```

```
1 head( iris$Sp )
```

```
[1] setosa setosa setosa setosa  
Levels: setosa versicolor virg
```

```
1 head( tbl_iris$Sp )
```

```
Warning: Unknown or uninitialised  
NULL
```

Tibbles are lazy (length coercion)

Only vectors with length 1 will undergo length coercion / recycling - anything else throws an error.

```
1 data.frame(x = 1:4, y = 1)
```

	x	y
1	1	1
2	2	1
3	3	1
4	4	1

```
1 tibble(x = 1:4, y = 1)
```

```
# A tibble: 4 × 2
      x     y
  <int> <dbl>
1     1     1
2     2     1
3     3     1
4     4     1
```

```
1 data.frame(x = 1:4, y = 1:2)
```

	x	y
1	1	1
2	2	2
3	3	1
4	4	2

```
1 tibble(x = 1:4, y = 1:2)
```

```
Error in `tibble()`:
! Tibble columns must have compatible sizes
• Size 4: Existing data.
• Size 2: Column `y`.
i Only values of size one are recycled
```

Tibbles and S3

```
1 t = tibble(  
2   x = 1:3,  
3   y = c("A","B","C")  
4 )  
5  
6 class(t)
```

```
[1] "tbl_df"      "tbl"        "data.frame" [1] "data.frame"
```

```
1 d = data.frame(  
2   x = 1:3,  
3   y = c("A","B","C")  
4 )  
5  
6 class(d)
```

```
1 methods(class="tbl_df")
```

```
[1] [      [[      [[<-      [<-      $  
[6] $<-      as.data.frame coerce      initialize names<-  
[11] Ops      row.names<-  show      slotsFromS3 str  
[16] tbl_sum  
see '?methods' for accessing help and source code
```

```
1 methods(class="tbl")
```

```
[1] [[<-      [<-      $<-      coerce      format  
[6] glimpse      initialize Ops      print      show  
[11] slotsFromS3 tbl_sum  
see '?methods' for accessing help and source code
```

Tibble support?

Tibbles are just specialized data frames, and will fall back to base data frame methods when needed.

```
1 d = tibble(  
2   x = rnorm(100),  
3   y = 3 + x + rnorm(100, sd = 0.1)  
4 )
```

```
1 lm(y~x, data = d)
```

Call:


```
lm(formula = y ~ x, data = d)
```

Coefficients:

(Intercept)	x
3.0120	0.9901

Why did this work?

Sta 323 - Spring 2026



R's base pipe

What is a pipe

In software engineering, a pipeline consists of a chain of processing elements (processes, threads, coroutines, functions, etc.), arranged so that the output of each element is the input of the next;

[Wikipedia - Pipeline \(software\)](#)

R's base pipe (`|>`) is an infix operator that allows us to link two functions together in a way that is readable from left to right.

The following examples are equivalent:

```
1 f(g(x=1, y=2), n=2)
```

```
1 g(x=1, y=2) |> f(n=2)
```

```
1 g(x=1, y=2) %>% f(n=2) # library(magrittr)
```


Readability

All of the following are fine; it comes down to personal preference. Try to be consistent.

Nested:

```
1 h( g( f(x), y=1), z=1 )
```

Piped:

```
1 f(x) |>  
2   g(y=1) |>  
3   h(z=1)
```

Intermediate:

```
1 res = f(x)  
2 res = g(res, y=1)  
3 res = h(res, z=1)
```

What about other arguments?

Sometimes we want to send our results to a function argument other than first one. In these cases we can refer to the previous result using `_` (as long as the argument is named).

```
1 data.frame(a = 1:3, b = 3:1) |> lm(a~b, data=_)
```

Call:

```
lm(formula = a ~ b, data = data.frame(a = 1:3, b = 3:1))
```


Coefficients:

(Intercept)	b
4	-1

For non-named arguments we can use an anonymous function.

```
1 data.frame(a = 1:3, b = 3:1) |> (function(x) x[[1]])()
```

```
[1] 1 2 3
```



A Grammar of Data Manipulation

dplyr is based on the concepts of functions as verbs that manipulate data frames.

Core single data frame functions / verbs:

- `filter()` / `slice()` - pick rows based on criteria
- `mutate()` / `transmute()` - create or modify columns
- `summarise()` / `count()` - reduce variables to values
- `group_by()` / `ungroup()` - modify other verbs to act on subsets
- `select()` / `rename()` - select columns by name
- `pull()` - grab a column as a vector
- `arrange()` - reorder rows
- `distinct()` - filter for unique rows
- `relocate()` - change column order
- ... (many more)

dplyr rules

1. First argument is *always* a data frame
2. Subsequent arguments say what to do with the data frame
3. *Always* return a data frame
4. Don't modify in place (how does this affect memory usage?)
5. Magic via non-standard evaluation + lazy evaluation and S3

Example Data

We will demonstrate dplyr's functionality using the nycflights13 data.

```
1 library(nycflights13)
2 flights
```

```
# A tibble: 336,776 × 19
```

	year	month	day	dep_time	sched_dep_time	dep_delay	arr_time
	<int>	<int>	<int>	<int>	<int>	<dbl>	<int>
1	2013	1	1	517	515	2	830
2	2013	1	1	533	529	4	850
3	2013	1	1	542	540	2	923
4	2013	1	1	544	545	-1	1004
5	2013	1	1	554	600	-6	812
6	2013	1	1	554	558	-4	740
7	2013	1	1	555	600	-5	913
8	2013	1	1	557	600	-3	709
9	2013	1	1	557	600	-3	838
10	2013	1	1	558	600	-2	753


```
# i 336,766 more rows
```

```
# i 12 more variables: sched_arr_time <int>, arr_delay <dbl>,
```

```
# carrier <chr>, flight <int>, tailnum <chr>, origin <chr>, dest <chr>
```

Example 1

1. How many flights to Los Angeles (LAX) did each of the legacy carriers (AA, UA, DL or US) have in May from JFK, and what was their average duration?
2. What was the shortest flight out of each airport in terms of distance?
3. Which plane (check the tail numbers) flew out of each New York airport the most?
4. Which 5 days should you consider flying on if you want to have the lowest possible average departure delay?



Reshaping data

Wide vs Long

wide

id	x	y	z
1	a	c	e
2	b	d	f

Wide -> Long

country	1999	2000
A	0.7K	2K
B	37K	80K
C	212K	213K



country	year	cases
A	1999	0.7K
B	1999	37K
C	1999	212K
A	2000	2K
B	2000	80K
C	2000	213K

`pivot_longer` (previously `gather` or `reshape2::melt`)

Syntax

```
1 (d = tibble::tribble(  
2   ~country, ~"1999", ~"2000",  
3     "A", "0.7K", "2K",  
4     "B", "37K", "80K",  
5     "C", "212K", "213K"  
6 ))
```

```
# A tibble: 3 × 3  
  country `1999` `2000`  
  <chr>   <chr>   <chr>  
1 A      0.7K    2K  
2 B      37K    80K  
3 C     212K   213K
```

```
1 pivot_longer(  
2   d,  
3   cols = "1999":"2000",  
4   names_to = "year",  
5   values_to = "cases"  
6 )
```

```
# A tibble: 6 × 3  
  country year  cases  
  <chr>   <chr> <chr>  
1 A      1999  0.7K  
2 A      2000   2K  
3 B      1999  37K  
4 B      2000  80K  
5 C      1999 212K  
6 C      2000 213K
```

Long -> Wide

country	year	type	count		country	year	cases	pop
A	1999	cases	0.7K	→	A	1999	0.7K	19M
A	1999	pop	19M		A	2000	2K	20M
A	2000	cases	2K		B	1999	37K	172M
A	2000	pop	20M		B	2000	80K	174M
B	1999	cases	37K		C	1999	212K	1T
B	1999	pop	172M		C	2000	213K	1T
B	2000	cases	80K					
B	2000	pop	174M					
C	1999	cases	212K					
C	1999	pop	1T					
C	2000	cases	213K					
C	2000	pop	1T					

`pivot_wider` (previously `spread`)

Syntax

```
1 ( d = tibble::tribble(  
2   ~country, ~year, ~type, ~count,  
3     "A", 1999, "cases", "0.7K",  
4     "A", 1999, "pop", "19M",  
5     "A", 2000, "cases", "2K",  
6     "A", 2000, "pop", "20M",  
7     "B", 1999, "cases", "37K",  
8     "B", 1999, "pop", "172M",  
9     "B", 2000, "cases", "80K",  
10    "B", 2000, "pop", "174M",  
11    "C", 1999, "cases", "212K",  
12    "C", 1999, "pop", "1T",  
13    "C", 2000, "cases", "213K",  
14    "C", 2000, "pop", "1T"  
15  )  
16 )
```

```
# A tibble: 12 × 4  
  country year type count  
  <chr>   <dbl> <chr> <chr>  
1 A      1999 cases 0.7K  
2 A      1999 pop 19M  
3 A      2000 cases 2K  
4 A      2000 pop 20M  
5 B      1999 cases 37K  
6 B      1999 pop 172M  
7 B      2000 cases 80K  
8 B      2000 pop 174M  
9 C      1999 cases 212K  
10 C     1999 pop 1T  
11 C     2000 cases 213K  
12 C     2000 pop 1T
```

```
1 pivot_wider(  
2   d,  
3   id_cols = country:year,  
4   names_from = type,  
5   values_from = count  
6 )
```

```
# A tibble: 6 × 4  
  country year cases pop  
  <chr>   <dbl> <chr> <chr>  
1 A      1999 0.7K 19M  
2 A      2000 2K 20M  
3 B      1999 37K 172M  
4 B      2000 80K 174M  
5 C      1999 212K 1T  
6 C      2000 213K 1T
```

Exercise 1

The `palmerpenguins` package contains measurement data on various penguin species on islands near Palmer Station in Antarctica. The code below shows the # of each species measured on each of the three islands (missing island, penguin pairs implies that species does not occur on that island).

```
1 palmerpenguins::penguins |>  
2   count(island, species)
```

```
# A tibble: 5 × 3  
  island    species     n  
  <fct>    <fct>   <int>  
1 Biscoe  Adelie     44  
2 Biscoe  Gentoo    124  
3 Dream   Adelie     56  
4 Dream   Chinstrap 68  
5 Torgersen Adelie     52
```

Starting from these data construct a contingency table of counts for island (rows) by species (columns) using the pivot functions we've just discussed.

Separate - wider

country	year	rate		
A	1999	0.7K/19M		
A	2000	2K/20M		
B	1999	37K/172M		
B	2000	80K/174M		



country	year	cases	pop
A	1999	0.7K	19M
A	2000	2K	20M
B	1999	37K	172
B	2000	80K	174

```
1 separate_wider_delim(d, rate, delim = "/", names = c("cases", "pop"))
```

```
# A tibble: 6 × 4
```

```
  country year cases pop
  <chr>   <dbl> <chr> <chr>
1 A      1999 0.7K  19M
2 A      2000 2K    20M
3 B      1999 37K   172M
4 B      2000 80K   174M
5 C      1999 212K  1T
6 C      2000 213K  1T
```

Separate - longer

country	year	rate
A	1999	0.7K/19M
A	2000	2K/20M
B	1999	37K/172M
B	2000	80K/174M



country	year	rate
A	1999	0.7K
A	1999	19M
A	2000	2K
A	2000	20M
B	1999	37K
B	1999	172M
B	2000	80K
B	2000	174M

```
1 separate_longer_delim(d, rate, delim =
```

```
# A tibble: 12 × 3  
  country year rate  
  <chr>   <dbl> <chr>  
1 A      1999 0.7K  
2 A      1999 19M  
3 A      2000 2K  
4 A      2000 20M  
5 B      1999 37K  
6 B      1999 172M  
7 B      2000 80K  
8 B      2000 174M  
9 C      1999 212K  
10 C     1999 1T  
11 C     2000 213K  
12 C     2000 1T
```

Other separates

In previous versions of tidyr there was a single catch-all `separate()` function. This still exists and is available in the package but it is **superseded**.

Other helpful separate functions:

- `separate_longer_position()`
- `separate_wider_position()`
- `separate_wider_regex()`

Unite

country	century	year		country	year
Afghan	19	99	→	Afghan	1999
Afghan	20	0		Afghan	2000
Brazil	19	99		Brazil	1999
Brazil	20	0		Brazil	2000
China	19	99		China	1999
China	20	0		China	2000

```
1 unite(d, century, year, col = "year", sep = "")
```

```
# A tibble: 6 × 2
```

```
  country year  
  <chr>   <chr>  
1 Afghan 1999  
2 Afghan 2000  
3 Brazil 1999  
4 Brazil 2000  
5 China  1999  
6 China  2000
```

Example 2 - tidy grades

Is the following data tidy?

```
1 grades = tibble::tribble(  
2   ~name,    ~hw_1, ~hw_2, ~hw_3, ~hw_4, ~proj_1, ~proj_2,  
3   "Alice",   19,    19,    18,    20,    89,    95,  
4   "Bob",     18,    20,    18,    16,    77,    88,  
5   "Carol",   18,    20,    18,    17,    96,    99,  
6   "Dave",    19,    19,    18,    19,    86,    82  
7 )
```

How would we calculate a final score based on the following formula,

Semi-tidy approach

```
1 grades |>
2   mutate(
3     hw_avg = (hw_1+hw_2+hw_3+hw_4)/4,
4     proj_avg = (proj_1+proj_2)/2
5   ) |>
6   mutate(
7     overall = 0.5*(proj_avg/100) + 0.5*(hw_avg/20)
8   )
```

A tibble: 4 × 10

	name	hw_1	hw_2	hw_3	hw_4	proj_1	proj_2	hw_avg	proj_avg	overall
	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	Alice	19	19	18	20	89	95	19	92	0.935
2	Bob	18	20	18	16	77	88	18	82.5	0.862
3	Carol	18	20	18	17	96	99	18.2	97.5	0.944
4	Dave	19	19	18	19	86	82	18.8	84	0.889

pivot_longer (Wide -> Long)

```
1 tidyr::pivot_longer(  
2   grades,  
3   cols = hw_1:proj_2,  
4   names_to = "assignment",  
5   values_to = "score"  
6 )
```

```
# A tibble: 24 × 3  
   name assignment score  
   <chr> <chr>      <dbl>  
1 Alice hw_1      19  
2 Alice hw_2      19  
3 Alice hw_3      18  
4 Alice hw_4      20  
5 Alice proj_1     89  
6 Alice proj_2     95  
7 Bob   hw_1      18  
8 Bob   hw_2      20  
9 Bob   hw_3      18  
10 Bob   hw_4      16  
# i 14 more rows
```

Split type and id

```
1 tidyr::pivot_longer(  
2   grades,  
3   cols = hw_1:proj_2,  
4   names_to = c("type", "id"),  
5   names_sep = "_",  
6   values_to = "score"  
7 )
```

```
# A tibble: 24 × 4  
  name type id score  
  <chr> <chr> <chr> <dbl>  
1 Alice hw 1 19  
2 Alice hw 2 19  
3 Alice hw 3 18  
4 Alice hw 4 20  
5 Alice proj 1 89  
6 Alice proj 2 95  
7 Bob hw 1 18  
8 Bob hw 2 20  
9 Bob hw 3 18  
10 Bob hw 4 16  
# i 14 more rows
```


Tidy approach?

```
1 grades |>
2   tidyr::pivot_longer(
3     cols = hw_1:proj_2,
4     names_to = c("type", "id"),
5     names_sep = "_",
6     values_to = "score"
7   ) |>
8   summarize(
9     total = sum(score),
10    .by = c(name, type)
11  )
```

```
# A tibble: 8 × 3
  name  type  total
<chr> <chr> <dbl>
1 Alice hw      76
2 Alice proj    184
3 Bob   hw      72
4 Bob   proj    165
5 Carol hw      73
6 Carol proj    195
7 Dave  hw      75
8 Dave  proj    168
```

pivot_wider - (Long -> Wide)

```
1 grades |>
2   tidyr::pivot_longer(
3     cols = hw_1:proj_2,
4     names_to = c("type", "id"),
5     names_sep = "_",
6     values_to = "score"
7   ) |>
8   summarize(
9     total = sum(score),
10    .by = c(name, type)
11  ) |>
12  tidyr::pivot_wider(
13    names_from = type,
14    values_from = total
15  )
```

```
# A tibble: 4 × 3
  name      hw  proj
<chr> <dbl> <dbl>
1 Alice     76   184
2 Bob       72   165
3 Carol     73   195
4 Dave      75   168
```

Wrapping up

```
1 final_grades = grades |>
2   tidyr::pivot_longer(
3     cols = hw_1:proj_2,
4     names_to = c("type", "id"),
5     names_sep = "_",
6     values_to = "score"
7   ) |>
8   summarize(
9     total = sum(score),
10    .by = c(name, type)
11  ) |>
12  tidyr::pivot_wider(
13    names_from = type,
14    values_from = total
15  ) |>
16  mutate(
17    score = 0.5*(hw/80) +
18           0.5*(proj/200)
19  )
20
```

```
# A tibble: 4 × 4
  name      hw  proj score
<chr> <dbl> <dbl> <dbl>
1 Alice     76   184 0.935
2 Bob       72   165 0.862
3 Carol     73   195 0.944
4 Dave      75   168 0.889
```