Shiny for R

Lecture 20

Dr. Colin Rundel



Shiny
www.rstudio.com

shiny


> Shiny is an R package that makes it easy to build interactive web apps straight from R. You can host standalone apps on a webpage or embed them in R Markdown documents or build dashboards. You can also extend your Shiny apps with CSS themes, htmlwidgets, and JavaScript actions.

Shiny App

Server



Client / Browser



bslib

The `bslib` package provides a modern UI toolkit for Shiny, R Markdown, and Quarto based on Bootstrap.

We will be talking more about this package and its features next time. For now we will be loading it alongside `shiny` and using some of its layout features today.



If you are confused about where a particular function comes from, in general `shiny` uses `camelCase` while `bslib` uses

Anatomy of an App

```R
library(shiny)
library(bslib)

ui = list()

server = function(input, output, session) {

}

shinyApp(ui = ui, server = server)
```

The `ui` describes what the browser shows, a collection of inputs, outputs, and layout. The `server` function describes how the outputs are computed from the inputs.

Shiny Layouts

https://shiny.posit.co/r/layouts/



Shiny Widgets Gallery

https://shiny.posit.co/r/gallery/widgets/widget-gallery/



A brief widget tour

rundel.shinyapps.io/widgets/



Beta-Binomial app

App background

I've brought a coin with me to class and I'm claiming that it is fair (equally likely to come up heads or tails).

I flip the coin 10 times and we observe 7 heads and 3 tails, should you believe me that the coin is fair? Or, more generally, what should you believe about the coin's fairness now?

Model

Let y be the number of successes (heads) in n trials then,

Likelihood, *[Math Processing Error]*

Prior, *[Math Processing Error]*

Posterior

From the definition of Bayes' rule,

[Math Processing Error]

We then plug in the likelihood and prior and simplify by dropping any terms not involving p,

[Math Processing Error]

Posterior distribution

Based on the form of the density we can see that the posterior of p must also be a Beta distribution with parameters,

$$p|y, n, a, b \sim \text{Beta}(y + a, n - y + b)$$

and our other distributions

[Math Processing Error]

To normalize the likelihood curve, divide by


[Math Processing Error]

Example

Build a Shiny app that lets the user set the data (y heads out of n flips) and the prior (a, b) and plots the prior, likelihood, and posterior densities along with a table of summary statistics for each.

The reactive graph

Shiny records dependencies as reactive code runs. A solid arrow `A → B` means that **B depends on A**.



Dependencies in the first Beta-Binomial app, with some inputs grouped. The dashed arrow shows the observer updating the `x` slider in the browser.

When an input changes

Suppose we change `input$a`.

1. `d()` and its dependent outputs are **invalidated**: their previous results are no longer current.
2. When an output next calls `d()`, it recomputes using the new input values.
3. The other output uses the cached result of `d()`; it does not repeat the density calculations.

Reactive expressions are **lazy** and **cached**: invalidating a reactive does not immediately recompute it.

What needs to run again if we change `input$bw` instead?

Observers and input updates

Observers run for their **side effects**. When invalidated, they schedule themselves to run; another reactive does not need to call them.

```r
observe({
  updateSliderInput(session, "x", max = input$n)
}) |>
  bindEvent(input$n)
```

- Here, `bindEvent(input$n)` makes `input$n` the observer's dependency.
- The dashed arrow represents the side effect of updating the slider. If the browser reports a changed value for `input$x`, that starts another reactive update.
- Outputs are also implemented using observers: their side effect is to send a result to the browser.

Summary

Takeaways

- A Shiny app has two parts, a `ui` that describes what the browser shows and a `server` function that computes outputs from inputs. `shinyApp()` runs them together.
- Inputs are created by `*Input()` functions and read from `input$id` in the server. Outputs are created by `*Output()` functions in the UI and assigned via `render*()` functions to `output$id`.
- Reactive expressions created with `reactive()` cache intermediate results that are shared by several outputs. When a dependency changes, the cached result is invalidated and recomputed the next time it is needed.
- `observe()` runs code for its side effects, such as updating an input with `update*Input()`. `bindEvent()` limits when an observer or reactive runs.
- `bslib` provides page layouts such as `page_sidebar()` and uses `snake_case`, while `shiny` functions use `camelCase`.

Learning more

- Mastering Shiny by Hadley Wickham, particularly the chapters on Basic UI, Basic reactivity, The reactive graph, and Reactive building blocks
- Shiny for R getting started guide, layouts, and components
- bslib
- Shiny cheatsheet