

A CycloneDX VEX Profile for FedRAMP Rev5 VDR/VER Disposition and Response

Matthew Venne
Chief Technology Officer, stackArmor

June 2026

Abstract

This is a companion to *A Deterministic, CVSS-Environmental Method for FedRAMP Rev5 VDR/VER Vulnerability Prioritization*, which assigns every detected finding a Potential Agency Impact rating (PAIN, N1–N5) and a remediation deadline by formula. That scoring is deterministic and computable *a priori*. Deciding whether a finding is *truly* exploitable in the running environment — and, when a fix will miss the deadline, attesting the compensating response — is a separate, *a posteriori* step that can only follow detection. FedRAMP’s Vulnerability Evaluation Requirements (VER) make that step normative but name no format. This proposal recommends **CycloneDX VEX** as the structured, machine-readable, signable carrier for it, chosen for the fit of its disposition and response *vocabulary* — not because it carries scores; it does not. We give the field mapping to VER, a thin worked example, an OCI-native distribution pattern, and an optional crosswalk to CISA’s status-justification labels for downstream interoperability. This document is an *implementation profile*: it shows one defensible way to satisfy existing VER requirements; it does not propose changing them. The key words MUST, SHOULD, and MAY are to be read as in RFC 2119.

1 Where disposition sits in the lifecycle

The method memo computes PAIN and a deadline for *every* finding a scanner emits. But a scan hit is a candidate, not a confirmed exposure: the flagged code may be absent, may never execute, may require a configuration nobody enabled, or may sit behind a control that already neutralizes it. Resolving which is the *disposition* step.

Disposition is an *a posteriori* determination. The factors that decide it — reachability, configuration, surrounding mitigations — are specific to a given vulnerability on a given deployment and cannot be enumerated before that vulnerability is known. The analysis therefore necessarily follows detection, acutely so for novel vulnerabilities, where no prior due-diligence could exist. This is a statement about *timing*, not about who or what performs it: the determination MAY be fully automated or AI/agent, but it cannot be precomputed.

Because VER’s clocks are short, the determination must be captured in a form that machines can produce, exchange, sign, and act on. A disposition resolves a finding onto one of two tracks:

- **Not truly affected** — the finding is suppressed, with a machine-readable justification recording *why* (code absent, unreachable, configuration-gated, or already mitigated).
- **Affected but remediation will be late** — the finding is accepted within process, with an attested mitigation and a planned response, rather than silently breaching the deadline.

2 Why CycloneDX: the vocabulary fits the lifecycle

FedRAMP is not bound to any single VEX format, and VER specifies *fields and content*, not a schema (Section 3). The provider therefore chooses the carrier — the same latitude FedRAMP itself exercised in substituting PAIN for SSVC. On that basis the deciding factor is *expressiveness*: which format’s disposition vocabulary most precisely captures the real outcomes above. CycloneDX’s **analysis** object is the strongest fit. The same granularity pays off when disposition is automated: because each justification names a distinct precondition, an automated or AI/agentic analyzer can map each evidence source one-to-one to a justification, where a coarser vocabulary would collapse several distinct findings onto a single label.

CycloneDX field	Values (and what they capture)
<code>analysis.state</code>	<code>resolved</code> , <code>resolved_with_pedigree</code> , <code>exploitable</code> , <code>in_triage</code> , <code>false_positive</code> , <code>not_affected</code> — note a first-class <code>false_positive</code> and an <code>in_triage</code> (work-in-progress) state.
<code>analysis.justification</code>	<code>code_not_present</code> , <code>code_not_reachable</code> , <code>requires_configuration</code> , <code>requires_dependency</code> , <code>requires_environment</code> , <code>protected_by_compiler</code> , <code>protected_at_runtime</code> , <code>protected_at_perimeter</code> , <code>protected_by_mitigating_control</code> — nine reasons, naming configuration, reachability, and perimeter/runtime controls explicitly.
<code>analysis.response</code>	<code>can_not_fix</code> , <code>will_not_fix</code> , <code>update</code> , <code>rollback</code> , <code>workaround_available</code> — the planned action, which the late-remediation track needs and lighter formats lack.
<code>analysis.detail</code>	free text for human-readable context and evidence.

Table 1: CycloneDX’s **analysis** block: states, justifications, and responses.

The operational cases a CSP actually encounters map onto native values without contortion:

Real-world disposition	CycloneDX expression
Scanner false positive	<code>state: false_positive</code>
Vulnerable code absent / removed	<code>not_affected + code_not_present</code>
Vulnerable path never executes	<code>not_affected + code_not_reachable</code>
Needs an unset configuration	<code>not_affected + requires_configuration</code>
Neutralized at the edge (WAF/IAP)	<code>not_affected + protected_at_perimeter</code>
Neutralized at runtime / by a control	<code>not_affected + protected_at_runtime / protected_by_mitigating_control</code>
Affected; fix will miss deadline	<code>exploitable + response:[workaround_available, update] + detail</code>
Under evaluation	<code>in_triage</code>

Table 2: Operational dispositions and their native CycloneDX encodings.

3 Mapping to FedRAMP VER

VER requires the disposition step and a machine-readable report, in each case by function rather than by named format. CycloneDX satisfies each clause:

VER requirement	CycloneDX mechanism
VER-EVA-EFP (evaluate false positives)	<code>analysis.state = false_positive</code>
VER-EVA-AIA (assume exploitable absent evidence)	a VEX statement <i>is</i> the “evidence otherwise”; its absence leaves the assume-exploitable default in force
VER-RPT-VDT (per-finding disposition)	<code>analysis.state + justification + response</code> keyed to the CVE and component
VER-TFR-MAV / VER-RPT-AVI (accepted vulns)	<code>state = exploitable</code> with <code>response</code> and <code>detail</code> recording the acceptance and mitigation
VER-TFR-MRH (machine-readable JSON history)	CycloneDX is JSON; statements accrete over time with timestamps

Table 3: FedRAMP VER clauses and the CycloneDX fields that satisfy them.

4 A thin attestation: what it carries, and what it does not

The disposition artifact stays deliberately small. It carries only what identifies the finding and records the judgment:

- the vulnerability `id` and its `source`;
- the affected component, by `affects[].ref` (a package URL / `bom-ref`);
- the `analysis` block — `state`, `justification`, `response`, `detail`;
- provenance — author, timestamp, and a signature over the artifact.

It deliberately *omits* PAIN, the LEV/IRV axes, the Certification Class, and the CVSS vector. Those are computed deterministically by the method and live in the provider’s scoring report; duplicating them into the disposition artifact would invite drift and tempt a reader to treat an attestation as a place to re-score. The two records are joined on a stable key — the **CVE identifier plus the component reference** — so a reporting layer can attach each disposition to the finding it governs and recover the retained PAIN for audit. The disposition changes a finding’s *handling*; it never changes its score.

5 Worked example

A single signed CycloneDX document can carry several statements. Below, one finding is dispositioned `not_affected` (unreachable code) and one is `exploitable` with an attested perimeter mitigation because the vendor fix will arrive after the deadline. Note the absence of any score, rating, or PAIN field.

```
{
  "bomFormat": "CycloneDX",
  "specVersion": "1.6",
  "version": 1,
  "metadata": {
    "timestamp": "2026-06-28T14:00:00Z",
    "authors": [{ "name": "CSP Security Team" }],
    "component": {
      "type": "application",
      "name": "payments-api",
      "bom-ref": "payments-api@2.4.1"
    }
  },
  "vulnerabilities": [
```

```

{
  "id": "CVE-2026-10101",
  "source": { "name": "NVD",
    "url": "https://nvd.nist.gov/vuln/detail/CVE-2026-10101" },
  "analysis": {
    "state": "not_affected",
    "justification": "code_not_reachable",
    "detail": "Vulnerable parser entrypoint is never invoked; only the
      signing helper from this library is linked."
  },
  "affects": [{ "ref": "pkg:golang/example.com/parser@1.2.3" }]
},
{
  "id": "CVE-2026-20202",
  "source": { "name": "NVD",
    "url": "https://nvd.nist.gov/vuln/detail/CVE-2026-20202" },
  "analysis": {
    "state": "exploitable",
    "response": ["workaround_available", "update"],
    "detail": "Vendor fix ETA exceeds the VER deadline. Perimeter WAF
      virtual patch deployed and egress restricted; tracked for
      update on vendor release."
  },
  "affects": [{ "ref": "pkg:deb/debian/libxyz@2.1.0-1" }]
}
]
}

```

6 Distribution and retrieval over OCI

For containerized workloads the disposition artifact SHOULD travel with the image it describes. CycloneDX documents have a defined media type and can be stored as OCI artifacts in the same registry as the image and associated with it through the registry's referencers/attestation mechanism. A scanner that already pulls an image to detect vulnerabilities can, in the same pass, resolve the image's attached VEX and apply the dispositions automatically — so the *a posteriori* judgment, once made and signed, is rediscovered and reused on every subsequent scan without re-litigation. This keeps disposition co-located with the artifact under evaluation, versioned with it, and verifiable by signature, and folds it natively into the existing detection workflow rather than bolting on a side channel.

7 Optional interoperability: CycloneDX to CISA labels

A FedRAMP-facing report needs nothing beyond the above. Some downstream consumers — agency tooling, or a CSAF advisory pipeline — speak CISA's narrower status-justification vocabulary instead. CISA, like CycloneDX, separates the two axes: each CycloneDX **state** coarsens onto a CISA *status* and each **justification** onto a CISA *justification label*, in both cases without loss of safety (the mapping only ever generalizes; it never invents a stronger claim). This crosswalk is OPTIONAL and exists solely for interchange.

CycloneDX justification / state	CISA label (coarsened)
code_not_present	vulnerable_code_not_present
code_not_reachable	vulnerable_code_not_in_execute_path
requires_configuration	vulnerable_code_not_in_execute_path
requires_dependency	vulnerable_code_not_in_execute_path
requires_environment	vulnerable_code_not_in_execute_path
protected_by_compiler	inline_mitigations_already_exist
protected_at_runtime	inline_mitigations_already_exist
protected_at_perimeter	inline_mitigations_already_exist
protected_by_mitigating_control	inline_mitigations_already_exist
state: not_affected	not_affected (paired with the justification above as the CISA label)
state: false_positive	not_affected (component_not_present where the component is truly absent)
state: in_triage	under_investigation
state: exploitable	affected
state: resolved / resolved_with_pedigree	fixed

Table 4: Optional coarsening of CycloneDX dispositions onto CISA’s labels/statuses.

8 Standing and adoption

CycloneDX introduced its vulnerability and VEX capabilities in version 1.4 (January 2022), ahead of CISA’s status-justification guidance (June 2022); its richer vocabulary is thus an independent, earlier design rather than a divergence from a later one. CycloneDX is now an Ecma International standard (ECMA-424). Adoption is additive: the disposition layer sits on top of the unchanged scoring pipeline of the method memo, joined by CVE and component, and a provider MAY emit the optional CISA crosswalk for consumers that require it. As with the method’s archetype catalog, this profile is offered as a workable existence proof, not as a new FedRAMP standard — the choice of carrier remains the provider’s.