

Numerical simulation of compressible flows with immersed boundaries using Discontinuous Galerkin methods

Bachelorarbeit von Simone Katharina Stange
January 7, 2016



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Fachbereich Maschinenbau

Simone Katharina Stange
Matrikelnummer: 2012232
Studiengang: B.Sc. Computational Engineering

Bachelorarbeit

Thema: Numerical simulation of compressible flows with immersed boundaries using Discontinuous Galerkin methods

Eingereicht: January 7, 2016

Betreuer: Dr.-Ing. Björn Müller

Prof. Dr.-Ing. Martin Oberlack
Fachgebiet für Strömungsdynamik
Fachbereich Maschinenbau
Technische Universität Darmstadt
Otto-Berndt-Str. 2
64287 Darmstadt

Abstract

Informationen zu Inhalten der Zusammenfassung entnehmen Sie bitte Kapitel 6.1 des Skripts zur Veranstaltung *Wissenschaftliches Arbeiten und Schreiben für Maschinenbau-Studierende*.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

– Abstract –

Informationen zu Inhalten des Abstracts entnehmen Sie bitte Kapitel 6.1 des Skripts zur Veranstaltung "Wissenschaftliches Arbeiten und Schreiben für Maschinenbau-Studierende".

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egetas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Contents

1. Motivation	1
2. Fundamentals	2
2.1. Essential equations	2
2.1.1. Equations of State	2
2.1.2. Ideal Gas Law	2
2.1.3. Navier-Stokes Equations	3
2.2. Dimensionless Measures	4
2.2.1. Non-dimensional Ideal Gas Law	4
2.2.2. Dimensionless Navier-Stokes Equation	5
3. The Runge-Kutta Discontinuous Galerkin Method	6
3.1. DG space discretization	6
3.1.1. Weak formulation	6
3.1.2. Numerical fluxes	7
3.2. RK time discretization	8
4. Immersed Boundaries	12
4.1. The DG Scheme with Immersed Boundaries	12
4.2. RK Time Discretization with Immersed Boundaries	13
4.3. Cell Agglomeration	13
5. Parametric study of a flow around a cylinder	14
5.1. Robustness study	14
5.2. Convergence study of mesh size and polynomial degree	16
6. The viscous cylinder	18
6.1. Theory	18
6.1.1. The Laminar Steady Regime	19
6.1.2. Laminar Vortex Shedding	19
6.2. Simulations	19
6.2.1. Steady State Simulations ($Re < 40 - 50$)	19
6.2.2. Unsteady Simulations ($Re > 40 - 50$)	20
7. Discussion	21
8. Ehrenwörtliche Erklärung	VI
9. Declaration of Academic Integrity	VII
List of Figures	VIII

List of Tables	IX
-----------------------	-----------

A. Anhang	XI
------------------	-----------

A.1. Ein Anhang	XI
A.1.1. Teil eines Anhangs	XI
A.1.2. Noch ein Teil eines Anhangs	XI
A.2. Noch ein Anhang	XI
A.2.1. Teil des weiteren Anhangs	XI
A.2.2. Noch ein Teil des weiteren Anhangs	XII



1 Motivation

2 Fundamentals

2.1 Essential equations

In the following we will introduce the essential equations that form the basis of all results discussed in this thesis.

2.1.1 Equations of State

First, I will enumerate the basic thermodynamic equations of state that describe the relations between the specific inner energy e , the local temperature T , the specific enthalpy \bar{h} , the pressure $p = p(\rho, e)$, the density ρ and the specific entropy s . Assuming that all material parameters are constant, we receive

$$e = c_v T \quad (2.1)$$

$$\bar{h} = c_p T = e + \frac{p}{\rho} \quad (2.2)$$

with the material parameters c_p and c_v as specific heat capacities at constant pressure and volume, respectively. Using these relations, we can define the heat capacity ratio

$$\gamma = \frac{c_p}{c_v} = \frac{\bar{h}}{e}. \quad (2.3)$$

As we will only be modelling standard air in this thesis, we will use $\gamma = 1.4$.

Another essential equation is the relation for the specific entropy

$$T ds = de + p d\rho^{-1}. \quad (2.4)$$

2.1.2 Ideal Gas Law

The equations of state mentioned above are not yet complete as there is missing a law for the pressure $p = p(\rho, e)$. In this thesis we will confine ourselves to the ideal gas law for we are only

modelling standard air.

The ideal gas law is defined as

$$p = (\gamma - 1)\rho e \quad (2.5)$$

with $\rho e \in \mathbb{R}^+$ denoting the inner energy.

The speed of sound is defined as

$$a = \sqrt{\left. \frac{\partial p}{\partial \rho} \right|_s}. \quad (2.6)$$

Using this definition combined with the ideal gas law and an equation for the change of entropy as can be read in [Mueller.2014] leads to the useful relations

$$a^2 = \gamma \frac{p}{\rho} \quad (2.7)$$

$$\frac{p}{\rho^\gamma} = \text{const.} \quad (2.8)$$

2.1.3 Navier-Stokes Equations

The compressible Navier-Stokes equations (CNS) in conservative forms read as

$$\frac{\partial \mathbf{U}}{\partial t} + \frac{\partial \mathbf{F}_i^c(\mathbf{U})}{\partial x_i} - \frac{\partial \mathbf{F}_i^v(\mathbf{U}, \nabla \mathbf{U})}{\partial x_i} = \mathbf{B}, \quad (2.9)$$

with the denotations \mathbf{U} as the conserved flow variables, \mathbf{F}_i^c and \mathbf{F}_i^v as the convective and viscous fluxes and \mathbf{B} as source terms:

$$\mathbf{U} = \begin{pmatrix} \rho \\ \rho v_j \end{pmatrix}, \quad \mathbf{F}_i^c = \begin{pmatrix} \rho v_i \\ \rho v_i v_j + p \delta_{ij} \\ v_i(\rho E + p) \end{pmatrix}, \quad \mathbf{F}_i^v = \begin{pmatrix} 0 \\ \tau_{ij} \\ \tau_{ij} + q_i \end{pmatrix}, \quad \mathbf{B} = \begin{pmatrix} 0 \\ \rho F_j \\ \rho F_j v_j + Q_i \end{pmatrix}. \quad (2.10)$$

In addition to the denotations in 2.1.1 we have F_j as body forces, Q_i as heat sources, the viscous stress tensor

$$\tau_{ij} = \mu \left[\left(\frac{\partial v_i}{\partial x_j} + \frac{\partial v_j}{\partial x_i} \right) - \frac{2}{3} \frac{\partial v_k}{\partial x_k} \delta_{ij} \right] \quad (2.11)$$

with the dynamic viscosity μ and the heat flux q_i modelled using Fourier's Law

$$q_i = k \frac{\partial T}{\partial x_i}. \quad (2.12)$$

Euler Equations

Regarding only compressible inviscid flow, the viscous fluxes and the source terms dissolve ($\mathbf{F}_i^v = \mathbf{B} = \mathbf{0}$) and the Navier-Stokes equations simplify to

$$\frac{\partial \mathbf{U}}{\partial t} + \frac{\partial \mathbf{F}_x^c(\mathbf{U})}{\partial x} + \frac{\partial \mathbf{F}_y^c(\mathbf{U})}{\partial y} = 0. \quad (2.13)$$

2.2 Dimensionless Measures

Dimensionless measures are very useful @TODO: wofür benötigt asterisk

$$t^* = \frac{V_\infty}{L_\infty} \cdot t, \quad x_i^* = \frac{1}{L} \cdot x_i, \quad v_i^* = \frac{1}{V_\infty} \cdot v_i, \quad \rho^* = \frac{1}{\rho_\infty} \cdot \rho, \quad p^* = \frac{1}{\rho_\infty V_\infty^2} \cdot p, \quad (2.14)$$

$$\mu^* = \frac{1}{\mu_\infty} \cdot \mu, \quad k^* = \frac{1}{k_\infty} \cdot k, \quad T^* = \frac{R}{V_\infty^2} \cdot T, \quad F_j^* = \frac{1}{g_\infty} \cdot F_j, \quad \rho E^* = \frac{1}{\rho_\infty V_\infty^2} \cdot \rho E, \quad (2.15)$$

$$Q_i^* = \frac{L}{V_\infty^3} \cdot Q \quad (2.16)$$

The dimensionless operators

$$\frac{\partial}{\partial t} = \frac{\partial t^*}{\partial t} \frac{\partial}{\partial t^*} = \frac{V_\infty}{L} \frac{\partial}{\partial t^*}, \quad (2.17)$$

$$\frac{\partial}{\partial x_i} = \frac{\partial x_i^*}{\partial x_i} \frac{\partial}{\partial x_i^*} = \frac{1}{L} \frac{\partial}{\partial x_i^*}, \quad (2.18)$$

$$\nabla = \frac{1}{L} \nabla^* \quad (2.19)$$

2.2.1 Non-dimensional Ideal Gas Law

In order to close the system of equations we need the ideal gas law in dimensionless form:

$$p^* = \rho^*(\gamma - 1)e^* \quad (2.20)$$

$$= (\gamma - 1) \left(\rho E^* - \frac{1}{2} \rho^* \mathbf{v}^{*2} \right). \quad (2.21)$$

2.2.2 Dimensionless Navier-Stokes Equation

Using the dimensionless measures and operators and defining the dimensionless relations

$$\text{Reynolds Number } \text{Re} = \frac{\rho_\infty V_\infty L}{\mu_\infty} \propto \frac{\text{inertia forces}}{\text{viscous forces}},$$

$$\text{Froude Number } \text{Fr} = \frac{V_\infty}{\sqrt{gL}} \propto \frac{\text{body inertia}}{\text{gravitational forces}},$$

$$\text{Prandtl Number } \text{Pr} = \frac{\mu_\infty c_p}{k_\infty} \propto \frac{\text{viscous diffusion rate}}{\text{thermal diffusion rate}},$$

we receive the dimensionless Navier-Stokes equations. As they only depend on dimensionless quantities we can drop the asterisk:

$$\frac{\partial \mathbf{U}}{\partial t} + \frac{\partial \mathbf{F}_i^c(\mathbf{U})}{\partial x_i} - \frac{\partial \mathbf{F}_i^v(\mathbf{U}, \nabla \mathbf{U})}{\partial x_i} = \mathbf{B} \quad (2.22)$$

with the dimensionless fluxes

$$\mathbf{F}_i^c = \begin{pmatrix} \rho v_i \\ \rho v_i v_j + p \delta_{ij} \\ v_i(\rho E + p) \end{pmatrix}, \quad \mathbf{F}_i^v = \frac{1}{\text{Re}} \begin{pmatrix} 0 \\ \tau_{ij} \\ \tau_{ij} v_j + \frac{\gamma}{\text{Pr}(\gamma - 1)} q_i \end{pmatrix}, \quad \mathbf{B} = \frac{1}{\text{Fr}^2} \begin{pmatrix} 0 \\ \rho F_j \\ \rho F_j v_j \end{pmatrix} + \begin{pmatrix} 0 \\ 0 \\ Q_j \end{pmatrix}. \quad (2.23)$$

3 The Runge-Kutta Discontinuous Galerkin Method

This thesis deals with a software that uses a Runge-Kutta Discontinuous Galerkin (RKDG) method for the numerical approximation of compressible flows. The RKDG method is split into the DG method for space discretization and the RK method as an explicit time discretization. By using an explicit time-marching algorithm, the parallelization is made much easier.

In the following sections we will study the DG and RK methods separately considering simple examples and using the same notation as in [Mueller.2014].

3.1 DG space discretization

First, we will study the Discontinuous Galerkin method which can be seen as combination of the Finite Volume and the Finite Element method.

As a simple example we will consider the scalar conservation law

$$\frac{\partial c}{\partial t} + \nabla \cdot \mathbf{f}(c) = 0 \quad (3.1)$$

for the concentration $c = c(\mathbf{x}, t)$ with $\vec{x} \in \Omega \subset \mathbb{R}^D$ and $t \in \mathbb{R}_0^+$ and a smooth function $\mathbf{f} : \mathbb{R} \rightarrow \mathbb{R}^D$ that also contains suitable initial and boundary conditions. [Mueller.2014]

3.1.1 Weak formulation

Our first step of the DG method will be transferring the partial differential equation (3.1) into a weak formulation. Priorly to this we need a discretization Ω_h of Ω consisting of a tessellation of cells $\{\mathcal{K}_i\}_{i=1,\dots,N}$, where h represents a measure for the size of the cells. Each cell \mathcal{K}_i is of dimension D with an outward unit normal vector \mathbf{n} .

After having discretized our geometry, we now need a set of cell-local test functions $\{\Phi_{i,j}\}_{j=1,\dots,M}$ with $\Phi_{i,j} = \Phi_{i,j}(\mathbf{x}) : \mathbb{R}^D \rightarrow \mathbb{R}$ that forms the basis of polynomials $P_{\mathcal{K}_i}(P)$ with the maximum degree P .

In order to obtain the weak formulation we will now multiply equation (3.1) by $\Phi_{i,j}$, integrate over a cell \mathcal{K}_i and then integrate by parts:

$$\begin{aligned}
\frac{\partial c}{\partial t} + \nabla \cdot \mathbf{f}(c) &= 0 \\
\frac{\partial c}{\partial t} \Phi_{i,j} + \nabla \cdot \mathbf{f}(c) \Phi_{i,j} &= 0 \\
\int_{\mathcal{K}_i} \frac{\partial c}{\partial t} \Phi_{i,j} dV + \int_{\mathcal{K}_i} \nabla \cdot \mathbf{f}(c) \Phi_{i,j} dV &= 0 \\
\int_{\mathcal{K}_i} \frac{\partial c}{\partial t} \Phi_{i,j} dV + \int_{\partial \mathcal{K}_i} (\mathbf{f}(c) \cdot \mathbf{n}) \Phi_{i,j} dA - \int_{\mathcal{K}_i} \mathbf{f}(c) \nabla \Phi_{i,j} dV &= 0.
\end{aligned}$$

Considering that the cell's surface $\partial \mathcal{K}_i$ consists of internal or boundary edges $\{\mathcal{E}_{i,e}\}_{e=1,\dots,E_i}$ we can rewrite the equation as

$$\int_{\mathcal{K}_i} \frac{\partial c}{\partial t} \Phi_{i,j} dV + \sum_{e=1}^{E_i} \int_{\mathcal{E}_{i,e}} (\mathbf{f}(c) \cdot \mathbf{n}) \Phi_{i,j} dA - \int_{\mathcal{K}_i} \mathbf{f}(c) \nabla \Phi_{i,j} dV = 0. \quad (3.2)$$

3.1.2 Numerical fluxes

As the concentration c is unknown, we need to introduce a modal approximation

$$c(\mathbf{x}, t) |_{\mathcal{K}_i} \approx \bar{c}(\mathbf{x}, t) |_{\mathcal{K}_i} = c_i(x, t) = \sum_{k=0}^M c_{i,k}(t) \Phi_{i,k}(\mathbf{x}) \quad (3.3)$$

with the Galerkin approach of identical Ansatz and test functions. For we do not enforce continuity on $\mathcal{E}_{i,e}$ and thus

$$c_i |_{\mathcal{E}_{i,e}} =: c^- \neq c^+ := c_{n(i,e)} |_{\mathcal{E}_{i,e}} \quad (3.4)$$

we cannot simply insert the approximation into equation (3.2). Therefore we will introduce a monotone, Lipschitz continuous numerical flux function $f = f(c^-, c^+, \mathbf{n}) : \mathbb{R}^{D+2} \rightarrow \mathbb{R}$ satisfying the consistency property

$$f(c^-, c^+, \mathbf{n}) = -f(c^-, c^+, -\mathbf{n}). \quad (3.5)$$

By including these definitions into (3.2) we receive

$$\int_{\mathcal{K}_i} \frac{\partial c_i}{\partial t} \Phi_{i,j} dV + \underbrace{\sum_{e=1}^{E_i} \int_{\mathcal{C}_{i,e}} f(c^-, c^+, \mathbf{n}) \Phi_{i,j} dA - \int_{\mathcal{K}_i} \mathbf{f}(c_i) \cdot \nabla \Phi_{i,j} dV}_{=:(\mathbf{f}_i)_j} = 0 \quad (3.6)$$

with the discrete operator $\mathbf{f}_i = \mathbf{f}_i(t, \mathbf{c}_i) \in \mathbb{R}$.

Some well-known examples of numerical fluxes contain [Cockburn]:

- The Godunov flux
- The Engquist-Osher flux
- The Lax-Friedrichs flux
- The local Lax-Friedrichs flux
- The Roe flux with 'entropy flux',

whereby we will attend to the local Lax-Friedrichs or Rusanov flux, which is defined as

$$f(c^-, c^+, \mathbf{n}) = \frac{\mathbf{f}(c^-) + \mathbf{f}(c^+)}{2} \cdot \mathbf{n} - \frac{C_R}{2} (c^+ - c^-) \quad (3.7)$$

with the coefficient C_R based on a local stability criterion. In this thesis we will use an estimate based on the maximum local wave speed

$$C_R = \max(|\mathbf{u}^+ \cdot \mathbf{n}| + a^-, |\mathbf{u}^- \cdot \mathbf{n}| + a^+) \quad (3.8)$$

with u^\pm and a^\pm denoting the normal velocity and the local speed of sound at the edges. As the Rusanov flux has a high stability it will be used disregarding that it is prone to numerical diffusion.

3.2 RK time discretization

For we have studied the spatial discretization, we will now attend to the time discretization, using the Runge-Kutta method.

First of all, we need to reformulate equation (3.6) in order to achieve a system of coupled ODEs.

$$\int_{\mathcal{K}_i} \frac{\partial c_i}{\partial t} \Phi_{i,j} dV + \underbrace{\sum_{e=1}^{E_i} \int_{\mathcal{C}_{i,e}} f(c^-, c^+, \mathbf{n}) \Phi_{i,j} dA - \int_{\mathcal{K}_i} \mathbf{f}(c_i) \cdot \nabla \Phi_{i,j} dV}_{=:(\mathbf{f}_i)_j} = 0.$$

The first term of the equation above can be reformulated as

$$\begin{aligned} \int_{\mathcal{K}_i} \frac{\partial c_i}{\partial t} \Phi_{i,j} dV &= \int_{\mathcal{K}_i} \frac{\partial}{\partial t} \left(\sum_{k=0}^M c_{i,k}(t) \Phi_{i,k}(\mathbf{x}) \right) \Phi_{i,j} dV \\ &= \sum_{k=0}^M \frac{\partial c_{i,k}}{\partial t} \underbrace{\int_{\mathcal{K}_i} \Phi_{i,k} \Phi_{i,j} dV}_{=:(\mathbf{M}_i)_{k,j}} \\ &= \mathbf{M}_i \frac{\partial \mathbf{c}_i}{\partial t} \end{aligned}$$

thus leading to

$$\mathbf{M}_i \frac{\partial \mathbf{c}_i}{\partial t} + \mathbf{f}_i = 0 \quad (3.9)$$

with $\mathbf{M}_i \in \mathbb{R}^{M,M}$ being a cell-local symmetric mass matrix associated with \mathcal{K}_i . As we have assumed an orthonormal basis $\{\Phi_{i,j}\}_{j=1,\dots,M}$ thus reducing the mass matrix to the identity matrix I , the ODEs simplify to

$$\frac{\partial \mathbf{c}_i}{\partial t} + \mathbf{M}_i^{-1} \mathbf{f}_i = 0 \quad (3.10)$$

$$\frac{\partial \mathbf{c}_i}{\partial t} + \mathbf{f}_i = 0. \quad (3.11)$$

Using an explicit RK method of Order S we can now advance this system of ODEs and calculate the new coefficients from

$$\mathbf{c}_i(t_1) = \mathbf{c}_i(t_0) - \Delta t \sum_{s=1}^S (\alpha)_s \mathbf{k}_s, \quad (3.12)$$

with a known solution at t_0 to a new instant t_1 and $\Delta t = t_1 - t_0$, where

$$\mathbf{k}_s = \mathbf{f}_i \left(t_0 + (\beta)_s \Delta t, \mathbf{c}_i(t_0) + \Delta t \sum_{t=1}^s (\Gamma)_{s,t} \mathbf{k}_t \right). \quad (3.13)$$

The coefficients $\alpha \in \mathbb{R}^S$, $\beta \in \mathbb{R}^S$ and $\Gamma \in \mathbb{R}^S$ are specific for each RK method. The coefficients of the most common RK methods are displayed in the Butcher Tableaus in 3.2. They determine the stability and accuracy of the time integration scheme.

0					
β_2	Γ_{21}				
β_3	Γ_{31}	Γ_{32}			
\vdots	\vdots	\vdots	\ddots		
β_s	Γ_{s1}	Γ_{s2}	\cdots	$\Gamma_{s,s-1}$	
<hr/>					
	α_1	α_2	\cdots	α_{s-1}	α_s

Table 3.1.: Butcher tableau for the explicit RungeKutta method.

A well-known stability criterion according the explicit Euler time discretization for linear, hyperbolic PDEs, namely the Courant-Friedrichs-Lewy (CFL) criterion, restrains the temporal step-size Δt :

$$\Delta t \leq c_{CFL} \frac{h}{\underline{u}} \quad (3.14)$$

with $\underline{u} \in \mathbb{R}^+$ denoting the largest propagation velocity and a positive constant $c_{CFL} \leq 1$ depending on the applied spatial discretization procedure.

<table><tr><td>0</td><td></td></tr><tr><td></td><td>1</td></tr></table> <p>(a) Explicit Euler (first order)</p>	0			1	<table><tr><td>0</td><td></td><td></td></tr><tr><td>1</td><td>1</td><td></td></tr><tr><td></td><td>$\frac{1}{2}$</td><td>$\frac{1}{2}$</td></tr></table> <p>(b) Trapezoidal rule (second order)</p>	0			1	1			$\frac{1}{2}$	$\frac{1}{2}$	<table><tr><td>0</td><td></td><td></td><td></td></tr><tr><td>$\frac{1}{3}$</td><td>$\frac{1}{3}$</td><td></td><td></td></tr><tr><td>$\frac{2}{3}$</td><td>0</td><td>$\frac{1}{3}$</td><td></td></tr><tr><td></td><td>$\frac{1}{4}$</td><td>0</td><td>$\frac{3}{4}$</td></tr></table> <p>(c) Third order TVD (third order)</p>	0				$\frac{1}{3}$	$\frac{1}{3}$			$\frac{2}{3}$	0	$\frac{1}{3}$			$\frac{1}{4}$	0	$\frac{3}{4}$	<table><tr><td>0</td><td></td><td></td><td></td><td></td></tr><tr><td>$\frac{1}{2}$</td><td>$\frac{1}{2}$</td><td></td><td></td><td></td></tr><tr><td>$\frac{1}{2}$</td><td>0</td><td>$\frac{1}{2}$</td><td></td><td></td></tr><tr><td>1</td><td>0</td><td>0</td><td>1</td><td></td></tr><tr><td></td><td>$\frac{1}{6}$</td><td>$\frac{2}{6}$</td><td>$\frac{2}{6}$</td><td>$\frac{2}{6}$</td></tr></table> <p>(d) Classical RK (fourth order)</p>	0					$\frac{1}{2}$	$\frac{1}{2}$				$\frac{1}{2}$	0	$\frac{1}{2}$			1	0	0	1			$\frac{1}{6}$	$\frac{2}{6}$	$\frac{2}{6}$	$\frac{2}{6}$
0																																																									
	1																																																								
0																																																									
1	1																																																								
	$\frac{1}{2}$	$\frac{1}{2}$																																																							
0																																																									
$\frac{1}{3}$	$\frac{1}{3}$																																																								
$\frac{2}{3}$	0	$\frac{1}{3}$																																																							
	$\frac{1}{4}$	0	$\frac{3}{4}$																																																						
0																																																									
$\frac{1}{2}$	$\frac{1}{2}$																																																								
$\frac{1}{2}$	0	$\frac{1}{2}$																																																							
1	0	0	1																																																						
	$\frac{1}{6}$	$\frac{2}{6}$	$\frac{2}{6}$	$\frac{2}{6}$																																																					

Table 3.2.: Butcher Tableaus for different orders of RK

Concerning the Euler equations the largest propagation velocity is given by $\underline{u} = \|\mathbf{u}\| + a$ and by taking the influence of the approximation order P into account we can use

$$\Delta t \leq \frac{c_{CFL}}{2P+1} \frac{h}{\|\mathbf{u}\| + a} \quad (3.15)$$

as a sufficiently accurate estimate for the stability criterion in this thesis.

4 Immersed Boundaries

In the following chapter we will study the DG method with immersed boundaries. IBMs are characteristic in the way of creating the calculation mesh as they do not rely on body fitted grids but on a level set function φ that cuts the cells into the physical and the void region.

4.1 The DG Scheme with Immersed Boundaries

We regard an implicit representation of an immersed boundary using the level set function φ that parts the calculation area Ω_h into

the physical region $\mathcal{A} = \{\vec{x} \in \Omega_h : \varphi(\vec{x}) > 0\}$,

the void region $\mathcal{B} = \{\vec{x} \in \Omega_h : \varphi(\vec{x}) < 0\}$,

and the immersed boundary $\mathcal{I} = \{\vec{x} \in \Omega_h : \varphi(\vec{x}) = 0\}$.

In our next step we use the definitions above in 3.6 considering cell \mathcal{K}_i with the sub-domain $\mathcal{A}_i = \mathcal{K}_i \cap \mathcal{A}$ and the surface $\partial \mathcal{A}_i$. As in cut cells the surface $\partial \mathcal{A}_i$ consists not only of the edges $\{\mathcal{E}_{i,e}^{\mathcal{A}}\}_{e=1,\dots,E} = \{\mathcal{E}_{i,e} \cap \bar{\mathcal{A}}_i\}_{e=1,\dots,E}$ but also of the boundary segment $\mathcal{I}_i = \mathcal{K}_i \cap \mathcal{I}$, the discrete weak formulation using an IBM follows as

$$\int_{\mathcal{A}_i} \frac{\partial c_i}{\partial t} \Phi_{i,j} dV + \sum_{e=1}^{E_i} \int_{\mathcal{E}_{i,e}^{\mathcal{A}}} f(c^-, c^+, \mathbf{n}) \Phi_{i,j} dA + \int_{\mathcal{I}_i} f(c^-, c^+, \mathbf{n}_{\mathcal{I}}) \Phi_{i,j} dA - \int_{\mathcal{A}_i} \mathbf{f}(c_i) \cdot \nabla \Phi_{i,j} dV = 0 \quad (4.1)$$

with $\mathbf{n}_{\mathcal{I}} = -\frac{\nabla \varphi}{\|\nabla \varphi\|}$. In intersected cells the mass matrix is defined by

$$(\mathbf{M}_i)_{k,j} := \int_{\mathcal{A}_i} \Phi_{i,k} \Phi_{i,j} dV \quad (4.2)$$

and the discrete operator

$$(\mathbf{f}_i)_j := \sum_{e=1}^{E_i} \int_{\mathcal{E}_{i,e}^{\mathcal{A}}} f(c^-, c^+, \mathbf{n}) \Phi_{i,j} dA + \int_{\mathcal{I}_i} f(c^-, c^+, \mathbf{n}_{\mathcal{I}}) \Phi_{i,j} dA - \int_{\mathcal{A}_i} \mathbf{f}(c_i) \cdot \nabla \Phi_{i,j} dV. \quad (4.3)$$

The difficulty of the IBM lies in the correct evaluation of \mathcal{A}_i and \mathcal{J}_i and in the agglomeration of intersected cells with very small volume fractions

$$\text{frac}(\mathcal{A}_i) = \frac{\text{meas}(\mathcal{A}_i)}{\text{meas}(\mathcal{K}_i)} \quad (4.4)$$

as we will discuss in section 4.3.

4.2 RK Time Discretization with Immersed Boundaries

In this thesis we use only explicit Euler time discretization for immersed boundary problems:

$$\mathbf{c}_i(t_1) = \mathbf{c}_i(t_0) - \Delta t \mathbf{M}_i^{-1} \mathbf{f}_i(c). \quad (4.5)$$

Using IBMs we have to modify the stability criterion and therefore use the modified step restriction

$$\Delta t \leq \frac{c_{CFL}}{2P+1} \frac{\sqrt[p]{\text{meas}(\mathcal{A}_i)}}{\|\mathbf{u}\| + a} \quad (4.6)$$

with a strong influence of the sub-cell \mathcal{A}_i with the smallest volume.

4.3 Cell Agglomeration

As can be seen in 4.6 the time step size is strongly restricted in cell with very small volume fractions. This leads to a very long calculation process thus rendering the method impractical. Therefore we need to agglomerate those small cells to larger ones using a cell agglomeration factor $0 \leq \alpha \leq 1$

5 Parametric study of a flow around a cylinder

In the following chapter we will regard a flow at Mach 0.2 around a frictionless cylinder with adiabatic slip walls at changing parameters such as the polynomial degree, the mesh size and the position of the cylinder in order to validate Bounded Support Spectral Solver (BoSSS) with immersed boundaries concerning robustness and convergence.

5.1 Robustness study

In the first study regarding the frictionless cylinder, we compare the absolute error of entropy for a polynomial degree from 1 to 3 along a shift of the centre point of the cylinder from -0.075 to 0.075 at steps of 0.015 . By shifting the cylinder we can consider several cases where the cells would be cut differently and therefore cause different cell agglomerations. The cell agglomeration threshold is at a constant level of 0.5 in a mesh of 32×32 cells. In this example we aim at proving the robustness of the solver as for each position of the cylinder the error of entropy should not vary too much thus making it independent of the way the border cells are cut.




Figure 5.1.: Convergence Plot

As we look at the chart ??, first of all we will note that the absolute error of entropy decreases with increasing polynomial degree. As a higher polynomial degree implies a better approxima-

tion this can be explained very easily.

Secondly, we can observe that the error of entropy behaves roughly symmetrically to the ordinate. As we shifted the cylinder symmetrically this observation does not surprise us either.

Regarding the absolute error at a polynomial degree of 3, it is striking that this curve shows a much higher error difference compared to degrees 1 and 2. There are two peaks at a shift of ± 0.03 ; these discordant values were produced because the calculation stopped early. Unlike all other cases during this study, the calculation did not stop because the convergence criterion (change of error of entropy $\leq 10^{-13}$) was reached but because the CFL number got invalid.

As these two values rather count as exceptions, we now consider two cases with a degree of 2 at the shifts of -0.06 and -0.03 .




Figure 5.2.: Isolines of pressure

In figure 5.2 you can see the two mentioned cases with highlighted isolines of pressure and pseudocolored density. As only the upper half of the cylinder has been calculated, I reflected the results through the centre point of the cylinder. Therefore you can easily see that the results are not correct, as the flow before and after the obstacle should be identical. Furthermore you can see that in 5.2a the isolines are smoother than in 5.2b. In order to give an explanation for the higher error of entropy in 5.2b I highlighted the cells that should have been agglomerated in red. In the left case there are less agglomerated cells than in the right one, therefore there was a not so big agglomeration mistake made.

Except for the two discordant values at polynomial degree 3, the error of entropy changes very little for the different cases. We can therefore assume that the solver is good enough validated concerning the way the agglomerated cells influence the calculation. @TODO: cases nochmal rechnen um peaks wegzukriegen

5.2 Convergence study of mesh size and polynomial degree

In the second study we vary the mesh size of our geometry from 32×32 by 64×64 to 128×128 cells. Additionally we also vary the polynomial degree from 0 to 4, consequently regarding fifteen cases in total.

Our aim is the verification of the convergence of the RKDGM based solver for the inviscid cylinder. Therefore we hope to achieve an experimental order of convergence that is near the optimal rate $O(h^{P+1})$. In chart ?? I compared the absolute error entropy to the mesh size logarithmically for each polynomial degree.




Figure 5.3.: Convergence Plot

As you can see in ?? each graph has a more or less constant gradient that is higher with increasing polynomial degree which is approximately of the order $P+1$ as we hoped. Regarding the values of the 128×128 mesh there are two discordant values: the case with mesh size 128×128 and polynomial degree $P=4$ did not terminate due to the error of entropy residual but because the CFL number could not be determined and therefore no value for the error of entropy was computed. The case for $P=3$ has a disproportionately high value that is caused by two cells as can be seen in 5.4b. In order to correct the value I changed the *node count safety factor* from 2 to 5 which increases the robustness and therefore lets the calculation finish due to the residual. In 5.4 you can see the visualised flow of the inspected case with the critical spot where entropy is produced in 5.4b and the flow after the correction in 5.4c. Please remark that differently coloured entropy ranges had to be used in the two cases in order to point out the critical cell in 5.4b.




Figure 5.4.: Mesh size 128×128 , $P = 3$

Concluding, we remark that the convergence behaves as desired with an order close to the optimal rate of $O(h^{P+1})$. Nevertheless to receive the correct result it should always be guaranteed that the calculation stops due to the residual rather than illegal values for momentum even if that means heightening the overall runtime by increasing the node count safety factor thus robustness.

6 The viscous cylinder

The flow around a viscous cylinder has been approached by many papers both analytically [@TODO: wirklich?](#) and numerically, e.g. [@TODO: literatur](#), though very few numerical approaches use a Runge-Kutta Discontinuous Galerkin (RKDG) method combined with immersed boundaries. In order to verify the BoSSS code with immersed boundaries not only for the Euler equations as we did in 5 but also for the viscous case we will now consider different Reynolds numbers for the steady and unsteady flow and compare our results to those of other studies.

6.1 Theory

The flow around a viscous cylinder can be divided in different sections depending on the Reynolds number. The first section applies for a Reynolds number $0 < Re < 40 - 50$ characterised by a laminar steady flow. In that regime a recirculation region with two symmetric vortices with opposite directions is comprised by the wake. The flow can be described using the wake separation length W^* .

The second section contains all other Reynolds number $Re > 40 - 50$ and thus describes




Figure 6.1.: Overview of Base Suction Coefficients over Reynolds Number [@TODO: Quelle](#)

the unsteady flow. It can be subdivided in several subsections:

$40 - 50 < Re < 190$ laminar vortex shedding,

$190 < Re < 260$ 3-D wake-transition regime,


$260 < Re < 1000$ increasing disorder in the fine-scale three dimensionalities,

$1000 < Re < 200000$ shear layer transition regime,

$200000 < Re$ critical transition, supercritical regime and post-critical regime.

As we will only discuss Reynolds numbers up to $Re < 200$ the important phases for us are the laminar steady regime and the laminar vortex shedding. At around $Re = 190$ the three dimensionality of the system has a incrementing influence on the flow; for we only analyse the 2-D model of the experiment we stop at $Re = 200$ expecting slight deflection in our results.


6.1.1 The Laminar Steady Regime



STEADY WAKE

Figure 6.2.: Recirculation Region @TODO: Quelle

6.1.2 Laminar Vortex Shedding



UNSTEADY WAKE

Figure 6.3.: Karmán Vortex Street @TODO: Quelle

6.2 Simulations

In this section we will compare the lift and drag coefficients at different Reynolds numbers and mesh sizes at a constant agglomeration threshold of 0.3 and a polynomial degree of 1.

6.2.1 Steady State Simulations ($Re < 40 - 50$)

Simulation at Reynolds Number 10

Simulation at Reynolds Number 20

Simulation at Reynolds Number 40

6.2.2 Unsteady Simulations ($Re > 40 - 50$)

Simulation at Reynolds Number 100

Simulation at Reynolds Number 200

7 Discussion

8 Ehrenwörtliche Erklärung

Erklärung zur Abschlussarbeit gemäss § 22 Abs. 7 APB der TU Darmstadt

Hiermit versichere ich, Muster Mustermann, die vorliegende Master-Thesis / Bachelor-Thesis ohne Hilfe Dritter und nur mit den angegebenen Quellen und Hilfsmitteln angefertigt zu haben. Alle Stellen, die Quellen entnommen wurden, sind als solche kenntlich gemacht worden. Diese Arbeit hat in gleicher oder ähnlicher Form noch keiner Prüfungsbehörde vorgelegen. In der abgegebenen Thesis stimmen die schriftliche und elektronische Fassung überein.

Datum:

Unterschrift:

9 Declaration of Academic Integrity

Thesis Statement pursuant to § 22 paragraph 7 of APB TU Darmstadt

I herewith formally declare that I have written the submitted thesis independently. I did not use any outside support except for the quoted literature and other sources mentioned in the paper. I clearly marked and separately listed all of the literature and all of the other sources which I employed when producing this academic work, either literally or in content. This thesis has not been handed in or published before in the same or similar form.

In the submitted thesis the written copies and the electronic version are identical in content.

Date:

Signature:

List of Figures

5.1. Convergence Plot	14
5.2. Isolines of pressure	15
5.3. Convergence Plot	16
5.4. Mesh size 128×128 , $P = 3$	17
6.1. Overview of Base Suction Coefficients over Reynolds Number @TODO: Quelle . .	18
6.2. Recirculation Region @TODO: Quelle	19
6.3. Karmán Vortex Street @TODO: Quelle	19

List of Tables

3.1. Butcher tableau for the explicit RungeKutta method.	10
3.2. Butcher Tableaus for different orders of RK	10



A Anhang

A.1 Ein Anhang

Hier gibt es etwas zu sagen oder auch nicht.

A.1.1 Teil eines Anhangs

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A.1.2 Noch ein Teil eines Anhangs

- First itemtext
- Second itemtext
- Last itemtext
- First itemtext
- Second itemtext

A.2 Noch ein Anhang

Hier gibt es etwas zu sagen oder auch nicht.

A.2.1 Teil des weiteren Anhangs

1. First itemtext

2. Second itemtext

3. Last itemtext

4. First itemtext

5. Second itemtext

A.2.2 Noch ein Teil des weiteren Anhangs

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

$$\bar{x} = \frac{1}{n} \sum_{i=1}^{i=n} x_i = \frac{x_1 + x_2 + \dots + x_n}{n}$$

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

$$\int_0^\infty e^{-\alpha x^2} dx = \frac{1}{2} \sqrt{\int_{-\infty}^\infty e^{-\alpha x^2} dx} \int_{-\infty}^\infty e^{-\alpha y^2} dy = \frac{1}{2} \sqrt{\frac{\pi}{\alpha}}$$

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet

aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

$$\sum_{k=0}^{\infty} a_0 q^k = \lim_{n \rightarrow \infty} \sum_{k=0}^n a_0 q^k = \lim_{n \rightarrow \infty} a_0 \frac{1 - q^{n+1}}{1 - q} = \frac{a_0}{1 - q}$$

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

$$x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a} = \frac{-p \pm \sqrt{p^2 - 4q}}{2}$$

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

$$\frac{\partial^2 \Phi}{\partial x^2} + \frac{\partial^2 \Phi}{\partial y^2} + \frac{\partial^2 \Phi}{\partial z^2} = \frac{1}{c^2} \frac{\partial^2 \Phi}{\partial t^2}$$

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.