

# Pylightnix

Sergey Mironov

February 2021

## Abstract

Pylightnix is a minimalistic Python library for managing filesystem-based immutable data objects, inspired by Purely Functional Software Deployment Model thesis by Eelco Dolstra and the Nix package manager.

The library may be thought as of low-level API for creating caching wrappers for a subset of Python functions. In particular, Pylightnix allows user to

- Prepare (or, in our terms, **instantiate**) the computation plan aimed at creating a tree of linked immutable stage objects, stored in the filesystem.
- Implement (**realize**) the prepared computation plan, access the resulting artifacts. Pylightnix is able to handle **non-deterministic** results of the computation. As one example, it is possible to define a stage depending on best top-10 instances (in a user-defined sense) of prerequisite stages.
- Handle changes in the computation plan, re-use the existing artifacts whenever possible.
- Gain full control over all aspects of the cached data including the garbage-collection.

# Contents

<b>1</b>	<b>Quick start</b>	<b>2</b>
1.1	The problem . . . . .	2
1.2	Stages basics . . . . .	2
1.2.1	Parameter stage . . . . .	2
1.2.2	Annealing stage . . . . .	3
1.2.3	Plotting stage . . . . .	4
1.2.4	Running the experiment . . . . .	4
1.3	Nested stages . . . . .	4
1.4	Collaborative work . . . . .	5
1.5	Synchronization . . . . .	5

## 1 Quick start

We illustrate Pylighnix principles by showing how to use it for making a mock data science task. We'll follow the SciPy anneal example but imagine that we want to save some intermediate results and also that there are several people working on this task.

We start by importing the required Python modules.

---

```
1 import numpy as np
2 import scipy.optimize as o
3 import matplotlib.pyplot as plt
4
5 from pylighnix import *
```

---

### 1.1 The problem

The problem begins with defining a parametric function **f** for which we need to find an approximate minimum by running the simulated annealing algorithm.

---

```
1 def f(z, *params):
2     x, y = z
3     a, b, c, d, e, f, g, h, i, j, k, l, scale = params
4     return (a * x**2 + b * x * y + c * y**2 + d*x + e*y + f) + \
5           (-g*np.exp(-(x-h)**2 + (y-i)**2) / scale)) + \
6           (-j*np.exp(-(x-k)**2 + (y-l)**2) / scale))
```

---

### 1.2 Stages basics

Suppose we are to get the **f**'s parameters from elsewhere and that we want to get the following results: (a) the parameters themselves (b) the result of the annealing simulation and (c) a visual plot of the result.

#### 1.2.1 Parameter stage

Pylighnix Stage is a Python function that registers a user-defined action in the Manager and returns a DRef reference stating that the action is accepted.

---

```

1 def stage_params(m:Manager)->DRef:
2     def _config():
3         name = 'params'
4         out = [selfref, "params.npy"]
5         return locals()
6     def _make(b:Build):
7         np.save(mklens(b).out.syspath, (2, 3, 7, 8, 9, 10, 44, -1, 2, 26, 1,
8             ↪ -2, 0.5))
9     return mkdrv(m, mkconfig(_config()), match_only(), build_wrapper(_make))

```

---

Here, a user-defined action `_make` goes to Pylightnix by calling the `mkdrv` with the Manager and the following three arguments: (a) the set of prerequisites for the action; (b) the Matcher callback function; (c) the action itself that takes a Build context as an argument. In this example we are pretending to receive input parameters from a thirdparty. We could just as well have downloaded them from the Internet using a pre-defined stage `fetchurl`.

A few notes on the above code:

- We define configuration object by reading a local variables of a helper function named `_config()`. The resulting dictionary should match the Config requirements. As is often the case in Pylightnix, we use a standalone `mkconfig` constructor rather than create the object directly.
- We promise to produce an artifact named `out` by specifying its `selfref` path. Pylightnix will throw an error if it does not find such an artifact after the build action completes.
- When inside the build action, we refer to the pylightnix config items by using the `mklens` swiss knife function. `mklens` returns the Lens object which has an overloaded dot `"."` operator. The middle part of the lens expression encodes the path in the configuration and the last word `"syspath"` encodes the format of the expression result.
- We pass a `match_only()` matcher in the third argument of `mkdrv`. By this we say that we expect our action to return a deterministic result. Later we will see how to deal with non-deterministic actions.

### 1.2.2 Annealing stage

---

```

1 def stage_anneal(m:Manager, ref_params:DRef)->DRef:
2     def _config():
3         name = 'anneal'
4         nonlocal ref_params
5         trace_xs = [selfref, 'tracex.npy']
6         trace_fs = [selfref, 'tracef.npy']
7         out = [selfref, 'result.npy']
8         return locals()
9     def _make(b:Build):
10        params = np.load(mklens(b).ref_params.out.syspath)
11        xs = []; fs = []
12        def _trace(x,f,ctx):
13            nonlocal xs,fs

```

```

14     xs.append(x.tolist())
15     fs.append(f)
16     res = o.dual_annealing(f, [[-10,10],[-10,10]],
17                           x0=[2.,2.],args=params,
18                           maxiter=500, callback=_trace)
19     np.save(mklens(b).trace_xs.syspath, np.array(xs))
20     np.save(mklens(b).trace_fs.syspath, np.array(fs))
21     np.save(mklens(b).out.syspath, res['x'])
22     return mkdrv(m, mkconfig(_config()), match_only(), build_wrapper(_make))

```

---

### 1.2.3 Plotting stage

---

```

1 def stage_plot(m:Manager, ref_anneal:DRef)->DRef:
2     def _config():
3         name = 'plot'
4         nonlocal ref_anneal
5         out = [selfref, 'plot.png']
6         return locals()
7     def _make(b:Build):
8         xs=np.load(mklens(b).ref_anneal.trace_xs.syspath)
9         fs=np.load(mklens(b).ref_anneal.trace_fs.syspath)
10        res=np.load(mklens(b).ref_anneal.out.syspath)
11        plt.figure()
12        plt.title(f"Min {fs[-1]}, found at {res}")
13        plt.plot(range(len(fs)),fs)
14        plt.grid(True)
15        plt.savefig(mklens(b).out.syspath)
16    return mkdrv(m, mkconfig(_config()), match_latest(),
17               ↪ build_wrapper(_make))

```

---

### 1.2.4 Running the experiment

To run the experiment we register all the stages in the internal manager by calling `instantiate_inplace` and ask Pylighnix to provide us with the realization reference by calling `realize_inplace`.

```

1 ds=instantiate_inplace(stage_params)
2 cl=instantiate_inplace(stage_anneal,ds)
3 vis=instantiate_inplace(stage_plot,cl)
4 rref=realize_inplace(vis)
5 print(rref)

```

---

```
rref:cb252162ae8a0fe2c90fe48193f851f8-ff1dd5c155ee3faa445572e3246f0566-plot
```

## 1.3 Nested stages

In the previous sections we implicitly used a global Manager to register stages. To eliminate side-effects associated with the usage of a global object, we now define an umbrella stage covering the whole experiment.

---

```

1 def stage_all(m:Manager):
2     ds=stage_params(m)
3     cl=stage_anneal(m,ds)
4     vis=stage_plot(m,cl)
5     return vis

```

---

Now we can use reentrant `instantiate` and `realize` functions which rely on a temporary local Manager, disposing it before returning the result.

---

```

1 rref_all=realize(instantiate(stage_all))
2 assert rref_all==rref
3 print(rref_all)

```

---

```
rref:cb252162ae8a0fe2c90fe48193f851f8-ff1dd5c155ee3faa445572e3246f0566-plot
```

## 1.4 Collaborative work

Alice and Bob runs the same experiment using their machines. We model this situation by running Pylighnix with different storage settings.

---

```

1 Sa=mksettings('_storageA')
2 Sb=mksettings('_storageB')
3 fsinit(Sa,remove_existing=True)
4 fsinit(Sb,remove_existing=True)
5 rrefA=realize(instantiate(stage_all, S=Sa))
6 rrefB=realize(instantiate(stage_all, S=Sb))
7 print(rrefA)
8 print(rrefB)

```

---

Our annealing problem is stochastic by nature so the results naturally differ.

## 1.5 Synchronization

Alice sends her results to Bob, so he faces a problem of picking the best realizaion.

---

```

1 print("Bob's storage before the sync:")
2 for rref in allrrefs(S=Sb):
3     print(rref)
4 arch=Path('archive.zip')
5 pack([rrefA], arch, S=Sa)
6 # Alice transfers archive to Bob using her favorite pigeon post service.
7 unpack(arch, S=Sb)
8 print("Bob's storage after the sync:")
9 for rref in allrrefs(S=Sb):
10     print(rref)

```

---

```
Bob's storage before the sync:
rref:6f906ca9ad8d9b128c57ed0df95ab899-7c308bad0e7fa364790b71e6ffab924a-params
rref:e311af9ddcd9c443c6971e0037008b83-aeab4bea649e22497b49dfc1ec5ebedf-anneal
rref:f82e8d998cacb395759d582f1be63a16-ff1dd5c155ee3faa445572e3246f0566-plot
Bob's storage after the sync:
rref:6f906ca9ad8d9b128c57ed0df95ab899-7c308bad0e7fa364790b71e6ffab924a-params
rref:e311af9ddcd9c443c6971e0037008b83-aeab4bea649e22497b49dfc1ec5ebedf-anneal
rref:8f09667e399b8a312e2d7d442881ad4e-aeab4bea649e22497b49dfc1ec5ebedf-anneal
rref:97791a02fe07916bfb0cd795255d5a8f-ff1dd5c155ee3faa445572e3246f0566-plot
rref:f82e8d998cacb395759d582f1be63a16-ff1dd5c155ee3faa445572e3246f0566-plot
```

Bob writes a custom matcher that selects the realization which has the best annealing result.

```
1 def match_min(S, rrefs:List[RRef])>List[RRef]:
2     avail=[np.load(mklens(rref,S=S).trace_fs.syspath)[-1] for rref in rrefs]
3     best=sorted(zip(avail,rrefs))[0]
4     if best[1] in allrrefs(Sa):
5         print(f"Picking Alice ({best[0]}) out of {avail}")
6     else:
7         print(f"Picking Bob ({best[0]}) out of {avail}")
8     return [best[1]]
9
10 def stage_all2(m:Manager):
11     ds=stage_params(m)
12     cl=redefine(stage_anneal, new_matcher=match_min)(m,ds)
13     vis=stage_plot(m,cl)
14     return vis
15
16 rref_best=realize(instantiate(stage_all2,S=Sb))
17 print(rref_best)
```

```
Picking Bob (1.6165660253729455) out of [1.6165660253729455, 1.6165660253764846]
rref:f82e8d998cacb395759d582f1be63a16-ff1dd5c155ee3faa445572e3246f0566-plot
```