

DiffTrace: Efficient Whole-Program Trace Analysis and Diffing

Saeed Taheri
staheri@cs.utah.edu

University of Utah
Salt Lake City, Utah, United States

Martin Burtscher
burtscher@cs.txstate.edu
Texas State University
San Marcos, Texas, U.S.A.

Ian Briggs
ianbriggsutah@gmail.com

University of Utah
Salt Lake City, Utah, United States

Ganesh Gopalakrishnan
ganesh@cs.utah.edu
University of Utah
Salt Lake City, Utah, U.S.A.

ABSTRACT

Abstract to be written

KEYWORDS

diffing, tracing, debugging

ACM Reference Format:

Saeed Taheri, Ian Briggs, Martin Burtscher, and Ganesh Gopalakrishnan. 2019. DiffTrace: Efficient Whole-Program Trace Analysis and Diffing. In *Proceedings of ACM Conference (Conference'17)*. ACM, New York, NY, USA, 7 pages. <https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

1 INTRODUCTION

When the next version of an HPC software system is created, logical errors often get introduced. To maintain productivity, designers need effective and efficient methods to locate these errors. Given the increasing use of hybrid (MPI + X) codes and library functions, errors may be introduced through a usage contract violation at any one of these interfaces. Therefore, tools that record activities at multiple APIs are necessary. Designs find most of these bugs manually, and the efficacy of a debugging tool is often measured by how well it can highlight the salient differences between the executions of two versions of software. Given the huge number of things that could be different – individual iterative patterns of function calls, groups of functions calls, or even specific instruction types (e.g., non-vectorized versus vectorized floating-point dot vector loops) – designers cannot often afford to rerun the application multiple times to collect each facet of behavior separately. These issues are well summarized in many recent studies [20]

One of the major challenges of HPC debugging is the huge diversity of the applications, which encompass domains such as computational chemistry, molecular dynamics, and climate simulation. In addition, there are many types of possible “bugs” or, more precisely, errors. An **error** may be a deadlock or a resource leak.

These errors may be caused by different **faults**: an unexpected message reordering rule (for a deadlock) or a forgotten free statement (for a resource leak). There exists a collection of scenarios in which a bug can be introduced: when developing a brand new application, optimizing an existing application, upscaling an application, porting to a new platform, changing the compiler, or even changing compiler flags. Unlike traditional software, there are hardly any bug-repositories, collection of trace data or debugging-purpose benchmarks in HPC community. The heterogeneous nature of HPC bugs make developers come up with their own solutions to resolve specific class of bugs on specific architecture or platforms that are not usable on other [20].

When a failure occurs (e.g., deadlock or crash) or the application outputs an unexpected result, it is not economic to rerun the application and consume resources to reproduce the failure. In addition, HPC bugs might not be reproducible due to non-deterministic behavior of most of HPC applications. Also the failure might be caused by a bug present at different APIs, system levels or network, thus multiple reruns might be needed to locate the buggy area. In our previous work[43], we have introduced ParLOT that collects whole program function call traces efficiently using dynamic binary instrumentation. ParLOT captures function calls and returns at different levels (e.g., source-code and library) and incrementally compress them on-the-fly, resulting in low runtime overhead and significantly low required bandwidth, preserving the whole-program dynamic behavior for offline analysis.

In the current work, we introduce DiffTrace, a tool-chain that post-mortem analyze ParLOT traces in order to supply developers with information about dynamic behavior of HPC applications at different levels towards debugging. Topology of HPC tasks on both distributed and shared memory often follow a “symmetric” control flow such as SPMD, master/worker and odd/even where multiple tasks contain *similar* events in their control flow. HPC bugs often manifest themselves as divergence in the control flow of processes comparing to what was expected. In other words, HPC bugs violates the rule of “symmetric” and “similar” control flow of one or more thread/process in typical HPC applications based on the original topology of the application. We believe that finding the dissimilarities among traces is the essential initial step towards finding the bug manifestation, and consequently the bug root cause. Large-scale HPC application execution would result in thousands of ParLOT trace files due to execution of thousands of processes and threads. Since HPC applications spend most of their time in an outer

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference'17, July 2017, Washington, DC, USA

© 2019 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM...\$15.00

<https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

main loop, every single trace file also may contain million-long sequence of trace entries (i.e., function calls and returns). Finding the bug manifestation (i.e., dissimilarities caused by the bug) among large number of long traces is the problem of finding the needle in the haystack.

Decompressing ParLOT traces collected from long-running large-scale HPC applications for offline analysis produce overwhelming amount of data. However, missing any piece of collected data may result in losing key information about the application behavior. We propose a variation of NLR (Nested Loop Recognition) algorithm [25] that takes a sequence of trace entries as input and by recursively detecting repetitive patterns, re-compresses traces into “iterative sets” in a lossless fashion (intra-trace compression). Analyzing the application execution as a whole is another goal that we are pursuing in this work. By extracting *attributes* from pre-processed traces, we inject them a concept hierarchy data structure called Concept Lattice [16]. Concept lattices give us the capability of reducing the search space from thousands of instances to just a few *equivalent behavior classes of traces* by measuring the similarity of traces[3]

**** TODO:** Highlights of results obtained as a result of the above thinking should be here. This typically comes before ROADMAP of paper.

In summary, here are our main contributions:

- we have a powerful combination of ideas to locate bugs
- A variation of NLR algorithm to compress traces in lossless fashion for easier analysis and detecting (broken) loop structures
- FCA-based clustering of similar behavior traces, efficient,
- Ranking system based on delta-sim
- Visualization diffNLR

The rest of the paper is as follows:

- Sec 2 talks about backgrounds
- Sec 3: Talks about the design of diffTrace
- Sec 4: Evaluates diffNLR by initial recommendation turns into NLR-observable bug and confusion matrix scores how many TP,FP,TN,FN
- Sec 5 major related work will have a detailed discussion of related work
- Sec 6 discusses the potential limitations, future work, and conclusion.

2 BACKGROUND AND RELATED WORK

Why we need our components:

- ParLOT collects whole program function call trace with the mindset of paying a little upfront and save resource and time cost of reproducing the bug.
- detection of loops, lossless Compression, easier to analyze, information about loop structures, how many iteration each loop executed matters, broken loop matters
- Concept lattices, throw inter-process information, similarity, clustering
- diffNLR visualizes pairs of traces and reflect their differences where they are supposed to be equal.

2.1 Parlot Summary (changeme)

- why binary instrumentation? no need to modify the code to instrument - no need to recompile

- Parlot is portable, scalable, efficient,

mini related work discussion here, mainly to refocus mind to accepting that binary tracing has several advantages that don't come with other tracing approaches such as Dyninst etc.

2.2 Equivalencing behavior via concept lattices (changeme)

this is how it is cleanly defined (use our context or examples)

e.g. high-level : objects to attributes

in our case objects can be... and attributes can be

how we use them is ...

- Vijay Garg - Applications of lattice theory in distributed systems
 - Dimitry Ignatov [?] - Concept Lattice Applications in Information Retrieval
 - [16] [19] [4] [18]
- Similarity measurement using FCA [3]

2.2.1 *Attribute creation...* There are many of them (others have not

2.2.2 *incremental algos.* challenges : need incremental algo... end

2.3 Loop structure detection

loop detection has been addressed in xyz

challenges in our context are xyz...

highlights of what you did (briefly) and why it can help

2.4 diffing (changeme)

what you adapted

how does it help

[36]

2.5 STAT

Parallel debugger STAT[1]

- STAT gathers stack traces from all processes
- Merge them into prefix tree
- Groups processes that exhibit similar behavior into equivalent classes
- A single representative of each equivalence can then be examined with a full-featured debugger like TotalView or DDT

What STAT does not have?

- FP debugging
- Portability (too many dependencies)
- Domain-specific
- Loop structures and detection

2.6 Program Understanding

- Score-P [26]
- TAU [41]
- ScalaTrace: Scalable compression and replay of communication traces for HPC [38]
- Barrier Matching for Programs with Textually unaligned barriers [46]
- Pivot Tracing: Dynamic causal monitoring for distributed systems - Johnathan mace [32]
- Automated Characterization of parallel application communication patterns [40]
- Problem Diagnosis in Large Scale Computing environments [34]
- Probabilistic diagnosis of performance faults in large-scale parallel applications [28]
- detecting patterns in MPI communication traces - robert preissl [39]
- D4: Fast concurrency debugging with parallel differential analysis - bozhen liu [31]
- Marmot: An MPI analysis and checking tool - bettina krammer [27]
- MPI-checker - Static Analysis for MPI - Alexandrer droste [15]
- STAT: stack trace analysis for large scale debugging - Dorian Arnold [1]
- DMTracker: Finding bugs in large-scale parallel programs by detecting anomaly in data movements [17]
- SyncChecker: Detecting synchronization errors between MPI applications and libraries - [11]
- Model Based fault localization in large-scale computing systems - Naoya Maruyama [33]
- Synoptic: Studying logged behavior with inferred models - ivan beschastnikh [5]
- Mining temporal invariants from partially ordered logs - ivan beschastnikh [7]
- Scalable Temporal Order Analysis for Large Scale Debugging - Dong Ahn [2]
- Inferring and asserting distributed system invariants - ivan beschastnikh - stewart grant [21]
- PRODOMETER: Accurate application progress analysis for large-scale parallel debugging - subatra mitra [35]

- Automaded : Automata-based debugging for dissimilar parallel tasks - greg [9]
- Automaded : large scale debugging of parallel tasks with Automaded - ignacio [29]
- Inferring models of concurrent systems from logs of their behavior with CSight - ivan [6]

2.7 Trace Analysis

- Trace File Comparison with a hierarchical Sequence Alignment algorithm [44]
- structural clustering : matthias weber [45]
- building a better backtrack: techniques for postmortem program analysis - ben liblit [30]
- automatically characterizing large scale program behavior - timothy sherwood [42]

2.8 Visualizations

- Combing the communication hairball: Visualizing large-scale parallel execution traces using logical time - katherine e isaacs [23]
- recovering logical structure from charm++ event traces [22]
- ShiViz - Debugging distributed systems - [8]

2.9 Concept Lattice and LCA

- Vijay Garg - Applications of lattice theory in distributed systems
- Dimitry Ignatov [?] - Concept Lattice Applications in Information Retrieval
- [16] [19] [4] [18] [36]

2.10 Repetitive Patterns

- [12] [24] [37] [14] [13]

3 DFFTRACE TOOL ARCHITECTURE

3.1 General Idea

Here is a general overview of DiffTrace and its components

- Motivating example
- Problem statement
- Potential Approaches and Related Work
- Next subsections will explain the components that we have in our framework and the corresponding related work and background

3.2 Fault Injection

3.3 ParLOT


2-3 paragraph explanation about ParLOT and its mechanism [43]

3.4 Filter

Include a table with all filters and their regular expressions

3.4.1 General Filters.

- Returns
- .plt
- Memory
- Network

Figure 1: diffTrace Overview

- Polling
- String
- Customize
- IncludeEverything

3.4.2 Target Filters.

- MPI_
- MPIall
- MPI_Collectives
- MPI_Send/Recv
- OMPall
- OMPcritical
- OMPmutex

3.5 Nested Loop Recognition

3.5.1 Background.

3.5.2 Implementation.

3.6 Concept Lattice Analysis

3.6.1 Background.

- FCA (formal concept analysis) background and citations
- FCA applications in all areas
- FCA applications in Data Mining and Information Retrieval
- FCA applications in distributed systems (Garg's work)
- intro to Concept, Object, Attribute and other definitions

3.6.2 Objects/Attributes. Mapping of Object/Attribute (general) to Trace/Attribute (clTrace)

What do we expect to gain by doing so

- Single entity represents the whole execution of HPC application (can be used as signature/model in ML)
- Classifying similar behavior objects(traces)
- Efficient Incremental CL building makes it scalable
- Efficient full pair-wise Jaccard Similarity Matrix extraction

3.6.3 CL generation.

- background

- current approach

3.6.4 Jaccard Similarity Matrix.

- background
- LCA
- Benefits

3.7 diffNLR

- motivation
- diff algorithm
- visualization

3.8 FP-Trace

4 EXPERIMENTAL STUDIES

Filter	Attributes	Top Process diffNR Candidates	Top Thread diffNR Candidates
11.mpi.cust.0K10	sing.log10	1:(25)r259.10699.0,(65)r265.0114.0 2:(20)r259.10698.0,(75)r265.0116.0 3:(0)r259.10694.0,(55)r265.0112.0	1:(2)r259.10694.2,(78)r265.0116.3 2:(17)r259.10697.2,(64)r265.0113.4 3:(49)r265.0110.4,(58)r265.0112.4
11.mpi.cust.0K10	doub.orig	1:(25)r259.10699.0,(65)r265.0114.0 2:(20)r259.10698.0,(75)r265.0116.0 3:(0)r259.10694.0,(55)r265.0112.0	1:(32)r259.10700.2,(54)r265.0111.4 2:(14)r259.10696.4,(74)r265.0115.4 3:(53)r265.0111.3,(53)r265.0111.3
11.mpi.cust.0K10	doub.orig	1:(25)r259.10699.0,(65)r265.0114.0 2:(20)r259.10698.0,(75)r265.0116.0 3:(0)r259.10694.0,(55)r265.0112.0	1:(32)r259.10700.2,(54)r265.0111.4 2:(14)r259.10696.4,(74)r265.0115.4 3:(53)r265.0111.3,(53)r265.0111.3
01.mpi.cust.0K10	doub.orig	1:(25)r259.10699.0,(65)r265.0114.0 2:(20)r259.10698.0,(75)r265.0116.0 3:(0)r259.10694.0,(55)r265.0112.0	1:(32)r259.10700.2,(54)r265.0111.4 2:(14)r259.10696.4,(74)r265.0115.4 3:(53)r265.0111.3,(53)r265.0111.3
11.mpi.cust.0K10	sing.orig	1:(25)r259.10699.0,(65)r265.0114.0 2:(20)r259.10698.0,(75)r265.0116.0 3:(0)r259.10694.0,(55)r265.0112.0	1:(2)r259.10694.2,(78)r265.0116.3 2:(17)r259.10697.2,(64)r265.0113.4 3:(49)r265.0110.4,(58)r265.0112.4
01.mpi.cust.0K10	doub.actual	1:(25)r259.10699.0,(65)r265.0114.0 2:(20)r259.10698.0,(75)r265.0116.0 3:(0)r259.10694.0,(55)r265.0112.0	1:(32)r259.10700.2,(54)r265.0111.4 2:(14)r259.10696.4,(74)r265.0115.4 3:(53)r265.0111.3,(53)r265.0111.3

5 RESULTS

5.1 MPI Bugs

6 CASE STUDIES

6.0.2 Case Study: MFEM.

7 DISCUSSION AND FUTURE WORK

REFERENCES

- [1] D. H. Ahn, B. R. de Supinski, I. Laguna, G. L. Lee, B. Liblit, B. P. Miller, and M. Schulz. 2009. Scalable temporal order analysis for large scale debugging. In *Proceedings of the Conference on High Performance Computing Networking, Storage and Analysis*. 1–11. <https://doi.org/10.1145/1654059.1654104>
- [2] Dong H. Ahn, Bronis R. de Supinski, Ignacio Laguna, Gregory L. Lee, Ben Liblit, Barton P. Miller, and Martin Schulz. 2009. Scalable Temporal Order Analysis for Large Scale Debugging. In *Proceedings of the Conference on High Performance Computing Networking, Storage and Analysis (SC '09)*. ACM, New York, NY, USA, Article 44, 11 pages. <https://doi.org/10.1145/1654059.1654104>
- [3] Faris Alqadah and Raj Bhatnagar. 2011. Similarity measures in formal concept analysis. *Annals of Mathematics and Artificial Intelligence* 61, 3 (01 Mar 2011), 245–256. <https://doi.org/10.1007/s10472-011-9257-7>
- [4] Michael A. Bender, Martijn Farach-Colton, Giridhar Pemmasani, Steven Skiena, and Pavel Sumazin. 2005. Lowest common ancestors in trees and directed acyclic graphs. *Journal of Algorithms* 57, 2 (2005), 75 – 94. <https://doi.org/10.1016/j.jalgor.2005.08.001>
- [5] Ivan Beschastnikh, Jenny Abrahamson, Yuriy Brun, and Michael D. Ernst. 2011. Synoptic: Studying Logged Behavior with Inferred Models. In *Proceedings of the 19th ACM SIGSOFT Symposium and the 13th European Conference on Foundations of Software Engineering (ESEC/FSE '11)*. ACM, New York, NY, USA, 448–451. <https://doi.org/10.1145/2025113.2025188>
- [6] Ivan Beschastnikh, Yuriy Brun, Michael D. Ernst, and Arvind Krishnamurthy. 2014. Inferring Models of Concurrent Systems from Logs of Their Behavior with CSight. In *Proceedings of the 36th International Conference on Software Engineering (ICSE 2014)*. ACM, New York, NY, USA, 468–479. <https://doi.org/10.1145/2568225.2568246>
- [7] Ivan Beschastnikh, Yuriy Brun, Michael D. Ernst, Arvind Krishnamurthy, and Thomas E. Anderson. 2011. Mining Temporal Invariants from Partially Ordered Logs. In *Managing Large-scale Systems via the Analysis of System Logs and the Application of Machine Learning Techniques (SLAML '11)*. ACM, New York, NY, USA, Article 3, 10 pages. <https://doi.org/10.1145/2038633.2038636>
- [8] Ivan Beschastnikh, Patty Wang, Yuriy Brun, and Michael D. Ernst. 2016. Debugging Distributed Systems. *Commun. ACM* 59, 8 (July 2016), 32–37. <https://doi.org/10.1145/2909480>
- [9] B. Bronevetsky, I. Laguna, S. Bagchi, B. R. de Supinski, D. H. Ahn, and M. Schulz. 2010. AutomaDeD: Automata-based debugging for dissimilar parallel tasks. In *2010 IEEE/IFIP International Conference on Dependable Systems Networks (DSN)*. 231–240. <https://doi.org/10.1109/DSN.2010.5544927>

- [10] M. Burtischer and H. Rabeti. 2013. A Scalable Heterogeneous Parallelization Framework for Iterative Local Searches. In *2013 IEEE 27th International Symposium on Parallel and Distributed Processing*. 1289–1298. <https://doi.org/10.1109/IPDPS.2013.27>
- [11] Z. Chen, X. Li, J. Chen, H. Zhong, and F. Qin. 2012. SyncChecker: Detecting Synchronization Errors between MPI Applications and Libraries. In *2012 IEEE 26th International Parallel and Distributed Processing Symposium*. 342–353. <https://doi.org/10.1109/IPDPS.2012.40>
- [12] M. Crochemore and W. Rytter. 1991. Usefulness of the Karp-Miller-Rosenberg algorithm in parallel computations on strings and arrays. *Theoretical Computer Science* 88, 1 (1991), 59 – 82. <http://www.sciencedirect.com/science/article/pii/03043975.91.90073B>
- [13] Maxime Crochemore and Wojciech Rytter. 1994. *Text Algorithms*. Oxford University Press, Inc., New York, NY, USA.
- [14] Maxime Crochemore and Wojciech Rytter. 2002. *Jewels of Stringology*. World Scientific. <https://books.google.com/books?id=ipuPQgAACAAJ>
- [15] Alexander Droste, Michael Kuhn, and Thomas Ludwig. 2015. MPI-checker: Static Analysis for MPI. In *Proceedings of the Second Workshop on the LLVM Compiler Infrastructure in HPC (LLVM '15)*. ACM, New York, NY, USA, Article 3, 10 pages. <https://doi.org/10.1145/2833157.2833159>
- [16] Bernhard Ganter and Rudolf Wille. 1997. *Formal Concept Analysis: Mathematical Foundations* (1st ed.). Springer-Verlag New York, Inc., Secaucus, NJ, USA.
- [17] Q. Gao, F. Qin, and D. K. Panda. 2007. DMTracker: finding bugs in large-scale parallel programs by detecting anomaly in data movements. In *SC '07: Proceedings of the 2007 ACM/IEEE Conference on Supercomputing*. 1–12. <https://doi.org/10.1145/1362622.1362643>
- [18] Vijay K. Garg. 2013. Maximal Antichain Lattice Algorithms for Distributed Computations. In *Distributed Computing and Networking*, Davide Frey, Michel Raynal, Saswati Sarkar, Rudrapatna K. Shyamasundar, and Prasun Sinha (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 240–254.
- [19] Robert Godin, Rokia Missaoui, and Hassan Alaoui. [n. d.]. INCREMENTAL CONCEPT FORMATION ALGORITHMS BASED ON GALOIS (CONCEPT) LATTICES. *Computational Intelligence* 11, 2 ([n. d.]), 246–267.
- [20] Ganesh Gopalakrishnan, Paul D. Hovland, Costin Iancu, Sriram Krishnamoorthy, Ignacio Laguna, Richard A. Lethin, Koushik Sen, Stephen F. Siegel, and Armando Solar-Lezama. 2017. Report of the HPC Correctness Summit, Jan 25–26, 2017, Washington, DC. CoRR abs/1705.07478 (2017). arXiv:1705.07478 <http://arxiv.org/abs/1705.07478>
- [21] Stewart Grant, Hendrik Cech, and Ivan Beschastnikh. 2018. Inferring and Asserting Distributed System Invariants. In *Proceedings of the 40th International Conference on Software Engineering (ICSE '18)*. ACM, New York, NY, USA, 1149–1159. <https://doi.org/10.1145/3180155.3180199>
- [22] K. E. Isaacs, A. Bhatel, J. Liffander, D. B. Ähume, T. Gamblin, M. Schulz, B. Hamann, and P. Bremer. 2015. Recovering logical structure from Charm++ event traces. In *SC '15: Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*. 1–12. <https://doi.org/10.1145/2807591.2807634>
- [23] Katherine E. Isaacs, Peer-Timo Bremer, Ilir Jusufi, Todd Gamblin, Abhinav Bhatel, Martin Schulz, and Bernd Hamann. 2014. Combing the Communication Hairball: Visualizing Parallel Execution Traces using Logical Time. *IEEE Transactions on Visualization and Computer Graphics* 20 (2014), 2349–2358.
- [24] Richard M. Karp, Raymond E. Miller, and Arnold L. Rosenberg. 1972. Rapid Identification of Repeated Patterns in Strings, Trees and Arrays. In *Proceedings of the Fourth Annual ACM Symposium on Theory of Computing (STOC '72)*. ACM, New York, NY, USA, 125–136. <https://doi.org/10.1145/800152.804905>
- [25] Alain Ketterlin and Philippe Clauss. 2008. Prediction and Trace Compression of Data Access Addresses Through Nested Loop Recognition. In *Proceedings of the 6th Annual IEEE/ACM International Symposium on Code Generation and Optimization (CGO '08)*. ACM, New York, NY, USA, 94–103. <https://doi.org/10.1145/1356058.1356071>
- [26] Andreas Knüpfer, Christian Rössel, Dieter an Mey, Scott Biersdorff, Kai Diethelm, Dominic Eschweiler, Markus Geimer, Michael Gerndt, Daniel Lorenz, Allen D. Malony, Wolfgang E. Nagel, Yuri Oleynik, Peter Philippen, Pavel Saviankou, Dirk Schmidl, Sameer Shende, Ronny Tschüter, Michael Wagner, Bert Wesarg, and Felix Wolf. 2011. Score-P: A Joint Performance Measurement Run-Time Infrastructure for Periscope, Scalasca, TAU, and Vampir. In *Tools for High Performance Computing 2011 - Proceedings of the 5th International Workshop on Parallel Tools for High Performance Computing*, ZIH, Dresden, September 2011. 79–91.
- [27] Bettina Krammer, Matthias Măcășiller, and Michael Resch. 2004. MPI application development using the analysis tool MARMOT, Vol. 3038. 464–471. https://doi.org/10.1007/978-3-540-24688-6_61
- [28] Ignacio Laguna, Dong H. Ahn, Bronis R. de Supinski, Saurabh Bagchi, and Todd Gamblin. 2012. Probabilistic Diagnosis of Performance Faults in Large-scale Parallel Applications. In *Proceedings of the 21st International Conference on Parallel Architectures and Compilation Techniques (PACT '12)*. ACM, New York, NY, USA, 213–222. <https://doi.org/10.1145/2370816.2370848>

Table 1: Injected Bugs to ILCS-TSP

ID	Level	Bugs	Description
1	MPI	allRed1wrgOp-1-all-x	Different operation (MPI_MAX) in only one (buggyProc) for first MPI_ALLREDUCE() – L229:ilcsTSP.c
2		allRed1wrgSize-1-all-x	Wrong size in only one (buggyProc) for first MPI_ALLREDUCE() – L229:ilcsTSP.c
3		allRed1wrgSize-all-all-x	Wrong Size in all processes for first MPI_ALLREDUCE() – L229:ilcsTSP.c
4		allRed2wrgOp-1-all-x	Different operation (MPI_MAX) in only one (buggyProc) for first MPI_ALLREDUCE() – L277:ilcsTSP.c
5		allRed2wrgSize-1-all-x	Wrong size in only one (buggyProc) for first MPI_ALLREDUCE() – L277:ilcsTSP.c
6		allRed2wrgSize-all-all-x	Wrong Size in all processes for second MPI_ALLREDUCE() – L277:ilcsTSP.c
7		bcastWrgSize-1-all-x	Wrong Size in only one (buggyProc) of MPI_Bcast() – L290:ilcsTSP.c
8		bcastWrgSize-all-all-x	Wrong Size n all processes for MPI_Bcast() – L240:ilcsTSP.c
9	OMP	misCrit-1-1-x	Missing Critical Section in buggyProc and buggyThread – L170:ilcsTSP.c
10		misCrit-all-1-x	Missing Critical Section in buggyThread and all procoesses – L170:ilcsTSP.c
11		misCrit-1-all-x	Missing Critical Section in buggyProc and all threads – L170:ilcsTSP.c
12		misCrit-all-all-x	Missing Critical Section in all procs and threads – L170:ilcsTSP.c
13		misCrit2-1-1-x	Missing Critical Section in buggyProc and buggyThread – L230:ilcsTSP.c
14		misCrit2-all-1-x	Missing Critical Section in buggyThread – L230:ilcsTSP.c
15		misCrit2-1-all-x	Missing Critical Section in buggyProc and all threads – L230:ilcsTSP.c
16		misCrit2-all-all-x	Missing Critical Section in all procs and threads – L230:ilcsTSP.c
17		misCrit3-1-all-x	Missing Critical Section in buggyProc and all threads – L280:ilcsTSP.c
18		misCrit3-all-all-x	Missing Critical Section in all procs and threads – L280:ilcsTSP.c
19	General	infLoop-1-1-1	Injected an infinite loop after CPU_EXEC() in buggyProc,buggyThread & buggyIter L164:ilcsTSP.c




Figure 3: sample diffNLR

- [29] Ignacio Laguna, Todd Gamblin, Bronis R. de Supinski, Saurabh Bagchi, Greg Bronevetsky, Dong H. Anh, Martin Schulz, and Barry Rountree. 2011. Large Scale Debugging of Parallel Tasks with AutomaDeD. In *Proceedings of 2011 International Conference for High Performance Computing, Networking, Storage and Analysis (SC '11)*. ACM, New York, NY, USA, Article 50, 10 pages. <https://doi.org/10.1145/2063384.2063451>
- [30] Ben Liblit and Alex Aiken. 2002. *Building a Better Backtrace: Techniques for Postmortem Program Analysis*. Technical Report. Berkeley, CA, USA.
- [31] Bozhen Liu and Jeff Huang. 2018. D4: Fast Concurrency Debugging with Parallel Differential Analysis. In *Proceedings of the 39th ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI 2018)*. ACM, New York, NY, USA, 359–373. <https://doi.org/10.1145/3192366.3192390>
- [32] Jonathan Mace, Ryan Roelke, and Rodrigo Fonseca. 2018. Pivot Tracing: Dynamic Causal Monitoring for Distributed Systems. *ACM Trans. Comput. Syst.* 35, 4, Article 11 (Dec. 2018), 28 pages. <https://doi.org/10.1145/3208104>
- [33] N. Maruyama and S. Matsuoka. 2008. Model-based fault localization in large-scale computing systems. In *2008 IEEE International Symposium on Parallel and Distributed Processing*, 1–12. <https://doi.org/10.1109/IPDPS.2008.4536310>
- [34] A. V. Mirgorodskiy, N. Maruyama, and B. P. Miller. 2006. Problem Diagnosis in Large-Scale Computing Environments. In *SC '06: Proceedings of the 2006 ACM/IEEE Conference on Supercomputing*, 11–11. <https://doi.org/10.1109/SC.2006.50>
- [35] Subrata Mitra, Ignacio Laguna, Dong H. Anh, Saurabh Bagchi, Martin Schulz, and Todd Gamblin. 2014. Accurate Application Progress Analysis for Large-scale Parallel Debugging. In *Proceedings of the 35th ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI '14)*. ACM, New York, NY, USA, 193–203. <https://doi.org/10.1145/2594291.2594336>
- [36] Eugene W. Myers. 1986. An O(ND) Difference Algorithm and Its Variations. *Algorithmica* 1, 2 (1986), 251–266. <https://doi.org/10.1007/BF01840446>
- [37] Atsuyoshi Nakamura, Tomoya Saito, Ichigaku Takigawa, Mineichi Kudo, and Hiroshi Mamitsuka. 2013. Fast algorithms for finding a minimum repetition




Figure 4: sample diffNLR2

- representation of strings and trees. *Discrete Applied Mathematics* 161, 10 (2013), 1556 – 1575. <https://doi.org/10.1016/j.dam.2012.12.013>
- [38] Michael Noeth, Prasun Ratn, Frank Mueller, Martin Schulz, and Bronis R. de Supinski. 2009. ScalaTrace: Scalable compression and replay of communication traces for high-performance computing. *J. Parallel and Distrib. Comput.* 69, 8 (2009), 696 – 710. <https://doi.org/10.1016/j.jpdc.2008.09.001> Best Paper Awards: 21st International Parallel and Distributed Processing Symposium (IPDPS 2007).
- [39] Robert Preissl, Thomas Köckerbauer, Martin Schulz, Dieter Kranzlmüller, Bronis R. de Supinski, and Daniel J. Quinlan. 2008. Detecting Patterns in MPI Communication Traces. *2008 37th International Conference on Parallel Processing* (2008), 230–237.
- [40] Philip C. Roth, Jeremy S. Meredith, and Jeffrey S. Vetter. 2015. Automated Characterization of Parallel Application Communication Patterns. In *Proceedings of the 24th International Symposium on High-Performance Parallel and Distributed Computing (HPDC '15)*. ACM, New York, NY, USA, 73–84. <https://doi.org/10.1145/2749246.2749278>
- [41] Sameer S. Shende and Allen D. Malony. 2006. The Tau Parallel Performance System. *International Journal on High Performance Computer Applications* 20 (May 2006), 287–311. Issue 2. <https://doi.org/10.1177/1094342006064482>
- [42] Timothy Sherwood, Erez Perelman, Greg Hamerly, and Brad Calder. 2002. Automatically Characterizing Large Scale Program Behavior. In *Proceedings of the 10th International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS X)*. ACM, New York, NY, USA, 45–57. <https://doi.org/10.1145/605397.605403>
- [43] S. Taheri, S. Devale, G. Gopalakrishnan, and M. Burtcher. [n. d.]. PARLOT: Efficient Whole-Program Call Tracing for HPC Applications. In *7th Workshop on Extreme-Scale Programming Tools, ESPT@SC 2018, Dallas, TX, USA, November 16, 2018*.
- [44] M. Weber, R. Brendel, and H. Brunst. 2012. Trace File Comparison with a Hierarchical Sequence Alignment Algorithm. In *2012 IEEE 10th International Symposium on Parallel and Distributed Processing with Applications*. 247–254. <https://doi.org/10.1109/ISPA.2012.40>
- [45] Matthias Weber, Ronny Brendel, Tobias Hilbrich, Kathryn Mohror, Martin Schulz, and Holger Brunst. 2016. Structural Clustering: A New Approach to Support Performance Analysis at Scale. *IEEE*, 484–493. <https://doi.org/10.1109/IPDPS.2016.27>
- [46] Yuan Zhang and Evelyn Duesterwald. 2007. Barrier Matching for Programs with Textually Unaligned Barriers. In *Proceedings of the 12th ACM SIGPLAN Symposium on Principles and Practice of Parallel Programming (PPoPP '07)*. ACM, New York, NY, USA, 194–204. <https://doi.org/10.1145/1229428.1229472>