SUSPENSION SISTEM: AS-250







TECHNICAL SPECIFICATIONS

Suspension System		
Model	AS-250	
Color	Anodized, Inox (Standard), 20µm	
Material	AL 6082, 6061-T6, 5083-H321	
	SST 316 / 304L	
Bearings	Nylon bearings x4	
Weight	10,1 kg	
Dimensions	(250-220)x(350-380)x230	
Passenger	75-110Kg (165-242,5lbs) Standard	
weight	Optimum Range	
<u> </u>	•	

Shock	
Weight	0.33 KG (0.73 lb),
	240 mm (9.45 inch)
Adjustments	Rebound / Preload
Damper shaft	Hard chromed shock
	Ø 12 mm (0.47 inch)
	shaft.
	Dark hard-anodized
	AL-6061 shock body.
Riding style	AM / FR / DH

Warranty		
Metal structure and shock	2 years	
Maintenance		
Structure	Clean water after every usage	
	in salty environment	
Shock	Regular use of Denicol MULTI	
	USER 101 spray code 03101	
Applications		
Can be fitted to any seat using a special fitting		
adapter. For any High speed boat. Suggested for seats		
with passengers in seated positions. Indoor or outdoor use.		

The mechanism "AS-250" has been designed to cooperate with any seat which is going to be used for giving shock mitigation to extreme or pleasure high speed crafts.

The mechanism, due to its geometry and the reclining shock adjustment, provides:

Wider range of passenger weight. Better comfort conditions during any trip or mission. Optimal body posture for handling both static and dynamic loads. Optimum shock mitigation for spine and neck.