# **RO-Index: A survey of Research Object usage**

This manuscript (permalink) was automatically generated from stain/ro-index-paper@a3ce8d8 on September 10, 2019.

## **Authors**

# • Stian Soiland-Reyes

Department of Computer Science, The University of Manchester, UK; Informatics Institute, Faculty of Science, University of Amsterdam, NL · Funded by BioExcel-2 (European Commission H2020-INFRAEDI-02-2018-823830)

#### Paul Groth

**(D** 0000-0003-0183-6910 ⋅ **(7** pgroth

Informatics Institute, Faculty of Science, University of Amsterdam, NL

### **Abstract**

This manuscript is work in progress and (for now) follows the style of a Study Protocol for F1000Research Registered Reports

For this study we aim to build **RO-Index**, a broad and comprehensive corpus of Research Objects found "in the wild". The proposed methodology follows multiple strands to find the "breeding grounds" of research objects and further describes how Research Objects are selected for inclusion, along with post-processing to build the corpus.

The corpus of Research Objects will primarily be distributed as Open Data, including:

- Identifiers and access URLs
- Extracted manifests and annotation files
- Checksums/references for external data
- Metadata from repository (e.g. Datacite XML)
- Provenance of data gathering and post-processing

Research Objects that cannot be redistributed (e.g. unknown license) will only be examined for aggregates.

A brief set of qualitative and quantitative analytics will then be performed across the overall corpus, in particular to address research questions like:

- Where are Research Objects published?
- Which scientific domains produce Research Objects?
- What serializations are used for making Research Objects?
- What vocabularies are used to describe Research Objects and their content?
- What type of resources to Research Objects contain?
- What kinds of life cycles do Research Objects follow?

### Introduction

### **Protocol**

# **Finding Research Objects**

One goal of this work is to determine what kind of artifacts, in practice, can be considered a *research object*. For the purpose of building a corpus we need to have both inclusion and exclusion criteria.

The foundational article on the RO concept is [1] and its workshop predecessor [2]. The Research Object community has maintained lists of <u>initiatives</u> and <u>Research Object profiles</u> which provide curated, although potentially biased, collections of Research Object approaches and implementations.

# **Declared Research Object usage**

In order to determine potential sources of Research Objects we will start with these community lists, but expand based on a literature review by following any academic citation of the before-mentioned Research Object articles to find potential repositories, tools and communities that may conceptually claim to have or make "research objects". This is a broad interpretation that does not expand into general datasets or packaging formats. The list may be expanded by literate search for "Research Object", the RO vocabularies and standard URLs.

Each of the citing articles will then be assessed to see if they have openly accessible research objects that are possible to identify, and ideally retrieve, by building a programmatic crawler. Ideally such access would use an open harvesting protocol like <u>OAI-PMH</u> or

ResourceSync, but it is predicted that in the majority of cases custom crawler code will need to be developed per repository, in addition to manual harvesting of identifiers for smaller collections and individual Research Objects.

#### **Keyword searches**

In addition to this "self-claimed" research object usage we will search in more general repositories by developing a list of keywords like "research object", "robundle" or the RO vocabulary URLs. We will search in at least:

- <a href="https://github.com/">https://github.com/</a>
- https://gitlab.com/
- http://datacite.org/
- https://zenodo.org/
- https://toolbox.google.com/datasetsearch/
- https://dataverse.harvard.edu/

It is predicted that these searches will yield duplicates, but will be used to find potentially new Research Object sources or free-standing instances.

#### **Archives with manifests**

Finally we will consider broadly Open Data repositories of file archives (e.g. ZIP, tar.gz) to inspect for the presence of a *manifest*-like file (e.g. /manifest.rdf). For practical reasons this search will be restricted to a smaller selection of public repositories and formats, e.g. Zenodo (20k \*.zip Datasets), FigShare ("zip" Datasets), Mendeley Data "zip" File Set.

A list of trigger filename patterns will be developed, including:

- META-INF/manifest.xml and META-INF/container.xml from EPUB Open Container Format
- manifest.xml from <u>COMBINE archives</u> [3]
- .ro/manifest.rdf from RO Hub [4]
- .ro/manifest.json from Research Object Bundle [5]
- metadata/manifest.json from <u>RO-Bagit</u> and BDBag [6;]
- CATALOG.json from <a href="DataCrate">DataCrate</a> [7]
- ro-crate-metadata.jsonld from <a href="RO-Crate">RO-Crate</a> [8]

It is predicted that most of the archive files will *not* contain such a manifest, therefore they can be inspected "on the fly" by the crawler without intermediate storage, to first detect a short-list of archives that contain a manifest-like file. These can then be downloaded in full for further inspection. File-name matching will inspect potential sub-directories, e.g. to detect nested/data/manifest.xml, but will classify these archives differently from direct matches.

### **Candidate sources**

For each candidate source we will collect and assess:

- Date assessed
- · Assessed by
- URL
- Name
- Estimate # ROs
- Estimate # users
- Maintainer/publisher
- Community links (if any)
- RO profile/format (if any)
- Identifier scheme(s) (if any)
- Persistence/Versioning (if any)

Then for each candidate source we will evaluate:

- Accessability can we retrieve RO and/or their metadata
- License permissions and/or restrictions to redistribute the ROs and/or their metadata
- Feasibility can we programmatically retrieve all ROs (or just a sample)?
- Duplication could the "same" RO be present by multiple identifiers or in other repositories?
- Self-identified are Research Objects classified as such (or using similar terminology)?

We may contact the provider or maintainer to expand on these questions if unclear from public information, however we are not conducting a formal survey, as our main interest lays in the machine-readable information from the research objects themselves.

We will finally form a shortlist of sources for further harvesting, considering:

- Programmatically access (or interesting enough to warrant manual access)
- Diversity might this source be different from the majority of sources?
- Legality are we allowed to retrieve ROs (or their identifiers and metadata?)
- Confidentiality are the research objects accessible to the public? (anonymous access or access by 'fresh' user registration)

### Handling personally identifiable information

Research Objects may, by their nature, contain information about people and their research activities. It is therefore important that our data collection, processing and potential re-distribution is in consistent with the <u>General Data Protection Regulation (GDPR)</u>. To this end we will evaluate:

- Does the source have a GDPR-compliant privacy policy or equivalent?
- Is personally identifiable information contained by identifier (e.g. username)?
- May personally identifiable information be contained by the Research Object manifest/description
- May personally identifiable information be contained by the Research Object files/content?
- Does the RO (or the metadata) have a license that permits redistribution and attribution, e.g. <u>Creative Commons Attribution 4.0</u> (CC-BY)?

Evaluating this may require retrieving research objects in the first place, but particular care will be taken to classify Research Objects and their sources according to the above evaluation in order to filter information that can progress to be part of the Open Data RO-Index corpus. This forms a staged inclusion list:

- 1. Unfiltered list of identifiers for a source will be shared if the identifiers tend not to include personally identifiable information
- 2. Metadata will be shared if it is accessible and does not tend to include personally identifiable information
- 3. Metadata and identifier will be shared if an open attribution-permitting license is indicated (or implied by site)
- 4. Content/files will be shared if accessible and an open license is indicated (or, for archives, implied by archive license)

Note: In the above, "tend to" will be determined manually by inspecting a smaller subset of typically 10 research objects. The selection will aim to approximate a simple random subset, but may need to be expanded to take into account the overall diversity of ROs at the source, e.g. date, authors, subsystem, formats. The identifiers of the ROs of this subset will be recorded, along with a description of how the subset was selected.

The inclusion list may be further restricted based on findings from further processing (e.g. a repository is found to distribute sensitive data).

It is worth noting that compliance with open licenses like <u>Creative Commons Attribution 4.0 (CC-BY)</u> or <u>Apache License 2.0</u> **require** attribution to be propagated (if present). Attribution may sometimes take the form of a URL, identifier, project or organization which do not directly identify a person.

The inclusion list will form different subsets of Research Objects:

- 1. Identified Research Objects
- 2. "Non-sensitive" (but potentially closed) metadata
- 3. Open metadata (potentially personally identifiable)
- 4. Open content (potentially personally identifiable)

Data for any excluded Research Objects will only be kept for the purpose and duration of this study on computer infrastructure managed by The University of Manchester. Data from excluded Research Objects will only be used for non-person-identifiable aggregated results (e.g. number of CSV files) and broad categorization (e.g. vocabularies used in metadata).

The identifiers from category 1, metadata from category 3 and data from category 4 will be shared in the public Open Data repository Zenodo according to Zenodo's policies. Metadata from category 3 and 4 above may be exposed for programmatic querying (e.g. SPARQL) or converted to other formats. No additional linking with internal and external data sources will be performed, although the collected Research Objects may already contain such links (e.g. <a href="https://orcid.org/">https://orcid.org/</a> identifiers of authors); an exception to this rule is that linking will be permitted to detect duplicate Research Objects across multiple sources, and to access resources clearly aggregated as part of the Research Object.

For GDPR purposes the *Data Controller* is The University of Manchester, data subjects may contact info@esciencelab.org.uk for any enquiries, such as to request access to data about themselves, or to request update or removal of personally identifiable information.

#### Pre-identified data sources

### **Proto-research objects**

- myExperiment packs
- COMBINE archives [3,9]
- VoID datasets http://www.openphacts.org/specs/2013/WD-datadesc-20130912/ [10,3]
- DataONE Data packages [11]

• DataLad https://www.datalad.org/datasets.html [12]

#### **ORE-based research objects**

- CWL Viewer <a href="https://view.commonwl.org/workflows">https://view.commonwl.org/workflows</a> [13]
- RO Bundle <a href="https://w3id.org/bundle/2014-11-05/">https://w3id.org/bundle/2014-11-05/</a> [5]
- Workflow PROV corpus [14]
- CWLProv 10.1093/gigascience/giz095 aka [15]
- http://www.rohub.org/ [4]
- <a href="http://rohub.linkeddata.es/">http://rohub.linkeddata.es/</a>
- SEEK: <a href="https://fairdomhub.org/investigations">https://fairdomhub.org/investigations</a>
- BDBags with MinID [6;]
- Zenodo e.g. [16]
- Mendeley Data eg [17]
- Maven <a href="https://repository.mygrid.org.uk/artifactory/ops/org/openphacts/data/">https://repository.mygrid.org.uk/artifactory/ops/org/openphacts/data/</a>
- DocumentObject <a href="https://github.com/binfalse/DocumentObjectCompiler/">https://github.com/binfalse/DocumentObjectCompiler/</a>
- · GitHub search
- EOSC-Life (too early?)

# Software/container-based research objects

- <a href="https://sci-f.github.io/">https://sci-f.github.io/</a> [18]
- https://frictionlessdata.io/specs/data-package/
- The Journal of Research Objects <a href="http://jro.world/">http://jro.world/</a> (see also <a href="presentation">presentation</a>
- Tonkaz

https://docs.google.com/presentation/d/1YRKCM1KwHyNOz7B6AP2j5qIHjl7Ew9CnAtvXA1xSeNY/edit#slide=id.g419a3a9d09 1 93

ActivePaper / HDF5 [19] > HDF5 dataset attributes are used to store metadata, including a dataflow graph that records
provenance (requirement 5), but also creation time stamps and a data type indicator distinguishing references and executable
code from "plain" datasets.

#### 2nd generation ROs

- DataCrate: https://github.com/UTS-eResearch/datacrate/blob/master/spec/1.0/data crate specification v1.0.md#examples
- RO-Crate: https://data.research.uts.edu.au/examples/ro-crate/0.2/

#### **Manifest formats**

A key characteristic of a Research Object is the presence of a *manifest* that describes and relates the content. However, multiple potential formats and conventions have emerged for how to serialize such a format. (...)

# Proposed data gathering workflow

The overall data gathering workflow is envisioned as:

- 1. Traverse repository (or one of its sub-sections) using API like OAI-PMH
- 2. Filter for entries that have an archive-like file type (e.g. ZIP, tar.gz)
- 3. Retrieve entry's Datacite-like metadata from repository (e.g. DOI, author, license)
- 4. Start downloading archive
- 5. Stream archive though a utility like sunzip to list filenames within
- 6. Record filenames mapped to identifier
- 7. Select entries which have a manifest-like file in list
- 8. Re-download selected archives
- 9. Extract manifest(s) from archives
- 10. Classify manifests based on format and vocabulary (e.g. RDF/XML using ORE-OAI)
- 11. Record provenance of data gathering

### Post-processing workflow:

- 1. Convert manifests to a unified RDF format (e.g. N-Triples)
- 2. Populate quad store (e.g. Apache Jena) with converted manifests

3.

https://zenodo.org/communities/ro/?page=1&size=20

https://developers.zenodo.org/#metadata-formats

### **Prototype workflow**

A <u>prototype workflow</u> is being developed using <u>Common Workflow Language</u> [20], figure 1 shows how a a community sub-section of the <u>Zenodo</u> repository is being inspected to list the filenames contained within its downloadable ZIP files.

# Figure 1: CWL workflow: List ZIP content for Zenodo community Visualization by CWL Viewer

https://w3id.org/cwl/view/git/4360a062e7cff5aadacbf401e8e743a660657680/code/data-gathering/workflows/zenodo-zip-content.cwl

In brief the prototype workflow consists of these steps:

- 1. For a given Zenodo community, e.g. <a href="https://zenodo.org/communities/ro">https://zenodo.org/communities/ro</a>, retrieve its OAI-PMH entries using DataCite v4 XML e.g. <a href="https://zenodo.org/oai2d?verb=ListRecords&set=user-ro&metadataPrefix=datacite4">https://zenodo.org/oai2d?verb=ListRecords&set=user-ro&metadataPrefix=datacite4</a>
- 2. Extract the URI for the Zenodo record, e.g. <oai:zenodo.org:1484341>
- 3. Search-replace to build the URI of the the corresponding Zenodo landing page, e.g. https://zenodo.org/record/2838898
- 4. Retrieve the HTML of the landing page
- 5. Extract the <u>link relations</u> of type <u>alternate</u> to find the download links
- 6. Filter for download links that end with \*.zip
- 7. Retrieve ZIP file
- 8. List filenames within ZIP file
- 9. Detect filenames like "manifest.rdf" within list and return original Zenodo URI or null (in development)

The workflow and its components have been tested with the reference implementation <code>cwltool</code> [21] which can provide rich provenance captured in CWLProv research objects [22]

In developing this prototype several challenges where immediately detected:

- The <u>OAI-PMH records</u> contain substansive DataCite information, but do not include the links to the Zenodo record or the ZIP downloads. The identifiers for records is in a form that is specific to OAI-PMH, e.g. oai:zenodo.org:1310621 and had to be rewritten to a URI using the same record number.
  - The Zenodo API does include these additional URIs but is not available for anonymous use as it requires a registration token. Distributing this token as part of the workflow provenance would give access to the author's Zenodo account.
- The HTML landing page provides links to structured metadata, e.g. as JSON-LD using Schema.org
   https://zenodo.org/record/1310621/export/schemaorg\_jsonld
   but the structured data is included in a block within HTML
   (for copy-pasting) and not programmatically accessible. HTTP content-negotiation does not give direct access to the structured data. There are no alternate links from the HTML landing page to these "export" pages, so their URIs would have to be manually constructed.
  - The JSON-LD does include links to downloads of ZIP files etc, but only if the Record is of type Dataset in Zenodo, which in JSON-LD is represented as a DataDownload with a contentUrl
- To list filename contained in a ZIP file, the whole file must be downloaded because in the <u>ZIP format</u> the table of content is written at the end of the file
  - The host providing Zenodo downloads do not support the <a href="http://https
  - Some of the dataset downloads are larger than 1 GB
  - cwltool saves all intermediate values until the end of the workflow
- To preserve disk space use during download of ZIP file only, an initial idea was explored of using the CWL <u>streamable</u> feature so that the output of curl could be passed to the utillity <u>sunzip</u> which can extract/inspect ZIP files in a streaming fashion
  - It was found that while the sunzip tool supports streamable extraction and testing based on the intermediate file entry records of the ZIP file, it does not decide or list the filenames before the end of the download. Thus the output of sunzip -t (test extract) itself is not streamable
  - An experimental new feature sunzip -1 was attempted, where file names of records are printed as they are encountered.
     This is at the risk of printing files that have subsequently been deleted from the ZIP file and do not appear in the table of content. This was considered a small risk as the primary purpose was to detect ZIP files containing "manifest-like" files and it was assumed that most deposited ZIP files had been created in a one-off operation and would not have inconsistent file records.
  - The experimental feature however detected that several files found in Zenodo are written with a "deferred length" the intermitting ZIP records do not record their length and so sunzip is unable to find the offset to the next record without actually decompressing the stream.
  - It was found that cwltool --parallel did not seem to start the subsequent step and thus did not facilitate the
     streamable feature. The ZIP files were still saved to disk, and all the ZIP file downloads where completed before any of the
     ZIP extraction was started. Future work will explore using the implementation toil which have been argued to have better
     support for concurrency.

# Conclusions/Discussion

#### **Author contributions**

- Conceptualization:
- Data Curation:
- Formal Analysis:
- Funding Acquisition: SSR, CAG
- Investigation:
- Methodology:
- Project Administration:
- Resources: CAG, SSR
- Software: SSR
- Supervision: PG
- Validation:
- Visualization:
- Writing Original Draft Preparation: SSR
- Writing Review & Editing:

# **Competing interests**

### **Grant Information**

This work has been done as part of the BioExcel CoE (<a href="www.bioexcel.eu">www.bioexcel.eu</a>), a project funded by the European Union contracts <a href="https://excel.eu">H2020-INFRAEDI-02-2018-823830</a>, <a href="https://excel.eu">H2020-EINFRA-2015-1-675728</a>.

#### References

#### 1. Why linked data is not enough for scientists

Sean Bechhofer, Iain Buchan, David De Roure, Paolo Missier, John Ainsworth, Jiten Bhagat, Philip Couch, Don Cruickshank, Mark Delderfield, Ian Dunlop, ... Carole Goble

Future Generation Computer Systems (2013-02) https://doi.org/bgmqrb

DOI: 10.1016/j.future.2011.08.004

### 2. Why Linked Data is Not Enough for Scientists

Sean Bechhofer, John Ainsworth, Jiten Bhagat, Iain Buchan, Philip Couch, Don Cruickshank, David De Roure, Mark Delderfield, Ian Dunlop, Matthew Gamble, ... Shoaib Sufi

2010 IEEE Sixth International Conference on e-Science (2010-12) https://doi.org/cv5tzk

DOI: 10.1109/escience.2010.21

# 3. COMBINE archive and OMEX format: one file to share all information to reproduce a modeling project

Frank T Bergmann, Richard Adams, Stuart Moodie, Jonathan Cooper, Mihai Glont, Martin Golebiewski, Michael Hucka, Camille Laibe, Andrew K Miller, David P Nickerson, ... Nicolas Le Novère

BMC Bioinformatics (2014-12) https://doi.org/gb8wc5

DOI: 10.1186/s12859-014-0369-z · PMID: 25494900 · PMCID: PMC4272562

# 4. ROHub — A Digital Library of Research Objects Supporting Scientists Towards Reproducible Science

Raúl Palma, Piotr Hołubowicz, Oscar Corcho, José Manuel Gómez-Pérez, Cezary Mazurek *Communications in Computer and Information Science* (2014) https://doi.org/gf5m6p

DOI: <u>10.1007/978-3-319-12024-9\_9</u>

### 5. Research Object Bundle 1.0

Stian Soiland-Reyes, Matthew Gamble, Robert Haines Zenodo (2014-11-05) https://doi.org/gf5m6k

DOI: <u>10.5281/zenodo.12586</u>

### 6. Reproducible big data science: A case study in continuous FAIRness

Ravi Madduri, Kyle Chard, Mike D'Arcy, Segun C. Jung, Alexis Rodriguez, Dinanath Sulakhe, Eric Deutsch, Cory Funk, Ben Heavner, Matthew Richards, ... Ian Foster

PLOS ONE (2019-04-11) https://doi.org/gf5m6s

DOI: <u>10.1371/journal.pone.0213013</u> · PMID: <u>30973881</u> · PMCID: <u>PMC6459504</u>

### 7. Datacrate Submisssion To The Workshop On Research Objects

Peter Sefton

Zenodo (2018-07-15) https://doi.org/gf5twt

DOI: 10.5281/zenodo.1445817

### 8. A lightweight approach to research object data packaging

Eoghan Ó Carragáin, Carole Goble, Peter Sefton, Stian Soiland-Reyes

Zenodo (2019-06-20) https://doi.org/gf5twv

DOI: 10.5281/zenodo.3250687

#### 9. Ro-Combine-Archive

Stian Soiland-Reyes, Matthew Gamble Zenodo (2014-04-28) <a href="https://doi.org/gf5m6t">https://doi.org/gf5m6t</a>

DOI: 10.5281/zenodo.10439

### 10. Applying linked data approaches to pharmacology: Architectural decisions and implementation

Gray Alasdair J.G., Groth Paul, Loizou Antonis, Askjaer Sune, Brenninkmeijer Christian, Burger Kees, Chichester Christine, Evelo Chris T., Goble Carole, Harland Lee, ... Williams Antony J.

Semantic Web (2014) https://doi.org/gf5m6j

DOI: 10.3233/sw-2012-0088

#### 11. Preserving Reproducibility: Provenance and Executable Containers in DataONE Data Packages

Bryce Mecum, Matthew B. Jones, Dave Vieglais, Craig Willis

2018 IEEE 14th International Conference on e-Science (e-Science) (2018-10) https://doi.org/gf5m6q

DOI: 10.1109/escience.2018.00019

### 12. DataLab

Yang Zhang, Fangzhou Xu, Erwin Frise, Siqi Wu, Bin Yu, Wei Xu

Proceedings of the 2nd International Workshop on BIG Data Software Engineering - BIGDSE '16 (2016) https://doi.org/gf7hv6

DOI: 10.1145/2896825.2896830

#### 13. CWL Viewer: the common workflow language viewer

Mark Robinson, Stian Soiland-Reyes, Michael R. Crusoe, Carole Goble

F1000Research (2017) https://doi.org/cbq2
DOI: 10.7490/f1000research.1114375.1

# 14. A workflow PROV-corpus based on taverna and wings

Khalid Belhajjame, Jun Zhao, Daniel Garijo, Aleix Garrido, Stian Soiland-Reyes, Pinar Alper, Oscar Corcho

Proceedings of the Joint EDBT/ICDT 2013 Workshops on - EDBT '13 (2013) https://doi.org/gf5m6r

DOI: <u>10.1145/2457317.2457376</u>

# 15. Sharing interoperable workflow provenance: A review of best practices and their practical application in CWLProv

Farah Zaib Khan, Stian Soiland-Reyes, Richard O. Sinnott, Andrew Lonie, Carole Goble, Michael R. Crusoe

Zenodo (2019-07-15) https://doi.org/gf5tg8

DOI: <u>10.5281/zenodo.1208477</u>

### 16. W2Share Case Study: Workflow Research Object (Wro)

Lucas Carvalho, Claudia Bauzer Medeiros Zenodo (2018-10-18) https://doi.org/gf5m6m

DOI: 10.5281/zenodo.1465897

### 17. CWL run of Alignment Workflow (CWLProv 0.6.0 Research Object)

Stian Soiland-Reyes

Mendeley (2018-12-04) https://doi.org/gf5m6h

DOI: 10.17632/6wtpgr3kbj.1

# 18. The Scientific Filesystem

Vanessa Sochat

GigaScience (2018-03-13) https://doi.org/gdwq7f

DOI: 10.1093/gigascience/giy023 · PMID: 29718213 · PMCID: PMC5952957

#### 19. ActivePapers: a platform for publishing and archiving computer-aided research

Konrad Hinsen

F1000Research (2015-07-14) https://doi.org/gfrkvv

DOI: <u>10.12688/f1000research.5773.3</u> · PMID: <u>26064469</u> · PMCID: <u>PMC4448745</u>

#### 20. Common Workflow Language, v1.0

Peter Amstutz, Michael R. Crusoe, Nebojša Tijanić, Brad Chapman, John Chilton, Michael Heuer, Andrey Kartashov, Dan Leehr, Hervé Ménager, Maya Nedeljkovich, ... Luka Stojanovic

Figshare (2016) <a href="https://doi.org/gf6ppg">https://doi.org/gf6ppg</a>
DOI: <a href="https://doi.org/gf6ppg">10.6084/m9.figshare.3115156.v2</a>

# 21. common-workflow-language/cwltool: cwltool 1.0.20190815141648

Peter Amstutz, Michael R. Crusoe, Farah Zaib Khan, Stian Soiland-Reyes, Manvendra Singh, Kapil Kumar, Anton Khodak, John Chilton,

Thomas Hickman, Boysha, ... Ryan Spangler Zenodo (2019-08-15) https://doi.org/gf7s2s

DOI: <u>10.5281/zenodo.3369238</u>

22. Sharing interoperable workflow provenance: A review of best practices and their practical application in CWLProv

Farah Zaib Khan, Stian Soiland-Reyes, Richard O. Sinnott, Andrew Lonie, Carole Goble, Michael R. Crusoe

Zenodo (2019-05-23) https://doi.org/gf7s2r DOI: 10.5281/zenodo.3196309