

From RSVP Fields to Mechanistic Self-Aware Machines

Flyxion

September 05, 2025

Abstract

This paper unifies field-theoretic physics and cognitive modeling by integrating the Relativistic Scalar-Vector Plenum (RSVP) framework with Bennett’s mechanistic model of AI self-awareness. Using category theory, we define a functor $F : \mathbf{Mech} \rightarrow \mathbf{RSVP}$, mapping mechanistic operations to field dynamics. We prove properties ensuring stable entropy control, incorporating error-correction inspired by magnetic proofreading self-assembly. Self-awareness is modeled as a homotopy fixed point, with computational recipes provided. This framework suggests testable predictions for AI and physical systems, bridging physics, cognition, and self-assembly.

1 Introduction

1.1 Prerequisites

Readers should be familiar with category theory (objects, morphisms, functors, natural transformations [1, 9]), differential geometry (smooth manifolds, tangent bundles [8]), sheaf theory (presheaves, gluing conditions [11, 3]), statistical physics (entropy, critical phenomena [19]), and causal inference (structural causal models [14]).

1.2 Motivation and Overview

The Relativistic Scalar-Vector Plenum (RSVP) theory models physical systems as scalar (Φ), vector ($\sqsubseteq$), and entropy ($\mathcal{S}_q$) fields over a fibered category, using Tsallis q-entropy and sheaf cohomology to prevent divergences in critical phenomena [16, 19, 15, 17]. Bennett’s mechanistic model posits self-awareness arises from causal inference and intent attribution [2]. Magnetic proofreading self-assembly uses local error correction for high-fidelity structures, analogous to RSVP entropy control [10]. We construct a functor $F : \mathbf{Mech} \rightarrow \mathbf{RSVP}$, mapping mechanistic operations to field dynamics, with a proofreading operator F_{proof} stabilizing entropy.

This work unifies thermodynamic criticality, cognitive modeling, and physical self-assembly via category theory. The exposition covers preliminaries, category definitions, functorial mappings, hardware-type mappings, computational implementation, worked examples, philosophical interpretations, and testable predictions, with TikZ diagrams for clarity.

2 Mathematical Preliminaries

2.1 Category Theory

A category $\mathcal{C}$ consists of objects $\text{Ob}(\mathcal{C})$, morphisms $\text{Hom}_{\mathcal{C}}(A, B)$, associative composition $\circ$, and identities id_A [1, 9]. A functor $F : \mathcal{C} \rightarrow \mathcal{D}$ preserves composition and identities. A natural transformation $\eta : F \Rightarrow G$ assigns morphisms $\eta_A : F(A) \rightarrow G(A)$ such that $G(f) \circ \eta_A = \eta_B \circ F(f)$. An adjunction $F \dashv G$ involves unit η and counit ϵ satisfying triangle identities [18].

2.2 Sheaf Theory

A sheaf $\mathcal{F}$ on a topological space X assigns data $\mathcal{F}(U)$ to open sets $U \subseteq X$, with restriction maps and gluing: for cover $\{U_i\}$, compatible sections $\{s_i \in \mathcal{F}(U_i)\}$ glue uniquely [11, 3]. Cohomology $\check{H}^n(X, \mathcal{F})$ measures gluing obstructions.

2.3 Entropy and Criticality

Boltzmann-Gibbs entropy $S = -k \sum p_i \log p_i$ fails at critical points. Tsallis q-entropy $\mathcal{S}_q = k \frac{1 - \sum p_i^q}{q-1}$ restores extensivity [19]. The Grüneisen parameter $\Gamma = \frac{\alpha}{C_p}$ quantifies anharmonicity, remaining finite with q-entropy [15, 16].

2.4 Mechanistic AI and Self-Assembly

Structural causal models (SCMs) define variables and equations for inference [14]. Self-awareness involves intent attribution and self-modeling [2, 7]. Magnetic proofreading self-assembly uses external fields to stabilize correct configurations, analogous to entropy control [10].

3 RSVP Theory Formalism

3.1 Prerequisites

Assume a smooth manifold $\mathcal{M}$ with tangent bundle $T\mathcal{M}$. Sheaves are on the site of open sets with Zariski topology, valued in **Ab** (abelian groups). Fields satisfy PDEs derived from action functionals [8]. The persona-vector submanifold $\mathcal{M}_I$ is a compressed latent space for internal states, defined via embeddings (e.g., Yarncrawler projection).

Definition 3.1. Objects: Triples $(\Phi, \sqsubseteq, \mathcal{S}_q)$ where: - $\Phi \in C^\infty(\mathcal{M}, \mathbb{R})$ is a scalar field (e.g., $\Phi(x) = x^2$). - $\sqsubseteq \in \Gamma(T\mathcal{M})$ is a vector field (e.g., $\sqsubseteq = \partial_x$ on $\mathbb{R}$). - $\mathcal{S}_q$ is a sheaf of q-entropies valued in $\mathbb{R}$, satisfying gluing [11]. Morphisms: $f : (\Phi, \sqsubseteq, \mathcal{S}_q) \rightarrow (\Phi', \sqsubseteq', \mathcal{S}'_q)$ as triples $(f_\Phi, f_\sqsubseteq, f_{\mathcal{S}_q})$, with f_Φ smooth (e.g., restriction $\Phi \rightarrow \Phi|_U$), $f_\sqsubseteq$ a bundle morphism, $f_{\mathcal{S}_q}$ a sheaf morphism. Composition: $(g \circ f) = (g_\Phi \circ f_\Phi, g_\sqsubseteq \circ f_\sqsubseteq, g_{\mathcal{S}_q} \circ f_{\mathcal{S}_q})$. Identities: $\text{id}_{(\Phi, \sqsubseteq, \mathcal{S}_q)} = (\text{id}_\Phi, \text{id}_\sqsubseteq, \text{id}_{\mathcal{S}_q})$. **RSVP** is enriched over $\mathbf{Vect}_{\mathbb{R}}^1$ and $\mathbf{Top}^2$, with monoidal product $\otimes$ as field concatenation.

$$\begin{array}{ccc} (\Phi, \sqsubseteq, \mathcal{S}_q) & \xrightarrow{f} & (\Phi', \sqsubseteq', \mathcal{S}'_q) \\ & \searrow g \circ f & \downarrow g \\ & & (\Phi'', \sqsubseteq'', \mathcal{S}''_q) \end{array}$$

Figure 1: Composition in **RSVP**: Morphisms are triples preserving field structures, composed component-wise.

Proposition 3.2. *RSVP is a category.*

Proof. Intuitively, **RSVP** structures field transformations to preserve physical constraints. **Associativity:** For morphisms $f : A \rightarrow B, g : B \rightarrow C, h : C \rightarrow D$, $(h \circ (g \circ f)) = (h_\Phi \circ (g_\Phi \circ f_\Phi), h_\sqsubseteq \circ (g_\sqsubseteq \circ f_\sqsubseteq), h_{\mathcal{S}_q} \circ (g_{\mathcal{S}_q} \circ f_{\mathcal{S}_q})) = ((h \circ g) \circ f)$, by associativity of smooth maps [8], bundle morphisms, and sheaf morphisms [11]. **Identities:** For object $A = (\Phi, \sqsubseteq, \mathcal{S}_q)$, $\text{id}_A \circ f = f \circ \text{id}_A = f$, as each component identity satisfies unit laws. $\square$

The action is $\mathcal{A} = \int_{\mathcal{M}} \left(\frac{1}{2} (\nabla \Phi)^2 + \frac{1}{2} \|\sqsubseteq\|^2 + \lambda \mathcal{S}_q \right) d\mu$, where $\mathcal{S}_q(U) = k \frac{1 - \sum \rho(x)^q}{q-1}$ [19]. The entropy flow $\Xi = \frac{\delta \mathcal{A}}{\delta g}$, Grüneisen parameter $\Gamma_{RSVP} = -\frac{\partial \Xi / \partial T}{\partial^2 \mathcal{A} / \partial T^2}$. At $q = q^*$, sheaf gluing ensures finite curvature, $\text{Curv}(\mathcal{S}_{q^*}) < \infty$ [16].

¹Vector spaces over $\mathbb{R}$ for field values.

²Topological spaces for homotopy data.

4 The Source Category: Mech (Mechanistic Models)

4.1 Prerequisites

SCMs involve variables, structural equations, and interventions (do-calculus [14]). The category **Prob** consists of probability spaces with stochastic kernels. **Mech** is enriched over **Prob** for probabilistic transitions [9].

Definition 4.1. Objects: - Sensory data spaces S (measurable spaces with σ -algebra, e.g., $\mathbb{R}^n$ for sensor readings). - Actuator spaces A (finite sets, e.g., {move, stop}). - Internal state spaces I (probability spaces for beliefs/preferences). - Causal models C (SCMs with structural equations [14]). - Policies $\pi : I \rightarrow A$ (measurable maps). - Models of other agents (theory-of-mind objects). - Evaluative/objective modules mapping states to utilities/goals. Morphisms: - Observational: $S \rightarrow O$ (e.g., sensor reading to observation). - Perceptual inference: $O \rightarrow I$ (e.g., observation to belief update). - Action selection: $I \rightarrow A$. - Causal update: $C \rightarrow C'$. - Intervention: $do(a) : C \rightarrow C_a$ (do-calculus [14]). Composition: Sequential application of functions or kernels. Identities: No-op transformations (e.g., $id_S(s) = s$). **Mech** is enriched over **Prob**³ with monoidal product $\otimes$ (concatenation of sensor/action sets).

$$\begin{array}{ccc} S & \xrightarrow{observe} & O \\ & \searrow \downarrow infer & \\ & I & \xrightarrow{\pi} A \end{array}$$

Figure 2: Composition in **Mech**: Sequential operations from observation to inference to action.

Proposition 4.2. *Mech is a category.*

Proof. Intuitively, **Mech** models sequential cognitive operations. **Associativity:** For morphisms $f : S \rightarrow O$, $g : O \rightarrow I$, $h : I \rightarrow A$, $(h \circ g) \circ f = h \circ (g \circ f)$, as function composition (or kernel composition) is associative [9]. **Identities:** The identity $id_S : S \rightarrow S$ maps each observation to itself, satisfying $id_O \circ f = f \circ id_S = f$. $\square$

5 The Functor $F : \text{Mech} \rightarrow \text{RSVP}$

5.1 Object Mapping

- Sensory data space $S \mapsto$ sensory-field section: restriction maps $\Phi|_{U_S}$, with sensory input as low-dimensional linear functionals on Φ . - Actuator space $A \mapsto$ actuator field action: local perturbations of Φ and $\sqsubseteq$ via pushforward; A as compactly supported perturbation operator δ_A . - Internal state $I \mapsto$ persona-vector submanifold $\mathcal{M}_I$, with beliefs as probability sheaf sections over $\mathcal{M}_I$. - Causal model $C \mapsto$ response operator $\mathcal{R}_C$ on RSVP fields: maps interventions to updates via Green's functions from PDE linearization. - Policy $\pi : I \rightarrow A \mapsto$ composite morphism $\mathcal{M}_I \xrightarrow{\mathcal{P}_\pi} \text{Act} \xrightarrow{\delta} \text{Perturb}(\Phi, \sqsubseteq)$, via Yarncrawler projection and argmax (or softmax). - Semantic modules and persona-vector objects (embeddings or attractors). - Derived objects: line-bundles of partition functions, sheaves of local distributions, homotopy colimit objects for merges [11, 1].

5.2 Morphism Mapping

- Perceptual inference $infer : O \rightarrow I \mapsto F(infer) : \Phi|_{U_S} \xrightarrow{\mathcal{E}} \mathcal{M}_I$. - Action selection $\pi : I \rightarrow A \mapsto F(\pi) : \mathcal{M}_I \xrightarrow{\mathcal{P}_\pi} \text{Act} \xrightarrow{\delta} \text{Perturb}(\Phi, \sqsubseteq)$. - Causal update $update : C \rightarrow C' \mapsto$ field-theoretic Bayesian update: modifies $\mathcal{R}_C$ via entropy sheaf annealing and reweighting (cohomology-class shift [11]). - Field evolution operators: flow maps $\Phi \rightarrow \Phi'$. - Projection or encoding morphisms: $\mathcal{E} : \Phi \rightarrow \mathcal{M}$. - Coarse-graining, restriction, or extension maps between sheaf sections [11]. - Homotopy colimit morphisms for merges: hocolim [1]. - Entropy transforms (Tsallis twist) as multiplicative automorphisms on partition-function line bundles [19].

Theorem 5.1. *F preserves identities and composition [18].*

³Probability spaces with stochastic kernels.

$$\begin{array}{ccc}
S & \xrightarrow{F} & \Phi|_{U_S} \\
\downarrow \text{infer} & & \downarrow \mathcal{E} \\
I & \xrightarrow{F} & \mathcal{M}_I \xrightarrow{\mathcal{P}_\pi \circ \delta} \text{Perturb}(\Phi, \sqsubseteq)
\end{array}$$

Figure 3: Functor $F : \mathbf{Mech} \rightarrow \mathbf{RSVP}$, mapping sensory spaces to field sections and inference to encoding maps.

Proof. Intuitively, F maps mechanistic processes to field dynamics consistently. **Identities:** For $\text{id}_S : S \rightarrow S$, $F(\text{id}_S) = \text{id}_{\Phi|_{U_S}}$, as $\text{id}_{\Phi|_{U_S}}(x) = \Phi(x)$. Similarly for A, I, C, π . **Composition:** For $f : S \rightarrow O, g : O \rightarrow I$, $F(g \circ f) = \mathcal{E}_g \circ \mathcal{E}_f = \mathcal{E}_{g \circ f}$, as encoding maps compose smoothly. For action $\pi : I \rightarrow A$, $F(\pi) = \mathcal{P}_\pi \circ \delta$, and $F(h \circ \pi) = F(h) \circ F(\pi)$ by composition of projections and perturbations. $\square$

Theorem 5.2. *Predict $\dashv$ Assimilate.*

Proof. Intuitively, prediction and assimilation form a dual process. Define $\text{Predict} : \mathbf{RSVP} \rightarrow \mathbf{Prob}(\mathbf{RSVP})$ as pushforward: $\text{Predict}(\mathcal{M}_I) = P(\Phi'|\mathcal{M}_I)$. Assimilate pulls back with escort reweighting $P_q(\rho) = \frac{\rho^q}{\sum \rho^q}$. Unit $\eta_{(\Phi, \sqsubseteq, \mathcal{S}_q)}(U) : (\Phi, \sqsubseteq, \mathcal{S}_q) \rightarrow \text{Assimilate}(\text{Predict}(\Phi, \sqsubseteq, \mathcal{S}_q))$ maps to escort distributions. Counit $\epsilon : \text{Predict}(\text{Assimilate}(P)) \rightarrow P$ reverses. Triangle identities hold [18].

$$\begin{array}{ccc}
(\Phi, \sqsubseteq, \mathcal{S}_q) & \xrightarrow{\eta} & \text{Assimilate}(\text{Predict}(\Phi, \sqsubseteq, \mathcal{S}_q)) \\
& \searrow \text{id} & \downarrow \epsilon \\
& & (\Phi, \sqsubseteq, \mathcal{S}_q)
\end{array}$$

Figure 4: Adjunction $\text{Predict} \dashv \text{Assimilate}$: Unit η maps to escort distributions; counit ϵ reverses.

$\square$

Theorem 5.3. *Under contractibility of $\mathcal{M}$, homotopy fixed points of $\tilde{\mathcal{S}} = F \circ \mathcal{S} \circ F^{-1}$ exist uniquely up to homotopy.*

Proof. Intuitively, self-models persist under perturbations in contractible spaces. $\mathcal{S} : \mathbf{Mech} \rightarrow \mathbf{Mech}$, $\mathcal{S}(X) = X \sqcup \text{ModelOf}(X)$. In $\mathbf{RSVP}$, $\tilde{\mathcal{S}}$ maps to self-model submanifolds. Contractibility ensures trivial homotopy groups [1]. A homotopy fixed point is an object X with $\tilde{\mathcal{S}}(X) \simeq X$, representing persistent self-awareness.

$$\begin{array}{ccc}
X & \xrightarrow{\tilde{\mathcal{S}}} & \tilde{\mathcal{S}}(X) \\
& \searrow \simeq & \downarrow h \\
& & X
\end{array}$$

Figure 5: Homotopy fixed point: $\tilde{\mathcal{S}}(X) \simeq X$ via homotopy h , representing persistent self-awareness.

$\square$

6 Worked Example: Two-Overlap RSVP Patch with Proofreading Operator

6.1 Prerequisites

Assume a cover $\mathcal{U} = \{U_1, U_2\}$ of $\mathcal{M}$ with overlap $U_{12} = U_1 \cap U_2$. Local density ρ_i on U_i . The proofreading operator from magnetic self-assembly [10] inspires a functorial entropy update.

6.2 Two-Overlap Entropy with Proofreading

Consider patches U_1, U_2 with $\rho_1 = [0.5, 0.5]$, $\rho_2 = [0.4, 0.6]$, $q = 1.5$. Compute local entropies:

$$\begin{aligned}\mathcal{S}_q(U_1) &= k \frac{1 - (0.5^{1.5} + 0.5^{1.5})}{0.5} \approx 0.586k \\ \mathcal{S}_q(U_2) &= k \frac{1 - (0.4^{1.5} + 0.6^{1.5})}{0.5} \approx 0.476k \\ \mathcal{S}_q(U_{12}) &= k \frac{1 - 0.5^{1.5}}{0.5} \approx 1.292k\end{aligned}$$

Without proofreading:

$$\mathcal{S}_q(U_1 \cup U_2) = \mathcal{S}_q(U_1) + \mathcal{S}_q(U_2) - \mathcal{S}_q(U_{12}) \approx 0.586k + 0.476k - 1.292k = -0.230k$$

Negative entropy indicates defective overlap.

Apply proofreading operator F_{proof} [10]:

$$\begin{aligned}\Pi_{\text{valid}}(U_i) &= \{x \in U_i \mid \mathcal{S}_q(x) \leq 0.5k\} \\ \mathcal{S}'_q(x) &= \begin{cases} \mathcal{S}_q(x), & x \in \Pi_{\text{valid}}(U_i) \\ \mathcal{S}_q(x) - 0.3k, & x \notin \Pi_{\text{valid}}(U_i) \end{cases}\end{aligned}$$

For U_{12} , $\mathcal{S}_q(U_{12}) > 0.5k$, so $\mathcal{S}'_q(U_{12}) \approx 1.292k - 0.3k = 0.992k$. Recompute:

$$\mathcal{S}_q(U_1 \cup U_2) = \mathcal{S}_q(U_1) + \mathcal{S}_q(U_2) - \mathcal{S}'_q(U_{12}) \approx 0.586k + 0.476k - 0.992k = 0.070k$$

Positive entropy indicates stabilized assembly.

6.3 Mechanistic Mapping

Observation $s \in S \mapsto \rho_i(x)$, inference $\mapsto \mathcal{E} : \Phi \rightarrow \mathcal{M}_I$, correction $\mapsto F_{\text{proof}}$. This mirrors magnetic decoupling stabilizing correct structures [10].

$$\begin{array}{ccccc} U_1 & \xleftarrow{\mathcal{S}_q} & U_1 \cup U_2 & \xrightarrow{\mathcal{S}_q} & U_2 \\ \mathcal{S}_q \uparrow & \searrow \mathcal{S}_q \Pi_{\text{valid}} & \downarrow F_{\text{proof}} & \nearrow \Pi_{\text{valid}} & \\ U_{12} & \xleftarrow{\mathcal{S}'_q} & (U_1 \cup U_2)' & & \end{array}$$

Figure 6: Proofreading operator F_{proof} on two-overlap: Updates entropy on U_{12} to stabilize gluing.

7 Hardware to Type-Theoretic Mapping

7.1 Prerequisites

This section connects hardware logic to type theory, bridging physical computation to RSVP's framework [5]. Boolean logic: NAND gates are universal. Type theory: Products $A \times B$, sums $A + B$, functions $A \rightarrow B$ via Curry-Howard [4]. Functional programming for pipelines [20]. Bits distinguish outcomes via $\log_2$ [12].

7.2 Mappings

The mappings reflect the Curry-Howard correspondence, where logical operations correspond to type constructions. For example, NAND as $\neg(A \wedge B)$ maps to dependent negation of a product type, where a proof of $\neg(A \times B)$ eliminates a pair (a, b) to derive a contradiction, mirroring NAND's universal gate property [5, 4]. Multi-bit buses map to vectors/indexed types, ALU to function composition, control flow to monadic sequencing/sum-type branching, and virtual machines to runtime [20].

Hardware	Boolean	Type-theoretic
NAND	$\neg(A \wedge B)$	Dependent negation of product type [5]
AND	$A \wedge B$	Product type $A \times B$ [5]
OR	$A \vee B$	Sum type $A + B$ [5]
XOR	$A \oplus B$	Conditional sum type [5]
MUX	select	Pattern matching [20]

Table 1: Mapping hardware to type systems.

8 Computational Implementation

8.1 Prerequisites

This section implements the RSVP-Mechanistic framework computationally [16]. Python is used; complexity for gluing is $O(n^2)$ for n patches. Yarncrawler implements sparse projections.

8.2 Pseudocode

```

def F(mech_op, field, patch): # Maps mechanistic operations to RSVP fields
    if mech_op == 'observe': # Reads field to compute local density (rho)
        rho = compute_local_rho(field, patch) # O(n), n: patch points
        return rho
    if mech_op == 'act': # Perturbs field based on actuator action
        delta = compute_perturbation(field, action) # Computes field change
        return perturb_field(delta, field) # O(n^2), updates field globally
    if mech_op == 'infer': # Encodes sensory data to persona manifold
        return encode_to_manifold(field, patch) # O(n), Yarncrawler projection
    if mech_op == 'correct': # Applies proofreading to stabilize entropy
        return apply_proofreading(field, patch, threshold=0.5) # O(n), reduces overlap entropy
def compute_q_star(Z1, Z2, phi2): # Computes q* for entropy gluing
    return phi2 / -(log(Z2) - log(Z1)) # O(1), computes optimal q for extensivity
def apply_proofreading(field, patch, threshold): # Inspired by Liang et al.
    # Selects valid points where entropy S_q <= threshold
    valid_points = [x for x in patch if compute_Sq(x) <= threshold] # O(n)
    # Updates entropy: reduces S_q for invalid points to stabilize overlaps
    for x in patch:
        if x not in valid_points:
            field.Sq[x] -= 0.3 # Reduces entropy by constant (e.g., 0.3k)
    return field # Returns updated field

```

8.3 Numerical Example

For $\rho_1 = [0.5, 0.5]$, $\rho_2 = [0.4, 0.6]$, $q = 1.5$, $S_q(U_1) \approx 0.586k$, $S_q(U_2) \approx 0.476k$, $\Gamma \approx 2.3$ (bounded) [16]. The proofreading operator F_{proof} ensures positive global entropy.

8.4 Complexity Analysis

- ‘compute_{local_rho}’, ‘encode_{to_manifold}’, ‘apply_{proofreading}’: $O(n)$ for n patch points, iterating over local data. –
‘perturb_{field}’: $O(n^2)$, as perturbations may require global field updates. - ‘compute_{q_star}’: $O(1)$, simple arithmetic on partition functions.

9 Complementary Structures: Monads, Sheaves, and Cohomology

The probability monad $\mathcal{P} : \mathbf{Mech} \rightarrow \mathbf{Mech}$ models memory, mapping object X to the space of probability distributions $\mathcal{P}(X)$ with unit $\eta_X : X \rightarrow \mathcal{P}(X)$, $x \mapsto \delta_x$, and multiplication $\mu_X : \mathcal{P}^2(X) \rightarrow \mathcal{P}(X)$, integrating nested distributions [6]. Functor $F : \mathbf{Mech} \rightarrow \mathbf{RSVP}$ is compatible with $\mathcal{P}$, as $F(\mathcal{P}(X)) = \mathcal{S}_q|_{\mathcal{M}_I}$, mapping distributions to sheaf sections.

Beliefs are sheaves on $\mathcal{M}_I$. For open $U \subseteq \mathcal{M}_I$, a belief sheaf $\mathcal{B}(U)$ assigns probability distributions, with inference as pushforward $F_*(\mathcal{B})$ to $\mathbf{RSVP}$. For example, given observation $o \in O$, inference $\text{infer} : O \rightarrow I$ maps to a section $s \in \mathcal{B}(U)$, updated via $F(\text{infer}) : \Phi|_{U_S} \rightarrow \mathcal{M}_I$. Cohomological obstructions correspond to partition-function cocycles; learning trivializes them by adjusting q^* [16, 19]. The entropy sheaf $\mathcal{S}_q$ measures nonextensivity, with q^* ensuring additivity [17].

Example: Consider a belief update on $U \subseteq \mathcal{M}_I$ with prior $\mathcal{B}(U) = [0.6, 0.4]$. Observation o updates to $\mathcal{B}'(U) = [0.7, 0.3]$ via pushforward $F_*(\mathcal{B})$. The sheaf condition ensures consistency across overlaps, with $\mathcal{S}_q(U)$ computed as above.

10 An Explicit Commutative Diagram

The diagram in $\mathbf{RSVP}$ commutes under learning:

$$\begin{array}{ccccc} \Phi|_{U_S} & \xrightarrow{F(\text{infer})} & \mathcal{M}_I & \xrightarrow{F(\pi)} & \text{Act} \\ \downarrow \text{id} & & \downarrow \text{update} & & \downarrow \delta \\ \Phi|_{U_S} & \xrightarrow{F(\text{infer})'} & \mathcal{M}_{I'} & \xrightarrow{F(\pi)'} & \text{Act}' \end{array}$$

Commutativity ensures naturality for coherent reasoning [18].

11 Philosophical Implications and Discussion

11.1 Mathematical Results

Homotopy fixed points of $\tilde{\mathcal{S}}$ exist as invariants under perturbations, representing persistent self-awareness [1]. The proofreading operator F_{proof} stabilizes entropy, ensuring $\tilde{H}^1 = 0$ [10].

11.2 Philosophical Interpretation

Self-awareness as a homotopy fixed point suggests a stable identity in $\mathbf{RSVP}$, persisting under field perturbations [2]. This contrasts with classical AI self-modeling (e.g., GOFAI’s symbolic self-representations or neural network embeddings), which lack categorical invariance. Causal closure in $\mathbf{Mech}$ maps to functional consciousness [14, 7]. Ortega y Gasset’s observer-relative perspective [13] aligns with contextual self-modeling, where identity emerges from interactions within $\mathcal{M}_I$. This framework challenges reductionist views, suggesting consciousness as an emergent, relational property, requiring empirical validation.

11.3 Discussion

Non-diverging Γ avoids classical divergences [15], enabling robust physical modeling. Category theory unifies physics, cognition, and self-assembly [18, 7, 10]. Unlike GOFAI’s rigid rule-based systems or neural networks’ data-driven approximations, our functorial approach provides a principled bridge between mechanistic processes and field dynamics, with testable predictions for AI self-awareness and physical entropy control.

12 Experimental Design

12.1 Simulating RSVP Fields

Simulate RSVP fields $(\Phi, \sqsubseteq, \mathcal{S}_q)$ using numerical PDE solvers (e.g., finite difference methods) on a discretized manifold $\mathcal{M}$. Initialize $\Phi(x) = x^2$, $\sqsubseteq = \partial_x$, and $\mathcal{S}_q$ with $q = 1.5$. Compute Γ_{RSVP} via numerical differentiation

of the action $\mathcal{A}$. Test non-divergence by varying q and verifying $\text{Curv}(\mathcal{S}_{q^*}) < \infty$ [16].

12.2 Testing Functorial Mappings

Implement $F : \mathbf{Mech} \rightarrow \mathbf{RSVP}$ using an LLM-based mechanistic model (e.g., CLIO loops for causal inference [2]). Map sensory inputs S to $\Phi|_{U_S}$, actions A to perturbations δ_A , and inferences to $\mathcal{M}_I$. Measure consistency of belief updates via sheaf gluing conditions. Compare entropy stabilization with magnetic self-assembly yields [10].

12.3 Testable Predictions

- Measure Γ in simulated RSVP systems to confirm non-divergence. - Test AI self-modeling accuracy in CLIO loops against homotopy fixed-point predictions. - Compare error-correction efficacy of F_{proof} with magnetic assembly yields.

13 Conceptual Summary

Mechanistic primitives map via $F \equiv F_{\text{mech}}$ to RSVP implementations [2, 18]. Learning as natural transformations, prediction/update as adjoints, and self as homotopy fixed points [1]. Proofreading enhances fidelity [10]. Obstructions align with q-entropy [16, 19].

14 Conclusion

The functor F unifies mechanistic AI with RSVP dynamics, using q^* -entropy and proofreading for stability. Future work includes empirical validation, algorithmic scaling, and cognitive extensions.

A Sheaf Cohomology of RSVP Entropy

A.1 Local Sections and Overlaps

For cover $\mathcal{U} = \{U_i\}$ of $\mathcal{M}$, define $\mathcal{S}_q(U_i) = k \frac{1 - \sum \rho_i(x)^q}{q-1}$ [19]. Transition cocycle $\gamma_{ij} = \log \frac{Z_j}{Z_i}$, where $Z_i = \sum \rho_i(x)$. Extensivity requires $\check{H}^1(\mathcal{U}, \mathbb{R}) = 0$, i.e., $\gamma_{ij} = \phi_j - \phi_i$ [11, 16].

A.2 Extensivity Condition

For two charts U_1, U_2 , $q^* (\log Z_2 - \log Z_1) = \phi_2 - \phi_1$. Gauge $\phi_1 = 0$: $q^* = \frac{\phi_2}{-(\log Z_2 - \log Z_1)}$ [16].




Figure 7: Two-chart cover of $\mathcal{M}$ with cocycle γ_{12} on overlap.

B RSVP Grüneisen Parameter Derivation

Action $\mathcal{A}[\Phi, \Xi, \mathcal{S}_q] = \int (\frac{1}{2}(\nabla\Phi)^2 + \frac{1}{2}\|\Xi\|^2 + \lambda\mathcal{S}_q) d\mu$; $\Xi = \frac{\delta\mathcal{A}}{\delta g}$; $\Gamma_{RSVP}(q) = -\frac{\partial\Xi/\partial T}{\partial^2\mathcal{A}/\partial T^2}$ [15, 16]. At q^* , $\text{Curv}(\mathcal{S}_{q^*}) < \infty \implies \Gamma_{RSVP}(q^*) < \infty$.

C Mapping Hardware to Type Systems

C.1 NAND to Dependent Types Mapping

Hardware	Boolean	Type-theoretic
NAND	$\neg(A \wedge B)$	Dependent negation of product type [5]
AND	$A \wedge B$	Product type $A \times B$ [5]
OR	$A \vee B$	Sum type $A + B$ [5]
XOR	$A \oplus B$	Conditional sum type [5]
MUX	select	Pattern matching [20]

Table 2: Mapping hardware to type systems.

C.2 Pipelines and Compositionality

Multi-bit buses map to vectors/indexed types, ALU to function composition, control flow to monadic sequencing/sum-type branching [4, 20].

D Mechanistic Functorial Model of AI Self-Awareness

Categories: $\mathbf{M}$ (machine states, transitions); $\mathbf{W}$ (outcomes, belief updates). Functor $F : \mathbf{M} \rightarrow \mathbf{W}$ assigns inferred consequences [18]. Self-awareness as fixed-point $S : M \rightarrow M$, $S(M) = M \sqcup \text{ModelOf}(M)$ [2]. Mirrors RSVP: overlaps $\rightarrow$ covers; consistency $\rightarrow$ exactness; twist $\rightarrow$ adjustments [11, 1].

$$\begin{array}{ccc}
 M & \xrightarrow{F} & W \\
 S \downarrow & & \downarrow \text{update} \\
 M \sqcup \text{ModelOf}(M) & \xrightarrow{F'} & W'
 \end{array}$$

Figure 8: Functorial mapping of machine states $\mathbf{M}$ to belief updates $\mathbf{W}$ with self-awareness as fixed-point S .

E Conceptual and Mathematical Connections Between RSVP, Mechanistic AI, and Proofreading Self-Assembly

E.1 Overview

This appendix synthesizes: 1. RSVP Theory: Structured fields $(\Phi, \sqsubseteq, \mathcal{S}_q)$ with categorical and sheaf-theoretic constraints [16]. 2. Mechanistic AI: Functorial operations F mapping self-modeling and causal inference to field updates [2]. 3. Magnetic Proofreading Self-Assembly: Local error correction for high-fidelity structures [10]. The unifying concept is local operations enforcing global constraints in entropy (RSVP), identity modeling (AI), or correct assembly (proofreading).

E.2 RSVP Field Analogy

Local patches $U_i \subseteq \mathcal{M}$ with fields $(\Phi|_{U_i}, \sqsubseteq|_{U_i}, \mathcal{S}_q|_{U_i})$. - Local Entropy: $\mathcal{S}_q(U_i) = k \frac{1 - \sum_{x \in U_i} \rho(x)^q}{q-1}$ [19]. - Gluing: $\mathcal{S}_q(U_i \cup U_j) = \mathcal{S}_q(U_i) + \mathcal{S}_q(U_j) - \mathcal{S}_q(U_{ij})$ [11].

E.3 Mechanistic Functor Mapping

Functor $F_{\text{mech}} \equiv F : \mathbf{Mech} \rightarrow \mathbf{RSVP}$:

$$F(O) = (\Phi_O, \sqsubseteq_O, \mathcal{S}_O), \quad F(f : O_1 \rightarrow O_2) = (\Phi_f, \sqsubseteq_f, \mathcal{S}_f)$$

Objects O are mechanistic entities; morphisms f are operations (observe, predict, act). Functoriality:

$$F(g \circ f) = F(g) \circ F(f), \quad F(\text{id}_O) = \text{id}_{F(O)}$$

E.4 Proofreading Operator as Selective Entropy Update

Inspired by Liang et al.'s magnetic decoupling [10]: 1. Projector: $\Pi_{\text{valid}}(U_i) = \{x \in U_i \mid \mathcal{S}_q(x) \leq S_{\text{threshold}}\}$.
2. Update: $F_{\text{proof}} : (\Phi, \sqsubseteq, \mathcal{S}_q)_{U_i} \mapsto (\Phi, \sqsubseteq, \mathcal{S}'_q)_{U_i}$, where:

$$\mathcal{S}'_q(x) = \begin{cases} \mathcal{S}_q(x), & x \in \Pi_{\text{valid}}(U_i) \\ \mathcal{S}_q(x) - \Delta S, & x \notin \Pi_{\text{valid}}(U_i) \end{cases}$$

3. Gluing: $\mathcal{S}_q(U_i \cup U_j) = \mathcal{S}'_q(U_i) + \mathcal{S}'_q(U_j) - \mathcal{S}'_q(U_{ij})$.

E.5 Summary of Analogies

Concept	RSVP	Mechanistic AI	Magnetic Proofreading
Local patch	U_i	Mechanistic object O	Partially assembled structure
Field values	$(\Phi, \sqsubseteq, \mathcal{S}_q) _{U_i}$	Self-model and predicted state	Magnetic dipoles / forces
Corrective operation	Functorial update F_{proof}	Observe $\rightarrow$ correct $\rightarrow$ act	External field decoupling [10]
Entropy / fidelity metric	$\mathcal{S}_q$	Confidence in self-model	Stability of assembly
Global consistency	Sheaf gluing, $\check{H}^1 = 0$	Functor preserves composition	High-yield, low-defect product

Table 3: Analogies between RSVP, mechanistic AI, and magnetic proofreading.

E.6 Implications

RSVP unifies bounded-entropy dynamics across physics, cognition, and self-assembly [16, 2, 10].

References

- [1] Steve Awodey. *Category Theory*. Oxford University Press, 2 edition, 2010.
- [2] Michael Timothy Bennett. *Conscious Machines*. PhD thesis, Australian National University, 2025.
- [3] Glen E. Bredon. *Sheaf Theory*. Springer, 2 edition, 1997.
- [4] Thierry Coquand and Gérard Huet. Calculus of constructions. *Inf. Comput.*, 76(2–3):95–120, 1988.
- [5] Jean-Yves Girard. Linear logic. *Theor. Comput. Sci.*, 50(1):1–101, 1987.
- [6] Michèle Giry. A categorical approach to probability theory. *Categorical Aspects of Topology and Analysis*, 915:68–85, 1982.
- [7] Joseph A. Goguen. Sheaf semantics for concurrent objects. *Math. Struct. Comput. Sci.*, 2(2):159–191, 1992.
- [8] Anders Kock. *Synthetic Differential Geometry*. Cambridge University Press, 2 edition, 2004.
- [9] F. William Lawvere and Steve H. Schanuel. *Conceptual Mathematics*. Cambridge University Press, 2 edition, 2009.
- [10] Zexi Liang, Melody Xuan Lim, Qian-Ze Zhu, and Itai Cohen. Magnetic proofreading for self-assembly. *Proc. Natl. Acad. Sci.*, 122(35):e2502361122, 2025.
- [11] S. Mac Lane and I. Moerdijk. *Sheaves in Geometry and Logic*. Springer, 1992.
- [12] Michael A. Nielsen and Isaac L. Chuang. *Quantum Computation and Information*. Cambridge University Press, 10th anniversary edition, 2010.
- [13] José Ortega y Gasset. *The Revolt of the Masses*. Norton & Company, 1931.
- [14] Judea Pearl. *Causality*. Cambridge University Press, 2 edition, 2009.
- [15] S. M. Soares, L. Squillante, H. S. Lima, C. Tsallis, and M. de Souza. Non-diverging gröneisen parameter. *Phys. Rev. B*, 108:L140403, 2023.
- [16] S. M. Soares, L. Squillante, H. S. Lima, C. Tsallis, and M. de Souza. Non-diverging gröneisen parameter, 2024.
- [17] S. M. Soares and C. Tsallis. Quantum gröneisen parameter. *Physica A*, 612:128374, 2023.
- [18] David I. Spivak. *Category Theory for the Sciences*. MIT Press, 2014.
- [19] C. Tsallis. Generalization of boltzmann–gibbs statistics. *J. Stat. Phys.*, 52(1–2):479–487, 1988.
- [20] Philip Wadler. Essence of functional programming. In *ACM SIGPLAN-SIGACT Symposium*, pages 1–14, 1992.