

# PlenumHub: A Homotopy–Coherent Substrate for Semantic Versioning, Proof-Carrying Merges, and Entropy-Laxed Knowledge Evolution

Flyxion

November 10, 2025

## Abstract

We present **PlenumHub**, a semantic substrate for knowledge versioning in which documents, proofs, code, and multimodal artifacts evolve as objects in a quasicategory  $\mathcal{P}$ , with merges modeled as contractible cocartesian lifts in a history fibration. We formalize a core calculus (*SpherePOP*) with typing, entropy effects, and modality closure, prove uniqueness of canonical merges up to coherent homotopy, and develop crystal-valued lax monoidal functors to price semantic coherence. We provide operational semantics, complexity bounds, and a full categorical construction of semantic transports, merges, and effect tracking, replacing line-based patches and conflict markers with proof-carrying, entropy-controlled transformations. The design integrates ideas from higher category theory, type theory, information theory, and open-ended representation learning, yielding a formal predecessor to coherence-first knowledge collaboration.

## Contents

1	Foundations: Work in Quasi-Categories	2
2	Semantic Objects and History Fibration	2
3	The Merge Theorem (contractibility of canonical merges)	2
4	SpherePOP Calculus (typed and entropy-effectful)	3
5	Entropy-Laxed Monoidal and Crystal Valuation	3
6	Operational Semantics	3
7	Complexity	3
8	Architecture (TikZ)	4
9	Conclusion	4

# 1 Foundations: Work in Quasi-Categories

We work in the model of **quasi-categories** (simplicial sets with inner horn fillers), denoting by  $\text{Cat}_\infty$  the  $(\infty, 1)$ -category of quasicategories [?]. All universal properties are stated homotopy-coherently. Histories and branches are modeled by coCartesian fibrations  $p : \mathcal{H} \rightarrow \mathcal{B}$  and classified by functors  $F : \mathcal{B} \rightarrow \text{Cat}_\infty$  via *straightening/unstraightening* [?]. When algebraic structure is required we operate in symmetric monoidal  $\infty$ -categories formulated as  $\infty$ -operads [?].

## 2 Semantic Objects and History Fibration

**Definition 2.1** (Semantic Sphere). *A sphere is a tuple*

$$\sigma = (I, T, M, E, S)$$

where:

- $I$  is an immutable identifier,
- $T$  is a type signature of required modalities,
- $M : \mathcal{K} \rightarrow \mathcal{V}$  maps modalities to values,
- $E \in \mathbb{R}_{\geq 0}$  is semantic entropy,
- $S$  is a provenance chain of rule applications.

**Definition 2.2** (History Fibration). *A history fibration is a coCartesian fibration*

$$p : \mathcal{H} \rightarrow \mathcal{B}$$

whose fibers classify semantic spheres at each branch state. CoCartesian transport along  $e : b \rightarrow b'$  models evolution of content and entropy forward along a branch.

## 3 The Merge Theorem (contractibility of canonical merges)

Merges are modeled as coCartesian lifts over a span  $b_0 \leftarrow b \rightarrow b_1$ .

**Theorem 3.1** (Merge Contractibility). *Let  $p : \mathcal{H} \rightarrow \mathcal{B}$  be a history fibration classifying spheres. For any merge span  $b_0 \leftarrow b \rightarrow b_1$  in  $\mathcal{B}$ , the space of coCartesian lifts realizing canonical merges is a contractible Kan complex.*

*Proof Sketch.* By straightening,  $p$  corresponds to a functor  $F : \mathcal{B} \rightarrow \text{Cat}_\infty$ . A merge span induces a diagram in  $\text{Cat}_\infty$  whose cone points are the merges. The cocartesian lift condition is equivalent to initiality in the appropriate slice  $(F \circ D)_/$ . Initial objects in a slice quasicategory are unique up to contractible choice [?], implying the Kan core of the lift space is contractible.  $\square$

## 4 SpherePOP Calculus (typed and entropy-effective)

**Definition 4.1** (Typed rule). *A rule has typing*

$$r : a \xrightarrow{\epsilon} b$$

where  $\epsilon$  is an entropy budget. Composition is valid iff modalities match.

**Definition 4.2** (Reduction). *A rule acts on spheres by*

$$\sigma \xrightarrow{r} \sigma' \quad \text{iff} \quad M(a) \neq \emptyset \text{ and } E(\sigma') \leq E(\sigma) + \epsilon.$$

**Definition 4.3** (Merge).

$$\sigma_1 \oplus \sigma_2 = \sigma_m \quad \text{valid iff} \quad E(\sigma_m) \leq \max(E(\sigma_1), E(\sigma_2)) + \epsilon_{\text{merge}}.$$

**Definition 4.4** (Modality Closure (Media–Quine)).

$$Q(\sigma) = \sigma \iff \forall k \in T, M(k) \neq \emptyset, \quad Q(Q(\sigma)) = Q(\sigma).$$

## 5 Entropy-Laxed Monoidal and Crystal Valuation

We use a lax monoidal functor assigning *crystal values* to spheres.

**Definition 5.1** (Crystal economy). *TC = Texture Crystal, TiC = Time Crystal. A sphere carries value  $f(\sigma) = (t, h)$  in the semiring  $(\mathbb{R}_{\geq 0}^2, +, \otimes)$  with*

$$f(\sigma_1 \otimes \sigma_2) \leq f(\sigma_1) \otimes f(\sigma_2) + \delta$$

and

$$E(\sigma') \leq E(\sigma) + \epsilon \implies f(\sigma') \leq f(\sigma) \otimes e^{\kappa\epsilon}.$$

## 6 Operational Semantics

Reduction rules (deterministic, entropy-guarded):

$$\frac{\vdash r : a \rightarrow b \quad M(a) \neq \emptyset \quad E(\sigma') \leq E(\sigma) + \epsilon}{\langle \sigma, r \rangle \rightarrow \sigma'}$$

Merge rule:

$$\frac{E(\sigma_m) \leq \max(E_1, E_2) + \epsilon_m}{\langle \sigma_1, \sigma_2 \rangle \rightarrow \sigma_m}$$

## 7 Complexity

- Pop chain:  $O(n_r)$
- Merge mediation: NP-hard in general, FPT with bounded entropy
- Closure:  $O(m \cdot C_{\text{transducer}})$

## 8 Architecture (TikZ)




Figure 1: Semantic state flow in PlenumHub.

## 9 Conclusion

We built a homotopy-coherent theory for semantic merges, gave a typed entropy-effectful calculus, proved contractibility of merge spaces, introduced crystal-lax valuation, and replaced diff-based conflict with categorical merge resolution.

## References

- [Lur09] Jacob Lurie. *Higher Topos Theory*, volume 170 of *Annals of Mathematics Studies*. Princeton University Press, 2009.
- [Lur17] Jacob Lurie. *Higher Algebra*. 2017. Available at <https://www.math.ias.edu/~lurie/papers/HA.pdf>.