

Unsupervised ML with **K-Means**


by Dane Brown

Easy Data Visualization

Visualize the Data

Check it out -> **CV_ML**

- Limit the plotting to the first two features
 - sepal length
 - sepal width
- Notice the good separation of classes in the figure



Why K-Means Clustering

- Many clustering algorithms are available in Scikit-Learn
- but k-Means is easy to understand
- k-Means searches for a given number of clusters within an unlabeled multidimensional dataset
- It simply defines the optimal clustering

How K-Means Clustering


- The **cluster centre** is the arithmetic **mean** of all the points belonging to that cluster
- Each point is closer to its own cluster centre than to other cluster centres
- **Algorithm:**
 - Exhaustive search is not necessary instead, use an iterative approach **expectation-maximization**
 - **E (expectation) step**
 - **M (maximization) step**
 - each iteration will always result in a better estimate of the cluster characteristics

How K-Means Clustering

1. Guess some cluster centres
2. Repeat until converged
 - a. E-Step: assign points to the nearest cluster centre
 - b. M-Step: set the cluster centres to the mean


Not a Global Optimum Solution

- Many k-Means implementations run for multiple starting guesses to find a more optimal solution
- Scikit avoids the problems below



How K-Means Clustering

- Only three iterations



Disadvantages of k-Means

- The final result may not always be optimal, as the starting point differs based on random seed
- k must be specified
- limited to linear cluster boundaries
- low for large numbers of samples

k-Means for Colour Compression

- Clustering can be used for colour compression within images.
- In many images
 - a large number of the colours will be unused
 - many pixels will have similar/identical colours.