

 STANFORD STUDENT SPACE INITIATIVE <code>ssi.stanford.edu</code>	PROJECT	Quail
	SHEET	Solenoids & Pressure Transducers
	ENGINEER	Damian Loya
	ENGINEER	Matthew Pauly
Powered By Altium	REVISION	1.0
	REVIEWER	
Sheet 8 of 8	REVIEWED ON	


1

2

3

4

A



B

C

D

A

B

C

D

1

2

3


4

 STANFORD STUDENT SPACE INITIATIVE ssi.stanford.edu	PROJECT	Quail
	SHEET	Blinks and Boops
	ENGINEER	Damian Loya
	ENGINEER	Matthew Pauly
	POWERED BY	Altium
	REVISION	1.0

Sheet


8 of 8

REVIEWED ON



Title		
Date	Number	Revision
1.09.2021 File: C:\Users\...\Analogue\SchDoc	A2	Sheet of Drawn By:


A



Title		
Size	Number	Revision
A3		
Date: 1-05-2021	Sheet of	
File: C:\Users\...\Ethernet.SchDoc		Drawn By:

Level Shifters

The Squib Drivers operates using 5V logic, the MCU (SAMD51) uses 3.3V so the SPI interface between them needs to be converted




 STANFORD STUDENT SPACE INITIATIVE <code>ssi.stanford.edu</code>	PROJECT	Quail
	SHEET	Misc
	ENGINEER	Damian Loya
	ENGINEER	Matthew Pauly
	REVISION	1.0
	Sheet n of m	REVIEWED ON

Powered By **Altium**


A

A



B

B



C

C

△ This filter based on:
<https://electronics.stackexchange.com/questions/177575/capacitor-selection-for-filtering-of-low-level-signal>
 - Series resistance less than 10% of 350Ohm sensor impedance
 - Differential filter Fc = 4.8kHz
 - CM filter Fc = 24khz

It may need to be adjusted to suit a wider variety of load cells. Also, we might need better caps that don't have voltage derating

D

D

Title

Size
A

Number

Revision


Date: 1-05-2021

Sheet of

File: C:\Users\.\LoadCell.SchDoc


Drawn By:

Squib Drivers




Two Chips (MC33797) for 8 total channels
Pin 2 is Lo and Pin 1 is High on all connector

R Limit Calc: Ematch R=2ohm, wire is around 2-5ohm depending on length.
Recomended current is around 1 A
RSet = 10k sets limit to 1.4A




 <p>STANFORD STUDENT SPACE INITIATIVE</p> <p>ssi.stanford.edu</p>	PROJECT	Quail
	SHEET	Squibs
	ENGINEER	Damian Loya
	ENGINEER	Matthew Pauly
Powered By Altium	REVISION 1.0	REVIEWER
	Sheet n of m	REVIEWED ON

A



B



C

D

Title

Size

A

Number

Revision

Date: 1-05-2021

Sheet of


File: C:\Users\.\PressureTransducer.SchDoc Drawn By:

Radio Module

TODO






Swap Out with DRF Module

Radio for wireless communications
Dorji DRF1268T being used
Mainly on Tims Recomendation



(G)FSK/4(G)FSK/LoRa Modulation
433MHz transceiver
Max. 22dBm output power
-147dBm sensitivity
Standard SPI interface
Low RX current: 5.7 mA
Automatic RF sense and CAD monitor
Data Rate: <300 kbps
Standby current: <1uA
Supply voltage: 3.3V

 STANFORD STUDENT SPACE INITIATIVE <code>ssi.stanford.edu</code>	PROJECT	Quail
	SHEET	*
	ENGINEER	Damian Loya
	ENGINEER	Matthew Pauly
	REVISION	1.0
	Sheet	* of *
Powered By 		REVIEWED ON



A

B

C


D

A

B

C

D



Title: *	*
Size: A4	Number: * Revision: *
Date: 2021-01-05	Time: 04:04:23 Sheet*: of *
File: C:\Users\imv\SSI\Quail_Hardware\SD.SchDoc	

A

A

B


B

C

C

D

D



Title		
Size A	Number	Revision
Date: 1-05-2021		Sheet of
File: C:\Users\.\Thermocouple.SchDoc		Drawn By:

