


Efficient Phrases

These are efficient phrases:	These are not efficient phrases:
Cold Windowsill	Chilly Window Ledge
Cool Million	Good Thousand Thousand
Vivid Disillusions	Graphic Disappointments
Suspicious Conclusion	Mistrustful Ending

What makes an efficient phrase?


Data Structures

Data Structures



Data Structures


Data Structures



Data Structures

Data Structures


- Sequence Types
 - Tuples
 - Lists
 - range



Data Structures

Data Structures


- Sequence Types
 - Tuples
 - Lists
 - `range`
- Mapping Types
 - Dictionaries



Data Structures

Data Structures


- Sequence Types
 - Tuples
 - Lists
 - `range`
- Mapping Types
 - Dictionaries
- Sets



Data Structures

Data Structures


- Sequence Types
 - Tuples
 - Lists
 - `range`
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping



Data Structures

Data Structures

- Sequence Types
 - Tuples
 - Lists
 - `range`
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions



Sequence Types

Sequence type: an object type for storing an ordered collection of objects.

Sequence type: an object type for storing an ordered collection of objects.

Today, we'll be exploring `tuple` objects, `list` objects, and `range` objects!

Tuples

Tuple: immutable sequence type, typically used to store a collection of heterogeneous data.

Cannot be changed after it's been created.

Tuple: **immutable** sequence type, typically used to store a collection of heterogeneous data.

Tuple: **immutable** sequence type, typically used to store a collection of **heterogeneous data**.

Cannot be changed after it's been created.




```
graph TD; A["Cannot be changed after it's been created."] --> B["immutable"]; B --- C["heterogeneous data"]; C --> D["Can store objects of various type."]
```

Can store objects of various type.




```
congrats = ("Happy", 4, "you", "dude!")
```

congrats = "Happy", 4, "you", "dude!"



Parentheses are conventional, but optional!

Why Learn About Tuples?

Tuples are:

Why Learn About Tuples?

Tuples are:

Why Learn About Tuples?

Tuples are:

- **Hashable** - can be used as keys for dictionaries or as elements of sets.
(We'll see more of this soon!)

Why Learn About Tuples?

Tuples are:

- **Hashable** - can be used as keys for dictionaries or as elements of sets.
(We'll see more of this soon!)
- **Immutable** - "write-protect" data that doesn't need to be changed.

Why Learn About Tuples?

Tuples are:

- **Hashable** - can be used as keys for dictionaries or as elements of sets. (We'll see more of this soon!)
- **Immutable** - "write-protect" data that doesn't need to be changed.
- **Memory efficient** - immutability means they are stored more compactly than lists. (Matters more when storing many elements).

Unpacking Tuples

Unpacking Tuples

- Python supports the ready conversion of tuple elements to variables...

```
tup = (3, 2, 1)
```

```
three, two, one = tup
```

Unpacking Tuples

- Python supports the ready conversion of tuple elements to variables...

```
tup = (3, 2, 1)
three, two, one = tup
```

- ...and function arguments!

```
pow(*tup)
# => 0
```

Unpacking Tuples

- Python supports the ready conversion of tuple elements to variables...

```
tup = (3, 2, 1)
```

```
three, two, one = tup
```

- ...and function arguments!

```
pow(*tup) ← The * indicates tuple unpacking; Python  
# => 0      interprets this as pow(3, 2, 1)
```

Note: `pow(base, exp, mod)` returns `base**exp % mod`

Aside: Variable Swapping

Using a Temporary Variable:

Using Tuple Packing/Unpacking:

Aside: Variable Swapping

Using a Temporary Variable:

```
tmp = a
```

```
a = b
```

```
b = tmp
```

Using Tuple Packing/Unpacking:

Aside: Variable Swapping

Using a Temporary Variable:

```
tmp = a
a = b
b = tmp
```

Using Tuple Packing/Unpacking:

```
tup = (a, b)
b, a = tup
```


Aside: Variable Swapping

Using a Temporary Variable:

```
tmp = a
a = b
b = tmp
```

Using Tuple Packing/Unpacking:

We create a tuple (a, b) ...



The diagram illustrates the tuple packing and unpacking process for variable swapping. It features a yellow rectangular box containing the code `b, a = a, b`. An arrow points from the text "We create a tuple (a, b) ..." to the right side of the box (the tuple `a, b`). Another arrow points from the text "And unpack its values into b and a!" to the left side of the box (the variables `b, a`).


```
b, a = a, b
```

And unpack its values into b and a!

Data Structures

Data Structures


- ~~Sequence Types~~
 - Tuples
 - Lists
 - `range`
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions



Data Structures

Data Structures


- ~~Sequence Types~~
 - ~~Tuples~~
 - Lists
 - range
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions



Lists

List: mutable sequence type.


Can be changed after it's been created.



List: mutable sequence type.

```
jenny = [8, 6, 7, 5, 3, 0, 9]
```

jenny = [8, 6, 7, 5, 3, 0, 9]



Unlike with tuples, the brackets are mandatory!

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
---------------------------	--

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.
<code>.extend(iterable)</code>	Extends the list by appending all elements of <code>iterable</code> to the end.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.
<code>.extend(iterable)</code>	Extends the list by appending all elements of <code>iterable</code> to the end.
<code>.insert(idx, elem)</code>	Inserts the element <code>elem</code> at the index <code>idx</code> of the list.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.
<code>.extend(iterable)</code>	Extends the list by appending all elements of <code>iterable</code> to the end.
<code>.insert(idx, elem)</code>	Inserts the element <code>elem</code> at the index <code>idx</code> of the list.
<code>.sort(key=None, reverse=False)</code>	Sorts the list in-place.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.
<code>.extend(iterable)</code>	Extends the list by appending all elements of <code>iterable</code> to the end.
<code>.insert(idx, elem)</code>	Inserts the element <code>elem</code> at the index <code>idx</code> of the list.
<code>.sort(key=None, reverse=False)</code>	Sorts the list in-place.
<code>.reverse()</code>	Reverses the list in-place.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.
<code>.extend(iterable)</code>	Extends the list by appending all elements of <code>iterable</code> to the end.
<code>.insert(idx, elem)</code>	Inserts the element <code>elem</code> at the index <code>idx</code> of the list.
<code>.sort(key=None, reverse=False)</code>	Sorts the list in-place.
<code>.reverse()</code>	Reverses the list in-place.
<code>.pop(i=-1)</code>	Returns and removes the <code>i</code> th element from the list.

Working with Lists

- Standard slicing rules apply to access elements and subsequences.
- Additionally, special list methods include:

<code>.count(elem)</code>	Counts the occurrences of <code>elem</code> in the list.
<code>.index(elem)</code>	Returns the index of the first occurrence of <code>elem</code> in the list.
<code>.append(elem)</code>	Appends the element <code>elem</code> to the end of the list.
<code>.extend(iterable)</code>	Extends the list by appending all elements of <code>iterable</code> to the end.
<code>.insert(idx, elem)</code>	Inserts the element <code>elem</code> at the index <code>idx</code> of the list.
<code>.sort(key=None, reverse=False)</code>	Sorts the list in-place.
<code>.reverse()</code>	Reverses the list in-place.
<code>.pop(i=-1)</code>	Returns and removes the <code>i</code> th element from the list.
<code>.remove(elem)</code>	Removes the first instance of <code>elem</code> from the list, or raises <code>ValueError</code> .

Mutability and Immutability

```
CS41_staff = ("Elizabeth", "Antonio", "Theo", ["Pop Tart"])
```

```
CS41_staff[1].append("Unicornelius")
```

What's going to happen?

Mutability and Immutability

```
CS41_staff = ("Elizabeth", "Antonio", "Theo", ["Pop Tart"])
```

```
CS41_staff[1].append("Unicornelius")
```

What's going to happen?

Tuples store references to underlying objects; if the objects are mutable, they can still be changed.

Mutability and Immutability

```
CS41_staff = ("Elizabeth", "Antonio", "Theo", ["Pop Tart"])
```

```
CS41_staff[1].append("Unicornelius")
```

What's going to happen?

Tuples store references to underlying objects; if the objects are mutable,
they can still be changed.

```
CS41_staff = ("Elizabeth", "Antonio", "Theo",  
              ["Pop Tart", "Unicornelius"])
```

(If these objects aren't hashable, though, the tuple won't be either!)

An interview question: write a program to remove duplicate elements of a list.


An interview question: write a program to remove duplicate elements of a list.

Fun fact: freshman-year Michael failed to solve this problem in a real technical interview! 🙄

Data Structures

Data Structures


- ~~Sequence Types~~
 - ~~Tuples~~
 - Lists
 - `range`
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions



Data Structures

Data Structures

- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - `range`
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions



range

Range: represents an immutable sequence of numbers, commonly used for looping in `for` loops.

Range: represents an immutable sequence of numbers, commonly used for looping in `for` loops.

```
range(start, stop, step)
```


Range: represents an immutable sequence of numbers, commonly used for looping in `for` loops.

```
range(start, stop, step)
```



Assumed to be 0 if excluded.

Range: represents an immutable sequence of numbers, commonly used for looping in `for` loops.




```
range(10)
```

```
range(10)
```

```
range(3, 10)
```

```
range(10)
```


```
range(3, 10)
```

```
range(3, 10, 2)
```


Data Structures

Data Structures


- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - `range`
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions



Data Structures

Data Structures

- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - ~~range~~
- Mapping Types
 - Dictionaries
- Sets
- Advanced Looping
- Comprehensions




Mapping Types

Dictionaries

Dictionary: a data structure which maps hashable values to arbitrary objects.

For today, hashable and immutable mean the same thing - but we'll revisit this definition during the lecture on Object Oriented Python!



Dictionary: a data structure which maps **hashable** values to arbitrary objects.


For today, hashable and immutable mean the same thing - but we'll revisit this definition during the lecture on Object Oriented Python!

Dictionary: a data structure which maps **hashable** values to arbitrary objects.

Think Java's `HashMap`, or the Stanford C++ Library's `Map`.

```
cs41_staff = {  
    "Parth": "the wonderful",  
    "Antonio": "the bold",  
    "Elizabeth": "the intrepid",  
    "Theo": "the wizard"  
}
```


Curly braces denote a dictionary.



```
cs41_staff = {  
    "Parth": "the wonderful",  
    "Antonio": "the bold",  
    "Elizabeth": "the intrepid",  
    "Theo": "the wizard"  
}
```

Curly braces denote a dictionary.

```
cs41_staff = {  
    "Parth": "the wonderful",  
    "Antonio": "the bold",  
    "Elizabeth": "the intrepid",  
    "Theo": "the wizard"  
}
```

Colons separate keys, values; commas separate
(key, value) pairs.

Working with Dictionaries

Working with Dictionaries

```
val = d[key]
```

Access the value in `d` corresponding to `key`; place this value into the `val` variable.

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .
<code>d.get(key, default)</code>	Returns the value associated with <code>key</code> in <code>d</code> . If <code>key</code> does not exist in <code>d</code> , return <code>default</code> .

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .
<code>d.get(key, default)</code>	Returns the value associated with <code>key</code> in <code>d</code> . If <code>key</code> does not exist in <code>d</code> , return <code>default</code> .
<code>d.keys()</code>	Returns a collection of the keys in the dictionary.

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .
<code>d.get(key, default)</code>	Returns the value associated with <code>key</code> in <code>d</code> . If <code>key</code> does not exist in <code>d</code> , return <code>default</code> .
<code>d.keys()</code>	Returns a collection of the keys in the dictionary.
<code>d.values()</code>	Returns a collection of the values in the dictionary.

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .
<code>d.get(key, default)</code>	Returns the value associated with <code>key</code> in <code>d</code> . If <code>key</code> does not exist in <code>d</code> , return <code>default</code> .
<code>d.keys()</code>	Returns a collection of the keys in the dictionary.
<code>d.values()</code>	Returns a collection of the values in the dictionary.
<code>d.items()</code>	Returns a collection of (key, value) tuples in <code>d</code> .

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .
<code>d.get(key, default)</code>	Returns the value associated with <code>key</code> in <code>d</code> . If <code>key</code> does not exist in <code>d</code> , return <code>default</code> .
<code>d.keys()</code>	Returns a collection of the keys in the dictionary.
<code>d.values()</code>	Returns a collection of the values in the dictionary.
<code>d.items()</code>	Returns a collection of (key, value) tuples in <code>d</code> .
<code>del d[key]</code>	Removes <code>key</code> , and its associated value, from <code>d</code> . (If <code>key</code> is not in <code>d</code> , raises a <code>ValueError</code>).

Working with Dictionaries

<code>val = d[key]</code>	Access the value in <code>d</code> corresponding to <code>key</code> ; place this value into the <code>val</code> variable.
<code>d[key] = val</code>	Set the value in the dictionary corresponding to <code>key</code> equal to the value within <code>val</code> .
<code>d.get(key, default)</code>	Returns the value associated with <code>key</code> in <code>d</code> . If <code>key</code> does not exist in <code>d</code> , return <code>default</code> .
<code>d.keys()</code>	Returns a collection of the keys in the dictionary.
<code>d.values()</code>	Returns a collection of the values in the dictionary.
<code>d.items()</code>	Returns a collection of (key, value) tuples in <code>d</code> .
<code>del d[key]</code>	Removes <code>key</code> , and its associated value, from <code>d</code> . (If <code>key</code> is not in <code>d</code> , raises a <code>ValueError</code>).
<code>d.pop(key, default)</code>	Removes <code>key</code> , and its associated value, from <code>d</code> . (Returns the associated value if <code>key</code> is in <code>d</code> , otherwise returns <code>default</code>).

Common Dictionary Operations

Common Dictionary Operations

<code>len(d)</code>	Returns the number of keys in d.
---------------------	----------------------------------

Common Dictionary Operations

<code>len(d)</code>	Returns the number of keys in <code>d</code> .
<code>key in d</code>	Equivalent to <code>key in d.keys()</code>

Common Dictionary Operations

<code>len(d)</code>	Returns the number of keys in <code>d</code> .
<code>key in d</code>	Equivalent to <code>key in d.keys()</code>
<code>d.copy()</code>	Makes a shallow copy of <code>d</code> .


Common Dictionary Operations

<code>len(d)</code>	Returns the number of keys in <code>d</code> .
<code>key in d</code>	Equivalent to <code>key in d.keys()</code>
<code>d.copy()</code>	Makes a shallow copy of <code>d</code> .
<code>d.clear()</code>	Removes all (key, value) pairs from <code>d</code> .

Data Structures

Data Structures


- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - ~~range~~
- ~~Mapping Types~~
 - ~~Dictionaries~~
- ~~Sets~~
- ~~Advanced Looping~~
- ~~Comprehensions~~



Data Structures

Data Structures

- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - ~~range~~
- ~~Mapping Types~~
 - ~~Dictionaries~~
- Sets
- Advanced Looping
- Comprehensions



Sets

Set: an unordered collection with no duplicate elements.

```
nice_animals = {"unicorns", "elephants"}
```

`nice_animals = {"unicorns", "elephants"}`



Curly brackets denote a set!*

`nice_animals = {"unicorns", "elephants"}`



Curly brackets denote a set!*

* As long as it's not the empty set, which is denoted `set()`

Why Learn About Sets?

Sets enable:

Why Learn About Sets?

Sets enable:

Why Learn About Sets?

Sets enable:

- **Fast membership testing** - sets use hashing to enable $O(1)$ membership testing. (List membership testing is $O(n)$).

Why Learn About Sets?

Sets enable:

- **Fast membership testing** - sets use hashing to enable $O(1)$ membership testing. (List membership testing is $O(n)$).
- **$O(1)$ Duplicate Elimination** - can eliminate duplicate entries in a collection.

Why Learn About Sets?

Sets enable:

- **Fast membership testing** - sets use hashing to enable $O(1)$ membership testing. (List membership testing is $O(n)$).
- **$O(1)$ Duplicate Elimination** - can eliminate duplicate entries in a collection.
- **Efficient Set Operations** - union, intersection, and more of your favourites from set theory!

Basic Set Operations

Basic Set Operations

<code>s.add(val)</code>	Adds the value <code>val</code> to set <code>s</code> .
-------------------------	---

Basic Set Operations

<code>s.add(val)</code>	Adds the value <code>val</code> to set <code>s</code> .
<code>s.remove(val)</code>	Removes the value <code>val</code> from set <code>s</code> . (Raises <code>KeyError</code> if <code>val</code> not in <code>s</code>).

Basic Set Operations

<code>s.add(val)</code>	Adds the value <code>val</code> to set <code>s</code> .
<code>s.remove(val)</code>	Removes the value <code>val</code> from set <code>s</code> . (Raises <code>KeyError</code> if <code>val</code> not in <code>s</code>).
<code>s.discard(val)</code>	Removes the value <code>val</code> from set <code>s</code> if it is present.

Basic Set Operations

<code>s.add(val)</code>	Adds the value <code>val</code> to set <code>s</code> .
<code>s.remove(val)</code>	Removes the value <code>val</code> from set <code>s</code> . (Raises <code>KeyError</code> if <code>val</code> not in <code>s</code>).
<code>s.discard(val)</code>	Removes the value <code>val</code> from set <code>s</code> if it is present.
<code>s.pop()</code>	Remove and return an arbitrary element from <code>s</code> . (Raises <code>KeyError</code> if <code>s</code> is empty)

Mathematical Set Operations

$s \ \& \ t$	Set intersection.
$s \ \ t$	Set union.
$s \ < \ t$	Check whether s is a proper subset of t .
$s \ \leq \ t$	Check whether s is a subset of t .
$s \ \wedge \ t$	Symmetric difference.
$s \ - \ t$	Set difference.

An interview question: write a program to remove duplicate elements of a list that operates in $O(n)$ time.

set VS. frozenset

- An immutable and hashable set - the elements of a `frozenset` must be hashable for the `frozenset` to be hashable.
 - Can be used - for example - as keys in a dictionary.
- Behaves almost exactly like a regular set, except doesn't support "mutable" operations:
 - `add`
 - `remove`
 - `discard`
 - `pop`

Efficient Phrases


These are efficient phrases:	These are not efficient phrases:
Cold Windowsill	Chilly Window Ledge
Cool Million	Good Thousand Thousand
Vivid Disillusions	Graphic Disappointments
Suspicious Conclusion	Mistrustful Ending

What makes an efficient phrase?

Data Structures

Data Structures


- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - ~~range~~
- ~~Mapping Types~~
 - ~~Dictionaries~~
- Sets
- Advanced Looping
- Comprehensions



Data Structures

Data Structures


- ~~Sequence Types~~
 - ~~Tuples~~
 - ~~Lists~~
 - ~~range~~
- ~~Mapping Types~~
 - ~~Dictionaries~~
- ~~Sets~~
- Advanced Looping
- Comprehensions



Advanced Looping


`zip`: makes an iterator that aggregates elements
from each of the arguments.

An *iterator* is an object which iterates through a collection over which it is defined.




`zip`: makes an **iterator** that aggregates elements from each of the arguments.

An *iterator* is an object which iterates through a collection over which it is defined.



`zip`: makes an **iterator** that aggregates elements from **each of the arguments**.



An *iterable* is anything that can be looped over using a `for` loop (list, set, dict, etc.)