

# Lecture 1.2: Python Basics

*April 5, 2023*

# Announcements

- Assignment 0 due next Thursday
- Today is the last day to pick a group (more cocktail parties at the end of the day)
  - Once you have a group, sign up for a section on Axess (via assignments > groups on the website)
- Sections start **next week** in place of the Thursday lecture (don't come here; instead, go to your section room)
  - Room announcements will be announced on Tuesday in lecture
- We have office hours!

# Learning Goals

After today, students will be able to...

- Build a chatbot in Python.
- Define Python terms like “module” and “workspace” and create new modules on their computer.
- Identify resources for determining whether they are using appropriate Python style.

Making a module:  
`is_prime.py`

# Python Files

- You can write and edit code in files. This is the preferred method when you're working on a large codebase or repeatedly editing code.
- Code that should only be executed when the file is being called directly is placed in:

```
if __name__ == '__main__':  
    # only executes if this file is being called directly  
    ...
```

- Execute the file by calling `python file.py`

# Python Style



(a stylish python)

# Comments

# Comments

```
# A single-line comment in Python is denoted with the hash symbol.
```



# Comments

```
# A single-line comment in Python is denoted with the hash symbol.
```

```
"""  
Multi-line comments  
Lie between quotation marks  
This is a haiku  
"""
```

# PEP 8

# PEP 8

## Spacing

# PEP 8

## **Spacing**

Use four spaces to indent code (don't use tabs).

# PEP 8

## **Spacing**

Use four spaces to indent code (don't use tabs).

Use blank lines to separate functions from each other and logical sections within a function.

# PEP 8

## Spacing

Use four spaces to indent code (don't use tabs).

Use blank lines to separate functions from each other and logical sections within a function.

Use spaces around operators and after commas, but not directly inside delimiters.

```
a = f(1, 2) + g(3, 4) # good
a = f( 1, 2 ) + g( 3, 4 ) # bad
```

# PEP 8

# PEP 8

## Commenting



# PEP 8

## Commenting

Comment all nontrivial functions.

A function's docstring is the *first (unassigned) string* inside the function body.

# PEP 8

## Commenting

Comment all nontrivial functions.

A function's docstring is the *first (unassigned) string* inside the function body.

Describe parameters (value / expected type) and return (value / expected type).

# PEP 8

## Commenting

Comment all nontrivial functions.

A function's docstring is the *first (unassigned) string* inside the function body.

Describe parameters (value / expected type) and return (value / expected type).

As usual: list pre/post conditions if any.

# PEP 8

## Commenting

Comment all nontrivial functions.

A function's docstring is the *first (unassigned) string* inside the function body.

Describe parameters (value / expected type) and return (value / expected type).

As usual: list pre/post conditions if any.

Add header comments at the top of files before any imports.

# PEP 8

## Commenting

Comment all nontrivial functions.

A function's docstring is the *first (unassigned) string* inside the function body.

Describe parameters (value / expected type) and return (value / expected type).

As usual: list pre/post conditions if any.

Add header comments at the top of files before any imports.

If possible, put comments on a line of their own.



```
def my_function():  
    """  
    Summary line: do nothing, but document it.  
  
    Longer description: No, really, it doesn't do anything.  
  
    Returns: Gosh, for the last time... nothing (None)!  
    """  
    pass
```

```
def my_function():  
    """  
    Summary line: do nothing, but document it.  
  
    Longer description: No, really, it doesn't do anything.  
  
    Returns: Gosh, for the last time... nothing (None)!  
    """  
    pass  
  
print(my_function.__doc__)  
#     Summary line: do nothing, but document it.  
#  
#     Longer description: No, really, it doesn't do anything.  
#  
#     Returns: Gosh, for the last time... nothing (None)!
```



# PEP 8

# PEP 8

## **Naming**

# PEP 8

## **Naming**

Use `snake_case` for variables/functions; `CamelCase` for classes;  
`CAPS_CASE` for constants.

# PEP 8

## **Naming**

Use `snake_case` for variables/functions; `CamelCase` for classes;  
`CAPS_CASE` for constants.

## **Decomposition and Logic**

# PEP 8

## **Naming**

Use `snake_case` for variables/functions; `CamelCase` for classes; `CAPS_CASE` for constants.

## **Decomposition and Logic**

Same as 106A/B/X. Simple is better than complex!

# PEP 8

## **Naming**

Use `snake_case` for variables/functions; `CamelCase` for classes; `CAPS_CASE` for constants.

## **Decomposition and Logic**

Same as 106A/B/X. Simple is better than complex!

## **Automated Code Style Checking**

# PEP 8

## **Naming**

Use `snake_case` for variables/functions; `CamelCase` for classes; `CAPS_CASE` for constants.

## **Decomposition and Logic**

Same as 106A/B/X. Simple is better than complex!

## **Automated Code Style Checking**

Use [PEP8 Online](#) for mechanical violations (naming, spacing) and more advanced suggestions.

# PEP 8

## **Naming**

Use `snake_case` for variables/functions; `CamelCase` for classes; `CAPS_CASE` for constants.

## **Decomposition and Logic**

Same as 106A/B/X. Simple is better than complex!

## **Automated Code Style Checking**

Use [PEP8 Online](#) for mechanical violations (naming, spacing) and more advanced suggestions.

Use `pycodestyle` as a command line tool. Install with `pip install pycodestyle` (you'll do this in the installation instructions).



# ***Review Activity: Seesaw***

- Introduce yourself to your neighbor — well-being inquiries are in order!
- Work through this problem together (website → lectures → in class review activity)

For the remaining concepts:  
`chatbot.py`

File I/O

```
f = open(filename, method)
```

## *Read*

Function	Action
<code>next(f)</code>	Returns the next line in the file
<code>f.read()</code>	Returns the entire file as a string
<code>for line in f:</code>	Loops over the file, line by line
<code>f.readlines()</code>	Returns the lines of the file as a list of strings

## *Write*

Function	Action
<code>f.write(new_line)</code>	Writes <code>new_line</code> to the file
<code>f.writelines([collection of new, lines])</code>	Writes the collection of lines to the file

*\* Writing appends or overwrites, depending on the method*

```
f.close()
```

```
f = open(filename, method)
```

- r - Read
  - w - Write
  - a - Append
  - b - Bytes Mode

Read

Function	Action
<code>next(f)</code>	Returns the next line in the file
<code>f.read()</code>	Returns the entire file as a string
<code>for line in f:</code>	Loops over the file, line by line
<code>f.readlines()</code>	Returns the lines of the file as a list of strings

Write

Function	Action
<code>f.write(new_line)</code>	Writes <code>new_line</code> to the file
<code>f.writelines([collection of new, lines])</code>	Writes the collection of lines to the file

*\* Writing appends or overwrites, depending on the method*

```
f.close()
```

Add a file read loop:  
`chatbot.py`

What happens without `f.close()`?

# What happens without `f.close()`?

- When the program ends (naturally or from an error), Python will try to clean up any objects that remain in memory.



# What happens without `f.close()`?

- When the program ends (naturally or from an error), Python will try to clean up any objects that remain in memory.
- This isn't guaranteed\*, but it happens sometimes. You should be concerned if you're writing code that will be run on many operating systems or Python versions.

\* Depends on the operating system, Python version, Python implementation (which language the interpreter was written in), ...

# What happens without `f.close()`?

- When the program ends (naturally or from an error), Python will try to clean up any objects that remain in memory.
- This isn't guaranteed\*, but it happens sometimes. You should be concerned if you're writing code that will be run on many operating systems or Python versions.
- If it isn't closed, the file could remain locked so other programs can't open it or become corrupted.

\* Depends on the operating system, Python version, Python implementation (which language the interpreter was written in), ...

# What happens without `f.close()`?

- When the program ends (naturally or from an error), Python will try to clean up any objects that remain in memory.
- This isn't guaranteed\*, but it happens sometimes. You should be concerned if you're writing code that will be run on many operating systems or Python versions.
- If it isn't closed, the file could remain locked so other programs can't open it or become corrupted.
- The safe option: use a **context manager**!

\* Depends on the operating system, Python version, Python implementation (which language the interpreter was written in), ...

```
with open("words.txt", "r") as f:
```

```
with open("words.txt", "r") as f:
```

`open("words.txt", "r")` is a file object - it has instructions about how to open and close the file.

The context manager makes sure those instructions are followed, no matter what.

```
with open("words.txt", "r") as f:
```

`open("words.txt", "r")` is a file object - it has instructions about how to open and close the file.

The context manager makes sure those instructions are followed, no matter what.



```
with open("words.txt", "r") as f:
```

`open("words.txt", "r")` is a file object - it has instructions about how to open and close the file.

The context manager makes sure those instructions are followed, no matter what.

Roughly equivalent to:

```
f = open("words.txt", "r")  
try:  
    ...  
finally:  
    f.close()
```



Safely read definitions:  
`chatbot.py`



# Strings, Revisited

# Useful String Methods

Method	Action
<code>.lower()</code>	Converts the string to lowercase
<code>.upper()</code>	Converts the string to uppercase
<code>.title()</code>	Converts the string to title case (every word capitalized)
<code>.strip([chars])</code>	Removes the characters from the ends of the string (or whitespace if chars is omitted)

Method	Action
<code>.find(substr)</code>	Finds the first occurrence of <code>substr</code> and returns the index (or -1 if not found)
<code>.replace(old, new)</code>	Replaces every instance of <code>old</code> with <code>new</code> and returns the new string
<code>.startswith(substr)</code> <code>.endswith(substr)</code>	Returns whether the string starts/ends with <code>substr</code>

# Useful String Methods

Method	Action
<code>.lower()</code>	Converts the string to lowercase
<code>.upper()</code>	Converts the string to uppercase
<code>.title()</code>	Converts the string to title case (every word capitalized)
<code>.strip([chars])</code>	Removes the characters from the ends of the string (or whitespace if <code>chars</code> is omitted)

Method	Action
<code>.find(substr)</code>	Finds the first occurrence of <code>substr</code> and returns the index (or -1 if not found)
<code>.replace(old, new)</code>	Replaces every instance of <code>old</code> with <code>new</code> and returns the new string
<code>.startswith(substr)</code> <code>.endswith(substr)</code>	Returns whether the string starts/ends with <code>substr</code>

# Splitting and Joining

```
"3-14-2015".split('-')
```

# Splitting and Joining

```
"3-14-2015".split('-')
```

# Splitting and Joining

```
"3-14-2015".split('-') # => ['3', '14', '2015']
```

# Splitting and Joining

```
"3-14-2015".split('-') # => ['3', '14', '2015']
```

```
"Tara Elizabeth Jones".split()
```

# Splitting and Joining

```
"3-14-2015".split('-') # => ['3', '14', '2015']
```

```
"Tara Elizabeth Jones".split()
```



# Splitting and Joining

```
"3-14-2015".split('-') # => ['3', '14', '2015']
```

```
"Tara Elizabeth Jones".split()  
# => ['Tara', 'Elizabeth', 'Jones']
```

# Splitting and Joining

```
"3-14-2015".split('-') # => ['3', '14', '2015']
```

```
"Tara Elizabeth Jones".split()  
# => ['Tara', 'Elizabeth', 'Jones']
```

```
", ".join(["Arpit", "Chase", "Will"])
```

# Splitting and Joining

```
"3-14-2015".split('-') # => ['3', '14', '2015']
```

```
"Tara Elizabeth Jones".split()  
# => ['Tara', 'Elizabeth', 'Jones']
```

```
", ".join(["Arpit", "Chase", "Will"])  
# => 'Arpit, Chase, Will'
```

**Finish the chatbot:**  
`chatbot.py`