

Lab 5

Network Function Virtualization:

Software Router and Containerization

Deadline: 2024/11/27 (WED) 23:59



Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References




Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References



Example Scenario

Interconnection of two networks




- **BGP**: Border Gateway Protocol
- AS: Autonomous System



Introduction to FRRouting

FRRouting is an open-source software that provides routing services


- Supports common routing protocols: BGP, OSPF, RIP, and IS-IS
- Consists of a core daemon Zebra and separate routing protocol daemons
- Routing Protocols (daemons) communicate their best routes to Zebra
- Zebra computes best routes and modifies kernel routing table through netlink





Introduction to FIB Pushing


- Zebra supports a FIB Push Interface (FPI)
 - FPI allows an external component to learn the forwarding information
- Forwarding Plane Manager (FPM):
 - Receives FIB
 - Decode FIB into routes
 - Programs forwarding plane
- FIB Pushing:
 - FPM establishes a TCP connection with zebra
 - Zebra pushes FIB to FPM





Introduction to Docker

- Docker is a software platform that allows you to build, test, and deploy applications quickly in packages called containers
- Typical steps for creating Docker containers:
 - 1. Build Docker images of the desired OS distribution and applications
 - 2. Store the images in a Docker Registry
 - Public (Docker Hub)
 - Private
 - 3. Run Docker to build containers of images





Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References



Installation of Docker

- Update apt (confirm to install the latest package)
 - \$ sudo apt-get update
- Install curl for data transfer
 - \$ sudo apt-get install -y curl
- Retrieve Docker installation script and install Docker
 - \$ sudo curl -ssl https://get.docker.com | sh
- Manage Docker as a non-root user
 - \$ sudo groupadd docker
 - \$ sudo usermod -aG docker \$USER
 - \$ newgrp docker

Other Methods: https://docs.docker.com/engine/install/ubuntu/



Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References



Pull Image

- Usage
 - \$ docker pull <name>:<tag>
- E.g., Pull ubuntu:22.04 image from Docker hub registry
 - \$ docker pull ubuntu:22.04
- List images
 - \$ docker images

```
cu@SDN-NFV:~$ docker images
REPOSITORY TAG IMAGE ID CREATED SIZE
ubuntu 22.04 e4c58958181a 2 weeks ago 77.8MB
```



Docker run (1/2)

- Run a command in a new container
 - Create and run a container
 - Execute a command in the container
- Usage
 - \$ docker run <options> <image>:<tag> <command> <arg...>

Create and Run a container Execute a command in the container

- E.g., Create and Run a container "test"
 - \$ docker run -d -it --name test ubuntu:22.04
 - -d: Detached (like a daemon in background)
 - -it: Interactive processes (like a shell)
 - --name: Assign a name to the container




Docker run (2/2)

- List containers
 - \$ docker ps -a
 - "--all", "-a": Show all containers

```
cu@SDN-NFV:~$ docker ps -a
CONTAINER ID IMAGE COMMAND CREATED STATUS PORTS NAMES
23497ece301e ubuntu:22.04 "/bin/bash" 4 seconds ago Up 3 seconds test
```

- Container is connected to docker0 bridge by default
- Default IP for docker0 bridge is 172.17.0.1/16
- Docker will assign an IP for the container





Docker exec

- Execute a command in a running container
- Usage
 - \$ docker exec <options> <container> <command>
- E.g., Exec bash command in a running container "test"
 - \$ docker exec -it test bash


```
cu@SDN-NFV:~$ docker exec -it test bash
root@23497ece301e:/#
```



Docker network - Create


- Create a bridge network
- Usage
 - \$ docker network create <bridge>
- E.g., Create a network bridge "testbr"
 - \$ docker network create testbr
- List networks
 - \$ docker network Is

```
cu@SDN-NFV:~$ docker network ls
NETWORK ID
                          DRIVER
                                    SCOPE
               NAME
35c1f8ddd132
                                    local
               bridge
                         bridge
b9d64cd68f56
               host
                         host
                                    local
5e0125ebf294
               none
                          null
                                    local
376b09c5a977
                          bridge
               testbr
                                    local
```






Network Environment after testbr Creation





Docker network - Connect

- Connect to a bridge network
- Usage
 - \$ docker network connect <network> <container>
- E.g., Connect container "test" to bridge "testbr"
 - \$ docker network connect testbr test
 - Docker will add an interface on the container and assign an IP






Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References



Steps to Setup Example Scenario

- 1. Prepare Docker images
- 2. Create containers
- 3. Setup container networks
 - Setup network for domains
 - Connect domains
- 4. Configure host gateways
 - Gateway of h1 = R1
 - Gateway of h2 = R2
- 5. Setup routers
- 6. Check routes





Step 1 – Prepare Docker images (1/3)

- Prepare docker image "host"
- Write Dockerfile
 - Create configuration file host.Dockerfile
 - \$ vi host.Dockerfile

```
FROM ubuntu:22.04
```

```
RUN apt-get update -y \
&& apt-get install -y traceroute \
&& apt-get install -y net-tools \
&& apt-get install -y iproute2 \
&& apt-get install -y iputils-ping
```

CMD ["sleep","infinity"]



Step 1 – Prepare Docker images (2/3)

- Build docker image with Dockerfile
 - \$ docker build -t host -f host.Dockerfile.
 - -t: Name and optionally a tag in the "name:tag" format
 - -f: Name of the Dockerfile (Default is 'PATH/Dockerfile')
- List image
 - \$ docker images

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
host	latest	97085d108578	About an hour ago	129MB
ubuntu	22.04	e4c58958181a	2 weeks ago	77.8MB



Step 1 – Prepare Docker images (3/3)

- Prepare Docker image frrouting
- Pull image frrouting/frr-debian from docker hub
 - \$ docker pull frrouting/frr-debian
- List image
 - \$ docker images

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
frr-debian	latest	649949e63ade	2 days ago	372MB
frr	alpine-c60f439098	aa15955dc3db	5 days ago	165MB
frr-fpm	latest	aa15955dc3db	5 days ago	165MB
<none></none>	<none></none>	6df23db9d8f2	5 days ago	164MB
host	latest	07970c916d32	5 days ago	139MB
quay.io/frrouting/frr	10.1.0	044587961d97	5 weeks ago	165MB
onosproject/onos	latest	2a4338117eab	4 months ago	876MB
frrouting/frr	latest	d19bacb84eae	22 months ago	151MB
frrouting/frr-debian	latest	c22c56056653	3 years ago	348MB
onosproject/onos	2.2-latest	b517cd3fdb88	3 years ago	854MB

Note: Do not use frrouting/frr image as it doesn't have the necessary component built for this lab.




Step 2 – Create Containers (1/2)

- Create a container with prepared image
 - \$ docker run --privileged --cap-add NET_ADMIN \
 --cap-add NET_BROADCAST -d -it \
 --name <container name> <image>
- --privileged: Give extended privileges to this container
- --cap-add: Add Linux capabilities
 - NET_ADMIN: Enable network administration operations
 - NET_BROADCAST: Make socket able to broadcasts, and listen to multicasts



Step 2 – Create Containers (2/2)


- Create container for a host h1 (h2)
 - \$ docker run --privileged --cap-add NET_ADMIN \
 --cap-add NET_BROADCAST -d -it \
 --name h1 host
- Create container for a virtual router R1 (R2)
 - \$ docker run --privileged --cap-add NET_ADMIN \
 --cap-add NET_BROADCAST -d -it \
 --name R1 frrouting/frr-debian





Step 3 – Setup Container Networks (1/3)


- Setup network for domains
- Create a bridge network R1h1br
 - \$ docker network create R1h1br
 - R1h1br: Bridge name
- Connect containers h1 and R1 to bridge R1h1br
 - \$ docker network connect R1h1br R1
 - \$ docker network connect R1h1br h1
 - Docker will assign IP to interfaces automatically





Step 3 – Setup Container Networks (2/3)

- Check the IP addresses of network interfaces
 - \$ docker inspect h1 (R1)
 - Inspected result for h1



Docker bridge


Inspected result for R1

- Repeat network setup procedure for another domain
 - Create bridge network R2h2br
 - Connect containers R2 and h2



Step 3 – Setup Container Networks (3/3)

- Connect two domains
- Create inter domain bridge
 - \$ docker network create R1R2br
- Connect containers R1 and R2 to bridge R1R2br
 - \$ docker network connect R1R2br R1
 - \$ docker network connect R1R2br R2






Step 4 – Configure Host Gateways (1/1)

- Run bash on h1 (h2)
 - \$ docker exec -it h1 bash
- Set R1 (R2) as default gateway of h1 (h2)

```
h1/# ip route del default
h1/# ip route add default via 172.18.0.2
```



Check route on h1 (h2)

h1/# route

```
h1's bash prompt
root@6e5f213a2112:/# route
Kernel IP routing table
Destination
                                                 Flags Metric Ref
                                                                      Use Iface
                Gateway
                                 Genmask
                R1.R1h1br
default
                                 0.0.0.0
                                                 UG
                                                               0
                                                                        0 eth1
172.17.0.0
                                 255,255,0,0
                                                                        0 eth0
172.18.0.0
                                 255.255.0.0
                                                                        0 eth1
```

Exit h1 bash via CTRL+D



Step 5 – Setup Routers (1/4)

- Run bash on R1 (R2)
 - \$ docker exec -it R1 bash
- Enable IP forwarding on R1 (R2)
 R1/# vi /etc/sysctl.conf
 - Uncomment
 "net.ipv4.ip_forward=1"
- Run sysctl toload configurationR1/# sysctl -p

```
# Note: This may impact IPv6 TCP sessions too
#net.ipv4.tcp syncookies=1
 Uncomment the next line to enable packet forwarding for IPv4
#net.ipv4.ip forward=l
# Uncomment the next line to enable packet forwarding for IPv6
# Note: This may impact IPv6 TCP sessions too
#net.ipv4.tcp_syncookies=1
# Uncomment the next line to enable packet forwarding for IPv4
net.ipv4.ip forward=1
```



Step 5 – Setup Routers (2/4)

- FRR daemons config file R1(R2)
 - Edit FRR daemon configuration file on R1 (R2)

R1/# vi /etc/frr/daemons

Edit bgpd=yes to turn on bgp routing daemon

```
# The watchfrr, zebra and staticd daemons are always started.

# bgpd=yes

sopfd=no

sopf6d=no

ripd=no

ripngd=no

isisd=no
```




Step 5 – Setup Routers (3/4)

- Set BGP configuration for routers
 - Edit configuration file frr.conf on R1

R1/# vi /etc/frr/frr.conf

```
! FRR configuration for R1
frr defaults datacenter
router bgp 65000
  bgp router-id 172.20.0.2
  timers bgp 3 9
  neighbor 172.20.0.3 remote-as 65001
  neighbor 172.20.0.3 ebgp-multihop
  neighbor 172.20.0.3 timers connect 5
  neighbor 172.20.0.3 advertisement-interval 5
  network 172.18.0.0/16
log stdout
line vty
```






Step 5 – Setup Routers (4/4)

- Set BGP configuration for routers
 - Edit configuration file frr.conf on R2

R2/# vi /etc/frr/frr.conf

```
! FRR configuration for R2
frr defaults datacenter
router bgp 65001
  bgp router-id 172.20.0.3
  timers bgp 3 9
  neighbor 172.20.0.2 remote-as 65000
  neighbor 172.20.0.2 ebgp-multihop
  neighbor 172.20.0.2 timers connect 5
  neighbor 172.20.0.2 advertisement-interval 5
  network 172.19.0.0/16
log stdout
line vty
```






Step 6 – Check Routes (1/2)

- Restart R1 (R2)
 - \$ docker restart R1
- Interact with FRR daemons

R1/# vtysh

Show routes on R1 (R2)

R1FRR> show ip route






Step 6 – Check Routes (2/2)


Show bgp route in R1 FRR (in vtysh)

R1FRR> show ip route bgp

Show bgp summary in R1 FRR (in vtysh)

R1FRR> show ip bgp summary








Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References




Introduction to Docker Compose

- A tool for defining and running multi-container Docker applications
- Use a YAML file to configure your application services
- Start all the services from your configuration with a single command
- The default name for Compose file is docker-compose.yml



Yaml template for example docker application






Docker Compose Example (1/4)

Create bridge R1h1br

network create

networks:
R1h1br:
driver: bridge
ipam:
config:

- subnet: 172.18.0.0/16






Docker Compose Example (2/4)

Create container h1 build, run, network connect

```
services:
 h1:
  image: host
  container name: h1
  privileged: true
  build:
   context:.
   dockerfile: host.Dockerfile
  cap add:
   - NET ADMIN
   - NET_BROADCAST
  networks:
   R1h1br:
    ipv4_address: 172.18.0.3
  entrypoint: ["/bin/sh","-c"]
  command:
   ip route del default
   ip route add default via 172.18.0.2
   sleep infinity
```






Docker Compose Example (3/4)

Create container R1 build, run, network connect

```
services:
 R1:
  image: frrouting/frr-debian
  container name: R1
  privileged: true
  sysctls:
   - net.ipv4.ip forward=1
  cap_add:
   - NET ADMIN
   - NET BROADCAST
  networks:
   R1h1br:
    ipv4_address: 172.18.0.2
  volumes:
   - ./config/daemons:/etc/frr/daemons
   - ./config/R1/frr.conf:/etc/frr/frr.conf
```






Docker Compose Example (4/4)

- At the root of the app project, write file docker-compose.yml
- Start the Docker application
 - \$ docker compose up -d
- List the running containers
 - \$ docker ps

CONTAINER ID	IMAGE	NAMES
6b539d9c0387	frrouting/frr-debian	R1
6eee0a771914	host	h1

- Stop and remove the Docker application
 - \$ docker compose down




Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
 - Overview & Workflow
 - How to Test your App
 - Supplements
- Submission & Scoring Criteria
- References



Topology of Lab 5



NYCU CS 4.




Step 1 – Create Containers

- Prepare docker-compose.yml for following network segments
- Create containers and networks with your docker-compose.yml
- \$ docker compose up -d ASN 65001 ASN 65003 **ASN 65000** 172,19.0.2 3/2 172.19.0.3 R2 **R1 R4** 172.18.0.2 172.23.0.2 172.21.0.2 172/18.0.3 172.21.0.3 172.23.0.3 172.24.0.3 172.22.0.3 3/2 h2 **R3** h3 h4 172.22.0.2 172.24.0.2 **ASN 65002**



Step 2 – Create OVS Bridge

- Create an OVS bridge to connect to network segments
 - Use ovs-vsctl to create OVS bridge
 - Use ip or ovs-docker to set a connection between bridge and container






Step 3 – Enable ONOS fwd Application

Enable ONOS reactive forwarding

onos@root > app activate fwd

Hint: Set OVS bridge controller to ONOS and set protocol to Openflow 1.4






Step 4 – Enable FPI and FPM

- Set FIB Push configuration on R1 FRR Zebra
- Enable ONOS FPM manager

onos@root > app activate fpm

Then, ONOS can receive FIB information from R1





Step 5 - Create Makefile

- Write a Makefile for your application which contains:
 - ONOS service creation and setup
 - Container creation
 - OVS bridge creation
 - Link setup
- Create the application with a single command
 - \$ make
- Stop the application with a single command
 - \$ make clean

Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
 - Overview & Workflow
 - How to Test your App
 - Supplements
- Submission & Scoring Criteria
- References




How to Test Your App (1/3)

- Check IP configuration
 - \$ docker exec h1 ifconfig

```
eth0 Link encap:Ethernet HWaddr 02:42:ac:12:00:03
inet addr:172.18.0.3 Bcast:172.18.255.255 Mask:255.255.0.0
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:95 errors:0 dropped:0 overruns:0 frame:0
TX packets:9 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:0
RX bytes:10725 (10.7 KB) TX bytes:714 (714.0 B)
```

- Activate ONOS fwd application
 - onos@root > app activate fwd
- Check host communication (h1 -> h3)
 - \$ docker exec -it h1 ping 172.22.0.3 -c 3





How to Test Your App (2/3)

- Run bash on R1
 - \$ docker exec -it R1 bash
- Interact with FRR daemons

R1/# vtysh

Show R1 bgp

R1FRR> show ip bgp

```
172.22.0.2
                                                                         172.24.0.2
                                                  ASN 65002
                                                                                ASN 65004
R1# show ip bgp
BGP table version is 4, local router ID is 172.20.0.2, vrf id 0
Default local pref 100, local AS 65000
Status codes: s suppressed, d damped, h history, * valid, > best, = multipath,
                i internal, r RIB-failure, S Stale, R Removed
Nexthop codes: @NNN nexthop's vrf id, < announce-nh-self
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found
   Network
                     Next Hop
                                          Metric LocPrf Weight Path
*> 172.18.0.0/16
                     0.0.0.0(R1)
                                                         32768 i
*> 172.21.0.0/16
                     172.19.0.3(R2)
                                                             0 65001 i
   172.22.0.0/16
                     172.20.0.3(R4)
                                                             0 65003 65002 i
                     172.20.0.3(R3)
                                                             0 65002 i
   172.24.0.0/16
                     172.20.0.4(R3)
                                                             0 65002 65003 65004 i
                     172.20.0.4(R4)
                                                             0 65003 65004 i
```

ASN 65001

172.21.0.2

172.21.0.3

R2 172.19.0.3

ASN 65000

172/18.0.3

172,19.0.2

R1 172.18.0.2

ONOS

172.20.0.2

172.22.0.3

172.20.0.3

ASN 65003

172.23.0.2

172.24.0.3

172.20.0.4

172.23.0.3

Displayed 4 routes and 6 total paths




How to Test Your App (3/3)

Activate ONOS FIB Push Manager (FPM)

onos@root > app activate fpm

Show routing message from ONOS

onos@root > routes



```
onos@root > routes
B: Best route, R: Resolved route
Table: ipv4
B R Network
                                        Source (Node)
                        Next Hop
     172.21.0.0/16
                        172.19.0.3
                                        FPM (172.10.0.2)
     172.22.0.0/16
                                        FPM (172.10.0.2)
                        172.20.0.3
     172.24.0.0/16
                        172.20.0.4
                                        FPM (172.10.0.2)
   Total: 3
Table: ipv6
                        Next Hop
   Network
                                        Source (Node)
   Total: 0
```

Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
 - Overview & Workflow
 - How to Test your App
 - Supplements
- Submission & Scoring Criteria
- References



Supplements (1/2)

TA will provide the following

```
SDNFV_Lab5/

Gonfite

— daemons

— R1

— frr.conf

— docker-compose.yml

— host.Dockerfile
```

• The files contain the basic configs for h1 and R1 that you can start the containers using Docker Compose.



Supplements (2/3)

- The docker compose file also defined a ONOS service for you to use
- Configure your app to connect to this ONOS instead of your local ONOS environment.
- ONOS service ports are exposed to host
- Connect to ONOS CLI

```
$ ssh -o "StrictHostKeyChecking=no"
-o GlobalKnownHostsFile=/dev/null
-o UserKnownHostsFile=/dev/null
onos@localhost -p 8101
```

```
onos:
 image: onosproject/onos:latest
 container name: onos
 hostname: onos
 privileged: true
 networks:
    - default
 environment:
    - ONOS APPS=fpm, fwd
  ports:
    - "2620:2620"
    - "6653:6653"
    - "8101:8101"
    - "8181:8181"
 stdin open: true
```



Supplements (3/3)

R1 is configured to connect to the host's localhost.

You can connect to ONOS services via 172.17.0.1 or the docker0

interface ip address in your container

```
R1:
  image: frrouting/frr-debian
  container name: R1
  hostname: R1
  privileged: true
  sysctls:
    - net.ipv4.ip_forward=1
  cap_add:
    - NET_ADMIN
    - NET_BROADCAST
  networks:
   R1h1br:
      ipv4_address: 172.18.0.2
 extra hosts:
   - "host.docker.internal:host-gateway"
  volumes:
    - ./config/daemons:/etc/frr/daemons
    - ./config/R1/frr.conf:/etc/frr/frr.conf
```



Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References



Scoring Criteria (1/3)

- Create Makefile
 - You must provide Makefile, which creates the application with a make command
 - Makefile should be placed at the root of the project directory
 - TA will use your Makefile to build your application
 - You will not earn any credit if Makefile is not provided
- (18%) Create containers
 - Use Docker to create four host and five router containers
 - You lose two credits for each container that is not created
- (10%) Create an OVS bridge
 - You must use the ovs-vsctl command
 - You will not earn any credit if you do not conform to the above regulation



Scoring Criteria (2/3)

• (18%) Setup links

- Set the connections and IPs based on the topology
- Use the Docker network to set a connection between each pair of container
- Use <u>ip</u> or <u>ovs-docker</u> to set a connection between a bridge and a container
- Each link with a wrong setting will result in two points deduction
- (20%) Setup BGP configurations
 - Set the AS number based on the topology
 - TA will check your settings in frr.conf for each router
 - Each router with a wrong setting will result in four points deduction
- (20%) Ping test
 - Every host in the topology should be able to ping each other
 - Each host failing to reach some hosts will result in five points deduction



Scoring Criteria (3/3)


- (14%) Setup FIB Pushing
 - ONOS can receive FIB information from R1
- Reminders
 - Use the docker ONOS environment and activate the needed apps.
 - You should not use ONOS environment other than the docker one.

```
cu@root > apps -a -s
   3 org.onosproject.route-service
                                                   Route Service Server
                                           2.7.0
  11 org.onosproject.drivers
                                                   Default Drivers
                                           2.7.0
  15 org.onosproject.fwd
                                           2.7.0
                                                    Reactive Forwarding
  21 org.onosproject.optical-model
                                                    Optical Network Model
                                           2.7.0
  23 org.onosproject.gui2
                                           2.7.0
                                                    ONOS GUIZ
                                                    FIB Push Manager (FPM) Route Receiver
  35 org.onosproject.fpm
                                           2.7.0
  44 org.onosproject.openflow-base
                                           2.7.0
                                                    OpenFlow Base Provider
  45 org.onosproject.lldpprovider
                                           2.7.0
                                                   LLDP Link Provider
  46 org.onosproject.hostprovider
                                           2.7.0
                                                   Host Location Provider
  72 org.onosproject.openflow
                                                    OpenFlow Provider Suite
                                           2.7.0
```



Submission Naming Convention

- Rename your directory as lab5_<student ID>
- Compress the directory into a zip file named lab5_<student ID>.zip
- Upload your zip file to <u>E3</u>
- Wrong file name or format will result in 10 points deduction
- 20% deduction for late submission in one week
 - Won't accept submissions over one week





Demo

- TA will open a demo time-reserved table a week before the demo
- The dates will be chosen after the deadline
- Demo questions will appear at the start of the demo
- The score of the demo is 40% total score of this lab
 - For example:
 - You earn 100% of the credits for submission
 - You earn 80% of the credits for the demo
 - then your total score for this lab will be:
 - $-100 \times 60\% + 80 \times 40\% = 92.$



About help!

- For any lab problem, ask at the e3 forum
 - Ask at the e3 forum
 - TAs will help to clarify lab contents instead of giving answers!
 - Please describe your questions with sufficient context,
 - E.g., Environment setup, Input/Output, Screenshots, ...
- For personal problems, mail to sdnta@win.cs.nycu.edu.tw
 - You have particular problems so that you can't meet the deadline
 - You got a weird score with the lab
- No Fixed TA hour



Outline

- Introduction
- Docker Installation
- Docker Usage
- Example Scenario Setup
- Introduction to Docker Compose
- Lab 5 Overview
- Submission & Scoring Criteria
- References



References

- Docker overview
- Docker commandline reference
- Docker compose reference
- FRRouting User Guide v8.0