HW#4 RTOS Analysis

Chun-Jen Tsai
NYCU
11/22/2024

Homework Goal

- In this homework, you will analyze the performance of a real-time OS (RTOS), FreeRTOS, for multithreading
- Your tasks:
  - Trace the OS kernel code and analyze how thread management and synchronization are done
  - Measure the context-switching overhead of the application (need to add counters in Aquila)
  - Measure the synchronization overhead of the application (better to add counters in Aquila)
- You should upload your report to E3 by 12/6, 17:00.
  - Report is 3 pages max, PDF format only. No demo this time.

FreeRTOS

- FreeRTOS is a C-based real-time operating system kernel for embedded devices
  - Developed by Richard Barry in 2003
  - Barry joined Amazon Web Services (AWS) and passed the stewardship of the project to AWS in 2017
  - The project adopts MIT License
- We used FreeRTOS v202111.00 in this HW:
  - All RISC-V unrelated sources are removed (way too big)
  - The original source available at https://www.freertos.org/
  - No need to modify source code of FreeRTOS for Aquila

FreeRTOS Multithreading API

- Unlike other programming languages, C does not have a standard API for multithreading
  - ISO C11 has a multithreading API since 2011, but the most popular API is still the non-standard pthread API
- FreeRTOS Multithreading API is quite simple:

```
/* Two threads creation for FreeRTOS */

int main(void)
{
    int prm1 = 1, prm2 = 2;
    xTaskCreate(Task_Handler, "Task1", 256, (void *) &prm1, 3, NULL);
    xTaskCreate(Task_Handler, "Task2", 256, (void *) &prm2, 4, NULL);
    vTaskStartScheduler();
}

void Task_Handler(void *pvParam)
{
    for (int idx = 0; idx < 10/(int) *pvParam; idx++) {
        printf("\nThis is Task%d.\n", (int) *pvParam);
        vTaskDelay(1000/portTICK_PERIOD_MS);  // sleep a while.
    }

    vTaskDelete(NULL); /* Thread ends, delete it from the task queue. */
}
```

Target Application: `rtos_run`

- Download `rtos_run.tgz` from E3:

```
rtos_run/
├── FreeRTOS/
│   ├── Demo/
│   ├── License/
│   ├── README.md
│   ├── Source/
│   │   ├── croutine.c
│   │   ├── event_groups.c
│   │   ├── include/
│   │   ├── list.c
│   │   ├── portable/
│   │   │   ├── Common/
│   │   │   ├── GCC/
│   │   │   │   └── RISC-V/
│   │   │   │       ├── Documentation.url
│   │   │   │       ├── chip_specific_extensions/
│   │   │   │       ├── port.c
│   │   │   │       ├── portASM.S
│   │   │   │       ├── portmacro.h
│   │   │   │       └── readme.txt
│   │   │   ├── MemMang/
│   │   │   └── readme.txt
│   │   ├── queue.c
│   │   ├── stream_buffer.c
│   │   ├── tasks.c
│   │   └── timers.c
│   └── Test/
├── FreeRTOSConfig.h
└── Makefile, rtos_run.c, rtos_run.ld
```

277 directories, 1446 files

After "make", a `build/` directory would contain the `rtos_run.map` and `rtos_run.objdump` files.

The executable `rtos_run.elf` will be in the top directory

portASM.S → Timer interrupt handling routine.

tasks.c → Multi-thread managers.

FreeRTOSConfig.h → FreeRTOS configurations for application.

Application Behavior of `rtos_run`

- There are three visible threads and two invisible threads in the `rtos_run` application:



Protection of Shared Resources

- In a preemptive multi-tasking OS, shared resources cannot be modified without protection:

```
volatile int
    shared_counter = 0,
    done = 0;

Task1()
{
    while (!done)
    {
        shared_counter++;
    }
}

Task2()
{
    while (!done)
    {
        shared_counter++;
    }
}
```

```
80000030 <Task1>:
80000030:  lui   a3, 0x80008
80000034:  lw    a5, 8(a3)    # <done>
80000038:  bnez  a5, 80000054 <Task1+0x24>
8000003c:  lui   a4, 0x80008
80000040:  lw    a5, 12(a4)  # <shared_counter>
80000044:  addi  a5, a5, 1
80000048:  sw    a5, 12(a4)
8000004c:  lw    a5, 8(a3)
80000050:  beqz  a5, 80000040 <Task1+0x10>
80000054:  ret
```

Default Execution

- When you compile and run the application you should see the following output
  - The result is bad because we did not enable mutex protection

```
================================================================================
Copyright (c) 2019-2023, EISL@NYCU, Hsinchu, Taiwan.
The Aquila SoC is ready.
Waiting for an ELF file to be sent from the UART ...

Program entry point at 0x8000144C, size = 0xAE60.
--------------------------------------------------------------------------------

Task 1 start running ...

Task 2 start running ...



At the end, the shared counter = 10000
Task1 local counter = 10000
Task2 local counter = 9263
Task1 counter + Task2 counter != Shared counter, the counter is corrupted.
```

FreeRTOS Mutex Protection

- There two types of synchronization APIs in FreeRTOS:
  1. `xSemaphoreTake() / xSemaphoreGive()`
  2. `taskENTER_CRITICAL() / taskEXIT_CRITICAL()`

- Note that in FreeRTOS, a mutex is a binary semaphore
- We use the 1st pair to protect the shared counter, and the 2nd pair to protect the UART (i.e. `printf()`)
  - What is the overhead (in cycles) of these two pairs of APIs?
  - What are the algorithmic differences of these two pairs of APIs?

Application with Mutex Protection

- With mutex protection of the shared variable, the output would be good
  - Made the change: "`#define USE_MUTEX 1`" in `rtos_run.c`

```
==========================================================================
Copyright (c) 2019-2023, EISL@NYCU, Hsinchu, Taiwan.
The Aquila SoC is ready.
Waiting for an ELF file to be sent from the UART ...

Program entry point at 0x800014C4, size = 0xAE60.
--------------------------------------------------------------------------

Task 1 start running ...

Task 2 start running ...



At the end, the shared counter = 10000
Task1 local counter = 3065
Task2 local counter = 6935
The shared counter is protected well.
```

Context-Switching Overhead

- A preemptive multi-tasking OS uses timer interrupts to assign CPU usage from one thread to the other
  - The context-switching overhead is inversely proportional to the time quantum (time slice)
  - The default value of FreeRTOS time quantum is 10 msec
- To measure the context-switching overhead, you must count the number of cycles between:
  - A timer interrupt arrives
  - A new thread begins execution
- You can change the time quantum size down to 5 msec to see its impact on the overhead

The Timer Interrupt Device

- In Aquila, the module `clint` is used to provide timer interrupts and software interrupts
- `Clint` has three registers
  - `mtime`: 64-bit counter of timer ticks
  - `mtimecmp`: Upper-threshold to trigger a timer interrupt
  - `msip`: a 32-bit register to trigger a software interrupt
- FreeRTOS will update `mtimecmp` to setup the next context-switch time (based on time quantum duration)

Changing Time Quantum

- In FreeRTOS, time quantum is configured by the header file: `FreeRTOSConfig.h`
  - The default time quantum is 10 msec:

```
...

#define CLINT_CTRL_ADDR                 ( 0xF0000000UL )
#define configMTIME_BASE_ADDRESS        ( CLINT_CTRL_ADDR + 0x0UL )
#define configMTIMECMP_BASE_ADDRESS     ( CLINT_CTRL_ADDR + 0x8UL )

#define configUSE_PREEMPTION            1
#define configUSE_IDLE_HOOK             0
#define configUSE_TICK_HOOK             1
#define configCPU_CLOCK_HZ              ( ( uint32_t ) ( 41666667 ) )
#define configTICK_RATE_HZ              ( ( TickType_t ) 100 )
#define configMAX_PRIORITIES            ( 7 )
#define configMINIMAL_STACK_SIZE        ( ( uint32_t ) 100 )
#define configTOTAL_HEAP_SIZE           ( ( size_t ) ( 12 * 1024 ) )

...
```

General Mutex for Synchronization

- A mutex is a variable to indicate two states: “locked” and “unlocked” of a shared resource:

```
int mutex;

mutex_take(mutex);
      code that uses the shared resource.
mutex_give(mutex);
```

Execution blocked here if the mutex has been taken by other threads.

- There are several ways to implement a mutex:
  - ISA-independent SW
  - Special instructions or ISA status flags
  - Hardware device

Mutex Implementation

- Software mutex implementation techniques
  - Software algorithms (e.g. the Peterson's algorithm)
    - Drawback: less efficient
  - Atomic test-and-set / Conditional load-store
    - Drawback: only supported by new ISAs
  - Disabling interrupt
    - Drawback: only works for single-core, single-hart
- Hardware mutex approach
  - A HW mutex is a device that contains a list of mutex registers
    - An unlocked mutex has zero in it
    - Each thread write their ID to the register to lock the mutex
    - Once locked, the mutex only accepts a write operation with the same ID, which unlocks the mutex back to zero

Peterson's Mutex Algorithm

- Peterson's algorithm† guarantees exclusive accesses to a shared resource among n threads (running on n cores) without special assembly instructions
- A two-thread version is as follows:

CPU 1

```
/* trying protocol for T1 */
Q1 = true; /* request to enter */
TURN = 2;  /* who's turn to wait */
wait until not Q2 or TURN == 1;
Critical Section;
/* exit protocol for T1 */
Q1 = false;
```

CPU 2

```
/* trying protocol for T2 */
Q2 = true; /* request to enter   */
TURN = 1;  /* who's turn to wait */
wait until not Q1 or TURN == 2;
Critical Section;
/* exit protocol for T2 */
Q2 = false;
```

† G. L. Peterson, "Myth about the Mutual Exclusion Problem," *Information Processing Letters*, **12**, no 3, June 30, 1981.

Test-and-Set Atomic Instructions

- For synchronization, a thread must execute the following code before entering a critical section:

```
int mutex; /* '0' means unlocked, '1' means locked */

while ( test_and_set(mutex) == 1) /* busy waiting */
  Code that uses the shared resource.
mutex = 0;
```

- A 'SWAP' instruction (`amoswap.w` in RSIC-V) can be used to implement the test-and-set function:

```
int test_and_set(int mutex)
{
        temp = mutex;
        mutex = 1;
        return temp;
}
```

The first two lines cannot be interrupted during execution!

Example Code of `amoswap`:

- Assume that `lock_addr` is the mutex address
  - mutex = 1 means lock, 0 means unlock
- Mutex take:

```
asm volatile ("lui t0, %hi(lock_addr)");
asm volatile ("lw t3, %lo(lock_addr)(t0)");
asm volatile ("li t0, 1");
asm volatile ("0:");
asm volatile ("lw t1, (t3)");
asm volatile ("bnez t1, 0b");
asm volatile ("amoswap.w.aq t1, t0, (t3)");
asm volatile ("bnez t1, 0b");
```

- Mutex give:

```
asm volatile ("lui t0, %hi(lock_addr)");
asm volatile ("lw t3, %lo(lock_addr)(t0)");
asm volatile ("amoswap.w.rl x0, x0, (t3)");
```

Conditional Load/Store Instructions

- Conditional load/store allows atomic operation without locking the buses
  - In RISC-V, we have LR/SC instructions
  - In ARM, we have LDREX/STREX instructions
- Code example of shared counter protection:
  - Each core add a shared counter by 100 times

```
    la a0, shared_counter # load address of the shared counter
    li a1, 100            # Initialize loop variables
1:
    lr.w a4, (a0)         # Read counter and make a reservation
    add a4, a4, 1         # Add 1 to a4
    sc.w a4, a4, (a0)     # Try to write to the shared counter
    bnez a4, 1b           # If failed, go back to do it again

    add a1, a1, -1        # decrement the loop variable
    bnez a1, 1b
```

Comments on the Homework

- The homework is about RTOS multi-threading analysis
  - Performance optimization is not required
- Grade is totally based on the analysis of the RTOS:
  - The context switching behavior analysis:
    - Description of the switching algorithm
    - Context switching overhead vs. time quantum size
    - *Impact to data cache due to context switching (the sample code is too small to show this!)*
  - The synchronization behavior analysis
    - The algorithmic description
    - The overhead (cycles required for mutex task & give, respectively)