Modular Data Workflow for Wine Quality Analysis — Module Summary

Author: Aung Ze Ya | **Date:** October 24, 2026 | **Course:** MSc Capstone / AI Programming Foundations

---

1. Overview

This academic summary report documents a modular, reproducible Python data processing and exploratory analysis workflow examining the physicochemical attributes of red wine within the context of the MSc Capstone / AI Programming Foundations curriculum. The primary objective is to evaluate chemical predictors of sensory ratings using the UCI Red Wine Quality dataset (winequality-red.csv, 1,599 observations × 12 variables), accessible at the UCI Machine Learning Repository (https://archive.ics.uci.edu/dataset/186/wine+quality).

2. Dataset Description

The dataset originates from the benchmark study by Cortez et al. (2009) and comprises 1,599 red wine observations. The data architecture contains 12 total numeric attributes, consisting of 11 physicochemical input features (fixed acidity, volatile acidity, citric acid, residual sugar, chlorides, free sulfur dioxide, total sulfur dioxide, density, pH, sulphates, and alcohol) and 1 ordinal target variable representing human preference quality ratings bounded between 3 and 8. All 12 variables are strictly continuous or discrete numeric measures obtained via standardized laboratory chemical assays.

3. Key Decisions and Assumptions

The data processing workflow in **data_workflow.ipynb** incorporates key software engineering decisions and analytical assumptions:

- **Delimiter Parsing:** Ingested raw sensor metrics from **winequality-red.csv** using semicolon delimiters (sep=";") to correctly parse UCI dataset formatting.
- **Column Standardization:** Executed **clean_column_names()** to strip whitespace, lowercase text, and convert headers into standardized **snake_case** (e.g., fixed acidity to fixed_acidity).
- **Feature Discretization:** Executed **add_quality_tier()** using pd.cut(bins=[0, 4, 6, 10]) to categorize continuous ratings into three ordinal tiers: Low (3–4), Medium (5–6), and High (7–8).
- **Class Distribution:** Raw ratings exhibit a heavy concentration in the Medium tier (82.5%, n = 1,319), while the Low tier contains n = 63 (3.9%) and the High tier contains n = 217 (13.6%).
- **Missing Values Assumption:** Verified zero missing or null values across all 1,599 rows.
- **Consensus Ratings Assumption:** Sensory scores are assumed to represent panel-consensus median/average scores evaluated by expert wine assessors.

DataFrame manipulation and grouped aggregations were performed using Pandas (McKinney, 2010), with numerical array operations supported by NumPy (Harris et al., 2020).

4. Responsible Practice

A rigorous evaluation of responsible data practices identifies critical limitations regarding sampling, scope, and discretization bias:

- **Geographic Sampling Bias:** All samples were collected exclusively from the Vinho Verde region in northern Portugal. The chemical thresholds reflect localized soil composition, microclimates, and regional grape varieties (e.g., Vinhão), limiting direct generalizability to other global viticultural regions (e.g., Napa Valley, Bordeaux, or Barossa Valley).
- **Omission of White Wine Metrics:** This workflow focused strictly on red wine samples (winequality-red.csv). White wine varieties (winequality-white.csv) exhibit distinct physicochemical dynamics, including significantly higher residual sugars and different sulfur dioxide balance.

- **Binning-Boundary Bias:** Discretizing ratings into Low (<=4), Medium (5-6), and High (>=7) imposes human-defined, hard cutoffs. Creating ordinal tiers risks introducing boundary bias where subtle continuous metric differences (e.g., score 4 vs 5) cross tier boundaries. This was mitigated by explicitly documenting exact bin definitions (pd.cut(bins=[0, 4, 6, 10])) and reporting both mean, median, and standard deviation metrics across all chemical properties.

5. Reproducibility

To ensure complete scientific reproducibility, all dependencies were pinned via pip freeze within a dedicated Conda environment (capstone-proj1) in **requirements.txt**: **pandas==3.0.6, numpy==2.5.3, matplotlib==3.11.2, seaborn==0.13.2, and ipykernel==7.3.0**. Version control is managed in GitHub repository ai-programming-foundations-project across main and dev branches, tracking key commit hashes 489a48b, f9376d2, and 4231b74 (**Pineau et al., 2021; Reproducible Data Science with Python, n.d.**).

6. Future Integration Reflections

Future predictive pipelines targeting quality_tier must employ a stratified train-test split to preserve the 82.5% Medium class distribution, wrapping StandardScaler alongside a RandomForestClassifier or ordinal logistic regression in an sklearn Pipeline. Neural network prep requires standardizing continuous features (alcohol, density, pH), adopting ordinal classification loss or one-hot targets, applying SMOTE or class weights to handle class imbalance, and training via the Adam optimizer with early stopping. Agentic automation provides substantial value for automated exploratory data analysis, hyperparameter sweeps, and anomaly detection in sensor data; however, autonomous re-binning, unsupervised feature selection on the small 217-sample High-tier subset, or auto-generated chemical interpretations without geographic caveats pose severe analytical risks.

7. Figure Interpretations

Grouped statistical aggregations and graphical interpretations demonstrate significant physicochemical differentiation across wine quality tiers:

Quality Tier	Alcohol (%) Mean ± Std (Med)	Volatile Acidity (g/dm³) Mean ± Std (Med)	Citric Acid (g/dm³) Mean ± Std (Med)	Sulphates (g/dm³) Mean ± Std (Med)	pH Mean ± Std (Med)
Low (3–4) n = 63	10.22 ± 0.92 (10.00)	0.724 ± 0.248 (0.680)	0.174 ± 0.207 (0.080)	0.592 ± 0.224 (0.560)	3.384 ± 0.175 (3.380)
Medium (5–6) n = 1,319	10.25 ± 0.97 (10.00)	0.539 ± 0.168 (0.540)	0.258 ± 0.188 (0.240)	0.647 ± 0.167 (0.610)	3.311 ± 0.152 (3.310)
High (7–8) n = 217	11.52 ± 1.00 (11.60)	0.406 ± 0.145 (0.370)	0.376 ± 0.194 (0.400)	0.743 ± 0.134 (0.740)	3.289 ± 0.154 (3.270)

- **Figure 1:** Shows a box plot illustrating the distribution of alcohol content across numerical quality scores and categorical tiers. Interpretation: High-tier wines display a significantly elevated alcohol distribution (mean 11.52%, median 11.60%) compared to Medium (mean 10.25%) and Low (mean 10.22%) tiers, establishing alcohol concentration (+0.48 correlation) as a primary positive driver of wine preference (Hunter, 2007).
- **Figure 2:** Shows a correlation matrix heatmap evaluating linear relationships among chemical properties and quality ratings. Interpretation: Wine quality exhibits strong positive linear correlations with alcohol (+0.48), sulphates (+0.25), and citric acid (+0.23), alongside a strong negative correlation with volatile acidity (−0.39), illustrating the combined influence of ethanol, preservation agents, and acidity profiles (Waskom, 2021).
- **Figure 3:** Shows a scatter plot displaying volatile acidity versus citric acid categorized by quality tier. Interpretation: High-tier wines predominantly cluster in the high-citric-acid (>0.30 g/dm³) and low-volatile-acidity (<0.50 g/dm³)

quadrant, demonstrating that fresh citrus notes combined with suppressed acetic acid vinegar profiles are strongly characteristic of premium ratings.

8. Summary & Interpretation

In summary, exploratory analysis of the UCI red wine quality dataset reveals that elevated alcohol, higher citric acid, and increased sulphate levels combined with low volatile acidity serve as the primary physicochemical hallmarks of high-quality wines. These findings are grounded in modular data processing decisions—including semicolon parsing, snake_case header standardization, and ordinal tier binning—which ensure structural integrity across 1,599 complete observations. However, practical application of these insights must account for key responsible practice considerations, notably the regional Vinho Verde sampling boundary, the 82.5% Medium class imbalance, and human-defined binning boundaries.

9. References

Cortez, P., Cerdeira, A., Almeida, F., Matos, T., & Reis, J. (2009). Modeling wine preferences by data mining from physicochemical properties. Decision Support Systems, 47(4), 547–553. https://doi.org/10.1016/j.dss.2009.05.016

Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., ... & Oliphant, T. E. (2020). Array programming with NumPy. Nature, 585(7825), 357–362. https://doi.org/10.1038/s41586-020-2649-2

Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. Computing in Science & Engineering, 9(3), 90–95. https://doi.org/10.1109/MCSE.2007.55

McKinney, W. (2010). Data structures for statistical computing in Python. In Proceedings of the 9th Python in Science Conference (Vol. 445, pp. 51–56).

Pineau, J., Vincent-Lamarre, P., Sinha, K., Larivière, V., Beygelzimer, A., Fox, E., Zheng, H., & Larochelle, H. (2021). Improving reproducibility in machine learning research (a report from the NeurIPS 2019 reproducibility program). Journal of Machine Learning Research, 22(164), 1–20.

Reproducible Data Science with Python. (n.d.). Course Module Article.

Waskom, M. L. (2021). Seaborn: Statistical data visualization. Journal of Open Source Software, 6(60), 3021. https://doi.org/10.21105/joss.03021