

Question 1 Of 30

Q2

Next: >

Score 0

Incorrect

Type : Mcq

Attempted

A reporting utility provides both `show(int x)` and `show(double x)` methods. During testing, the developer calls `show(10)`. Which overload will Java select?

☐ Compilation fails because methods share names

☒ Incorrect Answer

☐ `show(double)` is selected for integer input

☐ `show(int)` is selected for integer input

☒ Correct Answer

☐ Both methods execute for integer input

Question 2 Of 30

Q19

Score 1 Correct Type : Mcq Attempted

A delivery application starts with `LocalDate.of(2026, 10, 1)` and schedules a follow-up two days later using `plusDays(2)`. Which date will be produced?

- ☐ 10/2/2026
- ☐ 10/1/2028
- ☐ 11/1/2026
- ☒ 10/3/2026

Correct Answer

Question 3 Of 30

Q10

< Previous

Next: 

Score 1

Correct

Type : Mcq

Attempted

A support utility must inspect every file under a log directory, including nested folders. Which Java API is appropriate for traversing that directory tree?

- ☐ `Paths.get(...)` by itself
- ☐ `FileInputStream`
- ☒ `Files.walk(...)`
- ☐ `Files.readAllLines(...)`

 Correct Answer

Search

ENG
IN17:36
07-10-2026

Question 4 Of 30

Q12

< Previous

Next: 

Score 1

Correct

Type : Mcq

Attempted

A Scala ETL helper keeps business values in an immutable `List`. The developer wants to add a value while preserving the original list. Which operation follows immutable collection behavior?

- ☐ Call an in-place `list.add(value)` method
- ☐ Change the existing list length in place
- ☐ Assign directly with `list(0) = value`
- ☐ Create a new list with `value :: list`

 Correct Answer

Search

ENG
IN17:37
07-10-2026

Score 2

Correct

Type : Mcq

Attempted

An ingestion job reads nested JSON records, transforms the structured fields, and must store analytics-ready output efficiently. Which approach is appropriate for producing Parquet output?

- Convert nested JSON into CSV text before Spark can process it
- Read every JSON record as plain text and never parse nested fields
- Read JSON as structured data and write the result as Parquet with schema information
- Collect all JSON records to the driver before creating Parquet output

Correct Answer

Question 6 Of 30

Q15

Previous

Next

Score 1 Correct Type : Mcq Attempted

A Scala parser wraps `parse()` inside `Try(parse())` because malformed input may throw an exception. If an exception occurs, what value does `Try` produce?

- ☐ A compile-time error
- ☒ A `Failure`
- ☐ A `Success`
- ☐ A `None`

Correct Answer

Question 7 Of 30

Q13

Previous

Next

Score 1

Correct

Type : Mcq

Attempted

A Spark trainee has finished defining several RDD transformations and now needs an operation that actually triggers computation and returns a result. Which listed RDD operation is an action?

- ☐ `'filter()'`
- ☐ `'map()'`
- ☐ `'flatMap()'`
- ☒ `'count()'`

Correct Answer

Question 8 Of 30

Q29

< Previous

Next >

Score 2

Correct

Type : Mcq

Attempted

A DStream job uses checkpointing so that it can recover after a driver restart. For that recovery to work, where should the checkpoint information be stored?

- ☐ Only in executor memory for the current application run
- ☐ In a temporary directory on the failed driver only
- ☐ In a local Scala variable inside the streaming program
- ☒ In reliable durable storage that remains accessible after restart

✓ Correct Answer



Search



Question 9 Of 30

Q8

Previous

Next

Score 1

Correct

Type : Mcq

Attempted

In an HR system, 'Manager' is declared as 'class Manager extends Employee'. What relationship does this declaration represent?

- ☐ 'Manager' contains 'Employee' only through composition
- ☒ 'Manager' inherits members and behavior from 'Employee'
- ☐ 'Employee' defines only an interface method
- ☐ 'Manager' and 'Employee' remain completely unrelated classes

Correct Answer

Question 10 Of 30

Q5

Previous

Next

Score 1

Correct

Type : Mcq

Attempted

In an e-commerce class, one constructor starts with `this(10)` so that shared initialization logic can be reused. What does this call invoke?

☒ The call invokes another constructor in the class

Correct Answer

☐ The call invokes a static method directly

☐ The call invokes the object's `toString()` method

☐ The call invokes the parent constructor directly

Question 11 Of 30

Q11

Previous

Next

Score 1 Correct Type : Mcq Attempted

A Scala configuration program declares `val city = "Paris"` and later tries to assign a different city to the same name. Which statement explains the behavior of this binding?

- ☒ The binding cannot be reassigned after initialization
- ☐ The String object becomes globally constant everywhere
- ☐ The binding becomes mutable inside every loop
- ☐ The binding can be reassigned to another city

Correct Answer

Question 12 Of 30

Q24

< Previous

Next >

Score 2

Correct

Type : Mcq

Attempted

A Spark transformation can be expressed using named DataFrame columns and built-in functions instead of low-level RDD code. Why is the DataFrame-expression approach generally preferred?

- ☐ They work without requiring any schema information
- ☒ They provide structured semantics Spark can optimize
- ☐ They eliminate every shuffle during Spark execution
- ☐ They always execute on exactly one machine

✓ Correct Answer

Question 13 Of 30

Q26

< Previous

Next >

Score 2 Correct Type : Mcq Attempted

A legacy DStream application must resume correctly after its driver fails and restarts. Which configuration supports recovery of previously recorded streaming progress?

- ☐ Configure a larger browser cache for recovery
- ☐ Configure a new Java package for recovery
- ☒ Configure streaming checkpointing for saved progress
- ☐ Configure a different Scala collection for recovery

✓ Correct Answer

Score 2

Correct

Type : Mcq

Attempted

During a Spark Streaming lab, a trainee reads events from a socket at 'localhost:9999'. What limitation should the trainee understand about using a socket source?

- ☐ It provides persistent Kafka-style retention for incoming messages
- ☐ It provides a durable message queue that can replay all data after failure
- ☐ It guarantees automatic recovery without any checkpointing
- ☒ It is mainly a development/demo source and does not provide production durability

✓ Correct Answer



Search

ENG
IN

17:38

07-10-2026

Score 1

Correct

Type : Mcq

Attempted

A customer-service application creates a new 'Customer' while processing an order using 'Customer c = new Customer();'. At a beginner Java memory-model level, what does this statement most directly create?

☒ A local reference and new object☐ Only a class definition gets created☐ Two objects stored only on stack☐ A static field and new object

✓ Correct Answer



Q Search



Question 16 Of 30

Q9



< Previous

Next >

Score 1

Correct

Type : Mcq

Attempted

A batch job generates a human-readable report containing formatted text lines. Which Java class is most suitable for writing that report?

☒ `PrintWriter`

✓ Correct Answer

☐ `FileInputStream`

☐ `ObjectInputStream`

☐ `ThreadLocal`



Search



ENG IN



Score 1

Correct

Type : Mcq

Attempted

A pricing team wants calculation functions that are predictable and easy to unit-test: identical inputs should always produce identical outputs without changing shared state. Which practice best supports this requirement?

- ☐ Depend on current time for each result
- ☐ Modify shared global variables inside each function
- ☐ Use pure functions without changing shared state
- ☐ Update input collections directly inside each function

✓ Correct Answer

Question 18 Of 30

Q14

< Previous

Next >

Score 1

Correct

Type : Mcq

Attempted

A Scala utility needs to open and read a small local text configuration file. Which Scala API is commonly used for this purpose?

☒ `scala.io.Source.fromFile(...)`

✓ Correct Answer

☐ `scala.util.Try.read(...)`☐ `scala.io.FileWriter(...)`☐ `scala.collection.List.open(...)`

Search

ENG
IN17:39
07-10-2026

Question 19 Of 30

Q16

< Previous

Next >

Score 1

Correct

Type : Mcq

Attempted

A text-processing pipeline has a Scala collection of sentences and needs one flattened collection containing every individual word. Which transformation is the most appropriate?

- ☐ Use 'foreach' without returning a collection
- ☒ Use 'flatMap' to emit individual words
- ☐ Use 'filter' based on sentence length
- ☐ Use 'map' to return whole sentences

✓ Correct Answer

Question 20 Of 30

Q4

< Previous

Next >

Score 1

Correct

Type : Mcq

Attempted

An inventory program assigns a primitive-looking number using `Integer count = 10;`. What conversion is Java performing automatically?

- ☒ Autoboxes primitive `int` into an `Integer` object
- ☐ Promotes the numeric value directly to `double`
- ☐ Unboxes an `Integer` value into primitive `int`
- ☐ Creates a `String` object from numeric input

✓ Correct Answer



Q Search



ENG IN



17:39 07-10-2026

Question 21 Of 30

Q6

< Previous

Next >

Score 1

Correct

Type : Mcq

Attempted

A framework parent class declares a validation method as 'final'. A trainee creates a child class and wants to customize that method. What is the child class allowed to do?

- ☐ Remove the method from inherited class API
- ☐ Override the method freely in child class
- ☒ Call the method but never override it
- ☐ Make the inherited method abstract in child

✓ Correct Answer

Question 22 Of 30

Q21

< Previous

Next >

Score 2

Correct

Type : Mcq

Attempted

A Spark pipeline defines several RDD transformations, but Spark delays running them until an output is requested. Why does Spark use this lazy-evaluation behavior?

- ☐ It stores every intermediate result on the driver
- ☐ It executes every transformation twice before any action
- ☐ It disables Spark lineage and fault-tolerance tracking
- ☒ It builds a plan before actions trigger execution

✓ Correct Answer

Question 23 Of 30

Q27

< Previous

Next >

Score 2

Correct

Type : Mcq

Attempted

A shared Java list is read very frequently by many threads, while modifications happen only occasionally. Why might 'CopyOnWriteArrayList' be considered for this usage pattern?

- ☒ It supports safe iteration when reads dominate updates
- ☐ It automatically keeps collection elements sorted always
- ☐ It guarantees constant-time updates for every write
- ☐ It removes every need for synchronization mechanisms

✓ Correct Answer

Question 24 Of 30

Q22

< Previous

Next >

Score 2

Correct

Type : Mcq

Attempted

A data engineer investigates a slow DataFrame and runs `df.explain()`. The output contains operators such as `Project`, `Filter`, and `FileScan`. What does this output represent?

- ☐ The notebook dependency graph between cells
- ☐ The selected RDD persistence storage level
- ☒ The query execution plan used by Spark
- ☐ The DataFrame schema and column data types

✓ Correct Answer

Score 1 Correct Type : Mcq Attempted

During a code review, a trainee is asked where local method variables and newly created objects are generally kept in the basic Java memory model. Which statement is the best description?

- ☐ Objects and variables are stored only in source files
- ☐ Stack memory permanently stores all created Java objects
- ☒ Local variables use stack frames; objects generally use heap memory
- ☐ All runtime values are stored only on the heap

✓ Correct Answer

Q28

Score 2

Correct

Type : Mcq

Attempted

A web API repeatedly accesses a relational database and spends time creating new connections for every request. What problem is a connection pool such as HikariCP intended to solve?

- ☐ It recovers Spark RDD lineage after failures
- ☐ It executes Java bytecode inside the JVM
- ☒ It reuses database connections instead of recreating them
- ☐ It automatically designs SQL queries for applications

✓ Correct Answer



Search



Q28

Score 2 Correct Type : Mcq Attempted

A web API repeatedly accesses a relational database and spends time creating new connections for every request. What problem is a connection pool such as HikariCP intended to solve?

- ☐ It recovers Spark RDD lineage after failures
- ☐ It executes Java bytecode inside the JVM
- ☒ It reuses database connections instead of recreating them
- ☐ It automatically designs SQL queries for applications

Correct Answer

Question 27 Of 30

Q18

Previous

Next

Score 1

Correct

Type : Mcq

Attempted

A registration service must validate whether user-entered strings follow required formats such as email or phone patterns. What is a regular expression mainly used for?

- ☐ Allocating heap memory
- ☐ Opening database transactions
- ☒ Matching text patterns
- ☐ Creating Java threads

Correct Answer

Question 28 Of 30

Q25

< Previous

Next >

Score 2 Correct Type : Mcq Attempted

A live operations dashboard must continuously calculate the most recent 15 minutes of events as new data arrives. Which streaming concept is needed?

- ☐ A checkpoint without any time-based grouping
- ☐ A watermark without any aggregation window
- ☐ A static `groupBy` over a completed batch only
- ☒ A windowed aggregation over the event stream

✔ Correct Answer

Question 29 Of 30

Q7

< Previous

Next >

Score 1

Correct

Type : Mcq

Attempted

A media-processing program needs to save raw image bytes exactly as received. Which Java class is appropriate for writing those bytes to a file?

☒ `FileOutputStream`

✔ Correct Answer

☐ `PrintWriter` only☐ `FileReader`☐ `Scanner`

Question 30 Of 30

Q20

< Previous

Score 1

Correct

Type : Mcq

Attempted

During a Spark lab, a trainee already has a Scala collection in memory and wants to distribute it as an RDD. Which Spark call should be used?

- ☐ `data.toDataFrame.show()`
- ☒ `sc.parallelize(data)`
- ☐ `sc.collect(data)`
- ☐ `spark.sql(data)`

✓ Correct Answer