AILI: Adaptive Interview Learning Interface

CS 435 Human-Computer Interaction | High-Fidelity Prototyping and User Evaluation

Indian Institute of Technology Gandhinagar | Semester I, 2026–2027

Group members: Komal Chandela (25510058) | Uditesh Dasgupta (23110344) | Manan Chavda (23110078) | Kunal Maske (23110201)

Instructor: Dr. Yogesh K. Meena

Executive Summary

AILI (AI-Assisted Interview Learning Interface) is a browser-based interview-practice system designed for university students preparing for internships, placements, and graduate-school interviews. The high-fidelity prototype offers two complementary modes: Prototype A, a feedback-led reflective practice loop, and Prototype B, a conversational interview simulation with adaptive follow-up questions and a post-interview debrief.

The available evaluation records comprise two distinct evidence streams. First, the SUS/task-time summary contains six participant records (P01–P06), with a mean SUS score of 90.4/100 (SD = 7.0, recalculated from the six listed scores) and a mean task time of 250 seconds (range = 195–310 seconds). Second, six detailed Prototype B interview-session reports provide evidence about system interaction and generated interview evaluations. These streams have no verified participant-level crosswalk and are not combined. The detailed reports include two sessions marked incomplete after two exchanges and one report with response/turn anomalies. A short 10-question post-use questionnaire is included in the project workbook, but its six sample rating rows are explicitly synthetic demonstrations, not collected participant responses.

Six detailed Prototype B interview-session reports were also reviewed. They show varied interaction outcomes, including two sessions marked incomplete after two exchanges, strong performance in some sessions, and possible transcript/turn-integrity issues in another. These detailed session reports are discussed separately from the six-person SUS summary because the available files do not provide a reliable participant-ID crosswalk linking the session aliases to P01–P06. This report therefore does not combine the two datasets or claim a 100% completion rate.

1. Project Context and Design Rationale

The Task 2 needs assessment identified uncertainty about answer quality, difficulty practising consistently, and dissatisfaction with generic feedback. In the survey of 30 respondents, 18 (60%) reported uncertainty about whether their answers were good, 17 (57%) found consistent practice difficult, and 16 (53%) felt feedback was too generic. Respondents valued feedback on strengths and weaknesses (25/30, 83% each), specific suggestions (21/30, 70%), and clarity/structure (20/30, 67%). The survey was exploratory and should not be treated as representative of all interview candidates. Feedback that identifies the task or process gap and gives the learner a usable next step is consistent with Hattie and Timperley's (2007) account of effective feedback.

Personalisation informed the setup flow: 25/30 respondents (83%) wanted practice tailored to job role, 23/30 (77%) to CV/resume, and 22/30 (73%) to interview type. AILI therefore allows configuration of target role, company/domain, experience level, interview focus, interviewer persona, and optional CV/job-description context.

The design principles are learner control, evidence over scores, dialogue rather than verdict, practice as a repeatable loop, and transparency about automated feedback limitations. These principles also align with research on self-regulated learning, which describes learners setting goals, monitoring performance and reflecting to guide subsequent action (Zimmerman, 2002).

1.1 From Task 2 research to the high-fidelity design

The high-fidelity system is the next design iteration of the AILI low-fidelity work, not a separate product concept. Task 2 established the problem through three complementary inputs: a PRISMA-informed review of 35 studies (from 118 initial records and 94 records after de-duplication), comparison of existing interview-practice systems, and an exploratory online survey of 30 respondents. The survey was student-heavy (14 undergraduate, 13 Master's, one PhD, and two working professionals); its findings are descriptive and are used to guide design rather than to claim population-level prevalence.

The Task 2 synthesis identified six recurring themes: (1) realism must be balanced against pressure and anxiety; (2) feedback is more useful as an interaction than as a static score; (3) learning requires iterative and longitudinal practice; (4) personalisation needs to be transparent; (5) observed delivery behaviours should not be treated as direct measures of competence; and (6) learner autonomy matters because users may passively accept or over-trust AI advice. These themes informed the five design principles retained in the high-fidelity prototype: learner control, evidence over scores, dialogue rather than verdict, practice as a loop, and honesty about system limits.

The two low-fidelity alternatives were deliberately preserved as two complementary modes. Prototype A tested immediate feedback and reflective retry; Prototype B tested a more realistic, uninterrupted interview with adaptive follow-ups and delayed review. The high-fidelity implementation brings both into one interface so that users can choose the practice experience that fits their immediate goal.

1.2 User requirements carried forward from Task 2

The following requirements were derived from the Task 2 literature synthesis and survey. The high-fidelity implementation addresses them to differing degrees; the table distinguishes implemented interface support from capabilities that still require validation.

ID	User requirement	Task 2 evidence	High-fidelity design response
UR1	Personalised setup using role, interview type and optional CV/JD context	Role 25/30; CV 23/30; interview type 22/30	Setup captures target role, company/domain, experience, focus and optional context.
UR2	Realistic interview with context-aware follow-up questions	Literature theme: realism and adaptive questioning	Prototype B supports continuous interview turns and adaptive follow-ups.
UR3	Learner-calibrated pressure and pacing	Literature theme: realism can increase pressure/anxiety	Persona, difficulty and pacing controls; user can choose practice mode.
UR4	Specific strengths and improvement feedback grounded in the answer	Strengths and weaknesses 25/30 each; generic feedback 16/30	Four rubric dimensions, response-linked explanations and actionable suggestions.
UR5	Transparent explanation of why feedback was given	18/30 rated understanding of AI feedback 4–5/5	“Why This Feedback?” audit view links criteria to answer excerpts.
UR6	Reflection, retry and attempt comparison	16/30 unsure whether they were improving	Reflection prompt, same-question retry and comparison/progress views.
UR7	Learner control over when to retry or review	14/30 preferred both immediate retry and later review	Practice loop and interview debrief provide continuation/retry choices.
UR8	Support independent practice through voice or text	21/30 practised alone; 13/30 lacked mock-interview partners	Voice and keyboard response options.
UR9	Prevent and recover from slips or technical interruptions	Task 2 interaction/error-handling analysis	Input checks and controls are present; robust recovery remains a future validation target.
UR10	Separate measured delivery observations from AI interpretation	Literature theme: observed behaviour is not competence	The conceptual design separates observed indicators from interpretive feedback; avoid treating either as hiring evidence.

2. Conceptual Model and Interaction Metaphors

Prototype A — The Reflective Mirror: The system reflects an answer through four criteria: Relevance, Specificity, Evidence & Outcome, and Structure & Clarity. A “Why This Feedback?” audit links the evaluation to answer excerpts; a reflection prompt asks what the learner would change before retrying. The metaphor emphasises self-inspection and deliberate practice. The feedback-and-retry sequence is intended to support formative learning rather than simply produce a score (Hattie & Timperley, 2007; Zimmerman, 2002).

Prototype B — The Conversational Partner: The system acts as an interviewer, using spoken or typed responses and adaptive follow-up questions. Feedback is deferred until the interview is concluded, preserving a more continuous conversational flow. The metaphor emphasises realistic dialogue rather than interruption after every answer. The interface also follows human–AI interaction guidance that systems should communicate their capabilities and limitations and support users in responding to AI outputs (Amershi et al., 2019).

The design space is organised around feedback timing (immediate versus deferred) and interaction style (reflective text/voice practice versus spoken interview simulation). The modes represent complementary practice experiences; they do not establish that the system improves hiring outcomes. The choice to retain learner control over the interaction reflects the broader human-automation design concern that automation changes, rather than simply replaces, human activity (Parasuraman et al., 2000).

2.1 Target users, personas and use scenarios

AILI is intended for university students preparing for internships, campus placements and graduate-school interviews, especially those who practise independently and need structured feedback. The personas below are design representations synthesised from the Task 2 survey and literature; they are not claims about individual evaluation participants.

Persona 1 — Aditi, the self-directed UX research candidate. Aditi is a university student preparing for a UX Research internship. She practises alone, has project experience but is unsure how to communicate her contribution, evidence and outcomes concisely. She wants role-relevant questions, specific strengths and weaknesses, and feedback that points to the exact part of her answer that needs work.

Scenario 1 — Reflective practice (Prototype A). Aditi selects a UX Research Intern role, chooses a behavioural interview focus and answers a question by voice or text. She receives criterion-level feedback, opens “Why This Feedback?” to inspect the evidence, reflects on one change, retries the same question and compares the attempts. The intended outcome is a more deliberate practice cycle rather than passive acceptance of a score.

Persona 2 — Rahul, the candidate who needs realistic rehearsal. Rahul is a university student preparing for a software engineering placement. He can formulate answers but has limited access to a human mock interviewer and wants to rehearse follow-up probing under a chosen level of pressure. He needs the ability to pause, use text if voice input fails, and review feedback after the conversation.

Scenario 2 — Continuous simulation (Prototype B). Rahul configures a software engineering interview and selects an interviewer persona and pacing. He answers a sequence of questions; the system asks follow-ups based on his previous responses. At the end, he reviews the evaluation, identifies a weak question and chooses whether to retry it or plan another session.

These scenarios preserve the central Task 2 design question: how can AILI support realistic, self-directed and iterative interview practice while making feedback personalised, actionable and trustworthy?

3. System Design and Architecture

The latest implementation description supplied by the AILI team specifies a browser client built with HTML5, CSS3 and vanilla JavaScript, backed by a high-concurrency FastAPI/ASGI service with Pydantic v2 request/response schemas. Cloud language-model support is described as Gemini 3.5 Flash-Lite (model identifier: gemini-3.5-flash-lite), with a deterministic local NLP/rubric fallback intended to preserve core functionality when the cloud service is unavailable. The team also describes environment-key discovery and a diagnostic endpoint at /api/gemini/test. These are implementation details reported by the team; latency and availability targets should be supported by deployment benchmarks before being stated as measured guarantees. The presence of AI-generated feedback makes interaction guidance relevant: users need to understand what the system can do, where it may fail and how to recover (Amershi et al., 2019).

The latest architecture description identifies a multimodal audio path: browser audio is downsampled to 16 kHz PCM and passed to an in-memory Vosk Kaldi speech-recognition model (vosk-model-small-en-us-0.15) for offline transcription, with Gemini multimodal audio processing described as a fallback. The interview simulation is organised as a five-stage state machine: Icebreaker → Technical Deep Dive → Trade-Offs → Failure Modes → Candidate Inquiries. Stage progression is guarded by minimum-requirement checks (check_stage_minimum_requirements), with adaptive clarification probing. The reported flow also includes a 10-second silence timer with a 5-second countdown and manual stop/send controls. These details describe the current team-reported implementation; the exact behaviour should be demonstrated in the deployed build. The explanation step is informed by user-centred explainable-AI research, which emphasises understanding the questions people need answered about an AI system rather than exposing technical detail alone (Liao et al., 2020).

Voice privacy must be described by processing path. The team reports an in-memory, offline Vosk transcription path and a Gemini multimodal audio fallback. The offline path and cloud fallback have different privacy implications: audio routed to a cloud service may leave the device and be subject to that provider's processing terms. The interface and consent materials should clearly disclose when cloud processing is used, what transcript/audio data are retained, who can access them, and how deletion works. The team's description of a “Forget All Data” sanitisation function is a useful control, but GDPR compliance should not be claimed without a documented legal and technical assessment. Likewise, “100% private” should not be used as a blanket claim while a cloud audio fallback exists.

3.1 Interaction architecture and information flow

The information architecture is organised around a small set of user goals: choose a practice mode, configure a session, answer questions, interpret feedback, decide what to do next and review progress. Prototype A exposes feedback and reflection after each answer; Prototype B keeps the interview interaction continuous and moves the main evaluation to the end. Both modes share the setup layer and the learner-facing goal of identifying a concrete next practice action.

At the interaction level, the system follows a repeated cycle: (1) configure role and practice conditions; (2) receive a question; (3) respond by voice or text; (4) receive feedback at the mode-appropriate point; (5) inspect the reason for the feedback; and (6) retry, continue or review progress. Error and recovery considerations include empty responses, microphone permission or recognition failure, accidental session exit, and interrupted network/API responses. The interface provides alternative text input and session controls; comprehensive recovery behaviour should be tested rather than assumed.

3.2 Conceptual design space

The two modes occupy different points on two design dimensions. The first is feedback timing: immediate, after each answer (Prototype A), versus deferred, after the interview (Prototype B). The second is interaction style: reflective and criterion-led practice versus conversational simulation with adaptive probing. A third dimension is pressure calibration, from supportive practice to

more demanding interviewer behaviour. The design intentionally leaves control of this pressure with the learner to avoid equating stress with readiness.

4. High-Fidelity Prototype and Core Functionality

Home and setup: users choose between feedback-led practice and interview simulation, then configure target role, company/domain, experience level, interview focus, interviewer persona/difficulty, pacing, and optional CV/job-description context.

Question and response: the interface presents interview questions with text and voice options. It includes speech playback, speech-to-text interaction, transcript preview, and controls for response submission and playback.

Feedback and audit: Prototype A reports four rubric dimensions and provides strengths, gaps, actionable recommendations, and a "Why This Feedback?" explanation linking feedback to excerpts from the response. Linking feedback to response excerpts is a user-facing explanation strategy consistent with the need to design explainability around users' information needs (Liao et al., 2020).

Reflection and retry: users are prompted to articulate what they would change, retry the question, and compare attempts. The interface also includes progress views.

Interview simulation: Prototype B provides an interviewer persona, continuous question/answer turns, adaptive follow-up prompts, and a post-interview evaluation/debrief.

The latest backend description additionally reports SQLite persistence for sessions, turns, evaluations and comparisons; five-axis longitudinal tracking; DuckDuckGo real-time web-search grounding; and a seven-statement HCI Likert feedback instrument (1–5) whose submissions are stored in user_feedback_submissions.json. The team reports 57 automated unit tests passing and deployment on Render, with asset cache-busting. These are team-reported implementation and test details and should be accompanied by the current test output or a live demonstration where possible. The backend also describes a BARS-style rubric across Relevance, Specificity, Evidence, STAR and Inquiry, with quote-backed "Why This Feedback?" audits. The scores and generated hiring-style dossier remain practice-oriented prototype outputs, not validated psychometric measures or real hiring recommendations. Export functionality includes an interview dossier (.DOCX) and evaluation slide deck (.PPTX).

5. Prototyping Compromises

Horizontal: role breadth: the implementation prioritises three representative role families (UX Research Intern, Associate Product Manager, and Software Engineer) rather than attempting comprehensive coverage of every profession.

Horizontal: interview formats: the project focuses on behavioural and situational interview practice using STAR-oriented feedback. It does not attempt to provide a coding IDE, whiteboard environment, or full case-interview simulator.

Vertical: voice processing: browser-native speech recognition and synthesis were selected instead of a more complex dedicated speech-processing service. This reduces implementation and cost overhead but makes performance dependent on browser/device support and microphone conditions.

Vertical: evaluation depth: the four transparent dimensions provide an inspectable framework, while rule-based scoring and AI-assisted follow-upkeep the prototype manageable. Scores remain approximate indicators for practice and should not be interpreted as validated hiring assessments. This cautious framing is important because the prototype's rubric output is not a validated measure of job performance; human–AI interaction guidance recommends communicating system limitations and avoiding misleading expectations (Amershi et al., 2019).

Vertical: session length: the simulation uses a bounded question sequence with follow-up probing rather than reproducing a full-length recruitment interview.

5.1 Rationale for prototyping compromises

The horizontal compromises prioritise depth in common student interview contexts over broad occupational coverage. This keeps the question and feedback design manageable while allowing the team to demonstrate role-aware setup. The vertical compromises prioritise a working end-to-end interaction over production-grade speech infrastructure, validated psychometrics or a full recruitment platform. These are deliberate scope decisions for a course prototype; they also define what the evaluation can and cannot establish.

5.2 Design decisions and their trade-offs

Immediate feedback in Prototype A supports reflection but can interrupt the realism of a live interview. Deferred feedback in Prototype B preserves conversational flow but requires the learner to remember their own performance until the debrief. The two-mode design exposes this trade-off instead of assuming one timing is best for every practice goal. Likewise, rubric dimensions make evaluation inspectable but cannot eliminate subjectivity or model error. Voice input improves interaction naturalness but introduces device, browser, microphone and transcription dependencies; typed input is retained as an alternative.

6. User Evaluation: Method, Findings and Design Implications

Participants and setting: The project evaluation report records a usability study with six student participants (N=6) in a controlled academic laboratory setting at IIT Gandhinagar. Participants were drawn from student groups preparing for interviews and represented UX Research Intern, Associate Product Manager, and Software Engineer target roles.

Study design: The available SUS/task-time summary records task-based use of the prototype, task time and the 10-item System Usability Scale (SUS). Prototype exposure was not identical: P01, P02, P05 and P06 tested A and B; P03 tested A only; and P04 tested B only. The data therefore do not support treating all six participants as a complete within-subjects comparison of both modes. Separately, six detailed Prototype B interview-session reports were reviewed to inspect interaction flow, session completion, generated feedback and transcript/turn integrity.

Measures: The SUS/task-time summary reports SUS scores and task completion times. The six detailed Prototype B session reports provide supplementary qualitative and system-output evidence, including session length, AI-generated competency ratings, overall scores, confidence labels and recommendations. A concise researcher-developed post-use questionnaire is also present in the workbook: one practice-mode item, seven 5-point Likert statements covering ease of use, task completion, relevance, feedback quality, actionability, user control and perceived learning, and two optional open-ended questions. The workbook's six sample rating rows are synthetic demonstrations; no genuine responses to this questionnaire were provided in the supplied sheet.

Quantitative results: The mean SUS score was 90.4/100 (SD = 7.0, recalculated from the six listed scores; the project summary reports 7.2), with individual scores from 80.0 to 100.0. Mean recorded task time was 250 seconds (range = 195–310 seconds). These are descriptive results from a small sample and should not be generalised beyond the tested participants.

Learning-related indicator: The project report records mean Evidence & Outcome rubric scores of 4.2 on Attempt 1 and 8.1 on Attempt 2, a descriptive increase of 3.9 points (approximately +4.0). This reflects change in the prototype's own rubric output during retry. Without the raw paired scores, test statistic, and analysis details, it should not be described as statistically significant or as independently verified learning gain.

Detailed interaction-session review: The six Prototype B reports contain 23 recorded interview stages. AILI's generated overall scores were 1.2, 7.1, 7.7, 6.8, 8.0 and 8.0 out of 10 (mean = 6.47; median = 7.4; range = 1.2–8.0). These are automated prototype outputs about interview responses, not human usability ratings, validated measures of candidate competence or hiring decisions. Two sessions (Designer and Senior Machine Learning Engineer) ended after two exchanges and were labelled low-confidence / follow-up-required. One Software Engineer report included a non-substantive answer and a later response that duplicated the interviewer prompt. These observations point to opportunities to improve incomplete-session handling, response validation and turn attribution.

Data reconciliation note: The SUS/task-time records are labelled P01–P06, whereas the detailed interview reports use candidate labels A, 1, 3, 4, 6 and Aditi Sharma. No reliable crosswalk was supplied; therefore, the two sets are reported separately.

The usability results are one evidence stream within the broader design report, not the sole measure of project success. The high-fidelity prototype is also assessed through its continuity with the Task 2 research, coverage of user requirements, conceptual model, interaction design, working functionality and explicit prototyping compromises. The evaluation provides an initial check of usability and exposes concrete implementation issues; it does not establish learning efficacy, hiring validity or generalisable superiority of either mode. This distinction is consistent with formative-feedback and self-regulated-learning perspectives: usability feedback can inform the next design iteration, while learning effectiveness requires separate evidence (Hattie & Timperley, 2007; Zimmerman, 2002).

Post Feedback

Demo ID	Mode used	Q2 The website was easy to navigate and understand.	Q3 I was able to complete the practice tasks without difficulty.	Q4 The questions and practice experience were relevant to my interview goals.	Q5 The AI feedback was relevant and clearly identified strengths and areas for improvement.	Q6 The feedback and suggestions were understandable and actionable.	Q7 I felt in control of the practice process and could work at my own pace.	Q8 Using AILI helped me identify how to improve my interview answers.
Demo-01	Prototype B	4	4	4	5	4	5	4
Demo-02	Both	3	3	4	3	3	4	4
Demo-03	Prototype A	5	5	4	5	5	5	5
Demo-04	Prototype B	3	2	3	4	3	4	3
Demo-05	Both	4	5	5	5	4	5	5
Demo-06	Prototype B	2	3	3	3	2	3	3

7. Ethics, Privacy, and Risk Assessment

The project evaluation materials describe voluntary participation, a digital consent step, the option to withdraw, and anonymised SUS records using P01–P06 identifiers. The detailed interview reports retain candidate aliases/names as supplied; public-facing materials should pseudonymise these labels. The team should ensure that consent covers the use of interview transcripts and generated evaluations. Do not collect sensitive personal information, and explain voice-processing and transcript-retention behaviour accurately before a session. Where these details are not established by the supplied records, they should be verified rather than assumed.

Evaluative anxiety and fatigue: keep sessions time-bounded, allow participants to pause or stop, and explain that the scores are practice feedback rather than hiring decisions. The need for clear status, error prevention and recovery is a longstanding concern in usability engineering (Nielsen, 1994).

Voice and transcript privacy: disclose how speech recognition is processed, whether transcripts are saved, who can access them, and how long they are retained. Do not infer data deletion from a reset button alone. These safeguards are especially important in AI-mediated interactions, where users should be informed about system behaviour and limitations (Amershi et al., 2019).

CV and job-description privacy: discourage use of real personal documents in a pilot unless necessary and covered by consent. Remove identifying details from any report or shared dataset.

Algorithmic limitations: make rubric criteria visible, invite users to challenge feedback, and clearly label automated "Hire" or "Lean Hire" outputs as simulated practice feedback, not real recruitment recommendations.

8. Limitations and Future Work

The evaluation involved a small sample. The SUS/task-time summary includes six participant records, but the raw SUS item responses and full think-aloud transcripts were not supplied. Exposure to Prototype A and B was not uniform. The detailed Prototype B reports are a separate set of records without a verified crosswalk to P01–P06. The post-use questionnaire is prepared for future collection. The reported mean Evidence & Outcome score change (4.2 to 8.1) is a descriptive prototype-rubric output, not an independently measured learning gain.

The detailed interview-session reports reveal incomplete sessions and a possible duplicated-turn issue. These are valuable findings and should be reported as observed prototype behaviour, not concealed. Future work should validate transcript/turn handling, improve incomplete-session treatment, assess scoring against human raters, expand participant diversity, and conduct a larger evaluation with consistent exposure to both modes.

9. Conclusion

AILI translates the team's earlier needs assessment and low-fidelity design into a working high-fidelity interview-practice system. Its two modes balance reflective, criterion-based practice with a more continuous conversational simulation. The six-record SUS/task-time summary provides an encouraging initial usability signal (mean SUS = 90.4/100; mean task time = 250 seconds), while the separate Prototype B session records expose incomplete-session and response/turn-validation issues. The post-use questionnaire is prepared for subsequent data collection; its synthetic example rows are not treated as findings. Overall, the project's contribution lies in the integrated prototype, its conceptual model and the iterative design opportunities identified through evaluation.

Table 1. Participant-level usability summary (N=6)

Participant	Target role	Prototype(s)	Task time (s)	SUS /100
P01	UX Research Intern	Both A + B	230	100.0
P02	Associate Product Manager	Both A + B	290	87.5
P03	Software Engineer	Prototype A	195	80.0
P04	Associate Product Manager	Prototype B	310	92.5
P05	UX Research Intern	Both A + B	260	87.5
P06	Software Engineer	Both A + B	215	95.0

Table 2. Detailed Prototype B session reports reviewed

Candidate alias	Role / target	System rating	Session observation
A	Designer / Start up	1.2/10	Incomplete; 2 exchanges
6	Software Engineer	7.1/10	7 stages; includes weak/non-substantive and duplicated turn
4	Senior ML Engineer / HealthAI Labs	7.7/10	Incomplete; 2 exchanges
3	Associate Product Manager / Airbnb	6.8/10	5 stages
Aditi Sharma	UX Research Intern / Google	8.0/10	3 stages
1	Software Engineer / Google	8.0/10	4 stages

References

Amershi, S., Weld, D., Vorvoreanu, M., Fourney, A., Nushi, B., Collisson, P., Suh, J., Iqbal, S., Bennett, P. N., Inkpen, K., Teevan, J., Kikin-Gil, R., & Horvitz, E. (2019). Guidelines for human-AI interaction. In Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems (pp. 1–13). Association for Computing Machinery. https://doi.org/10.1145/3290605.3300233

Brooke, J. (1996). SUS: A quick and dirty usability scale. In P. W. Jordan, B. Thomas, B. A. Weerdmeester, & I. L. McClelland (Eds.), Usability evaluation in industry (pp. 189–194). Taylor & Francis.

Hattie, J., & Timperley, H. (2007). The power of feedback. Review of Educational Research, 77(1), 81–112. https://doi.org/10.3102/003465430298487

Liao, Q. V., Gruen, D., & Miller, S. (2020). Questioning the AI: Informing design practices for explainable AI user experiences. In Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems (pp. 1–15). Association for Computing Machinery. https://doi.org/10.1145/3313831.3376590

Nielsen, J. (1994). Enhancing the explanatory power of usability heuristics. In Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (pp. 152–158). Association for Computing Machinery. https://doi.org/10.1145/191666.191729

Norman, D. A. (2013). The design of everyday things: Revised and expanded edition. Basic Books.

Parasuraman, R., Sheridan, T. B., & Wickens, C. D. (2000). A model for types and levels of human interaction with automation. IEEE Transactions on Systems, Man, and Cybernetics—Part A: Systems and Humans, 30(3), 286–297. https://doi.org/10.1109/3468.844354

Zimmerman, B. J. (2002). Becoming a self-regulated learner: An overview. Theory Into Practice, 41(2), 64–70. https://doi.org/10.1207/S15430421TIP4102_2