

INSTRUCTIONS

3900,4300,4400
CMD2040WC

5100 SERIES
CMD333UWC

WARNING:*

**Rectifier Diode must be used for
AC applications**

<u>Voltage</u>	<u>*AC</u>	<u>DC</u>
6 V.	100 ohms	220 ohms
12 V.	330 ohms	680 ohms
28 V.	750 ohms	1500 ohms

RESISTOR: 1/2 WATT

IDENTIFICATION OF POLARITY:

4306R



4400 Series

4300 Series

(Bottom View)

ANODE
(+)



FLAT
OR
NOTCH

4307T

STRIPE ON
CATHODE SIDE



Model; 3990, 5100, 5110, 5210

Redlead: Anode (+)

Mtg. hole: 3990-7/32", 5100-1/4"
5210-3/16"

To mount Panel Clip
for 4304 series use 17/64 drill
or punch .265 hole in panel.

For 4305 CH series,
drill 1/4" hole.

MODELS	VOLTS	2 MA	2.5 MA
4300 LC SERIES	1.5 VDC	100 ohms	100 ohms
	3 VDC	620 ohms	470 ohms
	6 VDC	2.2K ohms	1.8K ohms
RESISTOR: 1/4 WATT	12 VDC	5.1K ohms	3.9K ohms
	24 VDC	10K ohms	9.1K ohms

LINROSE SUPERBRITE LED

Linrose products are warranted from defects in material or workmanship under normal use and we will, within 90 days from date of purchase repair or replace at our option, F.O.B. our factory, any product which our examination shall disclose to our satisfaction to be defective. This warranty does not apply to any unit which has been subject to misuse, alteration, accident, flood, or fire.

INSTRUCTIONS ON

MADE IN U.S.A.

LINROSE ELECTRONICS INC.
29 Cain Drive, Plainview, N.Y. 11803

B4310H31

1690 mcd - 5mm RED LED

1.8Vf @ 20mA-VIEWING ANGLE-30

SUNBURST SERIES

(#64)