

Ballistics: Application of Conservation Laws

Cameron Stark

PS-253 Section 12, Benedict Pineyro

Department of Physical Sciences,

Embry-Riddle Aeronautical University, Daytona Beach, FL.

September, 2018

Ballistics is the study of projectiles and how they behave when launched and during its flight. The purpose of this experiment was to calculate the velocity of the projectile at launch by employing the conservation of momentum and the conservation of energy. To determine the velocity of the projectile we employed two methods, the first being a ballistics pendulum and the other being a spring firing system from a constant height. The first method we performed 5 trials where we calculated the change in initial height with the final height after launch, the velocity we calculated came out to 6.23 m/s. The second method we performed 5 trials where we calculated the distance traveled from a fixed vertical height, the velocity we calculated came out to 6.13 m/s. The percent difference of these two methods velocities came out to 1.69%.

Section I: Background

By performing this experiment, we got to find velocity by employing two different methods which allowed us to explore and understand what uncertainty in measurements could be and how it could affect experiments trying to find the same answer. The experiments' objective was to take multiple measurements and apply them to the equations of the conservation of energy and momentum, in order to find the velocity of the ball at launch.

Section II: Theory and Procedure

The experiment that was preformed made use of spring-loaded fire mechanism that was fired by use of a trigger where the projectile (in this case a solid metal ball) was attached to a firing rod. The entire mechanism was attached to a solid base, which was attached to the surface of the table. The base also had a pendulum set where the ball would get caught in it and would travel up a rigid surface and get caught at the apex of the pendulum motion. The experiment was only concerned with the velocity of the ball so the spring is not of concern. In order to make use of the measurements we acquire in the first method (ballistics pendulum) we must make use of the following equation.

$$V = \frac{m+M}{m} \sqrt{2g\Delta h} \quad (1) \quad [1]$$

This equation is derived from the equations of conservation of momentum, which states that momentum (p) is equal to product of mass (m) and velocity (v).

$$\vec{p} = m\vec{v} = (m + M)\vec{v} = \vec{p} \quad (2) \quad [1]$$

For this method we must break up the mass variable into m (for the mass of the ball) and M (for the mass of the pendulum) since the pendulum is an active part of the experiment. To perform this first method of attaining the velocity of the ball, we must measure the initial resting height of the pendulum for the platform, and then fire the ball into the ballistics pendulum for five trials. Once fired we must measure the new height that the pendulum stops at on the arresting platform. Once we have five final height measurements, subtract each by the initial to get the change in height, and then apply it to equation 1. To find the velocity of the ball using the second method, we use the following equation.

$$V = x \sqrt{\frac{g}{2y}} \quad (3) \quad [1]$$

To obtain the velocity by this method, we need to know some constants such as the vertical height (y) of the ball will fall which will be measured from the floor to the platform it is being launched from, and the value we will be measuring will be the horizontal distance the ball will

travel which is (x). Fire the ball, and measure the distance traveled for five trials. Once five trials have been reached apply equation 3 to each horizontal distance and the average the five velocities. Once an average velocity has been found by each method, find the standard deviation of each by applying the standard deviation equation, then between the two values find the discrepancy between the two values.

$$\sigma = \sqrt{\frac{\sum v}{n}} (4) [1]$$

For equation for you sum up the velocities found and then divide the total number of trials and then square root either value. Once the standard deviations are found for both methods' velocity value, apply to the following equation 5 to find the discrepancy.

$$\delta_d = \sqrt{\sigma_{v1}^2 + \sigma_{v2}^2} (5) [1]$$

Once this is found the percent difference between the velocities is the last to be calculated with the following equation 6.

$$\%diff = \frac{|v_1 - v_2|}{\frac{(v_1 + v_2)}{2}} \times 100 (6) [1]$$

Section III: Results

The Measurements and results of the in total 10 trials, 5 for method 1 and 5 for method 2 are as follows. We found the constants for the experiment to be the following:

$$\begin{aligned} m (\text{mass of ball}) &= 0.0686 \text{ kg} \\ M (\text{mass of pendulum}) &= 0.276 \text{ kg} \\ y (\text{vertical distance}) &= 0.895 \text{ m} \\ h_i (\text{intital height}) &= 0.0575 \text{ m} \\ g (\text{gravity}) &= 9.8 \frac{\text{m}}{\text{s}^2} \end{aligned}$$

The Following are the results and calculations for the method 1:

Method 1 Measurements	
Trial	Height Measured m
1	0.133
2	0.137
3	0.137
4	0.14
5	0.133

Once we have measure for 5 trials we take the initial height and subtract it from the measured height.

$h_f - h_i = \Delta h (7)$	
Equation	Δh
$0.133 - 0.0575$	0.0755
$0.137 - 0.0575$	0.0795
$0.137 - 0.0575$	0.0795
$0.14 - 0.0575$	0.0825
$0.133 - 0.0575$	0.075

The above calculations are of the 5 changes in height of the five trials. Next steps were to find the standard deviation of the changes and then add that to the average change in height

$$\sigma = \sqrt{\frac{.075 + .0795 + .0795 + .0825 + .075}{5}} [1]$$

$$\sigma = 0.001341614$$

$$\Delta h_{avg} = \frac{.075 + .0795 + .0795 + .0825 + .075}{5} [1]$$

$$\Delta h_{avg} = 0.07984$$

The next steps are to find the initial velocity for each trial and add those up, this is done with equation 1.

$$V_1 = \frac{0.0686 + 0.276}{0.0686} \sqrt{2 * 9.8 * 0.0755}$$

Velocity #	Velocity m/s^2
1	6.118
2	6.277
3	6.277
4	6.395
5	6.118

From these values we can extrapolate the average calculated velocity for method 1:

$$v_{1 avg} = 6.237 \frac{m}{s^2}$$

Method 2 Measurements

To begin method 2, we need to first find a calculated (expected) horizontal travel distance with the calculated velocity method 1. To do this we will take equation 3 and solve for x.

$$x = \frac{v}{\sqrt{\frac{g}{2y}}}$$

$$x = \frac{6.237}{\sqrt{\frac{9.8}{2(.895)}}}$$

$$x = 2.688 \text{ m}$$

Our expected horizontal range based on our calculations is 2.688 meters, so we will place a target around that point to measure how accurate our calculations were to the actual velocity.

Expected	Actual	Difference
2.688	2.59	0.099
2.688	2.63	0.059
2.688	2.57	0.119
2.688	2.59	0.099
2.688	2.61	0.079

The next steps are to take the measured horizontal distances and calculate the velocities by applying it to equation 3 for each trial.

$$v = 2.59 \sqrt{\frac{9.8}{2 (.895)}} = 6.060$$

Velocity #	Velocity
1	6.060
2	6.154
3	6.013
4	6.060
5	6.106

After we find all of the velocities we find the average velocity, then the standard deviations of the velocities then add those 2 values to get the total mean velocity.

$$v_{avg} = 6.079$$

$$\sigma = \sqrt{\frac{6.060 + 6.154 + 6.0130 + 6.060 + 6.106}{5}}$$

$$\sigma = 0.0533$$

$$v_{tot} = 6.1322$$

From this point all we need to find is the percent difference between the two calculated velocities with equation 6

$$\%diff = \frac{(6.237 - 6.1322)}{\frac{6.237 + 6.1322}{2}} \times 100$$

$$\%diff = 1.69\%$$

The percent different in the two calculated velocities is 1.69% showing that both methods arrived at almost the value my measuring different values.

Section IV: References

- [1] Department of Physical Sciences. "Ballistics: Application of Conservation Laws."
Daytona Beach: Embry-Riddle Aeronautical University, 2016. PDF file.

Pendulum Launch	Height from Platform to Screw cm	Change in Height cm	Pendulum Initial Velocity
1	13.3	0.0755	6.117817125
2	13.7	0.0795	6.277787043
3	13.7	0.0795	6.277787043
4	14	0.0825	6.395139013
5	13.3	0.0755	6.117817125
	Average Height in Meters	0.0785	6.23726947
	Standard Deviation of Height	0.001341641	
	Total Mean Change in Height	0.079841641	
Range Launch	Horizontal Distance Traveled M	Difference in Expected to actual	Velocity based experimental x and y
1	2.59	0.098754928	6.060190642
2	2.63	0.058754928	6.15378432
3	2.57	0.118754928	6.013393803
4	2.59	0.098754928	6.060190642
5	2.61	0.078754928	6.106987481
		Average Velocity	6.078909377
		Standard Deviation of Velocity	0.053356606
		Total Mean Velocity	6.132265983
Mass of Ball kg		0.0686	
Vertical Distance Platform to Floor m		0.895	
Mass of Pendulum g		0.2764	
Height from platform to Screw at rest cm		5.75	
Pendulum Velocity m/s ²		6.291261564	
Estimation of Distance m		2.688754928	
Percent Difference Between the two methods		1.697775758	