

20260312_01:

- Xử lý khi hết token 401: Thông báo và chuyển về trang login
- In phiếu: xử lý in bị mất chữ khi in trên 16 SP
<https://erp.hqsoft.vn/app/issue/ISS-2026-00470>

parent [e5ef9640](#)

Branches

No related tags found

1 merge request [!220](#) # 20260312_01:

Showing with 36 additions and 18 deletions

▼  **android/app/build.gradle** +1 -1

...	...	@@ -48,7 +48,7 @@ android {
48	48	minSdkVersion 24
49	49	targetSdkVersion 34
50	50	//TODO: 2024-04-15:[Upgrade build] khi upgrade build android can tang version len de chay duoc upgrade
		auto
51	-	versionCode 71
	51	+ versionCode 72
52	52	versionName '1.0.0'
53	53	multiDexEnabled true
54	54	}
...	...	

▼  **android/app/src/main/java/vn/hqsoft/esales/esales_sfa/printer/GPrinterBluetoothPrinter.java** +28 -10

...	...	@@ -855,9 +855,9 @@ public class GPrinterBluetoothPrinter {
855	855	// 3) Calculate strip size for max ~80KB command
856	856	// ESC/POS raster: width in bytes = (pixels + 7) / 8
857	857	int widthInBytes = (width + 7) / 8;
858	-	int maxStripCommandSize = 120 * 1024; // 120 KB target
859	-	int linesPerStrip = maxStripCommandSize / (widthInBytes); // +20 overhead
860	-	linesPerStrip = Math.max(200, Math.min(linesPerStrip, height)); // min 200 lines
	858	+ int maxStripCommandSize = 80 * 1024; // 80 KB target
	859	+ int linesPerStrip = maxStripCommandSize / widthInBytes;
	860	+ linesPerStrip = Math.max(200, Math.min(linesPerStrip, height));
861	861	
862	862	int numStrips = (int) Math.ceil((double) height / linesPerStrip);
863	863	Log.d(TAG, "Width: " + width + "px = " + widthInBytes + " bytes/line");
...	...	@@ -869,7 +869,13 @@ public class GPrinterBluetoothPrinter {
869	869	initCmd.addSelectJustification(EscCommand.JUSTIFICATION.CENTER);
870	870	initCmd.addPrintAndFeedLines((byte) 1);
871	871	writeEscCommand(initCmd);
872	-	Thread.sleep(300);
	872	+ Thread.sleep(200);
	873	+
	874	+ // Set line spacing to 0 to prevent visible gaps between strips
	875	+ // ESC 3 n (0x1B 0x33 n) - sets line spacing to n dots
	876	+ byte[] setLineSpacingZero = new byte[]{0x1B, 0x33, 0x00};
	877	+ portManager.writeDataImmediately(setLineSpacingZero);
	878	+ Thread.sleep(100);
879	879	
874	880	// 5) Print each strip
875	881	for (int strip = 0; strip < numStrips; strip++) {
...	...	@@ -890,11 +896,12 @@ public class GPrinterBluetoothPrinter {
890	896	
891	897	// Create ESC command for strip
892	898	// Use addRastBitImage which handles conversion internally
	899	+ // NOTE: Do NOT add PrintAndLineFeed after raster - GS v 0 already
	900	+ // advances paper by the strip height. Extra LF causes content to be

```

901 + // dropped/corrupted at strip boundaries.
893 902 EscCommand stripCmd = new EscCommand();
894 903 stripCmd.addSelectJustification(EscCommand.JUSTIFICATION.CENTER);
895 904 stripCmd.addRastBitImage(stripBitmap, stripWidthPx, 0);
896 - // IMPORTANT: Add print and line feed after each strip to flush buffer
897 - stripCmd.addPrintAndLineFeed();
898 905
899 906 // Get command bytes
900 907 Vector<Byte> cmdData = stripCmd.getCommand();
... ... @@ -916,15 +923,26 @@ public class GPrinterBluetoothPrinter {
916 923
917 924 stripBitmap.recycle();
918 925
919 - // Wait between strips - longer wait to let printer actually print
926 + // Wait between strips - must wait for printer to mechanically finish
927 + // printing before sending next strip, otherwise receive buffer overflows.
928 + // Typical thermal printer speed: ~50mm/s. At 203 DPI (8 dots/mm):
929 + // wait = (stripHeight / 8) / 50 * 1000 ms + buffer margin
920 930 if (strip < numStrips - 1) {
921 - Thread.sleep(800); // Increased wait for printer to mechanically print
931 + int waitMs = (int)((stripHeight / 8.0 / 50.0) * 1000) + 500;
932 + waitMs = Math.max(800, Math.min(waitMs, 5000));
933 + Log.d(TAG, "Waiting " + waitMs + "ms for printer to render...");
934 + Thread.sleep(waitMs);
922 935 }
923 936 }
924 937
925 - // 6) Feed and cut - wait longer for printer to finish printing
938 + // 6) Restore line spacing, feed and cut
926 939 Log.d(TAG, "Waiting for printer to finish printing...");
927 - Thread.sleep(1500); // Wait for printer to finish printing last strip
940 + Thread.sleep(1500);
941 +
942 + // Restore default line spacing (ESC 2 = 0x1B 0x32)
943 + byte[] restoreLineSpacing = new byte[] {0x1B, 0x32};
944 + portManager.writeDataImmediately(restoreLineSpacing);
945 + Thread.sleep(100);
928 946
929 947 EscCommand endCmd = new EscCommand();
930 948 endCmd.addPrintAndFeedLines((byte) 3);
... ...

```

▼ [lib/data/constant/constant_app.dart](#)

+1 -1

```

... ... @@ -325,7 +325,7 @@ const String typeDisplayFacing = 'F';
325 325 const String typeDisplayInventories = 'I';
326 326 const String typeDisplayGroup = 'G';
327 327
328 - const String versionNewestApp = '20260310_03';
328 + const String versionNewestApp = '20260312_01';
329 329 const String versionAppName = '2023R2';
330 330
331 331 const String panoramaData = 'panoramaData##';
... ...

```

▼ [lib/views/screens/main_menu/bloc_main_menu/main_menu_form.dart](#)

+6 -6

```

... ... @@ -232,16 +232,16 @@ class MainMenuFormState extends State<MainMenuForm> with TickerProviderStateMixi
232 232 label: allTranslations.text(MainMenuLang.occasionalOrder),
233 233 iconPath: 'assets/images/ic_itinerant_order.png',
234 234 onTap: () async {
235 - // await Navigator.of(context).push(
236 - //   MaterialPageRoute(
237 - //     builder: (context) => ReceiptPreviewScreen(salesOrderResponse: SalesOrderResponse()),
238 - //   ),
239 - // );
240 235 await Navigator.of(context).push(
241 236   MaterialPageRoute(
242 - builder: (context) => const TransientCustomerScreen(),
243 + builder: (context) => ReceiptPreviewScreen(salesOrderResponse: SalesOrderResponse()),
244 237   ),
240 + // await Navigator.of(context).push(
241 + //   MaterialPageRoute(
242 + //     builder: (context) => const TransientCustomerScreen(),

```

