CIT4001 SOFTWARE IMPLEMENTATION AND TESTING

Programme manual and database design

PracticeChart EHR

University of Technology, Jamaica

Group 2

This document describes the implemented course application and the evidence recorded for it. It uses fictional patient data. Human training and user acceptance remain pending.

Public course copy. Student identification numbers and private course instruments are excluded.


Prepared for group review. This is not a record of clinical approval, a live pilot, completed training, or completed acceptance testing.

This manual describes the implemented source, database, interfaces, file formats, and operating controls. It is for the group programmer and technical operator. Use the separate user manual for staff tasks.


Source and architecture

The Next.js App Router hosts the login, workspace, report pages, and route handlers. The workspace is a client interface backed by authenticated server functions. Drizzle models define typed rows. SQL migrations add database-level invariants. The indexed source listing contains all authored application source, migrations, scripts, tests, and project configuration. Third-party packages and generated bundles are excluded.

The important source groups are src/app for routes and pages, src/components for interface modules, src/lib for authentication, validation, storage, and transactional services, and src/workflows for daily work. scripts contains setup, migration, test, performance, course analysis, and recovery tools. The SQL migrations are the authority for constraints and triggers. Schema hashes prevent silent migration changes.



Data design



Data flow

Database structure

The cloud uses a separate practicechart_ehr database. Preview uses practicechart_preview. The old ticket database is not part of this schema. Local tests use practicechart_test. Restore drills create a new timestamped local database.

Table	Purpose
users	Unique staff login, role, password hash, active state, protected demo flag, and version
sessions	SHA-256 session token hash, account reference, and expiry
login_attempts	Hashed attempt key, count, and expiry
patients	Immutable MRN, demographics, provisional link, archive flag, and version
doctor_hours	Doctor weekday start and end minutes
appointments	Patient, doctor, interval, state, and version
schedule_blocks	Unavailable doctor intervals
visits	Patient, doctor, optional unique appointment, clinical revision number, and filing state
clinical_revisions	Immutable doctor content, revision, state, correction reason, and author
prescriptions	Exact doctor-entered medicine fields linked to a final revision
documents	Patient association, private path, MIME, size, digest, replacement reference, and author
invoices	Unique number, manual line items, integer-cent total, state, reason, and version
audit_events	Append-only actor, action, record reference, metadata, and time
reminders	Unique appointment and due date pair
backup_runs	Backup status, private bundle reference, and time
migrations	Applied migration names, hashes, and time

MRNs and invoice numbers use independent sequences. The number formatting function does not truncate longer sequence values. Patient birth dates cannot exceed the Jamaica calendar day. Appointment intervals are positive and at most four hours. PostgreSQL GiST exclusion constraints reject active overlaps for both doctor and patient. Trigger checks serialize doctor availability changes and reject blocked or outside-hours bookings. A doctor account guard keeps at least one active doctor. Clinical, prescription, and audit histories reject update and delete operations.

The runtime role has no schema creation permission. It cannot update or delete protected history. The migration owner connection is separate from the runtime connection. Password hashes are never returned in staff API responses. Front desk patient queries omit clinical content and document metadata.

Column dictionary

Table	Column	PostgreSQL type	Nullable	Default
appointments	id	uuid	NO	gen_random_uuid()
appointments	patient_id	uuid	NO	
appointments	doctor_id	uuid	NO	
appointments	start_at	timestamp with time zone	NO	
appointments	end_at	timestamp with time zone	NO	
appointments	status	text	NO	'confirmed'::text
appointments	version	integer	NO	1
appointments	created_at	timestamp with time zone	NO	now()
audit_events	id	uuid	NO	gen_random_uuid()
audit_events	actor_id	uuid	YES	
audit_events	action	text	NO	
audit_events	entity	text	NO	
audit_events	entity_id	text	NO	''::text
audit_events	metadata	jsonb	NO	'{}'::jsonb
audit_events	created_at	timestamp with time zone	NO	now()
backup_runs	id	uuid	NO	gen_random_uuid()
backup_runs	status	text	NO	
backup_runs	pathname	text	YES	
backup_runs	created_at	timestamp with time zone	NO	now()
clinical_revisions	id	uuid	NO	gen_random_uuid()
clinical_revisions	visit_id	uuid	NO	
clinical_revisions	revision	integer	NO	
clinical_revisions	author_id	uuid	NO	
clinical_revisions	state	text	NO	
clinical_revisions	content	jsonb	NO	
clinical_revisions	reason	text	NO	''::text
clinical_revisions	created_at	timestamp with time zone	NO	now()
doctor_hours	doctor_id	uuid	NO	

Table	Column	PostgreSQL type	Nullable	Default
doctor_hours	weekday	integer	NO	
doctor_hours	start_min	integer	NO	
doctor_hours	end_min	integer	NO	
documents	id	uuid	NO	gen_random_uuid()
documents	patient_id	uuid	NO	
documents	title	text	NO	
documents	kind	text	NO	
documents	pathname	text	NO	
documents	mime	text	NO	
documents	size	integer	NO	
documents	sha256	text	NO	
documents	replaces_id	uuid	YES	
documents	author_id	uuid	NO	
documents	created_at	timestamp with time zone	NO	now()
invoices	id	uuid	NO	gen_random_uuid()
invoices	number	text	NO	next_record_number('INV-'::text, 'invoice_seq'::regclass)
invoices	patient_id	uuid	NO	
invoices	lines	jsonb	NO	
invoices	total_cents	integer	NO	
invoices	status	text	NO	'draft'::text
invoices	version	integer	NO	1
invoices	reason	text	NO	''::text
invoices	created_at	timestamp with time zone	NO	now()
login_attempts	key	text	NO	
login_attempts	count	integer	NO	1
login_attempts	expires_at	timestamp with time zone	NO	
migrations	name	text	NO	
migrations	sha256	text	NO	

Table	Column	PostgreSQL type	Nullable	Default
migrations	applied_at	timestamp with time zone	NO	now()
patients	id	uuid	NO	gen_random_uuid()
patients	mrn	text	NO	next_record_number('PC-'::text, 'mrn_seq'::regclass)
patients	first_name	text	NO	
patients	last_name	text	NO	
patients	dob	date	NO	
patients	phone	text	NO	
patients	address	text	NO	
patients	gender	text	NO	'Not stated'::text
patients	emergency_contact	text	NO	''::text
patients	insurance	text	NO	''::text
patients	provisional_reason	text	NO	''::text
patients	merged_into	uuid	YES	
patients	archived	boolean	NO	false
patients	version	integer	NO	1
patients	created_at	timestamp with time zone	NO	now()
prescriptions	id	uuid	NO	gen_random_uuid()
prescriptions	visit_id	uuid	NO	
prescriptions	revision_id	uuid	NO	
prescriptions	patient_id	uuid	NO	
prescriptions	content	jsonb	NO	
prescriptions	created_at	timestamp with time zone	NO	now()
reminders	id	uuid	NO	gen_random_uuid()
reminders	appointment_id	uuid	NO	
reminders	due_date	date	NO	
schedule_blocks	id	uuid	NO	gen_random_uuid()
schedule_blocks	doctor_id	uuid	NO	
schedule_blocks	start_at	timestamp with time zone	NO	
schedule_blocks	end_at	timestamp with time zone	NO	

Table	Column	PostgreSQL type	Nullable	Default
sessions	id	text	NO	
sessions	user_id	uuid	NO	
sessions	expires_at	timestamp with time zone	NO	
sessions	created_at	timestamp with time zone	NO	now()
users	id	uuid	NO	gen_random_uuid()
users	username	text	NO	
users	name	text	NO	
users	role	text	NO	
users	password_hash	text	NO	
users	active	boolean	NO	true
users	protected	boolean	NO	false
users	version	integer	NO	1
users	created_at	timestamp with time zone	NO	now()
visits	id	uuid	NO	gen_random_uuid()
visits	patient_id	uuid	NO	
visits	doctor_id	uuid	NO	
visits	appointment_id	uuid	YES	
visits	status	text	NO	'open'::text
visits	revision	integer	NO	0
visits	visit_at	timestamp with time zone	NO	now()
visits	filed_at	timestamp with time zone	YES	

Server interfaces

All application data routes require a current session except login and health. The cron route requires its separate secret. Browser mutations must have the same origin as the request host. JSON uses camelCase. Validation errors return 400. Missing sessions return 401. Denied roles return 403. Missing records return 404. Stale changes, duplicate values, and overlaps return 409 where applicable. Unconfirmed service failures return 503. Private responses are not cached.

Route group	Input contract and behaviour
POST /api/login	username and password; creates an eight-hour HTTP-only session cookie

Route group	Input contract and behaviour
POST /api/logout	closes the current server session and removes the cookie
POST /api/password	currentPassword and replacement password; closes existing sessions
GET or POST /api/patients	optional q search, or validated demographic fields
POST /api/patients/id	demographic fields and current version
POST /api/patients/id/archive	version and archived boolean; doctor only
POST /api/patients/id/reconcile	targetId and reason; doctor only
GET /api/availability	doctorId and Jamaica date
POST /api/appointments	patientId, doctorId, ISO startAt and endAt; confirms transactionally
POST /api/appointments/id	booking fields and current version; confirmed bookings only
POST /api/appointments/id/status	version and arrived or cancelled state
POST /api/visits	patientId, doctorId, optional matching appointmentId
POST /api/visits/id/clinical	expectedRevision, state, structured content, and correction reason; doctor only
POST /api/visits/id/file	expectedRevision; server requires the final diagnosis
GET or POST /api/documents	doctor-only listing or multipart patientId, title, kind, file, optional replacesId
GET /api/documents/id	authorised private file bytes, not a public storage URL
POST /api/invoices	patientId and description, quantity, unitCents line items
POST /api/invoices/id	version, issued or void state, and void reason
GET or POST /api/users	doctor-only account listing, creation, and versioned changes
GET /api/audit	doctor-only recent audit events
GET /api/reports/type	type-specific record ID and server role check
GET or POST /api/hours	read doctor hours; doctor-only guarded hour changes
POST /api/blocks	doctor-only interval creation or removal
GET /api/cron	secret-authenticated daily workflow start

Clinical and invoice payloads

Clinical content has symptoms, notes, diagnosis, treatment, allergies, vitals, labResults, medications, and certificate fields. Each medication has medication, dosage, route, frequency, duration, quantity, and instructions. The system neither infers nor recommends clinical content. Final entries require a diagnosis. A correction after a final entry requires a reason and another final revision.

Invoice lines contain description, positive integer quantity, and non-negative integer unitCents. The server calculates the total. Stored totals must fit the configured bound. Invoice states are draft, issued, and void. No payment settlement state or provider connection exists.

File and external data structure

Diagnostic objects use a private practicechart/records or practicechart/preview prefix and a random UUID. Metadata is in PostgreSQL. Byte size, magic signature, claimed MIME, SHA-256, patient association, and optional replacement link are checked. The public demo accepts only the supplied fictional PDF. Earlier files are kept.

Local files live under PRIVATE_STORAGE_DIR, outside public. Cloud files use private Vercel Blob. The server fetches the stored object only after account and role checks. The response uses an attachment filename and private no-store caching. There are no external medical, pharmacy, laboratory, biometric, or Ministry integrations.

The recovery format begins with PCBACKUP1, a four-byte metadata length, a JSON encryption header, and authenticated encrypted compressed payload bytes. The payload contains a custom-format PostgreSQL dump, file bytes, row counts, hashes, creation time, and database identification. Recovery keys and bundles are private. See RECOVERY.md and the source listing for exact encoding.

Configuration and global data

Cloud functions prefer EHR_DATABASE_URL so the existing ticket connection settings can remain intact for rollback. Local commands use DATABASE_URL and DATABASE_URL_UNPOOLED. Other settings are APP_URL, DEMO_MODE, STORAGE_DRIVER, PRIVATE_STORAGE_DIR, BLOB_READ_WRITE_TOKEN, CRON_SECRET, and recovery settings. .env.example gives safe local values. Never put cloud values into NEXT_PUBLIC variables.

The process-wide PostgreSQL pool has at most five connections. The session cookie contains a random opaque token. PostgreSQL stores its SHA-256 hash. The session lifetime is eight hours. The practice time zone is America/Jamaica. Workflow runs pass record IDs and status counts. Patient note bodies and passwords do not belong in workflow state or logs.

Installation and operation

Run npm ci, npm run setup, and npm run dev. For the presentation, stop development, build, and start the production server. The setup script preserves existing local data. Docker uses a named PostgreSQL volume. The upload folder must also be preserved. Group and operator instructions are in GROUP_START_GUIDE.md and RECOVERY.md.

Verification

Vitest recorded 74 passing tests and 0 failed tests. Playwright recorded 8 passing browser tests and 0 unexpected failures. The measured Vitest library coverage was 91.42% of statements and 81.08% of branches. This is not a claim of full path coverage.

The control flow appendix records actual source-linked graphs and calculations. The test plan identifies feasible path cases and limits. Safe evidence includes automated results, axe results, load results, and an actual restore result. No human test or training completion is inferred from these files.

A patient report is a reading copy. It contains selected information for one patient. It does not contain the database schema, account data, all records, or every uploaded file. It cannot restore PracticeChart.

Full EHR backup

Run npm run backup from a private operator terminal. The command uses DATABASE_URL_UNPOOLED, not the pooled application connection. It refuses a database whose name does not start with practicechart.

The command opens a repeatable-read snapshot, runs PostgreSQL 18 pg_dump with that snapshot, and reads the document manifest from the same snapshot. It retrieves each referenced immutable file and checks its SHA-256 digest. The bundle includes the full separate EHR database, file bytes, row counts, and a manifest. It does not include the old ticket database or unrelated Blob paths.

The bundle is compressed and encrypted with AES-256-GCM. A new random content key is wrapped with RSA-OAEP using SHA-256. The first local run creates a 4096-bit recovery key pair in .private. Only the public key is needed for scheduled backup creation. The private key must remain outside Git and outside the public demo.

Local bundles are stored in backups. With STORAGE_DRIVER=blob, an encrypted copy goes to practicechart/backups/ in the private Blob store. Seven daily cloud copies are retained. The GitHub job runs at 06:00 UTC, which is 01:00 in Jamaica. GitHub can delay a scheduled job. Check its actual result and the backup run record.

Configure the daily job

Set these GitHub repository secrets through the account settings or a trusted operator tool:

- BACKUP_DATABASE_URL: the unpooled connection to the separate EHR database.

- BLOB_READ_WRITE_TOKEN: the private store token.

- BACKUP_PUBLIC_KEY: the base64-encoded PEM public recovery key.

Do not put the private recovery key in GitHub Actions. Do not publish backup bundles as Actions artifacts. Run the workflow manually once and check that the private backup exists before relying on its schedule.

Keep a separate encrypted recovery copy and the private key in separate controlled locations. Neon and Blob are different data services. A second file copy in the same Blob account is not protection against loss of that whole account.

Actual restore test

Start Docker, create a backup, and run npm run restore:test. The command decrypts the newest local bundle and creates a new local database named practicechart_restore followed by a timestamp. It refuses a remote restore target. It restores the full dump and writes files to an isolated .private/restore-test folder.

The test checks table counts, file hashes and bytes, the MRN sequence, history protection, and overlap rejection. Its measured result is in docs/evidence/restore-result.json. The test database is retained for inspection. No successful restore is claimed merely because a dump file exists.

Recovery drill and limits

Before replacing a presentation copy, keep its current database and files. Restore into a new database. Apply the runtime grants. Point a separate local server at the restored database and restored file folder. Log in and check patient search, clinical revisions, file retrieval, and booking conflicts. Switch the main local copy only after these checks pass.

Never restore into the live EHR database as a test. Cloud recovery requires a new empty database, operator access, the private key, and a controlled cutover. The automated restore script intentionally supplies no live overwrite command.

Database availability and file storage can fail separately. A failed backup is recorded as failed. A missing file stops a complete backup. The app does not report a successful clinical save from an unconfirmed server response. The restore result is test evidence, not a guarantee of recovery time for a larger real database.