

Support Vector Machines

Emmanuel Jakobowicz

1


Goal of SVM

- SVM is a **binary classifier**
- Example:
 - Classify patients
 - Classify customers
- SVM is a **supervised learning** algorithm
- The dependent variable is **binary**

2

Linear Separators

- Binary classification can be viewed as the task of separating classes in feature space:



3


Linear Discriminant Function

- $g(\mathbf{x})$ is a linear function:

$$g(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + b$$

- A hyper-plane in the feature space
- (Unit-length) normal vector of the hyper-plane:


$$\mathbf{n} = \frac{\mathbf{w}}{\|\mathbf{w}\|}$$



4

Linear Discriminant Function


- How would you classify these points using a linear discriminant function in order to minimize the error rate?
- Infinite number of answers!



5

Linear Discriminant Function

- How would you classify these points using a linear discriminant function in order to minimize the error rate?
- Infinite number of answers!




6

Linear Discriminant Function

- How would you classify these points using a linear discriminant function in order to minimize the error rate?

- Infinite number of answers!




7

Linear Discriminant Function

- How would you classify these points using a linear discriminant function in order to minimize the error rate?

- Infinite number of answers!


- Which one is the best?



8

Large Margin Linear Classifier


- The linear discriminant function (classifier) with the maximum **margin** is the best
- Margin is defined as the width that the boundary could be increased by before hitting a data point
- Why it is the best?
 - Robust to outliers and thus strong generalization ability



9

Classification Margin


- Distance from example \mathbf{x}_i to the separator is $r = \frac{\mathbf{w}^T \mathbf{x}_i + b}{\|\mathbf{w}\|}$
- Examples closest to the hyperplane are **support vectors**.
- **Margin** ρ of the separator is the distance between support vectors.



10

Maximum Margin Classification

- Maximizing the margin is good according to intuition.
- Implies that only support vectors matter; other training examples are ignorable.



11


Large Margin Linear Classifier

- We know that

$$\begin{aligned} \mathbf{w}^T \mathbf{x}^+ + b &= 1 \\ \mathbf{w}^T \mathbf{x}^- + b &= -1 \end{aligned}$$

- The margin width is:

$$\begin{aligned} M &= (\mathbf{x}^+ - \mathbf{x}^-) \cdot \mathbf{n} \\ &= (\mathbf{x}^+ - \mathbf{x}^-) \cdot \frac{\mathbf{w}}{\|\mathbf{w}\|} = \frac{2}{\|\mathbf{w}\|} \end{aligned}$$



12

Linear SVMs Mathematically

- Then we can formulate the *quadratic optimization problem*:

Find \mathbf{w} and b such that

$$\rho = \frac{2}{\|\mathbf{w}\|} \text{ is maximized}$$

and for all $(\mathbf{x}_i, y_i), i=1..n : y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

Which can be reformulated as:

Find \mathbf{w} and b such that

$$\Phi(\mathbf{w}) = \|\mathbf{w}\|^2 = \mathbf{w}^T \mathbf{w} \text{ is minimized}$$

and for all $(\mathbf{x}_i, y_i), i=1..n : y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

13

Solving the Optimization Problem

Find \mathbf{w} and b such that

$$\Phi(\mathbf{w}) = \mathbf{w}^T \mathbf{w} \text{ is minimized}$$

and for all $(\mathbf{x}_i, y_i), i=1..n : y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

- Need to optimize a *quadratic* function subject to *linear* constraints.
- Quadratic optimization problems are a well-known class of mathematical programming problems for which several (non-trivial) algorithms exist.
- The solution involves constructing a *dual problem* where a *Lagrange multiplier* α_i is associated with every inequality constraint in the primal (original) problem:

Find $\alpha_1 \dots \alpha_n$ such that

$$Q(\boldsymbol{\alpha}) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j \text{ is maximized and}$$

$$(1) \sum \alpha_i y_i = 0$$

$$(2) \alpha_i \geq 0 \text{ for all } \alpha_i$$

14

The Optimization Problem Solution

- Given a solution $\alpha_1 \dots \alpha_n$ to the dual problem, solution to the primal is:

$$\mathbf{w} = \sum \alpha_i y_i \mathbf{x}_i \quad b = y_k - \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x}_k \quad \text{for any } \alpha_k > 0$$

- Each non-zero α_i indicates that corresponding \mathbf{x}_i is a support vector.
- Then the classifying function is (note that we don't need \mathbf{w} explicitly):


$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$

- Notice that it relies on an *inner product* between the test point \mathbf{x} and the support vectors \mathbf{x}_i
- Also keep in mind that solving the optimization problem involved computing the inner products $\mathbf{x}_i^T \mathbf{x}_j$ between all training points.

15

Soft Margin Classification

- What if the training set is not linearly separable?
- Slack variables* ξ_i can be added to allow misclassification of difficult or noisy examples, resulting margin called *soft*.



What should our quadratic optimization criterion be?

Minimize

$$\frac{1}{2} \mathbf{w} \cdot \mathbf{w} + C \sum_{k=1}^R \varepsilon_k$$

C is an hyper-parameter

16

Soft Margin Classification Mathematically

- The old formulation:

Find \mathbf{w} and b such that
 $\Phi(\mathbf{w}) = \mathbf{w}^T \mathbf{w}$ is minimized
 and for all $(\mathbf{x}_i, y_i), i=1..n$: $y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

- Modified formulation incorporates slack variables:


Find \mathbf{w} and b such that
 $\Phi(\mathbf{w}) = \mathbf{w}^T \mathbf{w} + C \sum \xi_i$ is minimized
 and for all $(\mathbf{x}_i, y_i), i=1..n$: $y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1 - \xi_i$, $\xi_i \geq 0$

- Parameter C can be viewed as a way to control overfitting: it “trades off” the relative importance of maximizing the margin and fitting the training data.


17

Non-linear SVMs


- Datasets that are linearly separable with some noise work out great:



- But what are we going to do if the dataset is just too hard?




- How about... mapping data to a higher-dimensional space:



18

Non-linear SVMs: Feature spaces

- General idea: the original feature space can always be mapped to some higher-dimensional feature space where the training set is separable:



19

The “Kernel Trick”

- The linear classifier relies on inner product between vectors $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$
- If every datapoint is mapped into high-dimensional space via some transformation $\Phi: \mathbf{x} \rightarrow \phi(\mathbf{x})$, the inner product becomes:

$$K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$$

- A *kernel function* is a function that is equivalent to an inner product in some feature space.
- Example:

2-dimensional vectors $\mathbf{x} = [x_1 \ x_2]$; let $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^2$,

Need to show that $K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$:

$$\begin{aligned} K(\mathbf{x}_i, \mathbf{x}_j) &= (1 + \mathbf{x}_i^T \mathbf{x}_j)^2 = 1 + x_{i1}^2 x_{j1}^2 + 2 x_{i1} x_{j1} x_{i2} x_{j2} + x_{i2}^2 x_{j2}^2 + 2 x_{i1} x_{j1} + 2 x_{i2} x_{j2} = \\ &= [1 \ x_{i1}^2 \ \sqrt{2} x_{i1} x_{i2} \ x_{i2}^2 \ \sqrt{2} x_{i1} \ \sqrt{2} x_{i2}]^T [1 \ x_{j1}^2 \ \sqrt{2} x_{j1} x_{j2} \ x_{j2}^2 \ \sqrt{2} x_{j1} \ \sqrt{2} x_{j2}] = \\ &= \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j), \quad \text{where } \phi(\mathbf{x}) = [1 \ x_1^2 \ \sqrt{2} x_1 x_2 \ x_2^2 \ \sqrt{2} x_1 \ \sqrt{2} x_2] \end{aligned}$$

- Thus, a kernel function *implicitly* maps data to a high-dimensional space (without the need to compute each $\phi(\mathbf{x})$ explicitly).

20

What Functions are Kernels?

- For some functions $K(\mathbf{x}_i, \mathbf{x}_j)$ checking that $K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$ can be cumbersome.
- Mercer’s theorem:
Every semi-positive definite symmetric function is a kernel
- Semi-positive definite symmetric functions correspond to a semi-positive definite symmetric Gram matrix:

K=

$K(\mathbf{x}_1, \mathbf{x}_1)$	$K(\mathbf{x}_1, \mathbf{x}_2)$	$K(\mathbf{x}_1, \mathbf{x}_3)$...	$K(\mathbf{x}_1, \mathbf{x}_n)$
$K(\mathbf{x}_2, \mathbf{x}_1)$	$K(\mathbf{x}_2, \mathbf{x}_2)$	$K(\mathbf{x}_2, \mathbf{x}_3)$		$K(\mathbf{x}_2, \mathbf{x}_n)$
...
$K(\mathbf{x}_n, \mathbf{x}_1)$	$K(\mathbf{x}_n, \mathbf{x}_2)$	$K(\mathbf{x}_n, \mathbf{x}_3)$...	$K(\mathbf{x}_n, \mathbf{x}_n)$

For any non-zero vector \mathbf{x} , $\mathbf{x}^T \mathbf{K} \mathbf{x} > 0$

21

Examples of Kernel Functions

- Linear: $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$
- Polynomial of power p : $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^p$
- Gaussian (radial-basis function network):

$$K(\mathbf{x}_i, \mathbf{x}_j) = \exp\left(-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}\right)$$

- Sigmoid: $K(\mathbf{x}_i, \mathbf{x}_j) = \tanh(\beta_0 \mathbf{x}_i^T \mathbf{x}_j + \beta_1)$

22

Support Vector Machine: Algorithm

- 1. Choose a kernel function
- 2. Choose a value for C (*soft*)
- 3. Solve the quadratic programming problem (many software packages available)
- 4. Construct the discriminant function from the support vectors

23

Some Issues

- Choice of kernel
 - Gaussian or polynomial kernel are the mostly used non-linear kernels
 - if ineffective, more elaborate kernels are needed
 - domain experts can give assistance in formulating appropriate similarity measures
- Choice of kernel parameters
 - e.g. σ in Gaussian kernel
 - σ is the distance between closest points with different classifications
 - In the absence of reliable criteria, applications rely on the use of a validation set or cross-validation to set such parameters.
- Optimization criterion – Hard margin v.s. Soft margin
 - a lengthy series of experiments in which various parameters are tested

24

Why Is SVM Effective on High Dimensional Data?

- The complexity of trained classifier is characterized by the # of support vectors rather than the dimensionality of the data
- The support vectors are the essential or critical training examples — they lie closest to the decision boundary
- If all other training examples are removed and the training is repeated, the same separating hyperplane would be found
- The number of support vectors found can be used to compute an (upper) bound on the expected error rate of the SVM classifier, which is independent of the data dimensionality
- Thus, an SVM with a small number of support vectors can have good generalization, even when the dimensionality of the data is high

Weakness of SVM

- It is sensitive to noise
 - A relatively small number of mislabeled examples can dramatically decrease the performance
- It only considers two classes
 - how to do multi-class classification with SVM?
 - Answer:
 - 1) with output arity m , learn m SVM's
 - SVM 1 learns "Output==1" vs "Output != 1"
 - SVM 2 learns "Output==2" vs "Output != 2"
 - :
 - SVM m learns "Output== m " vs "Output != m "
 - 2) To predict the output for a new input, just predict with each SVM and find out which one puts the prediction the furthest into the positive region.

SVM applications

- SVMs were originally proposed by Boser, Guyon and Vapnik in 1992 and gained increasing popularity in late 1990s.
- SVMs are currently among the best performers for a number of classification tasks ranging from text to genomic data.
- SVMs can be applied to complex data types beyond feature vectors (e.g. graphs, sequences, relational data) by designing kernel functions for such data.
- SVM techniques have been extended to a number of tasks such as regression [Vapnik *et al.* '97], principal component analysis [Schölkopf *et al.* '99], etc.
- Most popular optimization algorithms for SVMs use *decomposition* to hill-climb over a subset of α_i 's at a time, e.g. SMO [Platt '99] and [Joachims '99]
- Tuning SVMs remains a black art: selecting a specific kernel and parameters is usually done in a try-and-see manner.

Summary: Support Vector Machine

- 1. Large Margin Classifier
 - Better generalization ability & less over-fitting
- 2. The Kernel Trick
 - Map data points to higher dimensional space in order to make them linearly separable.
 - Since only dot product is used, we do not need to represent the mapping explicitly.

SVM resources

- Many references here:
<http://www.kernel-machines.org>
- One of the first SVM software:
<http://www.csie.ntu.edu.tw/~cjlin/libsvm/>
- SVM are available in R and python
 - In R: package e1071
 - In python: library scikit-learn

29

WORKSHOP

- We work on the titanic dataset
- Either with R or python, run a SVM model on the training set and test it with the testing set
- The dependent variable is the survival variable

30

WORKSHOP – Parameters tuning

- Using python scikit-learn or R e1071, use a grid search to obtain the best parameters for your SVM model
- Choose an appropriate metric to fit parameters
- Obtain the ROC curve

31



How to tune Parameters of SVM?

- Here is the list of parameters
- `sklearn.svm.SVC(C=1.0, kernel='rbf', degree=3, gamma=0.0, coef0=0.0, shrinking=True, probability=False, tol=0.001, cache_size=200, class_weight=None, verbose=False, max_iter=-1, random_state=None)`
- Important parameters are C, kernel and gamma
- C is the regularization parameter
 - Penalty parameter C of the error term. It also controls the trade off between smooth decision boundary and classifying the training points correctly.
- Kernel is the type of kernel
- Gamma is kernel parameter
 - Kernel coefficient for 'rbf', 'poly' and 'sigmoid'. Higher the value of gamma, will try to exact fit the as per training data set i.e. generalization error and cause over-fitting problem.

Use `np.meshgrid` to build a grid and project the predicted classes

Try to modify the 3 main parameters to understand what happens

Work with the iris dataset



Pros and cons

- **Pros:**
 - It works really well with clear margin of separation
 - It is effective in high dimensional spaces.
 - It is effective in cases where number of dimensions is greater than the number of samples.
 - It uses a subset of training points in the decision function (called support vectors), so it is also memory efficient.
- **Cons:**
 - It doesn't perform well, when we have large data set because the required training time is higher
 - It also doesn't perform very well, when the data set has more noise i.e. target classes are overlapping
 - SVM doesn't directly provide probability estimates, these are calculated using an expensive five-fold cross-validation. It is related SVC method of Python scikit-learn library.