

# Interim Report

*Hukai Luo*

*13 November 2018*

## 1 Introduction

**The goal of this project** is to predict the *duration of taxi rides in NYC* based on features like trip coordinates or pickup date and time.

Since there are lots of parameters when we are estimating the trip duration, we will first study and visualise the original data, engineer new features, and examine potential outliers. Finally, we will choose some important parameters to curve fit the data using the least square method.

First of all, let's load the given data

```
library('tibble')
library('data.table')
train <- as.tibble(fread("/Users/luohukai/Documents/GitHub/final-project-hul17011/train.csv"))
test <- as.tibble(fread("/Users/luohukai/Documents/GitHub/final-project-hul17011/test.csv"))
sample <- as.tibble(fread("/Users/luohukai/Documents/GitHub/final-project-hul17011/sample.csv"))
```

Then find the structure of the data

```
library('dplyr')
summary(train)
combine <- bind_rows(train %>% mutate(dset = "train"),
                      test %>% mutate(dset = "test",
                                       dropoff_datetime = NA,
                                       trip_duration = NA))
combine <- combine %>% mutate(dset = factor(dset))
```

We find the data contains several factors: **vendor\_id** takes only 1 or 2 which represents two taxi companies; *pickup\_datetime*; *dropoff\_datetime*; *passenger\_count*; *pickup\_longitude*; *pickup\_latitude*; *dropoff\_longitude*; *dropoff\_latitude*; *store\_and\_fwd\_flag*; *trip\_duration* which is measured in seconds.


In order to make the data easy to use, we will make some change to the data.

```
library('lubridate')
train <- train %>%
  mutate(pickup_datetime = ymd_hms(pickup_datetime),
         dropoff_datetime = ymd_hms(dropoff_datetime),
         vendor_id = factor(vendor_id),
         passenger_count = factor(passenger_count))
```


## 2 Plot by single parameter

Now in order for us to get a better understanding of the data, we will begin by having a look at the distributions of the individual data features. First of all, let's plot the target feature *trip\_duration*.

```
library('ggplot2')
p1 <- ggplot(train, aes(train$trip_duration)) +
  geom_histogram(fill = "steelblue", bins = 150) +
  scale_x_log10() +
  scale_y_sqrt()
p1
```



Comments: Most trips will ends in nearly 1000 seconds, but there will also be some exceptions. Then we can also plot the distribution of passenger\_count, Vendor\_id, day of the week, hour of the day



Comments: Most trips only have 1 passenger; Thursday, Friday and Saturday are the most busy days; there is a strong dip during the early morning hours and another dip around 4pm.

## 3 Relations


While the previous section looked primarily at the distributions of the individual features, here we will examine in more detail how those features are related to each other and to our target `trip_duration`. In this project, we will assume that the `trip_duration` is only related to **Trip distance**, **passenger numbers**, **vendor\_id**, **day of the week**, **hour of the day**.

### 3.1 Trip distance vs trip\_duration



First, we need to calculate the exact trip distance by the pickup and dropoff location.

```
library('geosphere')
pick_coord <- train %>%
  select(pickup_longitude, pickup_latitude)
drop_coord <- train %>%
  select(dropoff_longitude, dropoff_latitude)
train$dist <- distCosine(pick_coord, drop_coord)
```


Then plot the Trip distance vs `trip_duration` distribution.



### 3.2 Pickup date/time vs trip\_duration



### 3.3 Passenger number vs trip\_duration



From this plot, we can find the trip\_duration doesn't have a strong relationship with the passenger numbers, the difference in the picture may only reveal the impact of different distance. For those passenger numbers = 7, 8, 9, we don't think that they are reasonable, so we just won't consider them.

## 4 Prediction/least square method

In this project, we assume the trip\_duration distribution function has three parameters: trip\_distance  $d$ , pickup date  $w$ , pickup time  $t$ .