

Bootstrap aggregated sparse FPCA for classification

Hyunsung Kim

February 7, 2020

Department of Statistics
Chung-Ang University

- *Probability-enhanced effective dimension reduction for classifying sparse functional data*(Yao et al.)
- 700 curves are generated with 200 training set and 500 test set.
- Bagged classifiers are obtained from 100 bootstrap resamples.
- We consider the following 2 cases.
 - Dense
 - Sparse

Dense Simulation Results

Table 1: The average classification error with standard error in percentage from 10 Monte Carlo repetitions for dense data

Method	Logistic Regression	LDA	QDA	Naive Bayes
Single	6.9 (2.02)	9.4 (2.60)	20.5 (2.11)	13.3 (2.72)
Majority vote	5.4 (1.51)	7.8 (1.90)	17.0 (2.99)	10.1 (2.48)
OOB weight	5.4 (1.58)	7.7 (1.98)	16.8 (2.63)	10.0 (2.55)
Paper(Single)	17.0 (0.17)	17.1 (0.18)	17.2 (0.17)	-

Sparse Simulation Results

Table 2: The average classification error with standard error in percentage from 10 Monte Carlo repetitions for sparse data

Method	Logistic Regression	LDA	QDA	Naive Bayes
Single	17.9 (3.56)	17.9 (3.84)	19.7 (4.07)	19.6 (4.27)
Majority vote	16.0 (2.63)	16.4 (2.96)	17.6 (2.65)	18.1 (3.82)
OOB weight	16.2 (2.73)	16.6 (3.10)	17.9 (2.79)	18.5 (3.87)
Paper(Single)	17.6 (0.29)	17.6 (0.23)	18.2 (0.21)	-