

# Sequencing: Bulk RNA-seq homework

Add your names here

8/6/2021

## Contents

<b>1</b>	<b>Default edgeR analysis</b>	<b>1</b>
<b>2</b>	<b>Impact of blocking</b>	<b>1</b>
<b>3</b>	<b>Analyze dataset using full-quantile normalization</b>	<b>1</b>
3.1	Implement and apply full-quantile normalization . . . . .	1
3.2	Visualize effect of FQ normalization . . . . .	2
3.3	edgeR analysis using full-quantile normalized data . . . . .	2
3.4	Compare DE genes at 5% FDR . . . . .	2

## 1 Default edgeR analysis

Analyze the data using `edgeR`, by using the code in the RNA-seq analysis intro lecture. **In all analyses, focus on the contrast comparing DPN treatment to control at 48h.**

## 2 Impact of blocking

Assess the difference in number of DE genes when not blocking on patient, i.e., removing the `patient` effect of the model. Compare the p-value distributions between these two models (i.e., with and without blocking).

## 3 Analyze dataset using full-quantile normalization

### 3.1 Implement and apply full-quantile normalization

```
### implement FQ normalization
FQnorm <- function(counts){
  ...
}

### normalize the data using FQ
```

### 3.2 Visualize effect of FQ normalization

Visualize the distributions of `log1p`-transformed counts (use the `density` function) to compare sample-specific count distributions before and after FQ normalization. What's the impact of FQ normalization on the differences in distribution between samples?

### 3.3 edgeR analysis using full-quantile normalized data

Don't forget to remove the `calcNormFactors` step in the `edgeR` analysis as data have already been normalized when using FQ-normalized counts as input!

```
### use FQ-normalized data as input to the edgeR analysis
```

### 3.4 Compare DE genes at 5% FDR

```
### Get list of DE genes using TMM and FQ normalization
```

```
### Compare list using, e.g., a Venn diagram
```