

Supplementary Figures: Quality control for the target decoy approach for peptide identification

Elke Debie¹ Milan Malfait¹ Ralf Gabriels^{2,3} Arthur Declercq^{2,3} Adriaan Sticker^{2,3} Lennart Martens^{2,3} Li

¹ Department of Applied Mathematics, Computer Science and Statistics, Ghent University, Ghent, Belgium

² VIB-UGent Center for Medical Biotechnology, VIB, Zwijnaarde, Belgium

³ Department of Biomolecular Medicine, Ghent University, Ghent, Belgium

⁴ Corresponding Author: lieven.clement@ugent.be




Figure 1: Histogram and PP-plot for a concatenated search on a *Pyrococcus* run against a database of canonical *P. furiosus* sequences from Swiss-Prot using X!Tandem without refinement. Both the histogram and the P-P plot show no violation of the TDA assumptions.




Figure 2: Histogram and PP-plot for a concatenated search on a *H. sapiens* run against a database of *H. Sapiens* sequences from UniProt using MS-GF+. Both the histogram and the P-P plot show no violation of the TDA assumptions.




Figure 3: Histogram and PP-plot for a concatenated search on an immunopeptidomics run using Andromeda. Both the histogram and the P-P plot show no violation of the TDA assumptions.




Figure 4: Histogram and PP-plot for rank 2 target and decoy PSM scores of a concatenated search on a H. sapiens run against a database of H. Sapiens sequences from UniProt using MS-GF+.