

Implementation Guide ASAP Standard For Prescription Drug Monitoring Programs

Version 5 • Release 0
Includes the ASAP Standards for
Error Reporting and Zero Reporting

**February 2023
02072023**

Not to be implemented prior to January 2024

Table of Contents

Introduction to ASAP Version 5.0.....	4
Summary of Version 5.0 Enhancements to Version 4.2B.....	5
ASAP Technical Specifications.....	8
Data Element Summary	8
Data Element Separators and Segment Terminators	9
Use of Escape Character.....	9
Segment and Data Ordering.....	10
Privacy and Security	10
Optionality - Required versus Optional and Situational	10
Real-Time versus Batch Transmissions	10
Use of Qualifiers.....	11
Reporting All Prescriptions	11
Examples of Looping	11
Real-Time Looping and Real-Time Transmission	12
Core Reporting Segments	14
Header Segments	15
Segment: TH Transaction Header	16
Segment: IS Information Source	18
Segment: PHA Pharmacy Header	19
Detail Segments.....	21
Segment: PAT Patient Information.....	22
Segment: DSP Dispensing Record	27
Segment: PRE Prescriber Information	34
Segment: CDI Compound Drug Ingredient Detail.....	36
Segment: AIR Additional Information Reporting	38
Summary Segments	42
Segment: TP Pharmacy Trailer	43
Segment: TT Transaction Trailer	44
Acknowledgment/Response	45
Segment: TH Transaction Header	46
Segment: IS Information Source	48
Segment: PHA Pharmacy Header	49
Segment: ACK Acknowledgment/Response	51
Segment: TP Pharmacy Trailer	52
Segment: TT Transaction Trailer	53
Example Transmissions	54
Appendix A List of Jurisdictions	59
Appendix B Reporting Quantity Dispensed.....	60
Appendix C Real-Time Transmission Reject Codes.....	62

Appendix D Examples of the Correct Use of Codes in DSP01.....65

Error Report Standard.....67

Zero Report Standard.....77

Introduction to ASAP Version 5.0

It has been several years since the release of the last iteration of ASAP Version 4.2B in December 2019. Since then, every state and numerous territories have adopted legislation to implement a Prescription Drug Monitoring Program (PDMP). Each of these jurisdictions is using one of the existing versions of the ASAP Standard dating back to the release of Version 4.1 in 2009. Much has changed since ASAP Version 4.2B. State PDMPs have grown, matured, and evolved, and continue to be recognized and promoted as valuable tools to address the opioid crisis — fraud, abuse, diversion, and improving patient care and safety. This new version was developed through multiple sessions with stakeholders from various backgrounds to meet the needs of state PDMPs.

This is a significant enhancement in the ASAP standards with 44 new fields and is thus considered a new version rather than an iteration of a previous version. The new fields address challenges with compliance monitoring, data integrity, and patient matching. There are also four fields that are being repositioned or decommissioned. The decommissioned fields will not be used in future versions so as to protect the data integrity of the original scope of data elements. There is also clarification as to the uses of the terms Required and Situational as well as the addition of the Optional field type.

ASAP recognizes the authority of each state and stresses that nothing in these standards shall supersede applicable laws and regulations of the state/jurisdiction in terms of how data fields are populated.

Summary of Version 5.0 Enhancements to Version 4.2B

Added language at the beginning of the document stating, “Nothing in these standards shall supersede applicable laws and regulations of the state/jurisdiction in terms of how data fields are populated.”

TH Transaction Header

TH06 Creation Time TM 7. The time zone should be reported in Coordinated Universal Time (UTC) without colons or non-numeric characters

IS Information Source

IS04 Pharmacy Dispensing Software Vendor (Optional) AN 60 – **NEW FIELD**

IS05 Phone Number of Vendor (Optional) N 10 – **NEW FIELD**

PHA Pharmacy Information

PHA Loop Description – Increase Max to 2,000 Loops

PHA10 Phone Number – Change data type to N 10

PHA14 Pharmacy/Dispenser Type (Optional) N 2 – **NEW FIELD**

PHA15 Mail Order Pharmacy (Optional) N 2 – **NEW FIELD**

PAT Patient Information

PAT02 ID Qualifier – Added new qualifier code 11 – Medicaid recipient ID number

PAT05 ID Qualifier – Added new qualifier code 11 – Medicaid recipient ID number

PAT07 Last Name – Recommendations of how to report name

PAT08 First Name - Recommendations of how to report name

PAT10 Name Prefix – Added recommendations of how to report name prefix

PAT11 Name Suffix – Added recommendations of how to report name suffix

PAT12 Address Information - 1 – Added language clarifying how to enter address information.

PAT15 Changed wording to read: Jurisdiction/State Address

PAT15 State Address – Changed attribute length to 2 characters

PAT16 ZIP Code Address – Changed attribute length to 10 characters

PAT17 Phone Number – Change data type to N 10

PAT18 Date of Birth – Added recommendation on how to report date of birth

PAT19 Gender. Added a new code of N – Nonbinary and a new code of X - Undisclosed

PAT21 Patient Location Code. Added new codes

PAT22 Country of Non-U.S. Resident – Added language on how to report

PAT23 Name of Animal - description revised. Deleted “and the pharmacist has access to this information at the time of preparing the prescription.”

PAT24 Patient Preferred or Alias Last Name (Optional) AN 50 – **NEW FIELD**

PAT25 Patient Preferred or Alias First Name Alias (Optional) AN 50 – **NEW FIELD**

PAT26 Patient Race Category (Optional) N 2 – **NEW FIELD.**

PAT27 Patient Ethnicity (Optional) N 2 – **NEW FIELD.**

PAT28 Veterinary Species Code (Optional) N 2 – **NEW FIELD**

PAT29 Animal Location Code (Optional) N 2 – **NEW FIELD**

DSP Dispensing Record

DSP04 Refills Authorized - Increased field size to 4 digits

DSP06 Fill Number - Increased field size to 4 digits

DSP07 Product ID Qualifier – Added new code 07 Cannabis

DSP08 Product ID – Description changed to read: Full product identification as indicated in DSP07, including leading zeros without punctuation. If DSP07 = 01, then DSP08 should contain the 11-digit NDC without hyphens

DSP12 Transmission Form of Rx Origin Code– Added new codes
DSP15 Pharmacist State License Number – Increased length to accommodate states with longer license numbers
DSP17 Date Sold —Clarified the description
DSP22 Quantity Prescribed – Changed Data Type and length to align with Quantity Dispensed
DSP24 Changed field name to Opioid Treatment Type
DSP26 Time Written (Optional) TM 7 – **NEW FIELD** added for reporting the time the prescription was written. Time will be reported using Coordinated Universal Time (UTC)
DSP27 Time Filled (Optional) TM 7 — **NEW FIELD** added for reporting the time the prescription was filled. Time will be reported using Coordinated Universal Time (UTC)
DSP28 Time Sold (Optional) TM 7 – **NEW FIELD** added for reporting the time the prescription was sold. Time will be reported using Coordinated Universal Time (UTC)
DSP29 Total Quantity Remaining for Prescription (Optional) D 11 – **NEW FIELD**.
DSP30 Total Quantity Remaining Drug Dosage Units Code (Optional) N 2 – **NEW FIELD**
DSP31 Discount Card (Situational) N 2 – **NEW FIELD** added with description: Identifies whether the type of payment occurred using a local or national discount card and if the PDMP requires Payment Type (DSP16). Required if Classification Code for Payment Type (DSP16) is required and contingent on qualifier as 01 (Private Pay) or 04 (Commercial Insurance) used in DSP16. (Qualifiers: Yes 01 No 02)
DSP32 Classification Code for Additional Payment Type (Optional) N 2 – **NEW FIELD**
DSP33 Discount Card for Additional Payment Type (Situational) N 2 – **NEW FIELD**
DSP34 DEA Schedule/State Designation (Optional) N 2 – **NEW FIELD**
DSP35 Last Name or Initials of Pharmacist Filling the Prescription (Optional) AN 50 – **NEW FIELD** moved from AIR09
DSP36 First Name or Initials of Pharmacist Filling the Prescription (Optional) AN 50 – **NEW FIELD** moved from AIR10

PRE Prescriber Information

PRE08 (Phone Number) – Change data type to N 10
PRE09 XDEA Number field is decommissioned, since DEA no longer issuing X DEA numbers
PRE11 Prescriber Address Information - 1 (Optional) AN 55 – **NEW FIELD**
PRE12 Prescriber Address Information - 2 (Optional) AN 55 – **NEW FIELD**
PRE13 Prescriber City Address (Optional) AN 35 – **NEW FIELD**
PRE14 Prescriber State Address (Optional) AN 2 – **NEW FIELD**
PRE15 Prescriber ZIP Code Address (Optional) AN 10 – **NEW FIELD**

CDI Compound Drug Ingredient Detail

CDI06 DEA Schedule/State Designation of Each Ingredient (Optional) N 2 – **NEW FIELD** same codes as DSP34

AIR Additional Information Reporting

AIR01 Jurisdiction Issuing the Rx Serial Number deleted the word state from the description so it reads U.S.P.S. code of Jurisdiction
AIR02 Jurisdiction Issued Rx Serial Number (Situational) AN 20 Used if AIR01 is used. Deleted wording (Required if jurisdiction issues serialize prescription pads for prescriber use.)
AIR03 Changed field name to Jurisdiction Issuing ID of Person Picking Up Rx
AIR06 Relationship of Person Picking Up Rx Dropped code 01 “Patient” and moved up the remaining codes. 01 now becomes Parent/Legal Guardian
AIR09 Last Name or Initials of the pharmacist dispensing the medication (Decommissioned and moved to the DSP Segment as DSP35)
AIR10 First Name of Pharmacist (Decommissioned and moved to DSP Segment as DSP36).
AIR11 Decommissioned, since there are now separate fields to address person Picking Up/Dropping Off

AIR04 through AIR19 used for person picking up the prescription

AIR12 Date of Birth of Person Picking Rx (Optional) **NEW FIELD**
AIR13 Address Information - 1 of Person Picking Up Rx (Optional) **NEW FIELD**
AIR14 Address Information - 2 of Person Picking Up Rx (Optional) **NEW FIELD**
AIR15 Person Picking Up City Address (Optional) AN 35 **NEW FIELD**
AIR16 Person Picking Up State Address (Optional) AN 2 **NEW FIELD**
AIR17 Person Picking Up ZIP Code Address (Optional) AN 10 **NEW FIELD**
AIR18 Phone Number of Person Picking Up Rx (Optional) N 10 **NEW FIELD**
AIR19 Picking Up Method of Delivery (Optional) N 2 **NEW FIELD**

Fields for Person Dropping Off Rx AIR20 through AIR32 will mirror AIR04 through AIR18 in attributes and codes.

AIR20 Jurisdiction Issuing ID of Person Dropping Off Rx (Optional) AN 2 **NEW FIELD**
AIR21 ID Qualifier of Person Dropping Off Rx (Optional) N 2 **NEW FIELD**
AIR22 ID of Person Dropping off Rx (Situational) AN 20 **NEW FIELD**
AIR23 Relationship of Person Dropping Off Rx (Optional) N 2 **NEW FIELD**
AIR24 Last Name of Person Dropping Off Rx (Optional) AN 50 **NEW FIELD**
AIR25 First Name of Person Dropping Off Rx (Optional) AN 50 **NEW FIELD**
AIR26 Date of Birth of Person Dropping Off Rx (Optional) **NEW FIELD**
AIR27 Address Information - 1 of Person Dropping Off Rx (Optional) **NEW FIELD**
AIR28 Address Information - 2 of Person Dropping Off Rx (Optional) **NEW FIELD**
AIR29 Person Dropping Off City Address (Optional) AN 35 **NEW FIELD**
AIR30 Person Dropping Off State Address (Optional) AN 2 **NEW FIELD**
AIR31 Person Dropping Off ZIP Code Address (Optional) AN 10 **NEW FIELD**
AIR32 Phone Number of Person Dropping Off Rx (Optional) N 10 **NEW FIELD**

TP Pharmacy Trailer

TP02 – Increase field length to 12

Appendix C – Real-Time Transmission Reject Codes – Added IS and PHA segments

ASAP Technical Specifications

Data Element Summary

The data element summary included within each segment includes the following types of information:

Reference Designator: This uses the segment identifier plus a data element sequence number within the segment to create a unique ID.

Data Element Name: This is the name assigned to the data element by ASAP.

Element Type: There are five basic data element types.

AN (Alphanumeric):

An alphanumeric field can accept both numbers and characters.

N (Numeric)

A numeric field is in character format, without a decimal point included. It is treated as alphanumeric. For negative values, the leading minus sign (-) is used. Lack of a minus sign indicates a positive number. For example, to send the number 0123 the field will contain 123. To send -567, the field will contain -567. If the number is a code value (rather than a counting number), with leading zeros, do not drop the leading zero. For example, a code value 01 would be sent as 01. An integer number of 1 would be sent as 1. Note: If a value is zero, report as 0 rather than a blank or empty value.

D (Decimal)

This is a numeric field in character format, with a decimal point included. The decimal point is not sent for whole numbers. For negative values, the leading minus sign (-) is used. Absence of a minus sign indicates a positive number. For example, to send the number 0123.987 the field contains 123.987. To send the number -567.00 the field contains -567.00. Do not use scientific notation.

DT (Date):

All dates expressed in the format CCYYMMDD.

TM (Time)

Time expressed in 24-hour clock time (HHMMSS or HHMM). Time range: 000000 through 235959. The time zone is assumed to be that of the reporting entity unless otherwise specified in this implementation guide. When reporting in UTC, the format should be HHMMSSZ (e.g., 235959Z). Do not include colons or other non-numeric characters other than "Z" for Zulu time.

Field Length: This is the maximum length the field can be.

Data Element Separators and Segment Terminators

The ASAP standard uses segments to carry information. This information is sent as a single file or transaction. Each file is an ordered collection of segments, and each segment is an ordered collection of data elements or fields. Data elements are composed of one or more bytes and may be variable in length. This document specifies the maximum length of each data element or field. The structure of the ASAP standard is variable in both file length and data element length. This means if a data element is sized for specific number of bytes, but the actual number being transmitted is smaller, the smaller length becomes the size of the field. However, no field length can be increased from that shown in the standard.

The segment identifier marks the beginning of each segment. The first two characters of any transaction are always TH, the identifier to indicate Transaction Header. The third character in the Transaction Header segment carries the character that is the data element/field separator used throughout the transaction. ASAP uses the asterisk (*) in the examples in this document.

A segment terminator character is used to mark the end of a segment. TH09 carries the segment terminator character that will be used throughout the transaction. ASAP uses the tilde (~) in the examples in this document.

Should additional state-required data elements follow the last Required reportable data element or field in a segment, the segment is ended after the last state-reportable data element. The same rule applies to segments. If, for example, a state PDMP does not require information in the CDI segment this segment is not included in the submission. Or if a particular prescription is not a compound, the CDI segment would not be included, even though it may be required by the PDMP for compounds.

Note: Separator and terminator characters must be used from the ASCII character set with the exception of the escape character (^), which may not be used as the separator or terminator character. Separator and terminator characters **must not** be used from the Extended ASCII character set (values 128 - 255 or 80h - FFh).

Whatever the choice of the ASCII character set of the submitter, these must be honored by the PDMP. The character used as the segment terminator must not be used as the data element separator.

Use of Escape Character

In the event that the character chosen as a data element/field separator or segment terminator is present within a prescription record being transmitted where it should not appear, that character must be preceded with an escape character. The escape character to use is a caret or circumflex accent (^ i.e., DEC 94, HEX 5E).

In the examples provided in this document, as previously noted, the asterisk is used as a data element/field separator and the tilde is used as the segment terminator.

In the following example, an asterisk is part of the pharmacy's name. Since the submitter uses the asterisk as the field separator, the asterisk in the pharmacy name must be preceded by the escape character.

IS*7564*ACME*PHARMACY~

Therefore, an escape character would be inserted in the record as follows:

IS*7564*ACME^*PHARMACY~

When an escape character is used within a data element as text (for example “ACME^PHARMACY”) an escape character must precede the caret in the pharmacy name as follows:

IS*7564*ACME^^PHARMACY~

The use of an escape character will allow the use of printable characters as data element/field separators and segment terminators, which were discouraged from use in previous releases of the ASAP standard.

Segment and Data Ordering

You will note that the PAT segment is the first segment in the detail segments, followed by the DSP segment to loop prescriptions by patient in batch transmissions.

Because the transaction is an ordered collection of segments, the segments must be reported in a consistent sequence to allow for correct processing.

Header and Trailer segments should be implemented as instructed and never modified.

Privacy and Security

For any standard that includes the transmission of patient-sensitive information, including Protected Health Information (PHI) or Patient Identifying Information (PII) outside the pharmacy, security measures to protect the privacy of such information should be employed. It is advised that the company and/or person implementing the standard be fully versed in federal and state privacy and security laws that may apply and take all necessary steps in the implementation to ensure compliance.

Optionality - Required versus Optional and Situational

What this means is that segments classified as “**Required**” must be transmitted. If the PDMP does not have a need for these segments then they are ignored by the receiving computer. The same rule applies for data elements within a segment that are classified as “**Required**.” Where data elements within the segments are classified as “**Situational**,” the situation for use is contingent on a linked field being required. Optional data elements can be required by the PDMP. Required data elements cannot be changed in definition to “not used.” To do so would compromise the standard. No data element can be redefined, nor can codes be added or attributes changed. The usage of “**Optional**” for a data element indicates that the field is not required but may be required by a state or may be used if the state allows. No segment, field, or code value can be added or redefined without going through the ASAP process for making changes to the standard.

Real-Time versus Batch Transmissions

This standard can be used for either real-time transmissions or batch-file transmissions. When used as a real-time transmission there will be only one provider and one patient combination in the transmission submitted. The response from the PDMP system will be specific for that transmission. Real-time transmissions would use the Virtual Instrument Software Architecture (VISA) telecommunications protocol. Real time means that a send and response takes place within three or four seconds. This standard also includes functionality to allow real-time transmission of two or more prescriptions on the same date and time, from the same location.

When used to transmit prescriptions as a batch file, the transmissions reported may include

one or more pharmacies with multiple patients. The response for a batch transmission simply confirms that the file was received and that the data that came through could be read. It is particularly important to pay attention to the syntax requirements and data element attributes as spelled out in this implementation guide, whether transmitted in real-time or batch.

Use of Qualifiers

When a qualifier field is used, it must be followed by the appropriate ID indicated in the qualifier field. Therefore, if you use the qualifier field, the associated Situational field is required. As an example, if PAT03 is populated, then PAT01 and PAT02 become required.

Reporting All Prescriptions

This standard can be used to report all prescriptions or cannabis if the state is considering this. The ASAP standard is already being used in one state to report all prescriptions.

Examples of Looping

Batch Transmission

The following is an example of how looping would take place within a TH/TT transaction.

TH – Transaction Header (one per file)

IS – Information Source (one per TH)

PHA — Pharmacy Header (one to 2,000 per IS)

PAT — Patient Information (one to 25,000 per PHA)

DSP — Dispensing Record (one to 300 per PAT)

PRE — Prescriber Information (one per DSP)

CDI — Compound Drug Ingredient Detail (zero to 25 per DSP)

AIR — Additional Information Reporting (zero to one per DSP)

PAT — Patient Information

DSP — Dispensing Record

PRE — Prescriber Information

CDI — Compound Drug Ingredient Detail

AIR — Additional Information Reporting

DSP — Dispensing Record

PRE — Prescriber Information

CDI — Compound Drug Ingredient Detail

AIR — Additional Information Reporting

DSP — Dispensing Record

PRE — Prescriber Information
CDI — Compound Drug Ingredient Detail
AIR — Additional Information Reporting
PAT — Patient Information
DSP — Dispensing Record
PRE — Prescriber Information
CDI — Compound Drug Ingredient Detail
AIR — Additional Information Reporting
TP — Pharmacy Trailer (one per PHA)
PHA — Pharmacy Header
PAT — Patient Information
DSP — Dispensing Record
PRE — Prescriber Information
CDI — Compound Drug Ingredient Detail
AIR — Additional Information Reporting
PAT — Patient Information
DSP — Dispensing Record
PRE — Prescriber Information
CDI — Compound Drug Ingredient Detail
AIR — Additional Information Reporting
TP — Pharmacy Trailer
TT — Transaction Trailer (one per TH)

Real-Time Looping

The following is an example of how looping would take place for the DSP Segment within a TH/TT transaction. It would be one transmission per PAT. The looping would take place within the PAT, where more than one DSP is involved for that PAT.

Real-Time Transmission

TH — Transaction Header
IS — Information Source
PHA — Pharmacy Header
PAT — Patient Information
DSP — Dispensing Record
PRE — Prescriber Information
CDI — Compound Drug Ingredient Detail
CDI — Compound Drug Ingredient Detail
AIR — Additional Information Reporting

DSP — Dispensing Record

PRE — Prescriber Information

AIR — Additional Information Reporting

TP — Pharmacy Trailer

TT — Transaction Trailer

Core Reporting Segments

Header

TH	Transaction Header	Required
IS	Information Source	Required
PHA	Pharmacy Header	Required

Detail

PAT	Patient Information	Required
DSP	Dispensing Record	Required
PRE	Prescriber Information	Required
CDI	Compound Drug Ingredient Detail	Situational
AIR	Additional Information Reporting	Optional

Summary

TP	Pharmacy Trailer	Required
TT	Transaction Trailer	Required

Acknowledgment/Response

Header Segments

TH	Transaction Header	Required
IS	Information Source	Required
PHA	Pharmacy Header	Required

Segment: TH Transaction Header

Level: Header

Usage: Required

Purpose: To indicate the start of a transaction. It also assigns the segment terminator, data element separator, and control number.

Note: Data element TH09 is required since it shows the Segment Terminator that will be used for the entire transaction. The character used as the Data Element Separator is defined by the value in the third byte of the transaction. Note use of the two tildes (~) at the end of the TH segment example. One is the TH09 definition and one is for terminating the segment.

Example: TH*5.0*857463*01**20230205*235959Z*P**~~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TH01	Version / Release Number (Required) Used to identify the transaction Version/Release. Format = x.x (5.0) ASAP Version 5 Release 0	AN	4
TH02	Transaction Control Number (Required) Sender assigned code uniquely identifying a transaction. This number must be used in TT01. Recommendation: Use a Globally Unique Identifier (GUID) or other nonrepeating alphanumeric combination to populate this field.	AN	40
TH03	Transaction Type (Situational) Identifies the purpose of initiating the transaction. 01 Send/Request Transaction 02 Acknowledgment (Used in Response only.) 03 Error Receiving (Used in Response only.) 04 Void (Used to void a specific Rx in a real-time transmission, or an entire batch file that has been transmitted. When 04 is used the appropriate transaction control number in TH02 for the specific prescription or batch file must be included. When 04 is used only the TH Header Segment and the Transaction Trailer Segment are used.)	N	2
TH04	Response ID (Situational) Contains the Transaction Control Number of a transaction that initiated the transaction. Required in response transaction only.	AN	40
TH05	Creation Date (Required) Date the file was created. Format: CCYYMMDD.	DT	8

TH06	Creation Time (Required) Time expressed in 24-hour clock time HMMSS or HHMM). Time range: 000000 through 235959. The time zone should be reported in Coordinated Universal Time (UTC) as HHMMSSZ (e.g., 235959Z). Do not include colons or non-numeric characters other than Z for Zulu time.	TM	7
TH07	File Type (Required) Code specifying the type of transaction. P Production T Test	AN	1
TH08	Routing Number/BIN (Optional) This field can be used for real-time transmissions that go through an intermediary or network switch to indicate, if necessary, the specific state that the transactions should be routed to.	N	6
TH09	Segment Terminator Character (Required) This terminates the TH segment and sets the actual value of the data segment terminator for the entire transaction. Note: This document uses the “~” in all examples. See the “Data Element Separators and Segment Terminators” in the introduction for more information.	AN	1

Segment: **IS Information Source**

Level: Header

Usage: Required

Purpose: To convey the name and identification number of the entity supplying the information.

Example: IS*7564*ACME PHARMACY~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
IS01	Unique Information Source ID (Required) Reference number or identification number as defined by the business partners. (Example: Phone number. However, if a phone number is used to populate this field, do not include hyphens.)	N	10
IS02	Information Source Entity Name (Required) Entity name of the Information Source.	AN	60
IS03	Message (Optional) Freetext message. Use of this field is defined by the PDMP. PDMPs may designate this field to hold the submission period date range of the file transmitted. When used to indicate the date range, it must be the first data text in the field and must be inserted using the following layout (where "#" and "-" are those literal characters): #CCYYMMDD#-#CCYYMMDD# For example, a pharmacy may be submitting records for the reporting period of December 5, 2023 through December 11, 2023 but only filled reportable prescriptions on December 5 and December 7. The full submission period date range would be reported in IS03 as #20230205#-#20230211# It is up to the PDMP to further define how to enter the submission date range for exceptional cases, such as for late submission records. Note: IS03 can also be used to show the date range for Zero Reports.	AN	60
IS04	Pharmacy Dispensing Software Vendor (Optional) Name of software vendor the pharmacy is using.	AN	60
IS05	Phone Number of Software Vendor (Optional)	N	10

Segment: **PHA Pharmacy Header**

Level: Header

Loop: Max 2,000 (Looping allowed for batch-file transmission. Not applicable for real-time transactions.)

Usage: Required

Purpose: To identify the pharmacy or the dispensing prescriber. It is required that information be provided in at least one of the following fields: PHA01, PHA02, or PH03. **(Note: PHA04 through PHA13 can be used if needed by the state to further identify the sending entity.)**

Example: PHA***ZZ1234563~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
PHA01	National Provider Identifier (NPI) (Optional) Identifier assigned to the pharmacy by CMS. Used if required by the PDMP.	AN	10
PHA02	NCPDP Provider ID (Optional) Identifier assigned to pharmacy by the National Council for Prescription Drug Programs. Used if required by the PDMP.	AN	7
PHA03	DEA Number (Optional) Identifier assigned to the pharmacy by the Drug Enforcement Administration. Used if required by the PDMP.	AN	9
PHA04	Pharmacy or Dispensing Prescriber Name (Optional) Freetext name of the pharmacy. Note: If a dispensing prescriber, the prescriber's name and professional degree should be entered, such as John Doe MD.	AN	60
PHA05	Address Information – 1 (Optional) Freetext for address information. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PHA06	Address Information – 2 (Optional) Freetext for additional address information. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PHA07	City Address (Optional) Freetext for city name.	AN	35
PHA08	State Address (Optional) Two-letter jurisdiction/state and possession abbreviation as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	2

PHA09	ZIP Code Address (Optional) United States Postal Service ZIP Code or ZIP+4 as described in United States Postal Service Publication 28 Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses. Do not include white spaces or special characters. Include hyphens in ZIP+4.	AN	10
PHA10	Phone Number (Optional) Complete phone number including area code. Exclude hyphens.	N	10
PHA11	Contact name (Optional) Freetext name of vendor contact.	AN	30
PHA12	Chain Site ID (Optional) Store number assigned by the chain to the pharmacy location. Used when PDMP needs to identify the specific pharmacy from which information is required.	AN	10
PHA13	Pharmacy's Permit Number/License Number (Optional) Used to help identify the sending pharmacy.	AN	20
PHA14	Pharmacy/Dispenser Type (Optional) 01 Independent Pharmacy 02 Chain Pharmacy 03 Long-term Care Pharmacy 04 Hospital Pharmacy 05 Opioid Treatment Program 06 Cannabis Dispensary 07 Veterinary/Vet Patient Only Dispenser 08 Dispensing Prescriber 09 Specialty Pharmacy 10 Federal 11 Tribal 99 Other	N	2
PHA15	Mail Order Pharmacy (Optional) 01 Yes 02 No	N	2

Detail Segments

PAT	Patient Information	Required
DSP	Dispensing Record	Required
PRE	Prescriber Information	Required
CDI	Compound Drug Ingredient Detail	Situational
AIR	Additional Information Reporting	Optional

Segment: **PAT Patient Information**

Level: Detail

Loop: Max 25,000 (Looping allowed for batch-file transmission. Looping of the PAT is not allowed in real-time transactions.)

Usage: Required

Purpose: Used to report the patient's name and basic information as contained in the pharmacy record.

Example: PAT*PA*06*987544****SMITH*JOHN****1234 MAIN ST**
SOMEWHERE*PA*19422**19500101*M~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
PAT01	ID Qualifier of Patient Identifier (Optional) Code identifying the jurisdiction that issues the ID in PAT03. Used if the PDMP requires such identification. If PAT01 is populated, then PAT02 and PAT03 must be populated as well. See Appendix A for list of jurisdictions.	AN	2
PAT02	ID Qualifier (Situational) Code to identify the type of ID in PAT03. If PAT02 is used, PAT03 is required. 01 Military ID 02 State Issued ID 03 Unique System ID 04 Permanent Resident Card (Green Card) 05 Passport ID 06 Driver's License ID 07 Social Security Number 08 Tribal ID 09 Vendor Specific (such as Bamboo Health, Experian, LexisNexis) 10 Veterinary Patient Microchip Number 11 Medicaid Recipient ID Number 99 Other (Trading partner agreed upon ID, such as cardholder ID.)	N	2
PAT03	ID of Patient (Situational) Identification number for the patient as indicated in PAT02. An example would be the driver's license number. Note: This field can only be populated with code 10 when provided on the prescription.	AN	20
PAT04	ID Qualifier of Additional Patient Identifier (Situational) Code identifying the jurisdiction that issues the ID in PAT06. Used if the PDMP requires such identification. See Appendix A for list for jurisdictions.	AN	2

PAT05	Additional Patient ID Qualifier (Situational) 01 Military ID 02 State Issued ID 03 Unique System ID 04 Permanent Resident Card (Green Card) 05 Passport ID 06 Driver's License ID 07 Social Security Number 08 Tribal ID 09 Vendor Specific (such as Bamboo Health, Experian, LexisNexis) 10 Veterinary Patient Microchip Number 11 Medicaid Recipient ID Number 99 Other (Trading partner agreed upon ID, such as cardholder ID.)	N	2
PAT06	Additional ID (Situational) Identification that might be required by the PDMP to further identify the individual. An example might be in that PAT03 driver's license is required and in PAT06 Social Security number is also required.	AN	20
PAT07	Last Name (Required) Patient's last name. Recommended way to report: Report the patient's complete legal last name ONLY as listed on a government-issued identification Do NOT report extraneous information or notes in this field Do NOT enter Prefix or Suffix in Last Name field Do NOT report special characters (e.g., parentheses, asterisk) other than a hyphen or apostrophe. If for a veterinary patient, enter information of PERSON responsible for the care of the animal or who arranges for the animal's veterinary care	AN	50
PAT08	First Name (Required) Patient's first name. Recommended way to report: Report the patient's complete legal first name ONLY as listed on a government-issued identification Do NOT report extraneous information or notes in this field Do NOT enter Prefix or Suffix in First Name field Do NOT report special characters (e.g., parentheses, asterisk) other than a hyphen or apostrophe. If for a veterinary patient, enter information of PERSON responsible for the care of the animal or who arranges for the animal's veterinary care	AN	50

PAT09	Middle Name (Optional) Patient's middle name or initial if available. Used if available in pharmacy system and required by the PDMP.	AN	30
PAT10	Name Prefix (Optional) Patient's name prefix such as Mr. or Dr. Used if available in pharmacy system and required by the PDMP. Do not report special characters other than a hyphen or a period.	AN	10
PAT11	Name Suffix (Optional) Patient's name suffix such as Jr. or the III. Used if available in pharmacy system and if required by the PDMP. Do not report special characters other than a hyphen or a period.	AN	10
PAT12	Address Information – 1 (Required) If the pharmacy management system stores 35 bytes or less for the address, no programming change is necessary. If the address stored in the system is a P.O. box number, defer to the specifications of the PDMP as to whether this should be reported in PAT12 or PAT13. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PAT13	Address Information – 2 (Optional) Fretext for additional address information, if required by the PDMP and is available in pharmacy system. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PAT14	City Address (Required) Fretext for city name.	AN	35
PAT15	Jurisdiction/State Address (Required) Jurisdiction/state and possession abbreviation as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	2
PAT16	ZIP Code Address (Required) United States Postal Service ZIP Code or ZIP+4 as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses. Do not include white spaces or special characters. Include hyphens in ZIP+4. Populate with zeros if patient address is outside the U.S.	AN	10

PAT17	Phone Number (Optional) Complete phone number including area code when a state PDMP requires and is available in the pharmacy system. Note: Exclude hyphens.	N	10
PAT18	Date of Birth (Required) Owner's date of birth as listed on a government-issued identification. If for a veterinary patient Date of Birth should be listed as directed by applicable state/jurisdiction PDMP laws and regulations. Format: CCYYMMDD.	DT	8
PAT19	Gender Code (Optional) Code indicating the sex of the patient if required by the PDMP. F Female M Male N Non-Binary U Unknown/Undisclosed X Unspecified/Other	AN	1
PAT20	Species Code (Optional) Used if required by the PDMP to differentiate a prescription for an individual from one prescribed for an animal. 01 Human 02 Veterinary	N	2
PAT21	Patient Location Code (Optional) Code indicating where patient is located when receiving services, if required by the PDMP. 01 Home 02 Intermediary Care 03 Nursing Home 04 Long-Term/Extended Care 05 Rest Home 06 Boarding Home 07 Skilled-Care Facility 08 Sub-Acute Care Facility 09 Acute-Care Facility 10 Outpatient 11 Hospice 12 Homeless/Unhoused 13 Transient Care 98 Unknown 99 Other	N	2
PAT22	Country of Non-U.S. Resident (Optional) Used when the patient's address is a foreign country and PAT12 through PAT16 are left blank. This is a freetext field. ASAP does not provide a list of countries for this field. PDMPs may permit some of the other address fields to not be used if this field is populated.	AN	20

PAT23	Name of Animal (Optional) Used if required by the PDMP for prescriptions written by a veterinarian. An unnamed animal could be described as COWSmith or as COW1Smith.	AN	30
PAT24	Patient Preferred or Alias Last Name (Optional) May be used for patient's preferred name, previous name, nickname, alias, or name used on insurance if different than legal last name.	AN	50
PAT25	Patient Preferred or Alias First Name (Optional) Maybe used for patient's preferred name, previous name, nickname, alias, or name used on insurance if different than legal first name.	AN	50
PAT26	Patient Race Category (Optional) Code used for general race category. 01 American Indian or Alaskan Native 02 Asian 03 Black or African American 04 Native Hawaiian or Other Pacific Islander 05 White 06 Multiracial 99 Other/Unknown	N	2
PAT27	Patient Ethnicity (Optional) Code used to describe general ethnicity group of the patient. 01 Hispanic or Latino 02 Not Hispanic or Latino 99 Undisclosed/Unknown	N	2
PAT28	Veterinary Species Code (Optional) Code used to describe animal species. 01 Cat/Feline 02 Dog/Canine 03 Small Animal (Hamster, Rabbit, Other Rodent) 04 Reptile 05 Bird 06 Livestock, Large Animal 99 Other	N	2
PAT29	Animal Location Code (Optional) 01 Home 02 Animal Shelter 03 Foster 04 Farm 05 Zoo 06 Circus/Traveling Show 99 Other	N	2

Segment: **DSP Dispensing Record**

Level: Detail

Loop: Max 300 for batch; max 10 for real time.

Usage: Required

Purpose: To identify the basic components of a dispensing of a given prescription order including the date and quantity.

Example: DSP*00*6542984*20230205*0*20230205*0*01*57866707401*30*15~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
DSP01	Reporting Status (Required) 00 New Record 01 Revise 02 Void DSP01 requires one of the codes below. An empty or blank field no longer indicates a new prescription dispensing transaction. A PDMP may elect to require a subset of the codes below, specifically 00 and 02, but not 01. 00 This code indicates a new prescription dispensing transaction. 01 This code indicates that one or more data element values in a previously submitted transaction are being revised. Examples of when a revision may be necessary include corrections to typographical errors in original data submissions; or change occurred to the prescription between the time the record was submitted and the time the patient picked it up, such as dispensing a smaller metric quantity, adding or correcting patient information, correcting prescriber DEA number, or payment type. When receiving a transaction with a DSP01 value of 01, the PDMP will override all of the detail segments' data of the original prescription transaction with all of the detail segments' data from the revised prescription transaction. It is essential to submit all of the data elements in all of the detail segments populated with the identical data as it appeared in the original record, with only the changed data element(s) content being different (and DSP01 with a value of 01). <u>Do not use 01 in combination with a zero metric quantity to indicate that the prescription was not picked up. Use the value 02 instead as described below.</u> If the PDMP receives a prescription transaction with DSP01 as 01 and a separate prescription transaction with DSP01 as 02, the PDMP will only void the original prescription transaction and will not attempt to apply a revision. Because the PAT segment loops at a higher level than the other detail segments, the only ways to submit revisions to PAT data elements are either: 1) to not loop the DSP segment within the PAT segment or 2) to loop the DSP segment within PAT segment and have every DSP01 record element within the loop have a DSP01 of 01. 02 This code is a message to the PDMP to remove the original prescription transaction from its database (or to mark the record as	N	2

	invalid and to be ignored). There can be several reasons for sending a void transaction. One example would be when the prescription was never picked up and the medication was returned to stock. Another example would be when the prescription was reported in error. A DSP01 value of 02 can also be used as an alternative to the DSP01 value of 01 in order to send PDMP corrections. When submitting corrections in this manner; first submit a record with a DSP01 of 02 to indicate to the PDMP to void the original prescription transaction; then submit a brand-new prescription transaction with a DSP01 value of 00 with the correct information. Note: Examples of the correct use of codes in DSP01 are shown in Appendix D, as well as the limited data set to void a prescription that PDMPs can elect to use.		
DSP02	Prescription Number (Required) Serial number assigned to the prescription by the pharmacy.	AN	25
DSP03	Date Written (Required) Date the prescription was written (authorized). Format: CCYYMMDD.	DT	8
DSP04	Refills Authorized (Required) The number of refills authorized by the prescriber.	N	4
DSP05	Date Filled (Required) Date prescription was prepared. Format: CCYYMMDD.	DT	8
DSP06	Fill Number (Required) Number of the fill of the prescription. 0 indicates original dispensing, 01-99 is the refill number.	N	4
DSP07	Product ID Qualifier (Required) Used to identify the type of product ID contained in DSP08. 01 NDC 02 UPC 03 HRI 04 UPN 05 DIN 06 Compound (Used to indicate it is a compound. The CDI segment then becomes a required segment. Also, see instructions for DSP08.) 07 Cannabis	N	2
DSP08	Product ID (Situational) Full product identification as indicated in DSP07, including zeros without punctuation. If DSP07 = 01, then DSP08 should contain the 11-digit NDC code without hyphens. If the product is a compound, use 99999 as the first five characters of the product code. The remaining six characters are assigned by the pharmacy. The CDI then becomes a required segment. Note: If a controlled substance is part of a kit, the NDC of the kit should be reported if it is a legitimate manufacturer's NDC. If not,	AN	15

	the NDC of the controlled substance within the kit should be reported. Also, if multiple controlled substances are in the kit, use the CDI segment to report it as a compound.		
DSP09	Quantity Dispensed (Required) Number of metric units dispensed in metric decimal format. Example: 2.5. Note: For compounds show the first quantity in CDI04. See Appendix B for specific instructions.	D	11
DSP10	Days Supply (Required) The calculated or estimated number of days the medication will cover.	N	3
DSP11	Drug Dosage Units Code (Situational) Identifies the unit of measure for the quantity dispensed in DSP09,if required by the PDMP. See Appendix B for specific instructions. 01 Each (used to report solid dosage units or indivisible package) 02 Milliliters (ml) (for liters adjust to the decimal milliliter equivalent) 03 Grams (gm) (for milligrams adjust to the decimal gram equivalent)	N	2
DSP12	Transmission Form of Rx Origin Code (Optional) Code indicating how the pharmacy received the prescription, if required by the PDMP 01 Written Prescription 02 Telephone Prescription 03 Telephone Emergency Prescription 04 Fax Prescription 05 Electronic Prescription 06 Transferred/Forwarded Rx 07 Order (Administered at Prescriber Location) 08 Dispensed from a Prescriber Location 09 Standing Order/Protocol 99 Other	N	2
DSP13	Partial Fill Indicator (Optional) This field is used when the quantity in DSP09 is less than the metric quantity per dispensing authorized by the prescriber. This dispensing activity is often referred to as a split filling. 00 Not a Partial Fill 01 First Partial Fill Note: For additional fills per prescription, increment by 1. The second partial fill would be reported as 02, up to a maximum of 99.	N	2
DSP14	Pharmacist National Provider Identifier (NPI) (Optional) Identifier assigned to the pharmacist by CMS. This number can be used to identify the pharmacist dispensing the medication.	AN	10

DSP15	Pharmacist State License Number (Optional) Assigned to the pharmacist by the State Licensing Board. This data element can be used to identify the pharmacist dispensing the medication.	AN	20
DSP16	Classification Code for Payment Type (Optional) Code identifying the type of payment, i.e., how it was paid for, if required by the PDMP. 01 Private Pay (Cash, Charge, Credit Card) 02 Medicaid 03 Medicare 04 Commercial Insurance 05 Military Installations and VA 06 Workers' Compensation 07 Indian Nations 99 Other	N	2
DSP17	Date Sold (Optional) This field is used to determine the date the prescription was dispensed (sold to, picked up by, or otherwise left the pharmacy), not the date it was prepared. This date could be captured from the point-of-sale (POS) system, if the pharmacy has a POS system, and there is a bidirectional flow with the pharmacy management system in order to capture and report this date. Or it could be captured and reported from a will-call management system, integrated with the pharmacy management system.	DT	8
DSP18	RxNorm Product Qualifier (Optional) 01 Semantic Clinical Drug (SCD) 02 Semantic Branded Drug (SBD) 03 Generic Package (GPCK) 04 Branded Package (BPCK) RxNorm code that is populated in the appropriate field in the SCRIPT transaction. Note: DSP18 and DSP19 are placeholder fields pending RxNorm becoming an industry standard. This field should not be required until such time. Use the 2-digit code and not the abbreviation.	AN	20
DSP19	RxNorm Code (Optional) Used for electronic prescriptions to capture the prescribed drug product identification, if required by the PDMP.	AN	15
DSP20	Electronic Prescription Reference Number (Optional) This field should be populated with the appropriate field in the SCRIPT transaction.	AN	35

DSP21	Electronic Prescription Order Number (Optional) This field will be populated with appropriate field in the SCRIPT standard. Note: DSP20 and DSP21 should be reported as a pair to the PDMP and the PDMP will decide which one, if not both, it decides to capture. By requiring the reporting of both, this avoids specification variations that would require custom programming to accommodate a PDMP. Also, the information reported by the pharmacy management system will depend on the information received at the pharmacy with an electronic prescription.	AN	35
DSP22	Quantity Prescribed (Optional) This field can clarify the value reported in DSP13 Partial Fill Indicator.	D	11
DSP23	Rx SIG (Optional) This field would capture the actual directions printed on the prescription vial label. If the directions exceed 200 characters, truncation would be allowed.	AN	200
DSP24	Opioid Treatment Type (Optional) This field is used to explain the reason for an opioid prescription. If the prescription is not for an opioid, then this field would not be used. 01 Not Used for Opioid Dependency Treatment 02 Used for Opioid Dependency Treatment 03 Pain Associated with Active and Aftercare Cancer Treatment 04 Palliative Care in Conjunction with a Serious Illness 05 End-of-Life and Hospice Care 06 A Pregnant Individual with a Pre-existing Prescription for Opioids 07 Acute Pain for an Individual with an Existing Opioid Prescription for Chronic Pain 08 Individuals Pursuing an Active Taper of Opioid Medications 09 Patient is Participating in a Pain Management Contract 10 Acute Opioid Therapy 11 Chronic Opioid Therapy 99 Other (trading partner agreed upon reason or not indicated) The definitions of Codes 03 to 11 can only be reported if required by the state to be provided by the prescriber on the prescription order.	N	2
DSP25	Diagnosis Code (Optional) This field is used to report the ICD-10 code. If required by a PDMP, this field would be populated only when the ICD-10 code is included with the prescription. Exclude the decimal point.	AN	7

DSP26	Time Written (Optional) Time expressed in 24-hour clock time HMMSS or HHMM). Time range: 000000 through 235959. The time zone should be reported in Coordinated Universal Time (UTC) as HHMMSSZ (e.g., 235959Z). Do not include colons or non-numeric characters other than Z for Zulu time.	TM	7
DSP27	Time Filled (Optional) The time the prescription record was prepared. Time expressed in 24-hour clock time HMMSS or HHMM). Time range: 000000 through 235959. The time zone should be reported in Coordinated Universal Time (UTC) as HHMMSSZ (e.g., 235959Z). Do not include colons or non-numeric characters other than Z for Zulu time.	TM	7
DSP28	Time Sold (Optional) The time the prescription record was sold to, picked up by, or otherwise left the pharmacy for the patient. Time expressed in 24-hour clock time HMMSS or HHMM). Time range: 000000 through 235959. The time zone should be reported in Coordinated Universal Time (UTC) as HHMMSSZ (e.g., 235959Z). Do not include colons or non-numeric characters other than Z for Zulu time.	TM	7
DSP29	Total Quantity Remaining on Prescription (Optional) Identifies the unit of measure for the total quantity remaining for the prescription after the current dispense in metric decimal format. Example: 2.5. Note: For compounding show the first quantity in CDI04. See Appendix B for specific instructions.	D	11
DSP30	Total Quantity Remaining Drug Dosage Units Code (Optional) Identifies the unit of measure for the quantity remaining in DSP29. See Appendix B for specific instructions. 01 Each (used to report solid dosage units or indivisible package) 02 Milliliters (ml) (for liters adjust to the decimal milliliter equivalent) 03 Grams (gm) (for milligrams adjust to the decimal gram equivalent)	N	2
DSP31	Discount Card (Situational) Identifies whether the type of payment occurred using a local or national discount card if the PDMP requires payment DSP16. Required if classification payment code is 01 (Private Pay) or 04 (Commercial Insurance) used in DSP16. 01 Yes 02 No	N	2

DSP32	Classification Code for Additional Payment Type (Optional) Code identifying the type of payment, i.e., how it was paid for, if required by the PDMP. 01 Private Pay (Cash, Charge, Credit Card) 02 Medicaid 03 Medicare 04 Commercial Insurance 05 Military Installations and VA 06 Workers' Compensation 07 Indian Nations 99 Other	N	2
DSP33	Discount Card for Additional Payment Type (Situational) Required if classification payment code is 01 (Private Pay) or 04 (Commercial Insurance) used in DSP32.	N	2
DSP34	DEA Schedule/State Designation (Optional) State or federal control level or other reporting designation. 01 Cannabis and Cannabis Extract 02 State or DEA Schedule 2 03 State or DEA Schedule 3 04 State or DEA Schedule 4 05 State or DEA Schedule 5 06 State Designated Other Controlled Substance or Drug of Concern 07 CBD 99 Legend or Non-Controlled Substances	N	2
DSP35	Last Name or Initials of Pharmacist Filling the Prescription (Optional) Last name or initials of the pharmacist dispensing the medication.	AN	50
DSP36	First Name of Pharmacist Filling the Prescription (Optional) First name of the pharmacist dispensing the medication.	AN	50

Segment: PRE Prescriber Information

Level: Detail

Usage: Required

Purpose: To identify the prescriber of the prescription.

Example: PRE**ZZ1234563~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
PRE01	National Provider Identifier (NPI) (Optional) Identifier assigned to the prescriber by CMS. Note: If the prescriber does not have a DEA number and prescribed a noncontrolled substance that is a reportable drug to the PDMP, this field should be used as the identifier.	AN	10
PRE02	DEA Number (Required) Identifying number assigned to a prescriber or an institution by the Drug Enforcement Administration (DEA). Required when the prescription is for a DEA-defined controlled substance.	AN	9
PRE03	DEA Number Suffix (Optional) Identifying number assigned to a prescriber by an institution when the institution's DEA number is used, if required by the PDMP.	AN	7
PRE04	Prescriber License Number (Optional) Identification assigned to the prescriber by the Licensing Board of a state or jurisdiction. This field can be used for veterinarian prescriptions. Used if required by the PDMP.	AN	20
PRE05	Last Name (Optional) Prescriber's last name. Used if required by the PDMP.	AN	50
PRE06	First Name (Optional) Prescriber's first name. Used if required by the PDMP.	AN	50
PRE07	Middle Name (Optional) Prescriber's middle name or initial. Used if required and is available in the pharmacy system.	AN	30
PRE08	Phone Number (Optional) The prescriber's primary phone number.	N	10
PRE09	XDEA Number (Decommissioned) This field has been decommissioned since DEA no longer issues XDEA numbers. This field is not to be used.	AN	9
PRE10	Jurisdiction or State Issuing Prescriber License Number (Situational) This field can be used to further identify the information in PRE04, depending on the PDMP's need for this information.	AN	2

PRE11	Prescriber Address Information - 1 (Optional) Freetext for address information. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Address.	AN	55
PRE12	Prescriber Address Information - 2 (Optional) Freetext for additional address information. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PRE13	Prescriber City Address (Optional) Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	35
PRE14	Prescriber State Address (Optional) Two-letter jurisdiction/state and possession abbreviation as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	2
PRE15	ZIP Code Address (Optional) United States Postal Service ZIP Code or ZIP+4 as described in United States Postal Service Publication 28 Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses. Do not include white spaces or special characters. Include hyphens in ZIP+4 .	AN	10

Segment: **CDI Compound Drug Ingredient Detail**

Level: Detail

Loop: Max 25 for batch or real time.

Usage: Situational

Required when medication dispensed is a compound and one of the ingredients is a PDMP reportable drug. If more than one ingredient is for a prescription monitoring program reportable drug, then this would be incremented by 1 for each compound ingredient being reported. The first reportable ingredient is reported as “1” — each additional reportable ingredient is incremented by 1. Example: A compound with two reportable ingredients would have a 1 in CDI01 for the first ingredient. The second reportable ingredient would have a 2 in CDI01.

Purpose: To identify the individual ingredients that make up a compound.

Example: CDI*1*01*04532657401*2.5*03~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
CDI01	Compound Drug Ingredient Sequence Number (Required) The first reportable ingredient is 1. Each additional reportable ingredient is incremented by 1.	N	2
CDI02	Product ID Qualifier (Required) Code to identify the type of product ID contained in CDI03. 01 NDC 02 UPC 03 HRI 04 UPN 05 DIN 06 Compound (This code is not used in this segment.)	N	2
CDI03	Product ID (Required) Full product identification as indicated in CDI02, including leading zeros without punctuation. If DSP07 = 01, then DSP08 should contain the 11-digit NDC code without hyphens. If the product is a compound, use 99999 as the first five characters of the product code. The remaining six characters are assigned by the pharmacy. The CDI then becomes a required segment.	AN	15
CDI04	Component Ingredient Quantity (Required) Metric decimal quantity of the ingredient identified in CDI03. Example: 2.5. See Appendix B for specific instructions.	D	11

CDI05	Compound Drug Dosage Units Code (Situational) Identifies the unit of measure for the quantity dispensed in CDI04, if required by the prescription-monitoring program. See Appendix B for specific instructions. 01 Each (used to report solid dosage units or indivisible package) 02 Milliliters (ml) (for liters adjust to the decimal milliliter equivalent) 03 Grams (gm) (for milligrams adjust to the decimal gram equivalent)	N	2
CDI06	DEA Schedule/State Designation of Each Ingredient (Optional) 01 Cannabis and Cannabis Extract 02 State or DEA Schedule 2 03 State or DEA Schedule 3 04 State or DEA Schedule 4 05 State or DEA Schedule 5 06 State Designated Other Controlled Substance or Drug of Concern 07 CBD 99 Legend or Non-Controlled Substances	N	2

Segment: **AIR Additional Information Reporting**

Level: Detail

Usage: Optional

Used when state-issued serialized Rx pads are used or if state requires information on person picking up or dropping off the prescription, if other than the patient for which the prescription was written.

Purpose: To report a prescription blank serial number and information on person picking up or dropping off the prescription, if other than the patient. Note: If this segment is used, at least one of the data elements (fields) will be required.

Example: AIR*PA*787456493993~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
AIR01	Jurisdiction Issuing Rx Serial Number (Optional) U.S.P.S. code of jurisdiction that issued serialized prescription blank. This is required if AIR02 is used. See Appendix A for list of jurisdictions.	AN	2
AIR02	Jurisdiction Issued Rx Serial Number (Optional) Number assigned to state issued serialized prescription blank.	AN	20
AIR03	Jurisdiction Issuing ID of Person Picking Up Rx (Situational) Code identifying the jurisdiction that assigned the ID for the person picking up in AIR05. See Appendix A for list of jurisdictions.	AN	2
AIR04	ID Qualifier of Person Picking Up Rx (Situational) Code to identify the type of ID in AIR05. If AIR03 is used, AIR04 is required. 01 Military ID 02 State Issued ID 03 Unique System ID 04 Permanent Resident Card (Green Card) 05 Passport ID 06 Driver's License ID 07 Social Security Number 08 Tribal ID 09 Vendor Specific (such as Bamboo Health, Experian, LexisNexis) 10 Veterinary Patient Microchip Number 11 Medicaid Recipient ID Number 99 Other (Trading partner agreed upon ID, such as cardholder ID.)	N	

AIR05	ID of Person Picking Up Rx (Situational) Identification number for the person picking up the prescription as indicated in AIR 04. An example would be the driver's license number. Note: This field can only be populated with code 10 when provided on the prescription.	AN	20
AIR06	Relationship of Person Picking Up Rx (Optional) Code indicating the relationship of the person picking up Rx to the patient, if required by the PDMP. Note: Code 01 is now Parent/Legal Guardian, not Patient. 01 Parent/Legal Guardian 02 Spouse 03 Caregiver 99 Other	N	2
AIR07	Last Name of Person Picking Up (Required) Person picking up last name. An apostrophe or period are acceptable characters to include.	AN	50
AIR08	First Name of Person Picking Up (Required) Person picking up first name. An apostrophe or period are acceptable characters to include.	AN	50
AIR09	Last Name or Initials of Pharmacist (Field Decommissioned and Moved to DSP Segment)	AN	50
AIR10	First Name of Pharmacist (Field Decommissioned and Moved to DSP Segment)	AN	50
AIR11	Dropping Off/Picking Up Identifier Qualifier (Situational) (Field Decommissioned: Picking Up and Dropping Off now being handled separately.)	N	2
AIR12	Date of Birth of Person Picking Rx (Optional) Date person was born. Format: CCYYMMDD.	DT	8
AIR13	Address Information - 1 of Person Picking Up Rx (Optional) Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
AIR14	Address Information - 2 of Person Picking Up Rx (Optional) Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
AIR15	Person Picking Up City Address (Optional) Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	35

AIR16	Person Picking Up State Address (Optional) Jurisdiction/state and possession abbreviation as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	2
AIR17	Person Picking Up ZIP Code Address (Optional) United States Postal Service ZIP Code or ZIP+4 as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses. Do not include white spaces or special characters. Include hyphens in ZIP+4.	AN	10
AIR18	Phone Number of Person Picking Up Rx (Optional)	N	10
AIR19	Picking Up Method of Delivery (Optional) 01 Person Picked Up 02 Mailed/Shipped Note: Same Field Descriptions in AIR03 to AIR18 Apply to AIR20 to AIR32, respectively.	N	2
AIR20	Jurisdiction Issuing ID of Person Dropping Off Rx (Situational) Code identifying the jurisdiction that issues the ID contained in AIR22. Used if required by the PDMP. See Appendix A for list of jurisdictions.	AN	2
AIR21	ID Qualifier of Person Dropping Off Rx (Situational) Code to identify the type of ID in AIR22. If AIR20 is used, AIR21 is required. 01 Military ID 02 State Issued ID 03 Unique System ID 04 Permanent Resident Card (Green Card) 05 Passport ID 06 Driver's License ID 07 Social Security Number 08 Tribal ID 09 Vendor Specific (such as Bamboo Health, Experian, LexisNexis) 10 Veterinary Patient Microchip Number 11 Medicaid Recipient ID Number 99 Other (Trading partner agreed upon ID, such as cardholder ID.)	N	2
AIR22	ID of Person Dropping off Rx (Situational) Identification number for the person dropping off the prescription as indicated in AIR 21. An example would be the driver's license number. Note: This field can only be populated with code 10 when provided on the prescription.	AN	20

AIR23	Relationship of Person Dropping Off Rx (Optional) Code indicating the relationship of the person dropping off Rx to the patient, if required by the PDMP. Note: Code 01 is now Parent/Legal Guardian, not Patient. 01 Parent/Legal Guardian 02 Spouse 03 Caregiver 04 Other	N	2
AIR24	Last Name of Person Dropping Off Rx (Optional) Last name of the person dropping off Rx, if required by the PDMP.	AN	50
AIR25	First Name of Person Dropping Off Rx (Optional) First name of the person dropping off Rx, if required by the PDMP.	AN	50
AIR26	Date of Birth of Person Dropping Off Rx (Optional) Date of birth of the person dropping off Rx the prescription as listed on a government-issued identification.	DT	8
AIR27	Address Information - 1 of Person Dropping Off Rx (Optional) Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses	AN	55
AIR28	Address Information - 2 of Person Dropping Off Rx (Optional) Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	55
AIR29	Person Dropping Off City Address (Optional) Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	35
AIR30	Person Dropping Off State Address (Optional) Jurisdiction/state and possession abbreviation as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	10
AIR31	Person Dropping Off ZIP Code Address (Optional) United States Postal Service ZIP Code or ZIP+4 as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses. Do not include white spaces or special characters. Include hyphens in ZIP+4.	AN	10
AIR32	Phone Number of Person Dropping Off Rx (Optional) Complete 10-digit phone number. Do not include hyphens or other special characters.	N	10

Summary Segments

TP	Pharmacy Trailer	Required
TT	Transaction Trailer	Required

Segment: TP Pharmacy Trailer

Level: Summary

Loop: Max 2000 (Looping not allowed for real time.)

Usage: Required

Purpose: To identify the end of data for the entity submitting data and provide the count of the total number of detail segments, including the pharmacy header (PHA) and the pharmacy trailer (TP) segments.

Example: TP*6~

TH*5.0*857463*01**20230205*1045*P*1234567890~~ IS*7564*ACME PHARMACY~
PHA*1234567890~ PAT*PA*06*987544****SMITH*JOHN****1234 MAIN ST**
SOMEWHERE*PA*19422**19500101*M*01*10~DSP*00*6542984*20230205*0*20230205*
0*01*57866707401*30*15*01*01*01~ PRE**ZZ1234563~ AIR*PA*787456493993~TP*6~

1 PHA

2 PAT

3 DSP

4 PRE

5 AIR

6 TP

Note: Above transaction shows the count that goes in the TP segment.

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TP01	Detail Segment Count (Required)	N	10
	Number of detail segments included for the pharmacy including the pharmacy header (PHA) including the pharmacy trailer (TP) segments.		

Segment: **TT Transaction Trailer**

Level: Summary

Usage: Required

Purpose: To indicate the end of the transaction and provide the count of the total number of segments included in the transaction.

Example: TT*857463*9~

TH*5.0*857463*01**20230205*235959Z*P*1234567890~~ IS*7564*ACME PHARMACY~
PHA*1234567890~PAT*PA*06*987544****SMITH*JOHN****1234 MAIN ST**
SOMEWHERE*PA*19422**19500101*M*01*10~DSP*00*6542984*20230205*0*20230205*
0*01*57866707401*30*15*01*01*01~PRE**ZZ1234563~AIR*PA*787456493993~TP*6~TT*8574
63*9~

- 1 TH
- 2 IS
- 3 PHA
- 4 PAT
- 5 DSP
- 6 PRE
- 7 AIR
- 8 TP
- 9 TT

Note: Above transaction shows the count that goes in the TT segment.

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TT01	Transaction Control Number (Required) Identifying control number that must be unique. Assigned by the originator of the transaction. Must match the number in TH02.	AN	40
TT02	Segment Count (Required) Total number of segments included in the transaction, including the header and trailer segments.	N	12

Acknowledgment/Response

The following pages in this section provide the sending system with an acknowledgment/response that the transmission was received and could be read for batch-file transmissions.

For real-time transmissions, a response will be given as to whether the transmission was accepted or rejected and possibly responding with a reject code for missing information.

Core Reporting Segments

Header

TH	Transaction Header	Required
IS	Information Source	Required
PHA	Pharmacy Header	Required
ACK	Acknowledgment/Response	Required

Summary

TP	Pharmacy Trailer	Required
TT	Transaction Trailer	Required

Segment: TH Transaction Header

Level: Header

Usage: Required

Purpose: To indicate the start of a transaction. It also assigns the segment terminator, data element separator, and control number.

Note: Data element TH02 is required since it shows the Segment Terminator that will be used for the entire transaction. The character used as the data element separator is defined by the value in the third byte of the transaction.

Example: TH*5.0*223345*02*857460*20230205*235959Z*P**~~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TH01	Version / Release Number (Required) Used to identify the transaction Version/Release. Format = x.x (5.0) ASAP Version 5 Release 0	AN	4
TH02	Transaction Control Number (Required) Sender assigned code uniquely identifying a transaction. Suggested that as an option a Globally Unique Identifier (GUID) be used to populate this field so the number will never repeat. Recommendation: Use a Globally Unique Identifier (GUID) or other nonrepeating alphanumeric combination to populate this field.	AN	40
TH03	Transaction Type (Situational) Identifies the purpose of initiating the transaction. 01 Send/Request Transaction 02 Acknowledgment (Used in Response only) 03 Error Receiving (Used in Response only)	N	2
TH04	Response ID (Situational) Contains the Transaction Control Number of a transaction that initiated the transaction. <u>Required in response transaction only.</u>	AN	40
TH05	Creation Date (Required) Date the file was created. Format: CCYYMMDD.	DT	8
TH06	Creation Time (Required) Time the transaction was created. Time expressed in 24-hour clock time (HHMMSS or HHMM). Time range: 000000 through 235959. The time zone should be reported in Coordinated Universal Time (UTC) as HHMMSSZ (e.g., 235959Z). Do not include colons or non-numeric characters other than Z for Zulu time.	TM	7
TH07	File Type (Required) Code specifying the type of transaction. P Production T Test	AN	1

TH08	Routing Number/BIN (Optional) This field can be used for real-time transmissions that go through an intermediary or network switch to indicate, if necessary, the specific state that the transactions should be routed to.	N	6
TH09	Segment Terminator Character (Required) This terminates the TH segment and sets the actual value of the data segment terminator for the entire transaction. Note: This document uses the “~” in all examples. See the “Data Element Separators and Segment Terminators” in the introduction for more information.	AN	1

Segment: IS Information Source

Level: Header

Usage: Required

Purpose: To convey the name and identification numbers of the entity supplying the response information.

Example: IS*333223*STATE PDMP REPOSITORY~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
IS01	Unique Information Source ID (Required) Reference number or identification number as defined by the business partners. (Example: Phone number. However, if a phone number is used to populate this field, do not include hyphens.)	N	10
IS02	Information Source Entity Name (Required) Entity name of the Information Source.	AN	60
IS03	Message (Optional) Freetext message. Use of this field is defined by the PDMP. Many PDMP's may designate this field to hold the submission period date range of the file transmitted. When used to indicate the date range, it must be the first data text in the field and must be inserted with using the following layout (where "#" and "-" are those literal characters): #CCYYMMDD#-#CCYYMMDD# For example, a pharmacy may be submitting records for the reporting period of February 5, 2023, through February 7, 2023, but only filled reportable prescriptions on February 5 and February 7. The full submission period date range would be reported in IS03 as #20230205#-#20230207# It is up to the PDMP to further define how to enter the submission date range for exceptional cases, such as for late submission records. Note: IS03 can also be used to show the date range for Zero Reports.	AN	60
IS04	Pharmacy Dispensing Software Vendor (Optional) Name of software vendor the pharmacy is using.	AN	60
IS05	Phone Number of Software Vendor (Optional)	N	10

Segment: **PHA Pharmacy Header**

Level: Header

Loop: Max 2,000 (Looping is not allowed for real time.)

Usage: Required

Purpose: To identify the pharmacy or the dispensing prescriber. It is required that information be provided in at least one of the following fields: PHA01, PHA02, or PH03.

(Note: Situation for use of PHA04 through PHA15 is if needed by the state PDMP to further identify the pharmacy.)

Example: PHA***ZZ1234563~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
PHA01	National Provider Identifier (NPI) (Optional) Identifier assigned to the pharmacy by CMS. Used if required by the PDMP.	AN	10
PHA02	NCPDP Provider ID (Optional) Identifier assigned to pharmacy by the National Council for Prescription Drug Programs. Used if required by the PDMP.	AN	7
PHA03	DEA Number (Optional) Identifier assigned to the pharmacy by the Drug Enforcement Administration. Used if required by the PDMP.	AN	9
PHA04	Pharmacy or Dispensing Prescriber Name (Optional) Fretext name of the pharmacy. Note: If a dispensing prescriber, the prescriber's name and professional degree should be entered, such as John Doe MD.	AN	60
PHA05	Address Information – 1 (Optional) Fretext for address information. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PHA06	Address Information – 2 (Optional) Fretext for additional address information. Recommendation: Information should be reported according to United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specifications for Patient Addresses.	AN	55
PHA07	City Address (Optional) Fretext for city name.	AN	35

PHA08	State Address (Optional) Two-letter jurisdiction/state and possession abbreviation as described in United States Postal Service Publication 28-Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses.	AN	2
PHA09	ZIP Code Address (Optional) United States Postal Service ZIP Code or ZIP+4 as described in United States Postal Service Publication 28 Postal Addressing Standards or the most recently published version of the ONC Project US@ Technical Specification for Patient Addresses. Do not include white spaces or special characters. Include hyphens in ZIP+4.	AN	10
PHA10	Phone Number (Optional) Complete phone number including area code. Exclude hyphens.	N	10
PHA11	Contact name (Optional) Freetext name of vendor contact.	AN	30
PHA12	Chain Site ID (Optional) Store number assigned by the chain to the pharmacy location. Used when PDMP needs to identify the specific pharmacy from which information is required.	AN	10
PHA13	Pharmacy's Permit Number/License Number (Optional) Used to help identify the sending pharmacy.	AN	20
PHA14	Pharmacy/Dispenser Type (Optional) 01 Independent Pharmacy 02 Chain Pharmacy 03 Long-term Care Pharmacy 04 Hospital Pharmacy 05 Opioid Treatment Program 06 Cannabis Dispensary 07 Veterinary/Vet Patient Only Dispenser 08 Dispensing Prescriber 09 Specialty Pharmacy 10 Federal 11 Tribal 99 Other	N	2
PHA15	Mail Order Pharmacy (Optional) 01 Yes 02 No	N	2

Segment: **ACK Acknowledgment/Response Segment**

Level: Header

Loop: Max 20 (To be used if more than one reject code is needed in ACK02 for real-time transactions.)

Usage: Required

Purpose: To relay acceptance or rejection of a transaction to the host.

Example: ACK*A~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
ACK01	Acknowledgment Type (Required) Code indicating an accepted or rejected condition. A Accepted R Rejected Note: In a batch-file transmission, rejection means the entire file was rejected. In a real-time rejection where ACK01 = R, it is required that a reason for the reject be given in ACK02.	AN	1
ACK02	Reason for Reject (Optional) A code that can be used by the PDMP indicating the reason for a reject for a real-time transaction. This field can also be used to indicate a processing error, a no response, system down or other problem from the receiving system. If one of these four transmission problem codes is used, the following message field ACK03 is required to fully explain the problem. See Appendix C for list of real-time transmission reject codes.	N	2
ACK03	Message Explaining Reject (Optional) Can be used if required by the PDMP to convey more specific information to the pharmacy regarding the reason for a reject.	AN	300

Segment: **TP Pharmacy Trailer**

Level: Summary

Usage: Required

Purpose: To identify the end of data for a given pharmacy and provide the count of the total number of detail segments reported for the pharmacy, including the PHA, ACK, and TP segments.

Example: TP*3~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TP01	Detail Segment Count (Required) Number of detail segments included for the pharmacy including the pharmacy header (PHA) including the pharmacy trailer (TP) segments.	N	10

Segment: **TT Transaction Trailer**

Level: Summary

Usage: Required

Purpose: To indicate the end of the transaction and provide the count of the total number of segments included in the transaction.

Example: TT*857463*6~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TT01	Transaction Control Number (Required) Identifying control number that must be unique. Assigned by the originator of the transaction. Must match the number in TH02.	AN	40
TT02	Segment Count (Required) Total number of segments included in the transaction including the TH and TT segments.	N	12

Example Transmission

(Not a Compound)

TH*5.0*857463*01**20230205*235959Z*P**~ IS*7564*ACME PHARMACY~PHA***ZZ1234563~
PAT*PA*06*987544****SMITH*JOHN****1234 MAIN
ST**SOMEWHERE*PA*19422**19500101*M~DSP*00*6542984*20230205*0*20230205*0*01*5786
6707401*30*15~PRE**ZZ1234563~AIR*PA*787456493993~TP*6~TT*857463*9~

TH*5.0*857463*01**20230205*235959Z*P**~

TH*	Segment ID	
5.0*	TH01	ASAP Version 5 Release 0
857463*	TH02	Transaction Control Number
01*	TH03	Transaction Type
*	TH04	Not Used
20230205*	TH05	Creation Date
235959Z*	TH06	Creation Time
P*	TH07	File Type
*	TH08	Not Used
~ ~	TH09	Segment Terminator

IS*7564*ACME PHARMACY~

IS*	Segment ID	
7564*	IS01	Unique Information Source ID
ACME PHARMACY~	IS02	Information Source Entity Name

PHA***ZZ1234563~

PHA*	Segment ID	
*	PHA01	Not Used
*	PHA02	Not Used
ZZ1234563~	PHA03	DEA Number

PAT*PA*06*987544****SMITH*JOHN****1234 MAIN ST**SOMEWHERE*PA*19422**19500101*M~

PAT*	Segment ID	
PA*	PAT01	ID Qualifier of Patient Identifier
06*	PAT02	ID Qualifier
987544*	PAT03	ID of Patient
*	PAT04	Not Used
*	PAT05	Not Used
*	PAT06	Not Used
SMITH*	PAT07	Last Name
JOHN*	PAT08	First Name
*	PAT09	Not Used
*	PAT10	Not Used
*	PAT11	Not Used
1234 MAIN ST*	PAT12	Address Information - 1
*	PAT13	Not Used
SOMEWHERE*	PAT14	City Address
PA*	PAT15	State Address
19422*	PAT16	ZIP Code Address
*	PAT17	Not Used
19500101*	PAT18	Date of Birth
M~	PAT19	Gender Code

DSP*00*6542984*20230205*0*20230205*0*01*57866707401*30*15~

DSP*	Segment ID	
00*	DSP01	Reporting Status
6542984*	DSP02	Prescription Number
20230205*	DSP03	Date Written
0*	DSP04	Refills Authorized
20230205*	DSP05	Date Filled
0*	DSP06	Fill Number
01*	DSP07	Product ID Qualifier
57866707401*	DSP08	Product ID
30*	DSP09	Quantity Dispensed
15~	DSP10	Days Supply

PRE**ZZ1234563~

PRE*	Segment ID	
*	PRE01	Not Used
ZZ1234563~	PRE02	DEA Number

AIR*PA*787456493993~

AIR*	Segment ID	
PA*	AIR01	Jurisdiction Issuing Rx Serial Number
787456493993~	AIR02	Jurisdiction Issued Rx Serial Number

TP*6~

TP*	Segment ID	
6~	TP01	Detail Segment Count

TT*857463*9~

TT*	Segment ID	
857463*	TT01	Transaction Control Number
9~	TT02	Segment Count

Example Acknowledgment

TH*5.0*223345*857463*02**20230205*235959Z*P**~~IS*333223*STATE PDMP
REPOSITORY~PHA*1234567890~ACK*A~TP*3~TT*8547463*6~

TH*5.0*223345*02*857463*20230205*235959Z*P**~~

5.0*	TH01	ASAP Version 5 Release 0
223345*	TH02	Transaction Control Number
02*	TH03	Transaction Type
857463*	TH04	Response ID
20230205*	TH05	Creation Date
235959Z*	TH06	Creation Time
P*	TH07	File Type
*	TH08	Not Used
~ ~	TH09	Segment Terminator

IS*333223*STATE PDMP REPOSITORY~

IS*	Segment ID	
333223*	IS01	Unique Information Source ID
STATE PDMP REPOSITORY~	IS02	Information Source Entity Name

PHA*1234567890~

PHA*	Segment ID	
1234567890~	PHA01	National Provider Identifier (NPI)

ACK*A~

ACK*	Segment ID	
A~		Accepted

TP*3~

TP*	Segment ID	
3~	TP01	Detail Segment Count

TT*8547463*6~

TT*	Segment ID	
8547463*	TT01	Transaction Control Number
6~	TT02	Segment Count

Example Transmission

(Compound showing two ingredients.)

TH*5.0*857463*01**20230205*235959Z*P**~~IS*7564*ACME PHARMACY~PHA*1234567890~
PAT*PA*06*987544****SMITH*JOHN****1234 MAIN ST**
SOMEWHERE*PA*19422**19500101*M~DSP*00*6542984*20230205*0*20230205*0*06*99999123
456*2.5*15~PRE**ZZ1234563~CDI*1*01*04532657401*2.5*03~CDI*2*01*05422658415*3.0*02~AI
R*PA*787456493993~ TP*8~TT*857463*11~

TH*5.0*857463*01**20230205*235959Z*P**~~

TH*	Segment ID	
5.0*	TH01	ASAP Version 5 Release 0
857463*	TH02	Transaction Control Number
01*	TH03	Transaction Type
*	TH04	Not Used
20230205*	TH05	Creation Date
235959Z*	TH06	Creation Time
P*	TH07	File Type
*	TH08	Not Used
~ ~	TH09	Segment Terminator

IS*7564*ACME PHARMACY~

IS*	Segment ID	
7564*	IS01	Unique Information Source ID
ACME PHARMACY~	IS02	Information Source Entity Name

PHA*1234567890~

PHA*	Segment ID	
1234567890~	PHA01	National Provider Identifier (NPI)

PAT*PA*06*987544****SMITH*JOHN****1234 MAIN ST**SOMEWHERE*PA*19422**19500101*M~

PAT*	Segment ID	
PA*	PAT01	ID Qualifier of Patient Identifier
06*	PAT02	ID Qualifier
987544*	PAT03	ID of Patient
*	PAT04	Not Used
*	PAT05	Not Used
*	PAT06	Not Used
SMITH*	PAT07	Last Name
JOHN*	PAT08	First Name
*	PAT09	Not Used
*	PAT10	Not Used
*	PAT11	Not Used
1234 MAIN ST*	PAT12	Address Information
*	PAT13	Not Used
SOMEWHERE*	PAT14	City Address
PA*	PAT15	State Address
19422*	PAT16	ZIP Code Address
*	PAT17	Not Used
19500101*	PAT18	Date of Birth
M~	PAT19	Gender Code

DSP*00*6542984*20230205*0*20230205*0*06*99999123456*2.5*15~

DSP*	Segment ID	
00*	DSP01	Reporting Status
6542984*	DSP02	Prescription Number
20230205*	DSP03	Date Written
0*	DSP04	Refills Authorized
20230205*	DSP05	Date Filled
0*	DSP06	Fill Number
06*	DSP07	Product ID Qualifier
99999123456*	DSP08	Product ID
2.5*	DSP09	Quantity Dispensed
15~	DSP10	Days Supply

PRE**ZZ1234563~

PRE*	Segment ID	
*	PRE01	Not Used
ZZ1234563~	PRE02	DEA Number

CDI*1*01*04532657401*2.5*03~

CDI*	Segment ID	
1*	CDI01	Compound Drug Ingredient Number
01*	CDI02	Product ID Qualifier
04532657401*	CDI03	Product ID
2.5*	CDI04	Compound Ingredient Quantity
03~	CDI05	Compound Drug Dosage Units Code

CDI*2*01*05422658415*3.0*02~

CDI*	Segment ID	
2*	CDI01	Compound Drug Ingredient Number
01*	CDI02	Product ID Qualifier
05422658415*	CDI03	Product ID
3.0*	CDI04	Compound Ingredient Quantity
02~	CDI05	Compound Drug Dosage Units Code

AIR*PA*787456493993~

AIR*	Segment ID	
PA*	AIR01	Jurisdiction Issuing Rx Serial Number
787456493993~	AIR02	Jurisdiction Issued Rx Serial Number

TP*8~

TP*	Segment ID	
8~	TP01	Detail Segment Count

TT*857463*11~

TT*	Segment ID	
857463*	TT01	Transaction Set Control Number
11~	TT02	Segment Count

Appendix A

List of Jurisdictions/States

Note: ASAP grants permission to PDMPs to include this list of jurisdictions and states in their reporting specifications and for pharmacy software providers to distribute this list to their pharmacy clients.

AB	PROVINCE OF ALBERTA	ME	MAINE
BC	BRITISH COLUMBIA	MI	MICHIGAN
MB	PROVINCE OF MANITOBA	MN	MINNESOTA
NB	NEW BRUNSWICK	MO	MISSOURI
NF	NEWFOUNDLAND	MS	MISSISSIPPI
NL	NEWFOUNDLAND AND LABRADOR	MT	MONTANA
NS	NOVA SCOTIA	NC	NORTH CAROLINA
NT	NORTHWEST TERRITORIES	ND	NORTH DAKOTA
ON	PROVINCE OF ONTARIO	NE	NEBRASKA
PE	PRINCE EDWARD ISLAND	NH	NEW HAMPSHIRE
QC	PROVINCE OF QUEBEC	NJ	NEW JERSEY
SK	PROVINCE OF SASKATCHEWAN	NM	NEW MEXICO
YT	YUKON TERRITORIES	NV	NEVADA
CN	CANADA	NY	NEW YORK
MX	MEXICO	OH	OHIO
US	UNITED STATES	OK	OKLAHOMA
AK	ALASKA	OR	OREGON
AL	ALABAMA	PA	PENNSYLVANIA
AR	ARKANSAS	RI	RHODE ISLAND
AZ	ARIZONA	SC	SOUTH CAROLINA
CA	CALIFORNIA	SD	SOUTH DAKOTA
CO	COLORADO	TN	TENNESSEE
CT	CONNECTICUT	TX	TEXAS
DC	DISTRICT OF COLUMBIA	UT	UTAH
DE	DELAWARE	VA	VIRGINIA
FL	FLORIDA	VT	VERMONT
GA	GEORGIA	WA	WASHINGTON
HI	HAWAII	WI	WISCONSIN
IA	IOWA	WV	WEST VIRGINIA
ID	IDAHO	WY	WYOMING
IL	ILLINOIS	AS	AMERICAN SAMOA
IN	INDIANA	FM	MICRONESIA
KS	KANSAS	GU	GUAM
KY	KENTUCKY	MP	MARIANAS ISLANDS
LA	LOUISIANA	PR	PUERTO RICO
MA	MASSACHUSETTS	PW	PALAU
MD	MARYLAND	UM	MINOR ISLANDS
		VI	VIRGIN ISLANDS
		99	OTHER

Appendix B

Reporting Quantity Dispensed (DSP09), Drug Dosage Units Code (DSP11), Total Quantity Remaining on Prescription (DSP29), Total Quantity Remaining Drug Dosage Units (DSP30), Component Ingredient Quantity (CDI04), and Compound Dosage Units Code (CDI05).

Note: When referencing DSP09 or DSP11 in the examples below, these also apply to DSP29/DSP30 and CDI04/CDI05, respectively.

In solid dosage forms (e.g., capsule, diaphragm, disc, patch, plaster, suppository, suture, tablet, troche, wafer), the metric quantity is assumed to be "each solid," regardless of package size. The pharmacist would use the DSP11 code "01" meaning EACH. However, other dosage forms may be confusing. Therefore, it is essential — for accurate and consistent data — to report the proper dosage unit codes in DSP11 and CDI05 and the appropriate metric quantities in DSP09 and CDI04.

For liquid dosage forms (e.g., aerosol liquid, elixir, emulsion, extract, injectable liquid, mouthwash, oil, shampoo, soap, solution, spray, suspension, syrup, tincture), the pharmacist would use the DSP11 code "02" meaning ML.

For dosage forms reported as GM (aerosol powder, cream, crystal, gel, jelly, granule, ointment, powder), the pharmacist would use the DSP11 code "03" meaning GM.

Examples of commercially available products:

1. Diazepam syringes: Dispensed 1 package of 10 syringes, each containing 2 ml of 5 mg/ml diazepam.
The metric quantity dispensed is 20 ml.
Report DSP09 as 20 and DSP11 as 02.
2. Acetaminophen with Codeine Elixir 120-12 mg/5 ml: Dispensed 4 oz.
The metric quantity dispensed is 120 ml.
Report DSP09 as 120 and DSP11 as 02.
3. Stadol Nasal Spray: Dispensed 1 package containing 2.5 ml.
The metric quantity dispensed is 2.5 ml.
Report DSP09 as 2.5 and DSP11 as 02.
4. Codeine 15 mg tablets: Dispensed 10 tablets.
The metric quantity is 10 each.
Report DSP09 as 10 and DSP11 as 01.
5. Fentanyl 25 MCG/HR patch: Dispensed 20 patches.
The metric quantity is 20 each.
Report DSP09 as 20 and DSP11 as 01.
6. Nicotine Gum: Dispensed 100 pieces.
The metric quantity is 100.
Report DSP09 as 100 and DSP11 as 01.
7. Actiq oral transmucosal lozenges: Dispensed six "lollipops."
The metric quantity is 6 each.
Report DSP09 as 6 and DSP11 as 01.

8. Dilaudid-HP lyophilized 250 mg. 25 ml of sterile water is added by the dispenser to reconstitute the product. If one ampoule is dispensed, the metric quantity is 25 ml.
Report DSP09 as 25 and DSP11 as 02.

Appendix C

Real-Time Transmission Reject Codes

The following codes can be used to indicate a processing error, a no response, bad or missing data, or other problem from the receiving system.

Segment/Field	Reject Code
IS	01 01 Unique Information Source ID
	02 02 Information Source Entity Name
	03 03 Message
	04 04 Pharmacy Dispensing Software Vendor
	05 05 Phone Number of Software Vendor
PHA	01 06 National Provider Identifier (NPI)
	02 07 NCPDP Provider ID
	03 08 DEA Number
	04 09 Pharmacy or Dispensing Prescriber Name
	05 10 Address Information – 1
	06 11 Address Information – 2
	07 12 City Address
	08 13 State Address
	09 14 ZIP Code Address
	10 15 Phone Number
	11 16 Contact name
	12 17 Chain Site ID
	13 18 Pharmacy's Permit Number/License Number
	14 19 Pharmacy/Dispenser Type
	15 20 Mail Order Pharmacy
PAT	01 21 ID Qualifier of Patient Identifier
	02 22 ID Qualifier
	03 23 ID of Patient
	04 24 ID Qualifier of Additional Patient Identifier
	05 25 Additional ID Qualifier
	06 26 Additional ID
	07 27 Last Name
	08 28 First Name
	09 29 Middle Name
	10 30 Name Prefix
	11 31 Name Suffix
	12 32 Address Information – 1
	13 33 Address Information – 2
	14 34 City Address
	15 35 State Address
	16 36 ZIP Code Address
	17 37 Phone Number
	18 38 Date of Birth
	19 39 Gender Code
	20 40 Species Code
	21 41 Patient Location Code
	22 42 Country of Non-U.S. Resident
	23 43 Name of Animal
	24 44 Patient Preferred or Alias Last Name

	25	45 Patient Preferred of Alias First Name
	26	46 Patient Race Category
	27	47 Patient Ethnicity
	28	48 Veterinary Species Code
	29	49 Animal Location Code
DSP	01	50 Reporting Status
	02	51 Prescription Number
	03	52 Date Written
	04	53 Refills Authorized
	05	54 Date Filled
	06	55 Fill Number
	07	56 Product ID Qualifier
	08	57 Product ID
	09	58 Quantity Dispensed
	10	59 Days Supply
	11	60 Drug Dosage Units Code
	12	61 Transmission Form of Rx Origin Code
	13	62 Partial Fill Indicator
	14	63 Pharmacist National Provider Identifier
	15	64 Pharmacist State License Number
	16	65 Classification Code for Payment Type
	17	66 Date Sold
	18	67 RxNorm Product Qualifier (Placeholder Field)
	19	68 RxNorm (Placeholder Field)
	20	69 Electronic Prescription Reference Number
	21	70 Electronic Prescription Order Number
	22	71 Quantity Prescribed
	23	72 Rx SIG
	24	73 Treatment Type
	25	74 Diagnosis Code
	26	75 Time Written
	27	76 Time Filled
	28	77 Time Sold
	29	78 Total Quantity Remaining on Prescription
	30	79 Total Quantity Remaining Drug Dosage Units Code
	31	80 Discount Card
	32	81 Classification Code for Additional Payment Type
	33	82 Discount Card for Additional Payment Type
	34	83 DEA Schedule/State Designation
	35	84 Last Name or Initials of Pharmacist Filling Rx
	36	85 First Name of Pharmacist Filling Rx
PRE	01	86 National Provider Identifier
	02	87 DEA Number
	03	88 DEA Number Suffix
	04	89 Prescriber Jurisdiction or State License Number
	05	90 Last Name
	06	91 First Name
	07	92 Middle Name
	08	93 Phone Number
	09	94 XDEA Number (Decommissioned)

	10	95 Jurisdiction or State Issuing Number
	11	96 Prescriber Address Information - 1
	12	97 Prescriber Address Information - 2
	13	98 Prescriber City Address
	14	99 Prescriber State Address
	15	100 ZIP Code Address
CDI	01	101 Compound Drug Ingredient Sequence Number
	02	102 Product ID Qualifier
	03	103 Product ID
	04	104 Compound Ingredient Quantity
	05	105 Compound Drug Dosage Units Code
	06	116 DEA Schedule/State Designation of Each Ingredient
AIR	01	107 Jurisdiction Issuing Rx Serial Number
	02	108 Jurisdiction Issued Rx Serial Number
	03	109 Jurisdiction Issuing ID of Person Picking Up
	04	110 ID Qualifier of Person Picking Up Rx
	05	111 ID of Person Picking Up Rx
	06	112 Relationship of Person Picking Up Rx
	07	113 Last Name of Person Picking Up Rx
	08	114 First Name of Person Picking Up Rx
	09	115 Last Name or Initials of Pharmacist (Decommissioned, Moved to DSP Segment)
	10	116 First Name of Pharmacist (Decommissioned, Moved to DSP Segment)
	11	117 Dropping Off/Picking Up Identifier Qualifier (Decommissioned)
	12	118 Date of Birth of Person Picking Up Rx
	13	119 Address Information -1 of Person Picking Up
	14	120 Address Information - 2 of Person Picking Up
	15	121 Person Picking Up City Address
	16	122 Person Picking Up State Address
	17	123 Person Picking Up ZIP Code Address
	18	124 Phone Number of Person Picking Up
	19	125 Picking Up Method of Delivery
	20	126 Jurisdiction Issuing ID of Person of Dropping Off Rx
	21	127 ID Qualifier of Person Dropping Off Rx
	22	128 ID of Person Dropping Off Rx
	23	129 Relationship of Person Dropping Off Rx
	24	130 Last Name of Person Dropping Off Rx
	25	131 First Name of Person Dropping Off Rx
	26	132 Date of Birth of Person Dropping Off Rx
	27	133 Address Information -1 of Person Dropping Off
	28	134 Address Information - 2 of Person Dropping Off
	29	135 Person Dropping Off City Address
	30	136 Person Dropping Off State Address
	31	137 Person Dropping Off ZIP Code Address
	32	138 Phone Number of Person Dropping Off

Transmission Problem Codes

Processing Error	139
No Response	140
System Down	141
Other	142 (Note: If 142 is used, a message should be included in ACK03.)

Appendix D

Examples of the Correct Use of Codes in DSP01

Error Correction

The ASAP 5.0 standard requires a dispenser to select a code in the DSP01 field. Dispensers may submit new records, revise and resubmit records, and void (delete) records. This is communicated by supplying one of the following values in the DSP01 field:

- 00 New Record – indicates a new record.
- 01 Revise – indicates that one or more data elements in a previously submitted record have been revised.
- 02 Void – indicates that the original record should be deleted.

The following examples show how to create, revise/resubmit, or void a record.

Submit a New Record

Perform the following steps to submit a new record:

1. Create a record with the value **00** in the **DSP01** field.
2. Populate all other required fields and submit the record.

Note: These steps are used to submit new records *or* to submit records that were previously submitted but received a fatal status on the dispenser's error report. **Records with fatal errors are not loaded into the PDMP system.** The errors in these records must be corrected in the dispenser's system and resubmitted using the 00 status in the DSP01 field.

Revise a Record

Perform the following steps to revise a record:

1. Create a record with the value **01** in the **DSP01** field.
2. Populate the following fields with the same information originally submitted in the record that is being revised:

PHA01(National Provider Identifier (NPI)

And/or

PHA02 (NCPDP Provider ID)

And/or

PHA03 (DEA Number)

DSP02 (Prescription Number)

DSP05 (Date Filled)

3. Fill in all other data fields with the correct information. This information will override the original data linked to the fields referenced in step 2.

4. Submit the record.

Important note: If any of the fields referenced in Step 2 are part of the correction, the record should first be voided and then resubmitted using the value 00 in the DSP01 field.

Void a Record

Perform the following steps to void (delete) a record:

1. Send a record with the value 02 in the DSP01 field.
2. Fill in all other data identical to the original record. This will void the original record.
3. An option to sending all the identical data in the prescription is to send a limited data set. The reason for a limited data set to void a prescription is to simplify the process in the pharmacy. This data set would be an option that a PDMP could require, rather than the identical data of the entire original prescription. The entire limited data set would be sent and if a PDMP does not require a data element, it would be ignored by the PDMP.

Limited Data Set to Void a Prescription:

PHA01 (National Provider Identifier (NPI)

And/or

PHA02 (NCPDP Provider ID)

And/or

PHA03 (DEA Number)

DSP02 (Prescription Number)

DSP03 (Date Written)

DSP05 (Date Filled)

DSP06 (Fill Number)

DSP13 (Partial Fill Indicator)

Implementation Guide ASAP Standard for Prescription Drug Monitoring Programs Error Report

February 2023

American Society for Automation in Pharmacy

490 Norristown Road, Suite 251, Blue Bell, PA 19422

610/825-7783 (phone) 610/825-7641 (fax) www.asapnet.org

© Copyright 2019 American Society for Automation in Pharmacy. All rights reserved.

Introduction

The purpose of the ASAP Error Report standard is to provide a common data structure for each Prescription Drug Monitoring Program (PDMP) to communicate specific errors identified within each batch-file data submission. There is also a need to standardize the summary response message returned by each PDMP to communicate and confirm the number of records that were accepted from each batch submission.

The ASAP Error Report contains a data structure and a minimum data set to identify the prescription records and the specific data elements within that need to be corrected. Care was taken to ensure that the minimum data set addressed the “success criteria” used by PDMPs to flag prescription records that do not meet the criteria and must be corrected. Simplifying this process should improve compliance in correcting and resending the information.

The ASAP Error Report standard serves mainly as a communication tool and excludes areas that do not directly affect the identification of prescriptions that fail to meet the success criteria of a PDMP. Examples of these exclusions are:

- The quality and accuracy of data submitted by providers.
- Syntax errors which may have caused data submission failures.
- The PDMP’s timeliness in providing error reports.
- The timeliness of pharmacies correcting errors identified in the error reports.

The ASAP Error Report standard can be used with all versions of the ASAP standard.

The data structure consists of three record types:

- **Header**

Used to link the detail records to the original report submission. The format and content should match the TH segment as defined in the ASAP reporting standard. The transaction control number in TH02 identifies the batch of records where specific prescriptions must be corrected and resubmitted.

- **Summary**

The summary record is used to provide quantitative results from the PDMP's validation process. The results can be used to determine the number of prescriptions that must be resubmitted to the PDMP. The summary report can be returned as either a separate CSV file or embedded within an email message back to the pharmacy.

Some PDMPs escalate warnings that result in rejecting the entire batch of reported prescriptions.

Summary Record

Field Name	Description
Records Received	Total number of prescription records (DSP Dispensing record) reported to the PDMP. Does not include non-DSP record types.
Records Accepted	The number of DSP records that do not need to be resubmitted. Therefore, the equation of Records Received - Records Accepted = Records to be Resubmitted.
Total Errors	Total number of DSP records that did not meet the initial success criteria.
Total Warnings	Total number of DSP records that partially meet the PDMP's success criteria. The prescription will be added to the PDMP database unless the number of warnings exceeds a PDMP's threshold, whereby the entire batch of reported prescriptions is rejected and not added to the PDMP database.
Total Duplicates	Total number of DSP records that match a previously processed DSP record. Duplicates are not added to the PDMP database since they were previously reported. It is up to the submitting entity to review these records to determine the specific causes or whether they need to be modified and resubmitted.

Detail

- The minimum data set used to provide qualitative results from the PDMP's validation process. This must be returned as a CSV file.

Detailed Record Definition

Field Name	Description
Pharmacy ID Qualifier	PHA01 – NPI PHA02 – NCPDP PHA03 – DEA as noted in the ASAP standard
Pharmacy ID	10-character identifier value related to the pharmacy ID qualifier.
Prescription Number	As described by data element DSP02 in the ASAP standard.
Date Filled	As described by data element DSP05 in the ASAP standard.
Field Code	As described in the ASAP standard. Refer to Data Elements.
Field Description	Description of the field code. Refer to Data Elements section. Optional.
Processing Status	E – Error, rejected by PDMP W – Warning, accepted by PDMP (subject to threshold) D – Duplicate
Value Provided	Value of field, indicated by the Field Code, submitted by pharmacy provider that did not meet the success criteria of the PDMP.
Comment	Additional information specific to PDMP. Optional.

Segment: TH Transaction Header

Level: Header

Usage: Required

Purpose: To indicate the start of a transaction. It also assigns the segment terminator, data element separator, and control number.

Note: Data element TH02 is required since it shows the Segment Terminator that will be used for the entire transaction. The character used as the data element separator is defined by the value in the third character (byte 3) of the transaction.

Example: TH*5.0*223345*02*857460*20230205*235959Z*P**~~

Data Element Summary

REF	DATA ELEMENT NAME	ATTRIBUTES	
TH01	Version / Release Number (Required) Used to identify the transaction Version/Release. Format = x.x (5.0) ASAP Version 5 Release 0	AN	4
TH02	Transaction Control Number (Required) Sender assigned code uniquely identifying a transaction. Suggested that as an option a Globally Unique Identifier (GUID) be used to populate this field so the number will never repeat. Recommendation: Use a Globally Unique Identifier (GUID) or other nonrepeating alphanumeric combination to populate this field.	AN	40
TH03	Transaction Type (Situational) Identifies the purpose of initiating the transaction. 01 Send/Request Transaction 02 Acknowledgment (Used in Response only.) 03 Error Receiving (Used in Response only.)	N	2
TH04	Response ID (Situational) Contains the Transaction Control Number of a transaction that initiated the transaction. <u>Required in response transaction only.</u>	AN	40
TH05	Creation Date (Required) Date the file was created. Format: CCYYMMDD.	DT	8
TH06	Creation Time (Required) Time expressed in 24-hour clock time HMMSS or HHMM). Time range: 000000 through 235959. The time zone should be reported in Coordinated Universal Time (UTC) as HHMMSSZ (e.g., 235959Z). Do not include colons or non-numeric characters other than Z for Zulu time.	TM	7
TH07	File Type (Required) Code specifying the type of transaction. P Production T Test	AN	1

TH08	Routing Number/BIN (Optional) This field can be used for real-time transmissions that go through an intermediary or network switch to indicate, if necessary, the specific state that the transactions should be routed to.	N	6
TH09	Segment Terminator Character (Required) This terminates the TH segment and sets the actual value of the data segment terminator for the entire transaction. Note: This document uses the “~” in all examples. See the “Data Element Separators and Segment Terminators” in the introduction for more information.	AN	1

Communication Protocol

The communication protocol used to move the information to the submitter is something that is decided between the PDMP and the submitting provider. Therefore, it is not a component of the error report and does not influence the data in the error report.

Whether the transaction header information and summary report are embedded in an email message and the details sent as a separate file is a trading partner issue as well.

Cross-Field Check

The issue of a cross-field check when the date dispensed is earlier than the date written (DSP03 versus DSP05) is addressed by:

- Identifying this as a single error for DSP05 and including more information in the comment field or
- Listing the same prescription twice with each error field shown separately, along with the corresponding description field filled in, and the comment field used for clarity.

Duplicate Records

The only variable with duplicates is the quantity dispensed. All the other information for the prescription stays the same.

Therefore, as designed, the minimum data set addresses the duplicate issue by simply tagging a specific prescription as a duplicate.

Multiple Files

For multiple files submitted by the same pharmacy on the same day:

- The Transaction Control Number field is used to identify a unique file.
- If, for example, three files are transmitted on the same day from the same pharmacy, each file will have a different Transaction Control Number in order to correctly identify the file with records in question. That is the purpose of this field in the ASAP PDMP standard.

CSV Files

The ASAP Error Report Standard uses CSV (comma-separated files) files rather than an Excel file, since CSV files can be opened within a range of programs.

CSV files are comma delimited files and can be opened in Excel or viewed as a text file. It was agreed that the comma should be the delimiter.

Use 254 characters or fewer in any field because the display width of Excel is limited to 254 characters even though Excel cells can word-wrap to display 1,024 characters and can physically store 32,767 characters.

For an alphanumeric field with embedded commas or for an alphanumeric field that consists entirely of numerals (for example a ZIP code where a leading zero must not be dropped), enclose the field in double quotes.

Version Compatibility

The examples on the following pages are for Version 5.0. However, the error report can be used with all versions of the ASAP standard.

With the 1995 standard, which does not use data segments, the minimum data necessary to identify the prescription records that fail to meet the success criteria and the reason can still be used. The Field Code in the 1995 standard would be the Field Position. For example, Rx Number would be reported as 066072, which corresponds to field position 066-072 in the 1995 standard.

Real-Time Error Reporting

The Acknowledgment and Response Section of the ASAP Standard V4.0, V4.1, V4.2, V4.2A, 4.2B, and 5.0 describes the way error reporting is handled with real-time transmissions.

Examples

Summary Report Only as Email Message

(used if not returned as a CSV file)

In this scenario the TH Transaction Header segment information TH01 through TH09, as shown below in the second example, is part of the Summary Report transmitted as an email to the pharmacy.

5.0,88888888111,,20230205,235959Z,P,,

Records Received: 100

Records Accepted: 96

Total Errors: 03

Total Warnings: 01

Total Duplicates: 01

Summary Report with Header Information Included within CSV File (Optional)

Version Number (TH01)

Transaction Control Number (TH02)

Transaction Type (TH03)

Response ID (TH04)

Creation Date (TH05)

Creation Time (TH06)

File Type (TH07)

Routing Number/BIN (TH08)

Segment Terminator (TH09)

Records Received

Records Accepted

Total Errors

Total Warnings

Total Duplicates

Example: 5.0,88888888111,,20230205,235959Z,P,,~,100,96,3,1,1

Detail Report (CSV File) with Minimum Data Set for the Transaction Control Number Shown in the Summary Header

Pharmacy ID Qualifier
Pharmacy ID
Pharmacy Name
Prescription Number
Date Filled
Field Code
Field Description
Processing Status
Value Provided
Comment

NPI,'9988776655',National Chain# 3937,'1122345','20230205', PAT16,PATIENT
ZIP,Error,,Missing

NCPDP,3344455,National Chain# 2607,'2233456','20230205', PAT19,PATIENT
GENDER,Error,,Missing

DEA,AW5555555,National Chain# 1987,'3344567','20230205',PRE03,
PRESCRIBERS DEA NUMBER,Error,BG1111119,Invalid

DEA,AW5555555,National Chain# 1987,'3344567','20230205',DSP08,
NDC,Warning,'51552002906',Invalid

DEA,AW5555555,National Chain# 1987,'3344605','20230205',,, Duplicate,,Row
was a duplicate

Implementation Guide ASAP Standard for Prescription Drug Monitoring Programs Zero Report

February 2023

American Society for Automation in Pharmacy

490 Norristown Road, Suite 251, Blue Bell, PA 19422

610/825-7783 (phone) 610/825-7641 (fax) www.asapnet.org

© Copyright 2023 American Society for Automation in Pharmacy. All rights reserved.

Introduction

The Zero Report standard is a complete transaction that includes the Header Segments and the information that would normally be sent with a batch file and the Trailer Segments, also filled out as they would for reporting the dispensing of prescriptions.

However, for the detail segments, while all the segments and data elements within that are required by a state would be sent, only the Patient First Name, Last Name, and Date Filled fields would be populated. The values populating these fields would be First Name = Zero, Last Name = Report, and Date Filled = Date that the report is being sent. Note: IS03 can now be used to report the date range for Zero Reports using the following format: #CCYYMMDD#-#CCYYMMDD#, if required by the PDMP. All other fields in the detail segments would be left blank.

The reason for sending an entire transaction is when a state has a two-pass process when files are received. The first pass is to determine if all the required segments and data elements within are in the transaction. The second pass would look at the content of the required reporting fields. In such a case it would be the second pass where the receiving system would pick up the fact that this is a Zero Report.

The usefulness of a Zero Report is to let a state know that no controlled substances were dispensed during the required reporting period. Having a standard in place simplifies the process for system vendors having installations in more than one state and for chains with their own systems and have pharmacies in multiple states.

The Zero Report would be sent when you normally send a batch file for the reporting period.

Zero Report Transaction

Example shown here assumes that all segments are required by the prescription monitoring program. Other versions of the standard would follow this pattern.

TH Transaction Header Segment

TH	*
TH01	5.0*
TH02	857463*
TH03	01*
TH04	*
TH05	20230205*
TH06	235959Z*
TH07	P*
TH08	*
TH09	~~

IS Information Source Segment

IS	*
IS01	7564*
IS02	Acme Pharmacy*
IS03	#20230205#-#220230228#~

PHA Pharmacy Header Segment

PHA	*
PHA01	1234567890~

PAT Patient Header Segment

PAT	*
PAT01	*
PAT02	*
PAT03	*
PAT04	*
PAT05	*
PAT06	*
PAT07	Report*
PAT08	Zero*
PAT09	*
PAT10	*
PAT11	*
PAT12	*
PAT13	*

PAT14	*
PAT15	*
PAT16	*
PAT17	*
PAT18	*
PAT19	*
PAT20	*
PAT21	*
PAT22	*
PAT23	~

DSP Dispensing Record Segment

DSP	*
DSP01	*
DSP02	*
DSP03	*
DSP04	*
DSP05	20230205*
DSP06	*
DSP07	*
DSP08	*
DSP09	*
DSP10	*
DSP11	*
DSP12	*
DSP13	*
DSP14	*
DSP15	*
DSP16	*
DSP17	*
DSP18	*
DSP19	*
DSP20	*
DSP21	*
DSP22	*
DSP23	*
DSP24	*
DSP25	~

PRE Prescriber Segment

PRE	*
PRE01	*
PRE02	~

CDI Compound Drug Ingredient Detail Segment

CDI	*
CDI01	*
CDI02	*
CDI03	*
CDI04	~

AIR Additional Information Reporting Segment

AIR01	*
AIR02	~

TP Pharmacy Trailer Segment

TP	*
TP01	7~

TT Transaction Trailer Segment

TT	*
TT01	857463*
TT02	10~