

Python for Data Analysis

PREV

4. NumPy Basics: Arrays and Vectorized Computation

NEXT

6. Data Loading, Storage, and File Formats

Chapter 5. Getting Started with pandas

pandas will be the primary library of interest throughout much of the rest of the book. It contains high-level data structures and manipulation tools designed to make data analysis fast and easy in Python. pandas is built on top of NumPy and makes it easy to use in NumPy-centric applications.

As a bit of background, I started building pandas in early 2008 during my tenure at AQR, a quantitative investment management firm. At the time, I had a distinct set of requirements that were not well-addressed by any single tool at my disposal:

- Data structures with labeled axes supporting automatic or explicit data alignment. This prevents common errors resulting from misaligned data and working with differently-indexed data coming from different sources.
- Integrated time series functionality.
- The same data structures handle both time series data and non-time series data.
- Arithmetic operations and reductions (like summing across an axis) would pass on the metadata (axis labels).
- Flexible handling of missing data.
- Merge and other relational operations found in popular database databases (SQL-based, for example).

I wanted to be able to do all of these things in one place, preferably in a language well-suited to general purpose software development. Python was a good candidate language for this, but at that time there was not an integrated set of data structures and tools providing this functionality.

Over the last four years, pandas has matured into a quite large library capable of solving a much broader set of data handling problems than I ever anticipated, but it has expanded in its scope without compromising the simplicity and ease-of-use that I desired from the very beginning. I hope that after reading this book, you will find it to be just as much of an indispensable tool as I do.

Throughout the rest of the book, I use the following import conventions for pandas:

```
In [1]: from pandas import Series, DataFrame
In [2]: import pandas as pd
```

Thus, whenever you see `pd` in code, it's referring to `pandas`. `Series` and `DataFrame` are used so much that I find it easier to import them into the local namespace.

Introduction to pandas Data Structures

To get started with pandas, you will need to get comfortable with its two workhorse data structures: *Series* and *DataFrame*. While they are not a universal solution for every problem, they provide a solid, easy-to-use basis for most applications.

Series

A *Series* is a one-dimensional array-like object containing an array of data (of any NumPy data type) and an associated array of data labels, called its *index*. The simplest *Series* is formed from only an array of data:

```
In [4]: obj = Series([4, 7, -5, 3])

In [5]: obj
Out[5]:
0    4
1    7
2   -5
3    3
```

The string representation of a *Series* displayed interactively shows the index on the left and the values on the right. Since we did not specify an index for the data, a default one consisting of the integers 0 through *N* - 1 (where *N* is the length of the data) is created. You can get the array representation and index object of the *Series* via its `values` and `index` attributes, respectively:

```
In [6]: obj.values
```

```
Out[6]: array([ 4,  7, -5,  3])

In [7]: obj.index
Out[7]: Int64Index([0, 1, 2, 3])
```

Often it will be desirable to create a Series with an index identifying each data point:

```
In [8]: obj2 = Series([4, 7, -5, 3], index=['d', 'b', 'a', 'c'])

In [9]: obj2
Out[9]:
d    4
b    7
a   -5
c    3

In [10]: obj2.index
Out[10]: Index([d, b, a, c], dtype=object)
```

Compared with a regular NumPy array, you can use values in the index when selecting single values or a set of values:

```
In [11]: obj2['a']
Out[11]: -5

In [12]: obj2['d'] = 6

In [13]: obj2[['c', 'a', 'd']]
Out[13]:
c    3
a   -5
d    6
```

NumPy array operations, such as filtering with a boolean array, scalar multiplication, or applying math functions, will preserve the index-value link:

```
In [14]: obj2
Out[14]:
d    6
b    7
a   -5
c    3

In [15]: obj2[obj2 > 0]
Out[15]:
d    6
b    7
c    3

In [16]: obj2 * 2
Out[16]:
d    12
b    14
a   -10
c     6

In [17]: np.exp(obj2)
Out[17]:
d    403.42
b   1096.63
a     0.00
c    20.08
```

Another way to think about a Series is as a fixed-length, ordered dict, as it is a mapping of index values to data values. It can be substituted into many functions that expect a dict:

```
In [18]: 'b' in obj2
Out[18]: True

In [19]: 'e' in obj2
Out[19]: False
```

Should you have data contained in a Python dict, you can create a Series from it by passing the dict:

```
In [20]: sdata = {'Ohio': 35000, 'Texas': 71000, 'Oregon': 16000}

In [21]: obj3 = Series(sdata)

In [22]: obj3
Out[22]:
Ohio    35000
Oregon   16000
Texas    71000
Utah      5000
```

When only passing a dict, the index in the resulting Series will have the dict's keys in sorted order.

```
In [23]: states = ['California', 'Ohio', 'Oregon', 'Texas']

In [24]: obj4 = Series(sdata, index=states)

In [25]: obj4
Out[25]:
California    NaN
Ohio          35000
Oregon         16000
Texas          71000
```

In this case, 3 values found in `sdata` were placed in the appropriate locations, but since no value for 'California' was found, it appears as NaN (not a number) which is considered in pandas to mark missing or NA values. I will use the terms "missing" or "NA" to refer to missing data. The `isnull` and `notnull` functions in pandas should be used to detect missing data:

```
In [26]: pd.isnull(obj4)
Out[26]:
California    True
Ohio          False
Oregon        False

In [27]: pd.notnull(obj4)
Out[27]:
California    False
Ohio          True
Oregon         True
```

Texas	False	Texas	True
-------	-------	-------	------

Series also has these as instance methods:

```
In [28]: obj4.isnull()
Out[28]:
California    True
Ohio          False
Oregon        False
Texas         False
```

I discuss working with missing data in more detail later in this chapter.

A critical Series feature for many applications is that it automatically aligns differently-indexed data in arithmetic operations:

```
In [29]: obj3          In [30]: obj4
Out[29]:          Out[30]:
Ohio    35000      California    NaN
Oregon   16000      Ohio          35000
Texas    71000      Oregon        16000
Utah      5000      Texas          71000

In [31]: obj3 + obj4
Out[31]:
California    NaN
Ohio          70000
Oregon        32000
Texas        142000
Utah           NaN
```

Data alignment features are addressed as a separate topic.

Both the Series object itself and its index have a `name` attribute, which integrates with other key areas of pandas functionality:

```
In [32]: obj4.name = 'population'

In [33]: obj4.index.name = 'state'

In [34]: obj4
Out[34]:
state
California    NaN
Ohio          35000
Oregon        16000
Texas         71000
Name: population
```

A Series's index can be altered in place by assignment:

```
In [35]: obj.index = ['Bob', 'Steve', 'Jeff', 'Ryan']

In [36]: obj
Out[36]:
Bob      4
Steve    7
Jeff     -5
Ryan     3
```

DataFrame

A `DataFrame` represents a tabular, spreadsheet-like data structure containing an ordered collection of columns, each of which can be a different value type (numeric, string, boolean, etc.). The `DataFrame` has both a row and column index; it can be thought of as a dict of Series (one for all sharing the same index). Compared with other such `DataFrame`-like structures you may have used before (like R's `data.frame`), row-oriented and column-oriented operations in `DataFrame` are treated roughly symmetrically. Under the hood, the data is stored as one or more two-dimensional blocks rather than a list, dict, or some other collection of one-dimensional arrays. The exact details of `DataFrame`'s internals are far outside the scope of this book.

NOTE

While `DataFrame` stores the data internally in a two-dimensional format, you can easily represent much higher-dimensional data in a tabular format using hierarchical indexing, a subject of a later section and a key ingredient in many of the more advanced data-handling features in `pandas`.

There are numerous ways to construct a `DataFrame`, though one of the most common is from a dict of equal-length lists or NumPy arrays

```
data = {'state': ['Ohio', 'Ohio', 'Ohio', 'Nevada', 'Nevada'],
        'year': [2000, 2001, 2002, 2001, 2002],
        'pop': [1.5, 1.7, 3.6, 2.4, 2.9]}
frame = DataFrame(data)
```

The resulting `DataFrame` will have its index assigned automatically as with `Series`, and the columns are placed in sorted order:

```
In [38]: frame
Out[38]:
   pop  state  year
0  1.5   Ohio  2000
1  1.7   Ohio  2001
2  3.6   Ohio  2002
```

```
3  2.4  Nevada  2001
4  2.9  Nevada  2002
```

If you specify a sequence of columns, the DataFrame's columns will be exactly what you pass:

```
In [39]: DataFrame(data, columns=['year', 'state', 'pop'])
Out[39]:
   year  state  pop
0  2000   Ohio  1.5
1  2001   Ohio  1.7
2  2002   Ohio  3.6
3  2001  Nevada  2.4
4  2002  Nevada  2.9
```

As with Series, if you pass a column that isn't contained in data, it will appear with NA values in the result:

```
In [40]: frame2 = DataFrame(data, columns=['year', 'state', 'pop',
....:                                     index=['one', 'two', 'three', 'four']

In [41]: frame2
Out[41]:
   year  state  pop  debt
one  2000   Ohio  1.5  NaN
two  2001   Ohio  1.7  NaN
three 2002   Ohio  3.6  NaN
four  2001  Nevada  2.4  NaN
five  2002  Nevada  2.9  NaN

In [42]: frame2.columns
Out[42]: Index([year, state, pop, debt], dtype=object)
```

A column in a DataFrame can be retrieved as a Series either by dict-like notation or by attribute:

```
In [43]: frame2['state']
Out[43]:
one      Ohio
two      Ohio
three     Ohio
four     Nevada
five     Nevada
Name: state

In [44]: frame2.year
Out[44]:
one      2000
two      2001
three     2002
four      2001
five      2002
Name: year
```

Note that the returned Series have the same index as the DataFrame, and their name attribute has been appropriately set.

Rows can also be retrieved by position or name by a couple of methods, such as the ix indexing field (much more on this later):

```
In [45]: frame2.ix['three']
Out[45]:
year      2002
state     Ohio
pop        3.6
debt       NaN
Name: three
```

Columns can be modified by assignment. For example, the empty 'debt' column could be assigned a scalar value or an array of values:

```
In [46]: frame2['debt'] = 16.5

In [47]: frame2
Out[47]:
   year  state  pop  debt
one  2000   Ohio  1.5  16.5
two  2001   Ohio  1.7  16.5
three 2002   Ohio  3.6  16.5
four  2001  Nevada  2.4  16.5
five  2002  Nevada  2.9  16.5

In [48]: frame2['debt'] = np.arange(5.)

In [49]: frame2
Out[49]:
   year  state  pop  debt
one  2000   Ohio  1.5    0
two  2001   Ohio  1.7    1
three 2002   Ohio  3.6    2
four  2001  Nevada  2.4    3
five  2002  Nevada  2.9    4
```

When assigning lists or arrays to a column, the value's length must match the length of the DataFrame. If you assign a Series, it will be instead conformed exactly to the DataFrame's index, inserting missing values in any holes:

```
In [50]: val = Series([-1.2, -1.5, -1.7], index=['two', 'four',
In [51]: frame2['debt'] = val

In [52]: frame2
Out[52]:
   year  state  pop  debt
one  2000   Ohio  1.5  NaN
two  2001   Ohio  1.7 -1.2
three 2002   Ohio  3.6  NaN
four  2001  Nevada  2.4 -1.5
five  2002  Nevada  2.9 -1.7
```

Assigning a column that doesn't exist will create a new column. The `del` keyword will delete columns as with a dict:

```
In [53]: frame2['eastern'] = frame2.state == 'Ohio'

In [54]: frame2
Out[54]:
   year  state  pop  debt eastern
one   2000   Ohio  1.5   NaN    True
two   2001   Ohio  1.7  -1.2    True
three 2002   Ohio  3.6   NaN    True
four   2001  Nevada  2.4  -1.5   False
five   2002  Nevada  2.9  -1.7   False

In [55]: del frame2['eastern']

In [56]: frame2.columns
Out[56]: Index([year, state, pop, debt], dtype=object)
```

CAUTION

The column returned when indexing a DataFrame is a view on the underlying data, not a copy. Thus, any in-place modifications to the Series will be reflected in the DataFrame. The column can be explicitly copied using the Series's `copy` method.

Another common form of data is a nested dict of dicts format:

```
In [57]: pop = {'Nevada': {2001: 2.4, 2002: 2.9},
.....:         'Ohio': {2000: 1.5, 2001: 1.7, 2002: 3.6}}
```

If passed to `DataFrame`, it will interpret the outer dict keys as the columns and the inner keys as the row indices:

```
In [58]: frame3 = DataFrame(pop)

In [59]: frame3
Out[59]:
   Nevada  Ohio
2000    NaN   1.5
2001     2.4   1.7
2002     2.9   3.6
```

Of course you can always transpose the result:

```
In [60]: frame3.T
Out[60]:
   2000  2001  2002
Nevada  NaN   2.4   2.9
Ohio     1.5   1.7   3.6
```

The keys in the inner dicts are unioned and sorted to form the index in the result. This isn't true if an explicit index is specified:

```
In [61]: DataFrame(pop, index=[2001, 2002, 2003])
Out[61]:
   Nevada  Ohio
2001     2.4   1.7
2002     2.9   3.6
2003    NaN   NaN
```

Dicts of Series are treated much in the same way:

```
In [62]: pdata = {'Ohio': frame3['Ohio'][:1],
.....:           'Nevada': frame3['Nevada'][:2]}

In [63]: DataFrame(pdata)
Out[63]:
   Nevada  Ohio
2000    NaN   1.5
2001     2.4   1.7
```

For a complete list of things you can pass the `DataFrame` constructor, see [Table 5-1](#).

If a `DataFrame`'s `index` and `columns` have their `name` attributes set, these will also be displayed:

```
In [64]: frame3.index.name = 'year'; frame3.columns.name = 'stat'

In [65]: frame3
Out[65]:
stat  Nevada  Ohio
year
2000    NaN   1.5
2001     2.4   1.7
2002     2.9   3.6
```

Like `Series`, the `values` attribute returns the data contained in the `DataFrame` as a 2D ndarray:

```
In [66]: frame3.values
Out[66]:
array([[ nan,  1.5],
       [ 2.4,  1.7],
       [ 2.9,  3.6]])
```

If the DataFrame's columns are different dtypes, the dtype of the values array will be chosen to accomodate all of the columns:

```
In [67]: frame2.values
Out[67]:
array([[2000, Ohio, 1.5, nan],
       [2001, Ohio, 1.7, -1.2],
       [2002, Ohio, 3.6, nan],
       [2001, Nevada, 2.4, -1.5],
       [2002, Nevada, 2.9, -1.7]], dtype=object)
```

Table 5-1. Possible data inputs to DataFrame constructor

Type	Notes
2D ndarray	A matrix of data, passing optional row and column labels
dict of arrays, lists, or tuples	Each sequence becomes a column in the DataFrame. All sequences must be the same length.
NumPy structured/record array	Treated as the "dict of arrays" case
dict of Series	Each value becomes a column. Indexes from each Series are unioned together to form the result's row index if no explicit index is passed.
dict of dicts	Each inner dict becomes a column. Keys are unioned to form the row index as in the "dict of Series" case.
list of dicts or Series	Each item becomes a row in the DataFrame. Union of dict keys or Series indexes become the DataFrame's column labels
List of lists or tuples	Treated as the "2D ndarray" case
Another DataFrame	The DataFrame's indexes are used unless different ones are passed
NumPy MaskedArray	Like the "2D ndarray" case except masked values become NA/missing in the DataFrame result

Index Objects

pandas's Index objects are responsible for holding the axis labels and other metadata (like the axis name or names). Any array or other sequence of labels used when constructing a Series or DataFrame is internally converted to an Index:

```
In [68]: obj = Series(range(3), index=['a', 'b', 'c'])

In [69]: index = obj.index

In [70]: index
Out[70]: Index([a, b, c], dtype=object)

In [71]: index[1:]
Out[71]: Index([b, c], dtype=object)
```

Index objects are immutable and thus can't be modified by the user.

```
In [72]: index[1] = 'd'
-----
Exception                               Traceback (most recent
<ipython-input-72-676fdeb26a68> in <module>()
----> 1 index[1] = 'd'
/Users/wesn/code/pandas/pandas/core/index.pyc in __setitem__(self
302     def __setitem__(self, key, value):
303         """Disable the setting of values."""
-> 304         raise Exception(str(self.__class__) + ' object i
305
306     def __getitem__(self, key):
Exception: <class 'pandas.core.index.Index'> object is immutable
```

Immutability is important so that Index objects can be safely shared among data structures:

```
In [73]: index = pd.Index(np.arange(3))

In [74]: obj2 = Series([1.5, -2.5, 0], index=index)

In [75]: obj2.index is index
Out[75]: True
```

Table 5-2 has a list of built-in Index classes in the library. With some development effort, Index can even be subclassed to implement specialized axis indexing functionality.

NOTE

Many users will not need to know much about Index objects, but they're nonetheless an important part of pandas's data model.

Table 5-2. Main Index objects in pandas

Class	Description
Index	The most general Index object, representing axis labels in a NumPy array of Python objects.
Int64Index	Specialized Index for integer values.
MultIndex	"Hierarchical" index object representing multiple levels of indexing on a single axis. Can be thought of as similar to an array of tuples.
DatetimeIndex	Stores nanosecond timestamps (represented using NumPy's datetime64 dtype).
PeriodIndex	Specialized Index for Period data (timespans).

In addition to being array-like, an Index also functions as a fixed-size set:

```
In [76]: frame3
Out[76]:
state  Nevada  Ohio
year
2000    NaN    1.5
2001     2.4    1.7
2002     2.9    3.6

In [77]: 'Ohio' in frame3.columns
Out[77]: True

In [78]: 2003 in frame3.index
Out[78]: False
```

Each Index has a number of methods and properties for set logic and answering other common questions about the data it contains. These are summarized in Table 5-3.

Table 5-3. Index methods and properties

Method	Description
append	Concatenate with additional Index objects, producing a new Index
diff	Compute set difference as an Index
intersection	Compute set intersection
union	Compute set union
isin	Compute boolean array indicating whether each value is contained in the passed collection
delete	Compute new Index with element at index <i>i</i> deleted
drop	Compute new index by deleting passed values
insert	Compute new Index by inserting element at index <i>i</i>
is_monotonic	Returns True if each element is greater than or equal to the previous element
is_unique	Returns True if the Index has no duplicate values
unique	Compute the array of unique values in the Index

Essential Functionality

In this section, I'll walk you through the fundamental mechanics of interacting with the data contained in a Series or DataFrame. Upcoming chapters will delve more deeply into data analysis and manipulation topics using pandas. This book is not in-

tended to serve as exhaustive documentation for the pandas library; I instead focus on the most important features, leaving the less common (that is, more esoteric) things for you to explore on your own.

Reindexing

A critical method on pandas objects is `reindex`, which means to create a new object with the data *conformed* to a new index. Consider a simple example from above:

```
In [79]: obj = Series([4.5, 7.2, -5.3, 3.6], index=['d', 'b', 'a', 'c'])

In [80]: obj
Out[80]:
d    4.5
b    7.2
a   -5.3
c    3.6
```

Calling `reindex` on this Series rearranges the data according to the new index, introducing missing values if any index values were not already present:

```
In [81]: obj2 = obj.reindex(['a', 'b', 'c', 'd', 'e'])

In [82]: obj2
Out[82]:
a   -5.3
b    7.2
c    3.6
d    4.5
e     NaN
```

```
In [83]: obj.reindex(['a', 'b', 'c', 'd', 'e'], fill_value=0)
Out[83]:
a   -5.3
b    7.2
c    3.6
d    4.5
e     0.0
```

For ordered data like time series, it may be desirable to do some interpolation or filling of values when reindexing. The `method` option allows us to do this, using a method such as `ffill` which forward fills the values:

```
In [84]: obj3 = Series(['blue', 'purple', 'yellow'], index=[0, 2, 4])

In [85]: obj3.reindex(range(6), method='ffill')
Out[85]:
0    blue
1    blue
2   purple
3   purple
4   yellow
5   yellow
```

Table 5-4 lists available `method` options. At this time, interpolation more sophisticated than forward- and backfilling would need to be applied after the fact.

Table 5-4. `reindex` method (interpolation) options

Argument	Description
<code>ffill</code> or <code>pad</code>	Fill (or carry) values forward
<code>bfill</code> or <code>backfill</code>	Fill (or carry) values backward

With `DataFrame`, `reindex` can alter either the (row) index, columns, or both. When passed just a sequence, the rows are reindexed in the result:

```
In [86]: frame = DataFrame(np.arange(9).reshape((3, 3)), index=[
.....:                    'Ohio', 'Texas', 'California']

In [87]: frame
Out[87]:
Ohio Texas California
a      0      1      2
c      3      4      5
d      6      7      8

In [88]: frame2 = frame.reindex(['a', 'b', 'c', 'd'])

In [89]: frame2
Out[89]:
Ohio Texas California
a      0      1      2
b     NaN     NaN     NaN
c      3      4      5
d      6      7      8
```

The columns can be reindexed using the `columns` keyword:

```
In [90]: states = ['Texas', 'Utah', 'California']

In [91]: frame.reindex(columns=states)
Out[91]:
Texas Utah California
a      1     NaN      2
c      4     NaN      5
d      7     NaN      8
```


Both can be reindexed in one shot, though interpolation will only apply row-wise (axis 0):

```
In [92]: frame.reindex(index=['a', 'b', 'c', 'd'], method='ffill
....:               columns=states)
Out[92]:
   Texas  Utah  California
a      1   NaN           2
b      1   NaN           2
c      4   NaN           5
d      7   NaN           8
```

As you'll see soon, reindexing can be done more succinctly by label-indexing with ix:

```
In [93]: frame.ix[['a', 'b', 'c', 'd'], states]
Out[93]:
   Texas  Utah  California
a      1   NaN           2
b     NaN   NaN          NaN
c      4   NaN           5
d      7   NaN           8
```

Table 5-5. reindex function arguments

Argument	Description
index	New sequence to use as index. Can be Index instance or any other sequence-like Python data structure. An Index will be used exactly as is without any copying
method	Interpolation (fill) method, see Table 5-4 for options.
fill_value	Substitute value to use when introducing missing data by reindexing
limit	When forward- or backfilling, maximum size gap to fill
level	Match simple Index on level of MultiIndex, otherwise select subset of
copy	Do not copy underlying data if new index is equivalent to old index. True by default (i.e. always copy data).

Dropping entries from an axis

Dropping one or more entries from an axis is easy if you have an index array or list without those entries. As that can require a bit of munging and set logic, the drop method will return a new object with the indicated value or values deleted from an axis:

```
In [94]: obj = Series(np.arange(5.), index=['a', 'b', 'c', 'd',
In [95]: new_obj = obj.drop('c')

In [96]: new_obj
Out[96]:
a    0
b    1
d    3
e    4

In [97]: obj.drop(['d', 'c'])
Out[97]:
a    0
b    1
e    4
```

With DataFrame, index values can be deleted from either axis:

```
In [98]: data = DataFrame(np.arange(16).reshape((4, 4)),
....:                    index=['Ohio', 'Colorado', 'Utah', 'Ne
....:                    columns=['one', 'two', 'three', 'four']

In [99]: data.drop(['Colorado', 'Ohio'])
Out[99]:
   one  two  three  four
Utah   8   9    10    11
New York 12  13    14    15

In [100]: data.drop('two', axis=1)
Out[100]:
   one  three  four
Ohio   0     2     3
Colorado 4     6     7
Utah    8    10    11
New York 12    14    15

In [101]: data.drop(['tw
Out[101]:
   one  three  four
Ohio   0     2     3
Colorado 4     6     7
Utah    8    10    11
New York 12    14    15
```

Indexing, selection, and filtering

Series indexing (obj[...]) works analogously to NumPy array indexing, except you can use the Series's index values instead of only integers. Here are some examples this:

```
In [102]: obj = Series(np.arange(4.), index=['a', 'b', 'c', 'd']
In [103]: obj['b']
In [104]: obj[1]
```

```

Out[103]: 1.0          Out[104]: 1.0

In [105]: obj[2:4]      In [106]: obj[['b', 'a', 'd']]
Out[105]:              Out[106]:
c      2                b      1
d      3                a      0
                        d      3

In [107]: obj[[1, 3]]   In [108]: obj[obj < 2]
Out[107]:              Out[108]:
b      1                a      0
d      3                b      1

```

Slicing with labels behaves differently than normal Python slicing in that the end-point is inclusive:

```

In [109]: obj['b':'c']
Out[109]:
b      1
c      2

```

Setting using these methods works just as you would expect:

```

In [110]: obj['b':'c'] = 5

In [111]: obj
Out[111]:
a      0
b      5
c      5
d      3

```

As you've seen above, indexing into a DataFrame is for retrieving one or more columns either with a single value or sequence:

```

In [112]: data = DataFrame(np.arange(16).reshape((4, 4)),
.....:                    index=['Ohio', 'Colorado', 'Utah', 'N
.....:                    ews York'],
.....:                    columns=['one', 'two', 'three', 'four'])

In [113]: data
Out[113]:
   one  two  three  four
Ohio    0    1     2    3
Colorado 4    5     6    7
Utah    8    9    10   11
New York 12   13    14   15

In [114]: data['two']
Out[114]:
Ohio    1
Colorado 5
Utah    9
New York 13
Name: two

In [115]: data[['three', 'one']]
Out[115]:
   three  one
Ohio     2    0
Colorado 6    4
Utah    10    8
New York 14   12

```

Indexing like this has a few special cases. First selecting rows by slicing or a boolean array:

```

In [116]: data[:2]
Out[116]:
   one  two  three  four
Ohio    0    1     2    3
Colorado 4    5     6    7

In [117]: data[data['three'] > 10]
Out[117]:
   one  two  three  four
New York 12   13    14   15

```

This might seem inconsistent to some readers, but this syntax arose out of practicality and nothing more. Another use case is in indexing with a boolean DataFrame, such as one produced by a scalar comparison:

```

In [118]: data < 5
Out[118]:
   one  two  three  four
Ohio   True   True   True   True
Colorado True  False False False
Utah   False False False False
New York False False False False

In [119]: data[data < 5] = 0

In [120]: data
Out[120]:
   one  two  three  four
Ohio    0    0     0    0
Colorado 0    5     6    7
Utah    8    9    10   11
New York 12   13    14   15

```

This is intended to make DataFrame syntactically more like an ndarray in this case.

For DataFrame label-indexing on the rows, I introduce the special indexing field `ix`. It enables you to select a subset of the rows and columns from a DataFrame with NumPy-like notation plus axis labels. As I mentioned earlier, this is also a less verbose way to do reindexing:

```

In [121]: data.ix['Colorado', ['two', 'three']]
Out[121]:
two      5
three     6
Name: Colorado

In [122]: data.ix[['Colorado', 'Utah'], [3, 0, 1]]

```

```
Out[122]:
      four  one  two
Colorado   7   0   5
Utah      11   8   9

In [123]: data.ix[2]
Out[123]:
one      8
two      9
three    10
four     11
Name: Utah

In [124]: data.ix[:, 'two']
Out[124]:
Ohio      0
Colorado   5
Utah       9
Name: two

In [125]: data.ix[data.three > 5, :3]
Out[125]:
      one  two  three
Colorado   0   5     6
Utah       8   9    10
New York  12  13    14
```

So there are many ways to select and rearrange the data contained in a pandas object. For DataFrame, there is a short summary of many of them in [Table 5-6](#). You have a number of additional options when working with hierarchical indexes as you'll later see.

NOTE

When designing pandas, I felt that having to type `frame[:, col]` to select a column was too verbose (and error-prone), since column selection is one of the most common operations. Thus I made the design trade-off to push all of the rich label-indexing into `ix`.

Table 5-6. Indexing options with DataFrame

Type	Notes
<code>obj[val]</code>	Select single column or sequence of columns from the DataFrame. Special case conveniences: boolean array (filter rows), slice (slice rows), or boolean DataFrame (set values based on some criterion).
<code>obj.ix[val]</code>	Selects single row of subset of rows from the DataFrame.
<code>obj.ix[:, val]</code>	Selects single column of subset of columns.
<code>obj.ix[val1, val2]</code>	Select both rows and columns.
<code>reindex</code> method	Conform one or more axes to new indexes.
<code>xs</code> method	Select single row or column as a Series by label.
<code>icol, irow</code> methods	Select single column or row, respectively, as a Series by integer location.
<code>get_value, set_value</code> methods	Select single value by row and column label.

Arithmetic and data alignment

One of the most important pandas features is the behavior of arithmetic between objects with different indexes. When adding together objects, if any index pairs are not the same, the respective index in the result will be the union of the index pairs. Let's look at a simple example:

```
In [126]: s1 = Series([7.3, -2.5, 3.4, 1.5], index=['a', 'c', 'd']
In [127]: s2 = Series([-2.1, 3.6, -1.5, 4, 3.1], index=['a', 'c']

In [128]: s1
Out[128]:
a    7.3
c   -2.5
d    3.4
e    1.5

In [129]: s2
Out[129]:
a   -2.1
c    3.6
e   -1.5
f    4.0
g    3.1
```

Adding these together yields:

```
In [130]: s1 + s2
Out[130]:
a    5.2
c    1.1
d    NaN
e    0.0
f    NaN
g    NaN
```

The internal data alignment introduces NA values in the indices that don't overlap. Missing values propagate in arithmetic computations.

In the case of DataFrame, alignment is performed on both the rows and the columns:

```
In [131]: df1 = DataFrame(np.arange(9.).reshape((3, 3)), columns
.....:                  index=['Ohio', 'Texas', 'Colorado'])

In [132]: df2 = DataFrame(np.arange(12.).reshape((4, 3)), column
.....:                  index=['Utah', 'Ohio', 'Texas', 'Orego

In [133]: df1
Out[133]:
   b  c  d
Ohio  0  1  2
Texas  3  4  5
Colorado 6  7  8

In [134]: df2
Out[134]:
   b  d  e
Utah  0  1  2
Ohio  3  4  5
Texas  6  7  8
Oregon 9 10 11
```

Adding these together returns a DataFrame whose index and columns are the unions of the ones in each DataFrame:

```
In [135]: df1 + df2
Out[135]:
   b  c  d  e
Colorado NaN NaN NaN NaN
Ohio      3 NaN  6 NaN
Oregon   NaN NaN NaN NaN
Texas     9 NaN 12 NaN
Utah     NaN NaN NaN NaN
```

ARITHMETIC METHODS WITH FILL VALUES

In arithmetic operations between differently-indexed objects, you might want to fill with a special value, like 0, when an axis label is found in one object but not the other:

```
In [136]: df1 = DataFrame(np.arange(12.).reshape((3, 4)), column

In [137]: df2 = DataFrame(np.arange(20.).reshape((4, 5)), column

In [138]: df1
Out[138]:
   a  b  c  d
0  0  1  2  3
1  4  5  6  7
2  8  9 10 11

In [139]: df2
Out[139]:
   a  b  c  d  e
0  0  1  2  3  4
1  5  6  7  8  9
2 10 11 12 13 14
3 15 16 17 18 19
```

Adding these together results in NA values in the locations that don't overlap:

```
In [140]: df1 + df2
Out[140]:
   a  b  c  d  e
0  0  2  4  6 NaN
1  9 11 13 15 NaN
2 18 20 22 24 NaN
3 NaN NaN NaN NaN NaN
```

Using the add method on df1, I pass df2 and an argument to fill_value:

```
In [141]: df1.add(df2, fill_value=0)
Out[141]:
   a  b  c  d  e
0  0  2  4  6  4
1  9 11 13 15  9
2 18 20 22 24 14
3 15 16 17 18 19
```

Relatedly, when reindexing a Series or DataFrame, you can also specify a different fill value:

```
In [142]: df1.reindex(columns=df2.columns, fill_value=0)
Out[142]:
   a  b  c  d  e
0  0  1  2  3  0
1  4  5  6  7  0
2  8  9 10 11  0
```

Table 5-7. Flexible arithmetic methods

Method	Description
add	Method for addition (+)
sub	Method for subtraction (-)
div	Method for division (/)
mul	Method for multiplication (*)

OPERATIONS BETWEEN DATAFRAME AND SERIES

As with NumPy arrays, arithmetic between DataFrame and Series is well-defined. First, as a motivating example, consider the difference between a 2D array and one of its rows:

```
In [143]: arr = np.arange(12.).reshape((3, 4))

In [144]: arr
```

```

Out[144]:
array([[ 0.,  1.,  2.,  3.],
       [ 4.,  5.,  6.,  7.],
       [ 8.,  9., 10., 11.]])

In [145]: arr[0]
Out[145]: array([ 0.,  1.,  2.,  3.])

In [146]: arr - arr[0]
Out[146]:
array([[ 0.,  0.,  0.,  0.],
       [ 4.,  4.,  4.,  4.],
       [ 8.,  8.,  8.,  8.]])

```

This is referred to as *broadcasting* and is explained in more detail in [Chapter 12](#). Operations between a DataFrame and a Series are similar:

```

In [147]: frame = DataFrame(np.arange(12.).reshape((4, 3)), columns=[
.....:                    index=['Utah', 'Ohio', 'Texas', 'Oregon']

In [148]: series = frame.ix[0]

In [149]: frame
Out[149]:
   b  d  e
Utah  0  1  2
Ohio  3  4  5
Texas  6  7  8
Oregon 9 10 11

In [150]: series
Out[150]:
b    0
d    1
e    2
Name: Utah

```

By default, arithmetic between DataFrame and Series matches the index of the Series on the DataFrame's columns, broadcasting down the rows:

```

In [151]: frame - series
Out[151]:
   b  d  e
Utah  0  0  0
Ohio  3  3  3
Texas  6  6  6
Oregon 9  9  9

```

If an index value is not found in either the DataFrame's columns or the Series's index, the objects will be reindexed to form the union:

```

In [152]: series2 = Series(range(3), index=['b', 'e', 'f'])

In [153]: frame + series2
Out[153]:
   b  d  e  f
Utah  0 NaN  3 NaN
Ohio  3 NaN  6 NaN
Texas  6 NaN  9 NaN
Oregon 9 NaN 12 NaN

```

If you want to instead broadcast over the columns, matching on the rows, you have to use one of the arithmetic methods. For example:

```

In [154]: series3 = frame['d']

In [155]: frame
Out[155]:
   b  d  e
Utah  0  1  2
Ohio  3  4  5
Texas  6  7  8
Oregon 9 10 11

In [156]: series3
Out[156]:
Utah    1
Ohio    4
Texas    7
Oregon  10
Name: d

In [157]: frame.sub(series3, axis=0)
Out[157]:
   b  d  e
Utah -1  0  1
Ohio -1  0  1
Texas -1  0  1
Oregon -1  0  1

```

The axis number that you pass is the *axis to match on*. In this case we mean to match on the DataFrame's row index and broadcast across.

Function application and mapping

NumPy ufuncs (element-wise array methods) work fine with pandas objects:

```

In [158]: frame = DataFrame(np.random.randn(4, 3), columns=list(
.....:                    index=['Utah', 'Ohio', 'Texas', 'Oregon']

In [159]: frame
Out[159]:
   b         d         e
Utah -0.204708  0.478943 -0.519439
Ohio -0.555730  1.965781  1.393406
Texas  0.092908  0.281746  0.769023
Oregon 1.246435  1.007189 -1.296221

In [160]: np.abs(frame)
Out[160]:
   b         b
Utah  0.204708  0.47
Ohio  0.555730  1.96
Texas  0.092908  0.28
Oregon 1.246435  1.00

```

Another frequent operation is applying a function on 1D arrays to each column or row. DataFrame's `apply` method does exactly this:

```

In [161]: f = lambda x: x.max() - x.min()

In [162]: frame.apply(f)
Out[162]:
b    1.802165
d    1.684034

In [163]: frame.apply(f, axis=1)
Out[163]:
Utah    0.998382
Ohio    2.521511

```

e	2.689627	Texas	0.676115
		Oregon	2.542656

Many of the most common array statistics (like `sum` and `mean`) are `DataFrame` methods, so using `apply` is not necessary.

The function passed to `apply` need not return a scalar value, it can also return a `Series` with multiple values:

```
In [164]: def f(x):
.....:     return Series([x.min(), x.max()], index=['min', 'max'])

In [165]: frame.apply(f)
Out[165]:
```

	b	d	e
min	-0.555730	0.281746	-1.296221
max	1.246435	1.965781	1.393406

Element-wise Python functions can be used, too. Suppose you wanted to compute a formatted string from each floating point value in `frame`. You can do this with `applymap`:

```
In [166]: format = lambda x: '%.2f' % x

In [167]: frame.applymap(format)
Out[167]:
```

	b	d	e
Utah	-0.20	0.48	-0.52
Ohio	-0.56	1.97	1.39
Texas	0.09	0.28	0.77
Oregon	1.25	1.01	-1.30

The reason for the name `applymap` is that `Series` has a `map` method for applying an element-wise function:

```
In [168]: frame['e'].map(format)
Out[168]:
Utah      -0.52
Ohio       1.39
Texas       0.77
Oregon     -1.30
Name: e
```

Sorting and ranking

Sorting a data set by some criterion is another important built-in operation. To sort lexicographically by row or column index, use the `sort_index` method, which returns a new, sorted object:

```
In [169]: obj = Series(range(4), index=['d', 'a', 'b', 'c'])

In [170]: obj.sort_index()
Out[170]:
a    1
b    2
c    3
d    0
```

With a `DataFrame`, you can sort by index on either axis:

```
In [171]: frame = DataFrame(np.arange(8).reshape((2, 4)), index=
.....:                      columns=['d', 'a', 'b', 'c'])

In [172]: frame.sort_index()
Out[172]:
```

	d	a	b	c
one	4	5	6	7
three	0	1	2	3

```
In [173]: frame.sort_index(axis=1)
Out[173]:
```

	a	b	c	d
three	1	2	3	0
one	5	6	7	4

The data is sorted in ascending order by default, but can be sorted in descending order, too:

```
In [174]: frame.sort_index(axis=1, ascending=False)
Out[174]:
```

	d	c	b	a
three	0	3	2	1
one	4	7	6	5

To sort a `Series` by its values, use its `order` method:

```
In [175]: obj = Series([4, 7, -3, 2])

In [176]: obj.order()
Out[176]:
2    -3
3     2
0     4
1     7
```

Any missing values are sorted to the end of the `Series` by default:

```
In [177]: obj = Series([4, np.nan, 7, np.nan, -3, 2])

In [178]: obj.order()
Out[178]:
4    -3
5     2
0     4
```

```
2    7
1   NaN
3   NaN
```

On DataFrame, you may want to sort by the values in one or more columns. To do so, pass one or more column names to the `by` option:

```
In [179]: frame = DataFrame({'b': [4, 7, -3, 2], 'a': [0, 1, 0,
In [180]: frame          In [181]: frame.sort_index(by='b')
Out[180]:          Out[181]:
   a b              a b
0  0 4            2  0 -3
1  1 7            3  1  2
2  0 -3           0  0  4
3  1  2            1  1  7
```

To sort by multiple columns, pass a list of names:

```
In [182]: frame.sort_index(by=['a', 'b'])
Out[182]:
   a b
2  0 -3
0  0  4
3  1  2
1  1  7
```

Ranking is closely related to sorting, assigning ranks from one through the number of valid data points in an array. It is similar to the indirect sort indices produced by `numpy.argsort`, except that ties are broken according to a rule. The `rank` methods for Series and DataFrame are the place to look; by default `rank` breaks ties by assigning each group the mean rank:

```
In [183]: obj = Series([7, -5, 7, 4, 2, 0, 4])

In [184]: obj.rank()
Out[184]:
0    6.5
1    1.0
2    6.5
3    4.5
4    3.0
5    2.0
6    4.5
```

Ranks can also be assigned according to the order they're observed in the data:

```
In [185]: obj.rank(method='first')
Out[185]:
0    6
1    1
2    7
3    4
4    3
5    2
6    5
```

Naturally, you can rank in descending order, too:

```
In [186]: obj.rank(ascending=False, method='max')
Out[186]:
0    2
1    7
2    2
3    4
4    5
5    6
6    4
```

See [Table 5-8](#) for a list of tie-breaking methods available. DataFrame can compute ranks over the rows or the columns:

```
In [187]: frame = DataFrame({'b': [4.3, 7, -3, 2], 'a': [0, 1, 0,
.....:                  'c': [-2, 5, 8, -2.5]})

In [188]: frame          In [189]: frame.rank(axis=1)
Out[188]:          Out[189]:
   a b c              a b c
0  0 4.3 -2.0          0  2  3  1
1  1 7.0  5.0          1  1  3  2
2  0 -3.0  8.0          2  2  1  3
3  1 2.0 -2.5          3  2  3  1
```

Table 5-8. Tie-breaking methods with rank

Method	Description
'average'	Default: assign the average rank to each entry in the equal group.
'min'	Use the minimum rank for the whole group.
'max'	Use the maximum rank for the whole group.
'first'	Assign ranks in the order the values appear in the data.

Axis indexes with duplicate values

Up until now all of the examples I've showed you have had unique axis labels (index values). While many pandas functions (like `reIndex`) require that the labels be unique, it's not mandatory. Let's consider a small Series with duplicate indices:

```
In [190]: obj = Series(range(5), index=['a', 'a', 'b', 'b', 'c'])

In [191]: obj
Out[191]:
a    0
a    1
b    2
b    3
c    4
```

The index's `is_unique` property can tell you whether its values are unique or not:

```
In [192]: obj.index.is_unique
Out[192]: False
```

Data selection is one of the main things that behaves differently with duplicates. Indexing a value with multiple entries returns a Series while single entries return a scalar value:

```
In [193]: obj['a']      In [194]: obj['c']
Out[193]:              Out[194]: 4
a    0
a    1
```

The same logic extends to indexing rows in a DataFrame:

```
In [195]: df = DataFrame(np.random.randn(4, 3), index=['a', 'a', 'b', 'b'])

In [196]: df
Out[196]:
           0         1         2
a  0.274992  0.228913  1.352917
a  0.886429 -2.001637 -0.371843
b  1.669825 -0.438570 -0.539741
b  0.476985  3.248944 -1.021228

In [197]: df.ix['b']
Out[197]:
           0         1         2
b  1.669825 -0.438570 -0.539741
b  0.476985  3.248944 -1.021228
```

Summarizing and Computing Descriptive Statistics

pandas objects are equipped with a set of common mathematical and statistical methods. Most of these fall into the category of *reductions* or *summary statistics*, methods that extract a single value (like the sum or mean) from a Series or a Series of values from the rows or columns of a DataFrame. Compared with the equivalent methods of vanilla NumPy arrays, they are all built from the ground up to exclude missing data. Consider a small DataFrame:

```
In [198]: df = DataFrame([[1.4, np.nan], [7.1, -4.5]],
.....:                  [np.nan, np.nan], [0.75,
.....:                  index=['a', 'b', 'c', 'd'],
.....:                  columns=['one', 'two'])

In [199]: df
Out[199]:
           one  two
a    1.40  NaN
b    7.10 -4.5
c    NaN  NaN
d    0.75 -1.3
```

Calling DataFrame's `sum` method returns a Series containing column sums:

```
In [200]: df.sum()
Out[200]:
one    9.25
two   -5.80
```

Passing `axis=1` sums over the rows instead:

```
In [201]: df.sum(axis=1)
Out[201]:
a    1.40
b    2.60
c    NaN
d   -0.55
```

NA values are excluded unless the entire slice (row or column in this case) is NA. This can be disabled using the `skipna` option:

```
In [202]: df.mean(axis=1, skipna=False)
Out[202]:
a    NaN
b    1.300
c    NaN
d   -0.275
```

See [Table 5-9](#) for a list of common options for each reduction method options.

Table 5-9. Options for reduction methods

Method	Description
axis	Axis to reduce over. 0 for DataFrame's rows and 1 for columns.
skipna	Exclude missing values, True by default.
level	Reduce grouped by level if the axis is hierarchically-indexed (MultiIndex).

Some methods, like `idxmin` and `idxmax`, return indirect statistics like the index value where the minimum or maximum values are attained:

```
In [203]: df.idxmax()
Out[203]:
one    b
two    d
```

Other methods are *accumulations*:

```
In [204]: df.cumsum()
Out[204]:
   one  two
a  1.40 NaN
b  8.50 -4.5
c   NaN NaN
d  9.25 -5.8
```

Another type of method is neither a reduction nor an accumulation. `describe` is one such example, producing multiple summary statistics in one shot:

```
In [205]: df.describe()
Out[205]:
           one      two
count  3.000000  2.000000
mean    3.083333  2.900000
std     3.493685  2.262742
min     0.750000 -4.500000
25%     1.075000 -3.700000
50%     1.400000 -2.900000
75%     4.250000 -2.100000
max     7.100000 -1.300000
```

On non-numeric data, `describe` produces alternate summary statistics:

```
In [206]: obj = Series(['a', 'a', 'b', 'c'] * 4)

In [207]: obj.describe()
Out[207]:
count    16
unique     3
top        a
freq        8
```

See [Table 5-10](#) for a full list of summary statistics and related methods.

Table 5-10. Descriptive and summary statistics

Method	Description
<code>count</code>	Number of non-NA values
<code>describe</code>	Compute set of summary statistics for Series or each DataFrame column
<code>min</code> , <code>max</code>	Compute minimum and maximum values
<code>argmin</code> , <code>argmax</code>	Compute index locations (integers) at which minimum or maximum value obtained, respectively
<code>idxmin</code> , <code>idxmax</code>	Compute index values at which minimum or maximum value obtained, respectively
<code>quantile</code>	Compute sample quantile ranging from 0 to 1
<code>sum</code>	Sum of values
<code>mean</code>	Mean of values
<code>median</code>	Arithmetic median (50% quantile) of values
<code>mad</code>	Mean absolute deviation from mean value
<code>var</code>	Sample variance of values
<code>std</code>	Sample standard deviation of values
<code>skew</code>	Sample skewness (3rd moment) of values
<code>kurt</code>	Sample kurtosis (4th moment) of values
<code>cumsum</code>	Cumulative sum of values
<code>cummin</code> , <code>cummax</code>	Cumulative minimum or maximum of values, respectively
<code>cumprod</code>	Cumulative product of values
<code>diff</code>	Compute 1st arithmetic difference (useful for time series)
<code>pct_change</code>	Compute percent changes

Correlation and Covariance

Some summary statistics, like correlation and covariance, are computed from pairs of arguments. Let's consider some DataFrames of stock prices and volumes obtained from Yahoo! Finance:

```
import pandas.io.data as web

all_data = {}
for ticker in ['AAPL', 'IBM', 'MSFT', 'GOOG']:
    all_data[ticker] = web.get_data_yahoo(ticker, '1/1/2000', '1/1/2009')

price = DataFrame({tic: data['Adj Close']
                   for tic, data in all_data.iteritems()})
volume = DataFrame({tic: data['Volume']
                    for tic, data in all_data.iteritems()})
```

I now compute percent changes of the prices:

```
In [209]: returns = price.pct_change()

In [210]: returns.tail()
Out[210]:
```

	AAPL	GOOG	IBM	MSFT
Date				
2009-12-24	0.034339	0.011117	0.004420	0.002747
2009-12-28	0.012294	0.007098	0.013282	0.005479
2009-12-29	-0.011861	-0.005571	-0.003474	0.006812
2009-12-30	0.012147	0.005376	0.005468	-0.013532
2009-12-31	-0.004300	-0.004416	-0.012609	-0.015432

The `corr` method of Series computes the correlation of the overlapping, non-NA, aligned-by-index values in two Series. Relatedly, `cov` computes the covariance:

```
In [211]: returns.MSFT.corr(returns.IBM)
Out[211]: 0.49609291822168838

In [212]: returns.MSFT.cov(returns.IBM)
Out[212]: 0.00021600332437329015
```

DataFrame's `corr` and `cov` methods, on the other hand, return a full correlation or covariance matrix as a DataFrame, respectively:

```
In [213]: returns.corr()
Out[213]:
```

	AAPL	GOOG	IBM	MSFT
AAPL	1.000000	0.470660	0.410648	0.424550
GOOG	0.470660	1.000000	0.390692	0.443334
IBM	0.410648	0.390692	1.000000	0.496093
MSFT	0.424550	0.443334	0.496093	1.000000

```
In [214]: returns.cov()
Out[214]:
```

	AAPL	GOOG	IBM	MSFT
AAPL	0.001028	0.000303	0.000252	0.000309
GOOG	0.000303	0.000580	0.000142	0.000205
IBM	0.000252	0.000142	0.000367	0.000216
MSFT	0.000309	0.000205	0.000216	0.000516

Using DataFrame's `corrwith` method, you can compute pairwise correlations between a DataFrame's columns or rows with another Series or DataFrame. Passing a Series returns a Series with the correlation value computed for each column:

```
In [215]: returns.corrwith(returns.IBM)
Out[215]:
```

AAPL	0.410648
GOOG	0.390692
IBM	1.000000
MSFT	0.496093

Passing a DataFrame computes the correlations of matching column names. Here I compute correlations of percent changes with volume:

```
In [216]: returns.corrwith(volume)
Out[216]:
```

AAPL	-0.057461
GOOG	0.062644
IBM	-0.007900
MSFT	-0.014175

Passing `axis=1` does things row-wise instead. In all cases, the data points are aligned by label before computing the correlation.

Unique Values, Value Counts, and Membership

Another class of related methods extracts information about the values contained in a one-dimensional Series. To illustrate these, consider this example:

```
In [217]: obj = Series(['c', 'a', 'd', 'a', 'a', 'b', 'b', 'c',
```

The first function is `unique`, which gives you an array of the unique values in a Series:

```
In [218]: uniques = obj.unique()

In [219]: uniques
Out[219]: array([c, a, d, b], dtype=object)
```

The unique values are not necessarily returned in sorted order, but could be sorted after the fact if needed (`uniques.sort()`). Relatedly, `value_counts` computes a Series containing value frequencies:

```
In [220]: obj.value_counts()
Out[220]:
```

c	3
a	3
b	2
d	1

The Series is sorted by value in descending order as a convenience. `value_counts` is also available as a top-level pandas method that can be used with any array or sequence:

```
In [221]: pd.value_counts(obj.values, sort=False)
Out[221]:
```

a	3
b	2
c	3
d	1

Lastly, `isin` is responsible for vectorized set membership and can be very useful in filtering a data set down to a subset of values in a Series or column in a DataFrame:

```
In [222]: mask = obj.isin(['b', 'c'])

In [223]: mask
Out[223]:
```

0	True
1	False
2	False
3	False
4	False
5	True
6	True
7	True
8	True

```
In [224]: obj[mask]
Out[224]:
```

0	c
5	b
6	b
7	c
8	c

See [Table 5-11](#) for a reference on these methods.

Table 5-11. Unique, value counts, and binning methods

Method	Description
<code>isin</code>	Compute boolean array indicating whether each Series value is contained in the passed sequence of values.
<code>unique</code>	Compute array of unique values in a Series, returned in the order observed.
<code>value_counts</code>	Return a Series containing unique values as its index and frequencies as its values, ordered count in descending order.

In some cases, you may want to compute a histogram on multiple related columns in a DataFrame. Here's an example:

```
In [225]: data = DataFrame({'Qu1': [1, 3, 4, 3, 4],
.....:                    'Qu2': [2, 3, 1, 2, 3],
.....:                    'Qu3': [1, 5, 2, 4, 4]})

In [226]: data
Out[226]:
   Qu1  Qu2  Qu3
0    1    2    1
1    3    3    5
2    4    1    2
3    3    2    4
4    4    3    4
```

Passing `pandas.value_counts` to this DataFrame's `apply` function gives:

```
In [227]: result = data.apply(pd.value_counts).fillna(0)

In [228]: result
Out[228]:
   Qu1  Qu2  Qu3
1    1    1    1
2    0    2    1
3    2    2    0
4    2    0    2
5    0    0    1
```

Handling Missing Data

Missing data is common in most data analysis applications. One of the goals in designing pandas was to make working with missing data as painless as possible. For example, all of the descriptive statistics on pandas objects exclude missing data as you've seen earlier in the chapter.

pandas uses the floating point value `NaN` (Not a Number) to represent missing data in both floating as well as in non-floating point arrays. It is just used as a *sentinel* that can be easily detected:

```
In [229]: string_data = Series(['aardvark', 'artichoke', np.nan,
.....:                        'avocado'])

In [230]: string_data
Out[230]:
0    aardvark
1    artichoke
2         NaN
3     avocado

In [231]: string_data.isnull()
Out[231]:
0    False
1    False
2     True
3    False
```

The built-in Python `None` value is also treated as `NA` in object arrays:

```
In [232]: string_data[0] = None

In [233]: string_data.isnull()
Out[233]:
0     True
1    False
2     True
3    False
```

I do not claim that pandas's `NA` representation is optimal, but it is simple and reasonably consistent. It's the best solution, with good all-around performance characteristics and a simple API, that I could concoct in the absence of a true `NA` data type or bit pattern in NumPy's data types. Ongoing development work in NumPy may change this in the future.

Table 5-12. NA handling methods

Argument	Description
dropna	Filter axis labels based on whether values for each label have missing data, with varying thresholds for how much missing data to tolerate.
fillna	Fill in missing data with some value or using an interpolation method such as 'ffill' or 'bfill'.
isnull	Return like-type object containing boolean values indicating which values are missing / NA.
notnull	Negation of isnull.

Filtering Out Missing Data

You have a number of options for filtering out missing data. While doing it by hand is always an option, dropna can be very helpful. On a Series, it returns the Series with only the non-null data and index values:

```
In [234]: from numpy import nan as NA

In [235]: data = Series([1, NA, 3.5, NA, 7])

In [236]: data.dropna()
Out[236]:
0    1.0
2    3.5
4    7.0
```

Naturally, you could have computed this yourself by boolean indexing:

```
In [237]: data[data.notnull()]
Out[237]:
0    1.0
2    3.5
4    7.0
```

With DataFrame objects, these are a bit more complex. You may want to drop rows or columns which are all NA or just those containing any NAs. dropna by default drops any row containing a missing value:

```
In [238]: data = DataFrame([[1., 6.5, 3.], [1., NA, NA],
.....:                    [NA, NA, NA], [NA, 6.5
.....:                    ]])

In [239]: cleaned = data.dropna()

In [240]: data          In [241]: cleaned
Out[240]:              Out[241]:
0    1  2              0    1  2
0    1  6.5  3          0    1  6.5  3
1    1  NaN NaN
2  NaN  NaN NaN
3  NaN  6.5  3
```

Passing how='all' will only drop rows that are all NA:

```
In [242]: data.dropna(how='all')
Out[242]:
0    1  2
0    1  6.5  3
1    1  NaN NaN
3  NaN  6.5  3
```

Dropping columns in the same way is only a matter of passing axis=1:

```
In [243]: data[4] = NA

In [244]: data          In [245]: data.dropna(axis=1, how='all')
Out[244]:              Out[245]:
0    1  2  4              0    1  2
0    1  6.5  3 NaN          0    1  6.5  3
1    1  NaN NaN NaN          1    1  NaN NaN
2  NaN  NaN NaN NaN          2  NaN  NaN NaN
3  NaN  6.5  3 NaN          3  NaN  6.5  3
```

A related way to filter out DataFrame rows tends to concern time series data. Suppose you want to keep only rows containing a certain number of observations. You can indicate this with the thresh argument:

```
In [246]: df = DataFrame(np.random.randn(7, 3))

In [247]: df.ix[:4, 1] = NA; df.ix[:2, 2] = NA

In [248]: df          In [249]: df.dropna(thresh=2)
Out[248]:              Out[249]:
0    0 -0.577087      NaN      NaN          0    0 -0.577087      NaN      NaN
1    1  0.523772      NaN      NaN          1    1  0.523772      NaN      NaN
2    2 -0.713544      NaN      NaN          2    2 -0.713544      NaN      NaN
3    3 -1.860761      NaN  0.560145          3    3 -1.860761      NaN  0.560145
4    4 -1.265934      NaN -1.063512          4    4 -1.265934      NaN -1.063512
5    5  0.332883 -2.359419 -0.199543          5    5  0.332883 -2.359419 -0.199543
6    6 -1.541996 -0.970736 -1.307030          6    6 -1.541996 -0.970736 -1.307030
```

Filling in Missing Data

Rather than filtering out missing data (and potentially discarding other data along with it), you may want to fill in the “holes” in any number of ways. For most purposes, the `fillna` method is the workhorse function to use. Calling `fillna` with a constant replaces missing values with that value:

```
In [250]: df.fillna(0)
Out[250]:
```

	0	1	2
0	-0.577887	0.000000	0.000000
1	0.523772	0.000000	0.000000
2	-0.713544	0.000000	0.000000
3	-1.860761	0.000000	0.560145
4	-1.265934	0.000000	-1.063512
5	0.332883	-2.359419	-0.199543
6	-1.541996	-0.970736	-1.307030

Calling `fillna` with a dict you can use a different fill value for each column:

```
In [251]: df.fillna({1: 0.5, 3: -1})
Out[251]:
```

	0	1	2
0	-0.577887	0.500000	NaN
1	0.523772	0.500000	NaN
2	-0.713544	0.500000	NaN
3	-1.860761	0.500000	0.560145
4	-1.265934	0.500000	-1.063512
5	0.332883	-2.359419	-0.199543
6	-1.541996	-0.970736	-1.307030

`fillna` returns a new object, but you can modify the existing object in place:

```
# always returns a reference to the filled object
In [252]: _ = df.fillna(0, inplace=True)

In [253]: df
Out[253]:
```

	0	1	2
0	-0.577887	0.000000	0.000000
1	0.523772	0.000000	0.000000
2	-0.713544	0.000000	0.000000
3	-1.860761	0.000000	0.560145
4	-1.265934	0.000000	-1.063512
5	0.332883	-2.359419	-0.199543
6	-1.541996	-0.970736	-1.307030

The same interpolation methods available for reindexing can be used with `fillna`:

```
In [254]: df = DataFrame(np.random.randn(6, 3))

In [255]: df.ix[2:, 1] = NA; df.ix[4:, 2] = NA

In [256]: df
Out[256]:
```

	0	1	2
0	0.286350	0.377984	-0.753887
1	0.331286	1.349742	0.069877
2	0.246674	NaN	1.004812
3	1.327195	NaN	-1.549106
4	0.022185	NaN	NaN
5	0.862580	NaN	NaN


```
In [257]: df.fillna(method='ffill')
Out[257]:
```

	0	1	2
0	0.286350	0.377984	-0.753887
1	0.331286	1.349742	0.069877
2	0.246674	1.349742	1.004812
3	1.327195	1.349742	-1.549106
4	0.022185	1.349742	-1.549106
5	0.862580	1.349742	-1.549106


```
In [258]: df.fillna(method='bfill')
Out[258]:
```

	0	1	2
0	0.286350	0.377984	-0.753887
1	0.331286	1.349742	0.069877
2	0.246674	1.349742	1.004812
3	1.327195	1.349742	-1.549106
4	0.022185	NaN	NaN
5	0.862580	NaN	NaN

With `fillna` you can do lots of other things with a little creativity. For example, you might pass the mean or median value of a Series:

```
In [259]: data = Series([1., NA, 3.5, NA, 7])

In [260]: data.fillna(data.mean())
Out[260]:
```

	0	1	2	3	4
0	1.000000				
1	3.833333				
2	3.500000				
3	3.833333				
4	7.000000				

See [Table 5-13](#) for a reference on `fillna`.

Table 5-13. fillna function arguments

Argument	Description
value	Scalar value or dict-like object to use to fill missing values
method	Interpolation, by default 'ffill' if function called with no other arguments
axis	Axis to fill on, default axis=0
inplace	Modify the calling object without producing a copy
limit	For forward and backward filling, maximum number of consecutive periods to fill

Hierarchical Indexing

Hierarchical indexing is an important feature of pandas enabling you to have multiple (two or more) index levels on an axis. Somewhat abstractly, it provides a way for you to work with higher dimensional data in a lower dimensional form. Let's start with a simple example; create a Series with a list of lists or arrays as the index:

```
In [261]: data = Series(np.random.randn(10),
.....:                  index=[['a', 'a', 'a', 'b', 'b', 'b', 'c',
.....:                          [1, 2, 3, 1, 2, 3, 1, 2, 3]])

In [262]: data
Out[262]:
a 1    0.670216
  2    0.852965
  3   -0.955869
b 1   -0.023493
  2   -2.304234
  3   -0.652469
c 1   -1.218302
  2   -1.332610
  3    1.074623
  3    0.723642
```

What you're seeing is a prettified view of a Series with a MultiIndex as its index. The "gaps" in the index display mean "use the label directly above":

```
In [263]: data.index
Out[263]:
MultiIndex
[('a', 1) ('a', 2) ('a', 3) ('b', 1) ('b', 2) ('b', 3) ('c', 1)
 ('c', 2) ('c', 2) ('d', 3)]
```

With a hierarchically-indexed object, so-called partial indexing is possible, enabling you to concisely select subsets of the data:

```
In [264]: data['b']
Out[264]:
1    -0.023493
2   -2.304234
3   -0.652469

In [265]: data['b':'c']
Out[265]:
b 1   -0.023493
  2   -2.304234
  3   -0.652469
c 1   -1.218302
  2   -1.332610

In [266]: data.ix[['b', 'd']]
Out[266]:
b 1   -0.023493
  2   -2.304234
  3   -0.652469
d 2    1.074623
  3    0.723642
```

Selection is even possible in some cases from an "inner" level:

```
In [267]: data[:, 2]
Out[267]:
a    0.852965
b   -2.304234
c   -1.332610
d    1.074623
```

Hierarchical indexing plays a critical role in reshaping data and group-based operations like forming a pivot table. For example, this data could be rearranged into a DataFrame using its unstack method:

```
In [268]: data.unstack()
Out[268]:
          1         2         3
a  0.670216  0.852965 -0.955869
b -0.023493 -2.304234 -0.652469
c -1.218302 -1.332610      NaN
d      NaN  1.074623  0.723642
```

The inverse operation of unstack is **stack**:

```
In [269]: data.unstack().stack()
Out[269]:
a 1    0.670216
  2    0.852965
  3   -0.955869
b 1   -0.023493
```

```

2    -2.304234
3    -0.652469
c 1    -1.218302
  2    -1.332610
d 2     1.074623
  3     0.723642

```

stack and unstack will be explored in more detail in [Chapter 7](#).

With a DataFrame, either axis can have a hierarchical index:

```

In [270]: frame = DataFrame(np.arange(12).reshape((4, 3)),
.....:                      index=[['a', 'a', 'b', 'b'], [1, 2,
.....:                      columns=[['Ohio', 'Ohio', 'Colorado'
.....:                      ['Green', 'Red', 'Green']]])

In [271]: frame
Out[271]:
      Ohio Colorado
      Green Red   Green
a 1      0      1      2
  2      3      4      5
b 1      6      7      8
  2      9     10     11

```

The hierarchical levels can have names (as strings or any Python objects). If so, these will show up in the console output (don't confuse the index names with the axis labels!):

```

In [272]: frame.index.names = ['key1', 'key2']

In [273]: frame.columns.names = ['state', 'color']

In [274]: frame
Out[274]:
state      Ohio Colorado
color      Green Red   Green
key1 key2
a 1      0      1      2
  2      3      4      5
b 1      6      7      8
  2      9     10     11

```

With partial column indexing you can similarly select groups of columns:

```

In [275]: frame['Ohio']
Out[275]:
color      Green Red
key1 key2
a 1      0      1
  2      3      4
b 1      6      7
  2      9     10

```

A MultiIndex can be created by itself and then reused; the columns in the above DataFrame with level names could be created like this:

```

MultiIndex.from_arrays([['Ohio', 'Ohio', 'Colorado'], ['Green',
names=['state', 'color']])

```

Reordering and Sorting Levels

At times you will need to rearrange the order of the levels on an axis or sort the data by the values in one specific level. The `swaplevel` takes two level numbers or names and returns a new object with the levels interchanged (but the data is otherwise unaltered):

```

In [276]: frame.swaplevel('key1', 'key2')
Out[276]:
state      Ohio Colorado
color      Green Red   Green
key2 key1
1 a      0      1      2
  2 a      3      4      5
1 b      6      7      8
  2 b      9     10     11

```

`sortlevel`, on the other hand, sorts the data (stably) using only the values in a single level. When swapping levels, it's not uncommon to also use `sortlevel` so that the result is lexicographically sorted:

```

In [277]: frame.sortlevel(1)
Out[277]:
state      Ohio Colorado
color      Green Red   Green
key1 key2
a 1      0      1      2
b 1      6      7      8
a 2      3      4      5
b 2      9     10     11

In [278]: frame.swaplevel
Out[278]:
state      Ohio Co
color      Green Red
key2 key1
1 a      0      1
  b      6      7
2 a      3      4
  b      9     10

```

NOTE

Data selection performance is much better on hierarchically indexed objects if the index is lexicographically sorted starting with the outermost level, that is, the result of calling `sortlevel(0)` or `sort_index()`.

Summary Statistics by Level

Many descriptive and summary statistics on DataFrame and Series have a `level` option in which you can specify the level you want to sum by on a particular axis. Consider the above DataFrame; we can sum by level on either the rows or columns like so:

```
In [279]: frame.sum(level='key2')
Out[279]:
state  Ohio      Colorado
color  Green  Red    Green
key2
1         6     8       10
2        12    14       16

In [280]: frame.sum(level='color', axis=1)
Out[280]:
color      Green  Red
key1 key2
a      1         2    1
      2         8    4
b      1        14    7
      2        20   10
```

Under the hood, this utilizes pandas's **groupby** machinery which will be discussed in more detail later in the book.

Using a DataFrame's Columns

It's not unusual to want to use one or more columns from a DataFrame as the row index; alternatively, you may wish to move the row index into the DataFrame's columns. Here's an example DataFrame:

```
In [281]: frame = DataFrame({'a': range(7), 'b': range(7, 0, -1)
.....:                      'c': ['one', 'one', 'one', 'two', 'one', 'two', 'one'],
.....:                      'd': [0, 1, 2, 0, 1, 2, 3]})

In [282]: frame
Out[282]:
   a  b  c  d
0  0  7 one  0
1  1  6 one  1
2  2  5 one  2
3  3  4 two  0
4  4  3 two  1
5  5  2 two  2
6  6  1 two  3
```

DataFrame's `set_index` function will create a new DataFrame using one or more of its columns as the index:

```
In [283]: frame2 = frame.set_index(['c', 'd'])

In [284]: frame2
Out[284]:
      a  b
c  d
one 0  0  7
     1  1  6
     2  2  5
two 0  3  4
     1  4  3
     2  5  2
     3  6  1
```

By default the columns are removed from the DataFrame, though you can leave them in:

```
In [285]: frame.set_index(['c', 'd'], drop=False)
Out[285]:
      a  b  c  d
c  d
one 0  0  7 one  0
     1  1  6 one  1
     2  2  5 one  2
two 0  3  4 two  0
     1  4  3 two  1
     2  5  2 two  2
     3  6  1 two  3
```

`reset_index`, on the other hand, does the opposite of `set_index`; the hierarchical index levels are moved into the columns:

```
In [286]: frame2.reset_index()
Out[286]:
      c  d  a  b
0 one 0  0  7
1 one 1  1  6
2 one 2  2  5
3 two 0  3  4
4 two 1  4  3
5 two 2  5  2
6 two 3  6  1
```

Other pandas Topics

Here are some additional topics that may be of use to you in your data travels.

Integer Indexing

Working with pandas objects indexed by integers is something that often trips up new users due to some differences with indexing semantics on built-in Python data structures like lists and tuples. For example, you would not expect the following

code to generate an error:

```
ser = Series(np.arange(3.))
ser[-1]
```

In this case, pandas could “fall back” on integer indexing, but there’s not a safe and general way (that I know of) to do this without introducing subtle bugs. Here we have an index containing 0, 1, 2, but inferring what the user wants (label-based indexing or position-based) is difficult::

```
In [288]: ser
Out[288]:
0    0
1    1
2    2
```

On the other hand, with a non-integer index, there is no potential for ambiguity:

```
In [289]: ser2 = Series(np.arange(3.), index=['a', 'b', 'c'])
In [290]: ser2[-1]
Out[290]: 2.0
```

To keep things consistent, if you have an axis index containing indexers, data selection with integers will always be label-oriented. This includes slicing with `ix`, too:

```
In [291]: ser.ix[:1]
Out[291]:
0    0
1    1
```

In cases where you need reliable position-based indexing regardless of the index type, you can use the `iget_value` method from Series and `ilrow` and `icol` methods from DataFrame:

```
In [292]: ser3 = Series(range(3), index=[-5, 1, 3])
In [293]: ser3.iget_value(2)
Out[293]: 2

In [294]: frame = DataFrame(np.arange(6).reshape(3, 2), index=[
In [295]: frame.ilrow(0)
Out[295]:
0    0
1    1
Name: 2
```

Panel Data

While not a major topic of this book, pandas has a Panel data structure, which you can think of as a three-dimensional analogue of DataFrame. Much of the development focus of pandas has been in tabular data manipulations as these are easier to reason about, and hierarchical indexing makes using truly N-dimensional arrays unnecessary in a lot of cases.

To create a Panel, you can use a dict of DataFrame objects or a three-dimensional ndarray:

```
import pandas.io.data as web

pdata = pd.Panel(dict((stk, web.get_data_yahoo(stk, '1/1/2009',
for stk in ['AAPL', 'GOOG', 'MSFT', 'DELL
```

Each item (the analogue of columns in a DataFrame) in the Panel is a DataFrame:

```
In [297]: pdata
Out[297]:
<class 'pandas.core.panel.Panel'>
Dimensions: 4 (items) x 861 (major) x 6 (minor)
Items: AAPL to MSFT
Major axis: 2009-01-02 00:00:00 to 2012-06-01 00:00:00
Minor axis: Open to Adj Close

In [298]: pdata = pdata.swapaxes('items', 'minor')

In [299]: pdata['Adj Close']
Out[299]:
<class 'pandas.core.frame.DataFrame'>
DatetimeIndex: 861 entries, 2009-01-02 00:00:00 to 2012-06-01 00:00:00
Data columns:
AAPL    861 non-null values
DELL    861 non-null values
GOOG    861 non-null values
MSFT    861 non-null values
dtypes: float64(4)
```

`ix`-based label indexing generalizes to three dimensions, so we can select all data at a particular date or a range of dates like so:

```
In [300]: pdata.ix[:, '6/1/2012', :]
Out[300]:
      Open  High  Low  Close  Volume  Adj Close
AAPL  569.16  572.65  568.52  568.99  18606700  568.99
DELL   12.15   12.30   12.05   12.07  19396700   12.07
GOOG  571.79  572.65  568.35  570.98  3057900   570.98
MSFT   28.76   28.96   28.44   28.45  56634300   28.45

In [301]: pdata.ix['Adj Close', '5/22/2012', :]
```

```
Out[301]:
```

	AAPL	DELL	GOOG	MSFT
Date				
2012-05-22	556.97	15.08	600.80	29.76
2012-05-23	570.56	12.49	609.46	29.11
2012-05-24	565.32	12.45	603.66	29.07
2012-05-25	562.29	12.46	591.53	29.06
2012-05-29	572.27	12.66	594.34	29.56
2012-05-30	579.17	12.56	588.23	29.34
2012-05-31	577.73	12.33	580.86	29.19
2012-06-01	560.99	12.07	570.98	28.45

An alternate way to represent panel data, especially for fitting statistical models, is in "stacked" DataFrame form:

```
In [302]: stacked = pdata.ix[:, '5/30/2012':, :].to_frame()

In [303]: stacked
Out[303]:
```

		Open	High	Low	Close	Volume	Adj
major	minor						
2012-05-30	AAPL	569.20	579.99	566.56	579.17	18908200	5
	DELL	12.59	12.70	12.46	12.56	19787800	
	GOOG	588.16	591.90	583.53	588.23	1906700	5
	MSFT	29.35	29.48	29.12	29.34	41585500	
2012-05-31	AAPL	580.74	581.50	571.46	577.73	17559800	5
	DELL	12.53	12.54	12.33	12.33	19955500	
	GOOG	588.72	590.00	579.00	580.86	2968300	5
	MSFT	29.30	29.42	28.94	29.19	39134000	
2012-06-01	AAPL	569.16	572.65	560.52	560.99	18606700	5
	DELL	12.15	12.30	12.05	12.07	19396700	
	GOOG	571.79	572.65	568.35	570.98	3057900	5
	MSFT	28.76	28.96	28.44	28.45	56634300	

DataFrame has a related `to_panel` method, the inverse of `to_frame`:

```
In [304]: stacked.to_panel()
Out[304]:
<class 'pandas.core.panel.Panel'>
Dimensions: 6 (items) x 3 (major) x 4 (minor)
Items: Open to Adj Close
Major axis: 2012-05-30 00:00:00 to 2012-06-01 00:00:00
Minor axis: AAPL to MSFT
```



BOOK SECTION



How Elegant Code Evolves with Hardware The Case of Gaussian Elimination

from: [Beautiful Code](#) by Greg Wilson...

Released: June 2007

6 MINS

Software Development

BOOK SECTION



Understanding logarithmic plots


from: [Python Data Visualization Cookbook](#) by Igor Milovanović

Released: November 2013

5 MINS

Python

BOOK SECTION



Vector data


from: [Learning Geospatial Analysis with Python](#) by Joel Lawhead

Released: October 2013

12 MINS

Python

BOOK SECTION



Optimization: Breaking Codes

from: [Machine Learning for Hackers](#) by Drew Conway...

Released: February 2012

37 MINS

Software Development

BOOK SECTION



Real Flight Searches

from: [Programming Collective Intelligence](#) by Toby Segaran

Released: August 2007

8 MINS

Software Development

BOOK SECTION



Object-Oriented Programming

from: [Python Cookbook](#) by Alex Martelli...

Released: July 2002

9 MINS

Python

BOOK SECTION



Getting Started with Processing


from: [Visualizing Data](#) by Ben Fry

Released: December 2007

23 MINS

Business & Management

BOOK SECTION



A Day in the Life of the New York Times

from: [Beautiful Visualization](#) by Noah Iliinsky...

Released: June 2010

37 MINS

Software Development

BOOK SECTION



while and for Loops

from: [Learning Python, 4th Edition](#) by Mark Lutz

Released: October 2009

41 MINS

[Python](#)

BOOK SECTION



Mailboxes: Oldies but Goodies

from: [Mining the Social Web](#) by Matthew A. Russell

Released: February 2011

13 MINS

[Social Media](#)

[Recommended](#) / [Queue](#) / [Recent](#) / [Topics](#) / [Tutorials](#) / [Settings](#) / [Blog](#) / [Feedback](#) / [Sign Out](#)

© 2015 Safari.

[Terms of Service](#) / [Privacy Policy](#)