1. Intro to Grammar of Graphics



Grammar of Graphics

Data visualizations are made up of layers. Each layer consists of three parts:

data tabular dataset associated with the layer

geom graphical element associated with each observation

aesthetics mappings from properties of the plot that

associate **features** in the dataset with elements of

the geometry

(aes)

Complex plots can be constructed by putting together multiple layers.




Scatter Plot Example

data: food

geom: point

aes: { x: calories, y: total_fat }

each **observation** in the food dataset is represented by a point





Text Plot Example

data: food


geom: text

aes: { x: calories,

y: saturated_fat

label: item }

each **observation** in the food dataset is represented by a textual label





Segment Plot Example

data: food

geom: segment


aes: { x: calories,

y: saturated_fat

xend: calories,

yend: total_fat }

each observation in the food dataset is represented by a vertical line segment





Arrow Plot Example

data: food

geom: arrow


aes: { x: calories,

y: saturated_fat

xend: calories,

yend: total_fat }

each observation in the food dataset is represented by a vertical line segment plus an arrow!





Syntax

```
data: food
                                       food %>%
                                        ggplot() +
geom: point
     { x: calories, y: total_fat }
                                         geom_point(aes(x = calories, y = total_fat))
aes:
                                       food %>%
data: food
                                        ggplot() +
geom: text
      { x: calories,
                                         geom_text(aes(x = calories, y = total_fat,
aes:
        y: saturated_fat
                                                           label = item))
        label: item }
```



2. Fixed Aesthetics



Fixed Aesthetics

data: food

geom: segment

aes: { x: calories,


y: **0**,

xend: calories,

yend: total_fat }

we can map an aesthetic to a fixed value rather than a feature

we will see even better examples of why this is useful next time!





Fixed Aesthetic Syntax

```
data: food
   geom: segment
          { x: calories, y: 0, xend: calories, yend: total fat }
food %>%
 ggplot() +
  geom segment(aes(x = calories, xend = calories, yend = total fat), y = 0)
```

fixed aesthetics go OUTSIDE the aes function but inside the geom_* function

