

[← course home](#)

Bitwise NOT

The **NOT** bitwise operation inverts bits. A 0 becomes a 1. A 1 becomes a 0.

The NOT operator is often written as a **tilde character** ("~"):

```
~ 0000 0101
= 1111 1010
```

Python 3.6 ▾

When numbers are printed in base-10, the result of a NOT operation can be surprising. In particular, positive numbers can become negative and negative numbers can become positive. For example:

```
~ 5 # gives -6

# At the bit level:
# ~ 0000 0101 (5)
# = 1111 1010 (-6)
```

Python 3.6 ▾

This is because numbers are (usually) represented using two's complement, where the leftmost bit is actually negative. So flipping the leftmost bit usually flips the sign of the number.

[f Share](#)[t Tweet](#)[in Share](#)[← course home](#)[Next up: Bit Shifting →](#)

[Subscribe to our weekly question email list »](#)

Programming interview questions by company:

- [Google interview questions](#)
- [Facebook interview questions](#)
- [Amazon interview questions](#)
- [Uber interview questions](#)
- [Microsoft interview questions](#)
- [Apple interview questions](#)
- [Netflix interview questions](#)
- [Dropbox interview questions](#)
- [eBay interview questions](#)
- [LinkedIn interview questions](#)
- [Oracle interview questions](#)
- [PayPal interview questions](#)
- [Yahoo interview questions](#)

Programming interview questions by topic:

- [SQL interview questions](#)
- [Testing and QA interview questions](#)
- [Bit manipulation interview questions](#)
- [Java interview questions](#)
- [Python interview questions](#)
- [Ruby interview questions](#)
- [JavaScript interview questions](#)
- [C++ interview questions](#)
- [C interview questions](#)
- [Swift interview questions](#)
- [Objective-C interview questions](#)
- [PHP interview questions](#)
- [C# interview questions](#)

