

UMass Boston Computer Science
CS450 High Level Languages (section 2)
Compound Data Definitions

Monday, September 25, 2023

Logistics

- HW 1 in
 - ~~due: Sun 9/24 11:59 pm EST~~
 - Files should not start `big-bang` loop automatically
- HW 2 out
 - due: Sun 10/1 11:59 pm EST
- **STYLE** notes
 - Use **comments** to explain code if needed, BUT ...
 - ... the best code needs **no comments**
 - **Redundant comments** makes code harder to read
 - More comments ≠ “better”
 - Also, no **commented-out code**

(not a great variable name)


`(not (string? str))`

`; checks if str is a string
((not (string? str))`

Last
Time

Falling Ball Example

```
;; A WorldState is a Non-negative Integer  
;; Interp: Represents the y Coordinate of the center of a  
;;          ball in a `big-bang` animation.
```



← What if the ball can also move side-to-side? →

WorldState would need two pieces of data:
the *x* and *y* coordinates

```
;; A WorldState is an Integer ...  
;; ... and another Integer???
```

We need a way to create **compound data**
i.e., a new data definition that combines
values from other data defs

Last
Time

Kinds of Data Definitions

- Basic data
 - E.g., numbers, strings, etc
- Intervals
 - Data that is from a range of values, e.g., $[0, 100)$
- Enumerations
 - Data that is one of a list of possible values, e.g., “green”, “red”, “yellow”
- Itemizations
 - Data value that can be from a list of possible other data definitions
 - E.g., either a string or number (Generalizes enumerations)
- • Compound Data
 - Data that is a combination of values from other data definitions

today

Falling Ball Example


```
;; A WorldState is a  
(struct world [x y])  
;; where  
;; x: Integer - represents x coordinate of ball in animation  
;; y: Integer - represents y coordinate of ball
```

a struct definition creates a
new kind of **compound data**

Instances of the struct are
values of that kind of data


```
(define INITIAL-STATE (world 0 0))
```

Parts of a **struct** definition



(Implicitly) defines:

- A **constructor** function \longrightarrow `world`
 - Creates instances of the struct
- **Accessor** functions \longrightarrow `world-x, world-y`
 - Get an instance's field value
- A **predicate** \longrightarrow `world?`
 - Returns true for struct instances



Function Design Recipe

1. **Name**
2. **Signature** – types of the function input(s) and output
3. **Description** – explain (in English prose) the function behavior
4. **Examples** – show (using `rackunit`) the function behavior
5. **Code** – implement the rest of the function (arithmetic)
6. **Tests** – check (using `rackunit`) the function behavior

Function Design Recipe

1. **Name**
2. **Signature** – types of the function input(s) and output
3. **Description** – explain (in English prose) the function behavior
4. **Examples** – show (using `rackunit`) the function behavior
5. **Template** – sketch out the function structure (using input's Data Definition)
6. **Code** – implement the rest of the function (arithmetic)
7. **Tests** – check (using `rackunit`) the function behavior

Template for Compound data

- A function that consumes compound data must
 - extract the individual pieces, using accessors
 - combine them, with arithmetic

```
;; A WorldState is a  
(struct world [x y])  
;; where  
;; x: Integer - represents x coordinate of ball in animation  
;; y: Integer - represents y coordinate of ball
```

```
;; TEMPLATE for world-fn: WorldState -> ???  
(define (world-fn w)  
  .... (world-x w) ....  
  .... (world-y w) ....)
```

Code demo

- Moving ball
 - Both x and y coordinate can change
 - With mouse movement
 - (and keyboard directions?)

Check-In Quiz 9/25 on gradescope

(due 1 minute before midnight)