02246 Mandatory Assignment
Assignment 04 - Probabilistic Model Checking *

To be submitted on DTU Learn - see deadline on DTU Learn

You are encouraged to work in groups, but you must clearly identify the contributions of each group member, and you will be jointly responsible for the finished report. Register your group on DTU Learn before submitting as group submission.

Answers to all parts should be typed up using LaTeX and submitted electronically as a PDF report using the provided template. Drawings and formulae may be handwritten and scanned. More detailed instructions as to the style of answer we expect for each part are included below.

Some tasks require to upload files.

*Thanks to Michael Smith (the original author), and Lijun Zhang, Kebin Zeng, Flemming Nielson, Alberto Lluch Lafuente and Andrea Vandin (contributors).

Assignment 04 - Probabilistic Model Checking

A04P: Practical Problems

A04P.1 - Stefano Giroletti *Lottery scheduling* is a scheduling discipline where each task is assigned a number of tickets. To decide which task to execute, the scheduler randomly selects a ticket (under a uniform distribution), and the task owning the ticket is allowed to execute. A lottery scheduler can be either *pre-emptive*, in which a task can only execute for a certain amount of time before being interrupted, or *non pre-emptive* if a task always executes to completion once selected.

a) Construct a PRISM model of a pre-emptive lottery scheduler with three clients, where each task is given a single ticket, and the quantum (the length of time before a task is interrupted) is one time unit. You will have to decide on an appropriate way to model the tickets, which means deciding on an appropriate level of abstraction.

Modelling Choices for the Pre-emptive Lottery Scheduler

- **Ticket Assignment:** At job creation, the scheduler deterministically assigns 1 ticket to the new job. This explicit step makes the model flexible for different assignment methods in following exercises.
- **Job Length:** Upon creation, each job randomly and uniformly selects an execution length between 1 and 5 time units.
- **Execution Logic (1-unit quantum):** Jobs with at least one ticket are eligible to run. The CPU is granted to the job with the highest ticket count. For three jobs (j_1, j_2, j_3), the scheduling guards are:
  - $tickets(j_1) \geq tickets(j_2) \wedge tickets(j_1) \geq tickets(j_3) \rightarrow j_1$ executes.
  - $tickets(j_2) \geq tickets(j_1) \wedge tickets(j_2) \geq tickets(j_3) \rightarrow j_2$ executes.
  - $tickets(j_3) \geq tickets(j_1) \wedge tickets(j_3) \geq tickets(j_2) \rightarrow j_3$ executes.
- **Non-Determinism and Ties:** Because jobs can have equal tickets, guards overlap. This non-determinism is naturally resolved by PRISM's underlying uniform distribution, which simulates a fair lottery draw among the tied jobs.

UPLOAD REQUIRED: a prism model file `A04P.1.a.prism`.

b) We are now interested in the time taken for the first task from $\texttt{Client}_1$ to complete. To do so, let's introduce a new module called `Monitor`, which has a single Boolean variable called `finished`. The module should only perform $\texttt{finish}_1$ actions — the first time it does a $\texttt{finish}_1$ it changes its state so that `finished` = `true`, and for subsequent actions it remains in this state.

UPLOAD REQUIRED: a prism model file `A04P.1.b.prism`.

c) Write down a PCTL formula (using the '`P=?`' syntax), expressing the probability that the first task from $\texttt{Client}_1$ completes within t time units — you should define t as an integer constant, without a value. Use the experimentation feature of PRISM (as described in the tutorial), to plot a graph of this probability, for $0 \leq t \leq 20$.

The required PCTL formula is:

```
P=?  [F<=t (finished=true)]
```

The corresponding plot for $0 \leq t \leq 20$ is shown in Figure 1.

UPLOAD REQUIRED: a prism property file `A04P.1.c.props`.




Figure 1: Probability for job 1 to complete within t time units.

d) Is it possible for your lottery scheduler to suffer from starvation?

Theoretically speaking, starvation is possible, which can be verified by the formula `A [ F (finished=true) ]` that PRISM evaluates as false in the model. Nevertheless, this path has probability 0; in fact, the query `P=? [ F (finished=true) ]` returns 1, meaning that a job **almost surely terminates**.

e) Modify your model so that the quantum is two time units. How does this affect the time taken to complete a task from $\texttt{Client}_1$?

In order to check how the time changes with respect to the 1 time quantum scheduler we plot for both models the graph of P=? [F $\leq$ t(finished=true)]. As we can see from the graph for a given t the probability for job1 to finih before t are higher for the scheduler with 2 time quantum (green line)




Figure 2: Compared probability in scheduler 1 and scheduler 2 for job 1 to complete within t time units.

UPLOAD REQUIRED: a prism model file `A04P.1.e.prism`.

A04P.2 - Loke S. G. Jørgensen - Stefano Giroletti Rather than assigning the same number of tickets to each task, we can give varying priority to different tasks by assigning them *different* numbers of tickets.

a) By assigning different numbers of tickets to different tasks, approximate an SRT scheduler using lottery scheduling.

The number of tickets can now range from 0 (indicating no job is ready) to 5, and they are assigned with uniform probability upon job creation.

UPLOAD REQUIRED: a prism model file `A04P.2.a.prism`.

b) How does this affect the time taken to complete a task from $\texttt{Client}_1$? Is starvation possible?

Regarding starvation, the situation remains unchanged: the formula `A [ F (finished=true) ]` still evaluates to false, confirming the theoretical possibility of starvation, while the query `P=? [ F (finished=true) ]` still returns 1, ensuring almost sure termination.

The impact on execution time is illustrated in Figure 3, which compares the probability of Job 1 finishing within t time units under the original 1-ticket scheduler versus the new multi-ticket scheduler. As the graph shows, the up-to-5 tickets scheduler (green line) yields a higher completion probability in the first few steps. However, in the long run, the 1-ticket scheduler (blue line) reaches a higher probability sooner; because every job has exactly 1 ticket, it is easier for Job 1 to be repeatedly selected without having to constantly compete against jobs holding a permanently higher ticket count.




Figure 3: Comparison of the probability for Job 1 to complete within t time units between the 1-ticket and the up-to-5 tickets schedulers.

c) Increase the number of clients in your model until you reach the maximum for which PRISM can still build the underlying DTMC. Compare the time to build the DTMC to the time to run some analysis on it (e.g. a PCTL property).

PRISM encounters an "out of memory" error when attempting to build the DTMC with 9 clients (expanding the model `A04.P.2.a.prism`). With 8 clients, the DTMC is successfully constructed in 12.83 seconds, as shown in Figure 4.

However, during property verification, both the 7-client and 8-client models run out of memory. Consequently, we scaled down the experiments to 6 clients, which requires a significantly shorter build time of 0.337 seconds. For this 6-client model, the query `P=? [ F (finished=true) ]` is evaluated in 41.99 seconds, while the query `E [ F (finished=true) ]` takes 16.305 seconds to evaluate.

```
---------------------------------------------------------------------

Building model (engine:symbolic)...

Computing reachable states...

Reachability (BFS): 20 iterations in 0.72 seconds (average 0.036000, setup 0.00)

Time for model construction: 12.83 seconds.

Type:        DTMC
States:      1705782074882 (1 initial)
Transitions: 15971940656080

Transition matrix: 4069409 nodes (16 terminal), 15971940656080 minterms, vars: 57r/57c
```

Figure 4: Model building time for 8 clients.

d) Investigate what happens if one client tries to perform long jobs, but the others all generate very short jobs. Is the scheduler vulnerable to a denial of service attack?

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.




Figure 5: Evaluation time for `P=? [ F (finished=true) ]` with 6 clients.




Figure 6: Evaluation time for `A [ F (finished=true) ]` with 6 clients.

e) Can you express denial of service as a PCTL property? Explain your answer.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

A04P.3 - Loke S. G. Jørgensen In A04P.2 we reached the limits of model checking—here we explore the obscure abyss beyond them by resorting to simulation.

a) Replicate the model from A04P.2 but defining 10 clients, each with tasks of size six (i.e. of type `[0..5]`), and each also having six tickets defined in the same manner. Define a monitor that synchronises with these clients, and lets us observe when *all clients* have finished their tasks. Check how, in its default configuration, PRISM mems-out when trying to build this model. Report the *(i)* runtime and *(ii)* max memory used to reach this failure.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

UPLOAD REQUIRED: a prism model file `A04P.3.a.prism`.

b) Define a PCTL property using `P=?`, that queries the probability with which all clients may finish their tasks within t time units (the same integer constant defined for A04P.1). Estimate this probability for $t \in \{50, 56, 58, 60, 70, 80, 90, 100\}$ using the SMC capabilities of PRISM in their default configuration, as shown in class. Besides the estimated probabilities, report the width of the confidence interval achieved, and the runtime used to compute this estimate.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

c) Repeat the previous exercise with 10^4 simulations—in the modal dialog that opens when we simulate a property, in the field "Number of samples"—and also 10^5.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

d) Using simulation as above, find the probability with which all clients may finish their tasks within $t = 56$ time units (hint: it ain't zero), producing a confidence interval that does not contain zero.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

A04T: Theoretical Problems

A04T.1 Consider the DTMC in Figure 7(a), where the initial state is s_0, and the labels are shown on the states.




Figure 7: More DTMCs

a) For what values of p is it the case that $s_0 \models \mathbb{P}_{\geq \frac{1}{2}}(F^{\leq 2}\ a)$?

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.




Figure 8: Another DTMC

A04T.2 Consider the DTMC in Figure 8, which we will call $\mathcal{M} = (S, \boldsymbol{P}, s_1, AP, L)$, where $AP = \{b, c\}$. The initial state is s_1 and the labels are shown on the states. Determine which states of the DTMC satisfy the following PCTL formulae, by following the PCTL model checking algorithm seen in the course:

a) $\mathbb{P}_{\geq \frac{17}{19}}(b\ U\ c)$

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

b) $\mathbb{P}_{\geq \frac{1}{2}}(X\ \mathbb{P}_{> \frac{1}{3}}((b \vee c)\ U^{\leq 2}\ (b \wedge c)))$

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

A04T.3 As we have seen in the course, a step-bounded until formula $\Phi_1\ U^{\leq n}\ \Phi_2$ in PCTL is satisfied by a path if Φ_2 holds after at most n time steps, and until then Φ_1 always holds. We would like to generalise this to the form $\Phi_1\ U^{I}\ \Phi_2$, where I is an interval over the natural numbers.

a) Define the semantics $\mathcal{M}, \sigma \models \Phi_1 \; U^I \; \Phi_2$ of this new path formula, where σ is a path in the DTMC $\mathcal{M}$. You have some freedom to define the semantics, and there are several meaningful options.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

b) Consider four cases on the form of the interval I, for $0 < n \leq n'$: $[0, \infty)$, $[0, n]$, $[n, \infty)$ and $[n, n']$. For each case, can you encode the formula $\mathbb{P}_J(\Phi_1 \; U^I \; \Phi_2)$ in terms of the existing PCTL operators? If so, show how, and if not, explain why.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

c) For the cases where you cannot encode the formula, could you encode them in PTCL*?

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.

d) Design a model checking algorithm for $\mathbb{P}_J(\Phi_1 \; U^{\geq n} \; \Phi_2)$, i.e. $\mathbb{P}_J(\Phi_1 \; U^{[n,\infty)} \; \Phi_2)$. Get inspiration from the algorithms seen in the course for determining $\mathbb{P}_J(\Phi_1 \; U \; \Phi_2)$. Explain the correctness of your proposed algorithm.

Provide your answer here. Leave the special color (blue). Figures, tables, code snippets can be placed somewhere else but they need to be referred here.




Figure 9: One more DTMC