


Packet Tracer – Investigating Convergence

Topology



Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gateway
R1	G0/0	209.165.0.1	255.255.255.0	N/A
	G0/1	64.100.0.1	255.0.0.0	N/A
	S0/0/0	192.168.1.2	255.255.255.0	N/A
R2	G0/0	10.0.0.1	255.0.0.0	N/A
	S0/0/0	192.168.1.1	255.255.255.0	N/A
PC1	NIC	64.100.0.2	255.0.0.0	64.100.0.1
PC2	NIC	209.165.0.2	255.255.255.0	209.165.0.1
PC3	NIC	10.0.0.2	255.0.0.0	10.0.0.1

Objectives

Part 1: View the Routing Table of a Converged Network

Part 2: Add a New LAN to the Topology

Part 3: Watch the Network Converge

Background

This activity will help you identify important information in routing tables and witness the process of network convergence.

Part 1: View the Routing Table of a Converged Network

Step 1: Use show commands and interpret the output.

a. Show the directly connected networks of R1. How many routes are connected to R1?

```
R1# show ip route connected
```

- b. Show the running configuration of **R1**. What routing protocol is in use?
- This is asking if the IP addresses in the Addressing Table shown above the same as the address you see in the console. C. Are the IP addresses in the configuration advertised by RIP the same as those that are connected?
- d. Are these IP addresses assignable, network, or broadcast?

Under router rip, you can see the network

e. Show the networks of **R1** learned through RIP. How many routes are there?

```
R1# show ip route rip
```

f. Show all of the networks that **R1** has in its routing table. What do the leading letters represent?

```
R1# show ip route
```

g. Repeat step 1, a to f on **R2**. Compare the output of the two routers.

Step 2: Verify the state of the topology.

- a. Ping PC3 from PC2. The ping should be successful.
- b. Show the interface status on **R2**. Two interfaces should have assigned addresses. Each address corresponds to a connected network.

```
R2# show ip interface brief
```

c. Show the interface status on R1. How many interfaces have assigned addresses?

```
R1# show ip interface brief
```

Part 2: Add a New LAN to the Topology

Step 1: Add an Ethernet cable.

- a. Connect the correct Ethernet cable from **S1** to the appropriate port on **R1**.
- b. Ping from PC1 to PC2 after the affected S1 port turns green. Was the ping successful?
- c. Ping from PC1 to PC3. Was the ping successful? Why?

Step 2: Configure a route.

- a. Switch from Realtime mode to Simulation mode.
- b. Enter a new route on R1 for the 64.0.0.0 network.

```
R1(config)# router rip
R1(config-router)# network 64.0.0.0
```

c. Examine the PDUs leaving R1. What type are they?

Part 3: Watch the Network Converge

Step 1: Use debug commands.

a. Enable debugging on R2.

```
R2# debug ip rip
R2# debug ip routing
```

- b. For reference, show the routing table of R2 as in step 1f.
- c. Click Capture / Forward from simulation mode. What notification appeared in the terminal of R2?
- d. According to the debugging output, how many hops away from R2 is 64.0.0.0? 1
- e. What interface does **R2** send packets destined for the 64.0.0.0 network? \$0/0/0
- f. Show the routing table of R2. Record the new entry.

Step 2: Verify the state of the topology.

Ping from PC1 to PC3. Was the ping successful? Why?

Suggested Scoring Rubric

Activity Section	Question Location	Possible Points	Earned Points
Part 1: View the Routing	Step 1-a	6	
Table of a Converged Network.	Step 1-b	6	
	Step 1-c	6	
	Step 1-d	6	
	Step 1-e	6	
	Step 1-f	6	
	Step 2-c	6	
	42		
Part 2: Add a New LAN to	Step 1-b	6	
the Topology	Step 1-c	6	
	Step 2-c	6	
	18		
Part 3: Watch the Network	Step 1-c	6	
Converge	Step 1-d	6	
	Step 1-e	6	
	Step 1-f	6	
	Step 2-a	6	
	30		
Pa	10		
	100		