


OCL Modelling Quizzes



Juan de Lara, Elena Gómez, Esther Guerra
{Juan.deLara, MariaElena.Gomez, Esther.Guerra}@uam.es

Computer Science Department
Universidad Autónoma de Madrid

How do we express that...




Any machine can be operated by at most one operator.

Each operator operates at most one machine at the same time.

At every moment, in the factory, there should be at least one operator in some machine.


How do we express that...




context Factory

noMachineUnattended **inv**:

self.workers->exists(o | o.operates->notEmpty())




How do we express that...




context Factory

noMachineUnattended **inv**:

self.workers->exists(o | o.operates->notEmpty())




How do we express that...



“Not all MountainBikes owned by any MountainBiker have the same type”

How do we express that...



“Not all MountainBikes owned by any MountainBiker have the same type”

Hint:

`obj.ocllsKindOf(T)` → returns true if obj is of type T, or a supertype

`obj.ocllsTypeOf(T)` → returns true if obj is of type T

Example:

b: DownHillBike


`b.ocllsKindOf(DownHillBike)` → true

`b.ocllsTypeOf(DownHillBike)` → true

`b.ocllsKindOf(MountainBike)` → true

`b.ocllsTypeOf(MountainBike)` → false

How do we express that...





context MountainBiker


notSameBikes inv:

owns->exists(b | b.ocllsTypeOf(DownHillBike)) and

owns->exists(b | b.ocllsTypeOf(CrossCountryBike))



How do we express that...





context MountainBiker


notSameBikes inv:

owns->exists(b | b.ocllsTypeOf(DownHillBike)) and

owns->exists(b | b.ocllsTypeOf(CrossCountryBike))





How do we express that...




context MountainBiker

notSameBikes inv:

$\text{owns} \rightarrow \text{size}() = 1$ or (-- to consider the case where the biker has just one bike
 $\text{owns} \rightarrow \text{exists}(b \mid b.\text{oclIsTypeOf}(\text{DownHillBike}))$ and
 $\text{owns} \rightarrow \text{exists}(b \mid b.\text{oclIsTypeOf}(\text{CrossCountryBike}))$)




How do we express that...



“The most expensive wine is from the ‘Rioja’ region”


How do we express that...



“The most expensive wine is from the ‘Rioja’ region”


```
Wine.allInstances()->select( ew |  
  not Wine.allInstances()->exists ( w | w.price > ew.price ) )  
  .producedIn.name->includes('Rioja')
```

How do we express that...



A vehicle owner must be at least 18 years old

How do we express that...




A vehicle owner must be at least 18 years old

context Vehicle

inv: self.owner.age >= 18

What's the difference with...?




context Vehicle

inv: self.owner.age >= 18

context Person


inv: self.age >= 18

How do we express that...



A car owner must be at least 18 years old

How do we express that...




A car owner must be at least 18 years old.:

context Car


inv: self.owner.age >= 18

How do we express that...



Nobody has more than three vehicles

How do we express that...




Nobody has more than three vehicles

context Person

inv: `self.fleet->size <= 3` -- parentheses for operations w/o params optional


Or change cardinality

How do we express that...



All cars of a person are black

How do we express that...




All cars of a person are black

context Person

inv: self.fleet->forAll(v | v.colour = #black)

(we can do better)

How do we express that...




All cars of a person are black

context Person

inv: `self.fleet->forAll(v | v.oclIsKindOf(Car) implies v.colour = #black)`

How do we express that...




Nobody has more than 3 black vehicles

context Person

inv: self.fleet->select(v | v.colour = #black)->size <= 3


What does this expression mean?



context Person

inv: self.fleet->iterate(v; acc:Integer=0 | if (v.colour=#black)
then acc + 1 else acc endif) <=3

What does this expression mean?




context Person

inv: self.fleet->iterate(v; acc:Integer=0 | if (v.colour=#black)
then acc + 1 else acc endif) <=3

Nobody has more than 3 black vehicles


What does this expression mean?



context Person

inv: `age < 18` implies `self.fleet->forAll(v | not v.ocllsKindOf(Car))`

What does this expression mean?




context Person

inv: age<18 implies self.fleet->forAll(v | not v.ocllsKindOf(Car))

No child owns a car


What does this expression mean?



context Car

inv: Car.allInstances()->exists(c | c.colour=#red)

What does this expression mean?



context Car

inv: Car.allInstances()->exists(c | c.colour=#red)

There is at least one red car